

# The Unified Community Velocity Model Software Framework

Patrick Small<sup>a,1,\*</sup>, David Gil<sup>b,\*\*</sup>, Phil J. Maechling<sup>b,\*\*</sup>, Ricardo Taborda<sup>c</sup>, Thomas H. Jordan<sup>b,d</sup>, Geoffrey P. Ely<sup>e</sup>, Other Authors  
TBD

<sup>a</sup>Department of Computer Science, University of Southern California, Los Angeles, CA 90089, USA

<sup>b</sup>Southern California Earthquake Center, 3651 Trousdale Parkway, Suite 169, Los Angeles, CA 90089, USA

<sup>c</sup>Center for Earthquake Research and Information, and Department of Civil Engineering, University of Memphis, Memphis, TN 38152, USA

<sup>d</sup>Department of Earth Sciences, University of Southern California, Los Angeles, CA 90089, USA

<sup>e</sup>Leadership Computing Facility, Argonne National Laboratory, Argonne, IL 60439, USA

---

## Abstract

This paper presents the Unified Community Velocity Model (UCVM) software framework developed by the Southern California Earthquake Center. UCVM is a collection of software tools and application programming interfaces designed to provide standard access to multiple seismic velocity models used in seismology and geophysics research. Seismic velocity models are key components of current research efforts dedicated to advancing our knowledge of the Earth's crustal structure and its influence on the ground response during earthquakes, including both the regional deep geology and local effects due to the geometry, spatial distribution, and material composition of sediments in basins and valleys. In general, the UCVM software framework is designed to facilitate all research activities involving the use of seismic velocity models, but its development has been particularly driven by applications for deterministic physics-based earthquake ground-motion simulation and seismic hazard analysis. The UCVM has been extensively used in modeling and simulation activities in southern California. Here we describe the background that led to the development of the UCVM and its various software components, including advanced high-performance computer tools available within UCVM, and its capabilities in terms of product deliverables and performance. We also present examples of recent applications that use UCVM tools or output datasets.

## Keywords:

seismic velocity models, earthquake simulation, high-performance computing, meshing

---

## 1. Introduction

The quantitative understanding of the physical world is an essential goal of geoscience research. We use mathematical abstractions to represent the behavior of systems under static and dynamic conditions; and properties such as density and elastic moduli to characterize the capacity of materials to absorb or transmit forces in stationary and transient processes. In seismology and geophysics, our understanding of physical phenomena associated to earthquakes, their genesis, and effects, depends in a good measure on our knowledge and accurate representation of the geometry and material properties of the Earth's structure, as well as on our capacity to represent the mechanical characteristics of the rupture process that takes place when a seismic fault breaks and the subsequent seismic wave propagation problem. For the former case, we use stress conditions and dynamic rupture models to describe the faulting process. On the other hand, for the latter case, we use seismic

velocity and attenuation models to describe the geologic structure of the mantle and crust, and the mechanical properties of the materials in the different geologic units that compose these structures to describe the propagation of seismic waves through basins and sedimentary deposits, and thus determine the characteristics of the ground motion.

Source models and seismic velocity models are therefore the basic input to earthquake simulation. We are interested on how seismic velocity models are built and made available to geoscientists, and in particular, on how these models can help advance physics-based earthquake simulation. We call physics-based earthquake simulation, the modeling approaches that use deterministic numerical techniques—such as the finite element, finite difference, or spectral element methods—to simulate the ground motion in ways that incorporate the physics of earthquake processes explicitly. That is, methods that explicitly solve the associated wave propagation problem. The use of physics-based earthquake simulation has increased considerably over the last two decades thanks to the growth—in capacity and availability—of high-performance computing (HPC) facilities and applications (e.g., Aagaard et al., 2008; Olsen et al., 2009; Bielak et al., 2010; Cui et al., 2010). These simulations have specific applications of great impact in seismology and earthquake engineering in aspects such as the assessment of regional seismic hazard (e.g., Graves et al., 2011).

---

\*Principal corresponding author

\*\*Corresponding author

Email addresses: patrices@usc.edu (Patrick Small), davidgil@usc.edu (David Gil), maechlin@usc.edu (Phil J. Maechling)

<sup>1</sup>This is only a tentative author line-up. Final line-up to be agreed upon by the whole group

Recent simulations have highlighted the importance of velocity models in the accuracy of simulation results (e.g., Taborda and Bielak, 2014). Numerous seismic velocity models have been built for specific regional or local structures and used in particular simulations over the years (e.g., Frankel and Vidale, 1992; Brocher, 2008; Graves, 2008). The need for these models in simulation gave way to the conception of the community velocity models (CVMs). CVMs are seismic velocity models that have been developed, maintained, advanced and used by a community of interested investigators. Some examples of CVMs for the regions of southern and northern California, Utah, and the central United States are those models developed by Kohler et al. (2003); Brocher et al. (2006); Magistrale et al. (2006) and Ramírez-Guzmán et al. (2012).

CVMs have been typically distributed in the form of datasets or collections of files, or in the form of computer programs that can dynamically operate on these datasets and files to provide information about the geometry and material properties of the crust in a particular region. However, these datasets and computer programs have not always been thought carefully from a computational perspective. In addition, recent advances in earthquake simulations, powered by the increasing capability of supercomputers, have increased significantly the computational demand placed on CVMs as input to these simulations.

This paper presents the Unified Community Velocity Model (UCVM), a software framework designed to provide standardized and computationally efficient access to seismic velocity models, developed and maintained by the Southern California Earthquake Center (SCEC). UCVM is a collection of software tools and application programming interfaces (APIs) that facilitate the access to the material properties stored in CVMs. Although UCVM was conceived as a tool to aid physics-based earthquake ground-motion simulation and regional seismic hazard assessment, it can be used in other geosciences and engineering applications. Here, we describe the development of UCVM and its various software components, including features for use in high-performance parallel computers, and present examples of recent applications of UCVM tools in earthquake research.

## 2. The UCVM Software Framework

The primary functionality provided by UCVM is the ability to query a wide array of CVMs for material properties in standardized formats, independently of the particularities of each dataset or CVM. UCVM achieves this by registering datasets and velocity models into the framework. Registration of a velocity model or dataset consists of creating the appropriate programming application interface (API) to facilitate the communication between the framework utilities and tools, and the velocity models and datasets. Once a velocity model or dataset has been registered with UCVM, a client can use the framework utilities to retrieve information from the models at any geographic point within the coverage region of the model. A client can be either a user or another software. The primary data-point typically retrieved by a client consists of a float triplet with the seismic velocities ( $V_P$  and  $V_S$ ), and the material's density ( $\rho$ ).

The UCVM can then be used to produce standardized output in the form of three-dimensional (3D) volumetric datasets, two-dimensional (2D) vertical cross-sections and horizontal slices, and individual data-points. A client can also use other UCVM utilities for plotting and transforming models and datasets.

In order to facilitate access to the models, UCVM conceals each model's local coordinate system behind a generic querying interface. Data points are queried through this interface by geographic latitude and longitude, and a vertical  $z$ -coordinate. The framework allows defining the  $z$ -axis as either depth below the free surface (in meters, positive downward) or elevation relative to mean sea level (where zero is at sea level, positive upward and negative downward). The framework further extends the standardized interface by allowing multiple velocity models to be aggregated into a single composite model. Composition is accomplished by tiling two or more velocity models in three dimensions according to a user-specified priority ordering. To support this flexible query mechanism consistently across all models, UCVM includes a high-resolution digital elevation model (DEM). The DEM is synthesized from the USGS National Elevation Dataset (TODO: cite USGS NED) and the ETOPO1 Global Relief Model (TODO: cite ETOPO1).

With the exception of the Wasatch Front (Utah) CVM, currently the primary focus of UCVM has been on the State of California (along with portions of surrounding States). However, the framework has been designed to be easily modified to cover any arbitrary region of the Earth's surface, provided adequate resolution elevation datasets exist. Additional details are given in the Community Velocity Models section.

(good up to here. now working on the following text)

(pending to be included in another section)

An additional advantage to providing the built-in DEM is that UCVM is able to return the surface elevation at any query point in addition to the traditional  $V_P$ ,  $V_S$ , and  $\rho$  parameters.

Under this scheme, a query point is submitted sequentially to each velocity model within the ordered list that comprises the composite. The first model to return valid velocity data for the point is considered to have fulfilled the data request and subsequent models are not queried. Thus, overlap among the individual models is acceptable and their relative priority ordering arbitrates which one satisfies any given query. Generally, no smoothing is performed at the interfaces between models (an exception is interpolation between a geotechnical layer and a crustal model as discussed later in this paper). This tiling concept is illustrated in Figure ??.

Community velocity models vary widely in their area of coverage, depth extent, and resolution. UCVM is flexible in its support for such variability. However, in order to better accommodate high frequency ground motion simulations, it categorizes models into two general groups: crustal models, and geotechnical layers (GTLs). Crustal models provide subsurface seismic wave velocities associated with basin, crust, and mantle structures. These models may potentially extend to many tens of kilometers below the Earth's surface yet do so at coarse resolutions (TODO: cite CVM-H, CVM-S). Geotechnical layers, in contrast, provide velocities for only the near-surface (typically a few hundred meters) at very high resolution (TODO:

cite Ely Vs30 GTL). Ground motion simulations, in particular, rely on high-resolution near-surface velocities and therefore a GTL serves to supplement the coarser data provided by crustal models.

TODO: Interpolation of GTL with Crustal

### 3. Community Velocity Models

The UCVM framework supports different seismic velocity models.

#### 3.1. Utilities

##### 3.1.1. Querying

##### 3.1.2. Gridding and Meshing

##### 3.1.3. UCVM and the Etree Library

##### 3.1.4. New DEMs and Vs30 Maps

#### 3.2. Parallel Utilities

#### 3.3. Application Programming Interface

### 4. Computational Performance

*It would be desirable to do some experiments in terms of performance, especially for the parallel applications utilities in UCVM. With some examples of how long the same thing would take if doing it differently. We will need to discuss this.*

### 5. Recent Case Applications

*This section will be dedicated to show case applications. Some ideas for potential subsections follow.*

#### 5.1. Visualization and Model Comparisons

#### 5.2. Chino Hills Simulation Series

#### 5.3. CyberShake

### 6. Summary and Conclusions

*A couple of paragraphs with a summary of what is shown in the paper and a few key conclusions about the impact that we expect UCVM has already have and will have on earthquake research.*

### References

Aagaard, B.T., Brocher, T.M., Dolenc, D., Dreger, D., Graves, R.W., Harm-  
sen, S., Hartzell, S., Larsen, S., McCandless, K., Nilsson, S., Petersson,  
N.A., Rodgers, A., Sjogreen, B., Zoback, M.L., 2008. Ground-motion mod-  
eling of the 1906 San Francisco earthquake, Part II: Ground-motion esti-  
mates for the 1906 earthquake and scenario events 98, 1012–1046. URL:  
<http://www.bssaonline.org/cgi/content/abstract/98/2/1012>.  
Bielak, J., Graves, R.W., Olsen, K.B., Taborda, R., Ramírez-Guzmán,  
L., Day, S.M., Ely, G.P., Roten, D., Jordan, T.H., Maechling, P.J.,  
Urbanic, J., Cui, Y., Juve, G., 2010. The ShakeOut earthquake sce-  
nario: Verification of three simulation sets 180, 375–404. URL:  
<http://dx.doi.org/10.1111/j.1365-246X.2009.04417.x>,  
doi:10.1111/j.1365-246X.2009.04417.x.  
Brocher, T.M., 2008. Compressional and shear-wave velocity versus depth  
relations for common rock types in northern California 98, 950–968. URL:  
<http://www.bssaonline.org/cgi/content/abstract/98/2/950>,  
doi:10.1785/0120060403.

Brocher, T.M., Aagaard, B.T., Simpson, R.W., Jachens, R.C., 2006. The USGS  
3D seismic velocity model for northern California 87, Fall Meet. Suppl.,  
Abstr. S51B–1266.  
Cui, Y., Olsen, K., Jordan, T., Lee, K., Zhou, J., Small, P., Roten, D., Ely,  
G., Panda, D., Chourasia, A., Levesque, J., Day, S., Maechling, P., 2010.  
Scalable earthquake simulation on petascale supercomputers, in: SC '10:  
Proc. of the 2010 ACM/IEEE Int. Conf. for High Performance Computing,  
Networking, Storage and Analysis, pp. 1–20. doi:10.1109/SC.2010.45.  
Frankel, A., Vidale, J., 1992. A three-dimensional simula-  
tion of seismic waves in the Santa Clara Valley, Califor-  
nia, from a Loma Prieta aftershock 82, 2045–2074. URL:  
<http://www.bssaonline.org/cgi/content/abstract/82/5/2045>.  
Graves, R., Jordan, T., Callaghan, S., Deelman, E., Field, E., Juve, G., Kessel-  
man, C., Maechling, P., Mehta, G., Milner, K., Okaya, D., Small, P., Vahi,  
K., 2011. CyberShake: A physics-based seismic hazard model for Southern  
California 168, 367–381. doi:10.1007/s00024-010-0161-6.  
Graves, R.W., 2008. The seismic response of the San Bernardino basin  
region during the 2001 Big Bear lake earthquake 98, 241–252. URL:  
<http://www.bssaonline.org/cgi/content/abstract/98/1/241>,  
doi:10.1785/0120070013.  
Kohler, M.D., Magistrale, H., Clayton, R.W., 2003. Man-  
tle heterogeneities and the SCEC reference three-dimensional  
seismic velocity model version 3 93, 757–774. URL:  
<http://www.bssaonline.org/cgi/content/abstract/93/2/757>,  
doi:10.1785/0120020017.  
Magistrale, H., Olsen, K.B., Pechmann, J.C., 2006. Construction  
and Verification of a Wasatch Front Community Velocity Model.  
Technical Report 06HQGR0012. U.S. Geological Survey. URL:  
<http://earthquake.usgs.gov/research/external/reports/06HQGR0012.pdf>.  
Olsen, K.B., Day, S.M., Dalaguer, L.A., Mayhew, J., Cui, Y., Zhu, J.,  
Cruz-Atienza, V.M., Roten, D., Maechling, P., Jordan, T.H., Okaya,  
D., Chourasia, A., 2009. ShakeOut-D: Ground motion estimates us-  
ing an ensemble of large earthquakes on the southern San Andreas fault  
with spontaneous rupture propagation. Geophys. Res. Lett. 36, L04303.  
doi:10.1029/2008GL036832.  
Ramírez-Guzmán, L., Boyd, O.S., Hartzell, S., Williams, R.A., 2012. Seismic  
velocity model of the Central United States (Version 1): Description and  
simulation of the 18 April 2008 Mt. Carmel, Illinois, earthquake 102, 2622–  
2645. doi:10.1785/0120110303.  
Taborda, R., Bielak, J., 2014. Ground-motion simulation and validation of  
the 2008 Chino Hills, California, earthquake using different velocity models  
104, in press.