



Authentication Issue Fix Guide

Issue Summary

Users experiencing **401 Unauthorized** errors when attempting to log in to the CRTLPyme application deployed on Google Cloud Run.

Error Symptoms

- Login attempts return 401 status code
 - Error appears on `/api/auth/callback/credentials` endpoint
 - Error message: "Credenciales inválidas. Por favor verifica tu email y contraseña."
-



Root Cause Analysis

After thorough investigation of the codebase, the following potential causes were identified:

1. Credential Mismatch (Most Likely ★)

The seed script creates credentials that may not match what users are attempting to use:

Credentials Created by `seed-complete.ts` :

- Email: `admin@crtlpyme.com` (note: `.com` not `.cl`)
- Password: `Admin2025!` (note: `2025` not `123`)

Common User Mistakes:

- Using `admin@crtlpyme.cl` instead of `admin@crtlpyme.com`
- Using `Admin123!` instead of `Admin2025!`

2. User/Tenant Status Issues

The authentication checks for:

- User must be active (`user.isActive = true`)
- User's tenant must be active (`user.tenant.isActive = true`)

If either is false, authentication fails.

3. Database Connection or Seed Issues

- User might not exist in the database
- Seed script might not have run successfully
- Password hash might be corrupted

4. Password Hashing Configuration

Both the seed script and authentication use:

- Library: `bcryptjs` v2.4.3
 - Rounds: 10
 - These are **consistent and correct** ✓
-

✓ Solutions

Solution 1: Use Correct Credentials (Quick Fix)

Try logging in with the EXACT credentials from the seed script:

```
Email: admin@crtlpyme.com
Password: Admin2025!
```

Important Notes:

- Email domain is `.com` NOT `.cl`
- Password is `Admin2025!` NOT `Admin123!`
- Password is case-sensitive
- No extra spaces before/after

Solution 2: Reset Admin Password

If the correct credentials don't work, reset the password using our diagnostic script:

```
# Connect to Cloud Run or your deployment environment
# Then run:

cd /path/to/CRTLPyme

# Option A: Check if user exists
npx tsx scripts/fix-admin-password.ts check

# Option B: Test a specific password
npx tsx scripts/fix-admin-password.ts test admin@crtlpyme.com "Admin2025!"

# Option C: Reset password to default
npx tsx scripts/fix-admin-password.ts reset
```

The reset script will:

1. Find the admin user in the database
2. Create a fresh password hash for `Admin2025!`
3. Update the user in the database
4. Verify the new password works
5. Ensure user and tenant are active

Solution 3: Create Admin User from Scratch

If the user doesn't exist at all:

```
cd /path/to/CRTLPyme

# Create with default credentials
npx tsx scripts/create-admin-user.ts

# OR create with custom credentials
npx tsx scripts/create-admin-user.ts "your-email@example.com" "YourPassword123!"
```

This script will:

1. Create the platform tenant if needed
2. Hash the password correctly
3. Create/update the admin user
4. Verify everything works
5. Ensure all flags are set correctly

Solution 4: Deploy Debug Version

To get detailed logs and understand exactly what's failing:

```
cd /path/to/CRTLPyme

# Checkout the debug branch
git checkout fix/auth-debugging-401

# Build and deploy
docker build -t gcr.io/YOUR_PROJECT_ID/crtlpyme:debug .
docker push gcr.io/YOUR_PROJECT_ID/crtlpyme:debug

# Update Cloud Run service
gcloud run services update crtlpyme-app \
  --image gcr.io/YOUR_PROJECT_ID/crtlpyme:debug \
  --region us-central1
```

The debug version adds comprehensive logging:

- Email being attempted
- Whether user exists
- User active status
- Tenant active status
- Password hash comparison details

Check Cloud Run logs after attempting login to see the detailed output.



Deployment Steps

Step 1: Fix the Issue Locally

```
# Clone or navigate to repo
cd /home/ubuntu/github_repos/CRTLPyme

# Checkout fix branch
git checkout fix/auth-debugging-401

# Connect to production database (set DATABASE_URL)
export DATABASE_URL="postgresql://user:pass@your-cloud-sql-ip:5432/dbname"

# Run the fix script
npx tsx scripts/fix-admin-password.ts reset

# Or create fresh admin
npx tsx scripts/create-admin-user.ts
```

Step 2: Deploy Updated Code (if needed)

```
# Commit changes
git add .
git commit -m "fix: Add authentication debugging and password fix scripts"

# Push to GitHub
git push origin fix/auth-debugging-401

# Create PR or merge to main
```

Step 3: Rebuild and Deploy

```
# Build new image
docker build -t gcr.io/YOUR_PROJECT_ID/crtlpyme:latest .

# Push to GCR
docker push gcr.io/YOUR_PROJECT_ID/crtlpyme:latest

# Deploy to Cloud Run
gcloud run deploy crtlpyme-app \
  --image gcr.io/YOUR_PROJECT_ID/crtlpyme:latest \
  --region us-central1 \
  --allow-unauthenticated
```

Step 4: Test Authentication

1. Navigate to: `https://crtlpyme-app-399088129827.us-central1.run.app`
2. Click "Iniciar Sesión"
3. Enter credentials:
 - Email: `admin@crtlpyme.com`
 - Password: `Admin2025!`
4. Should successfully authenticate



Additional Diagnostics

Check Database Directly

```
# Connect to Cloud SQL
gcloud sql connect YOUR_INSTANCE_NAME --user=postgres

# Check if user exists
SELECT email, "isActive", role FROM "User" WHERE email = 'admin@crtlpyme.com';

# Check tenant status
SELECT u.email, u."isActive" as user_active, t."isActive" as tenant_active
FROM "User" u
JOIN "Tenant" t ON u."tenantId" = t.id
WHERE u.email = 'admin@crtlpyme.com';
```

Check Cloud Run Logs

```
# View recent logs
gcloud logging read "resource.type=cloud_run_revision AND re-
source.labels.service_name=crtlpyme-app" \
  --limit 50 \
  --format json

# Filter for auth errors
gcloud logging read "resource.type=cloud_run_revision AND textPayload=~'AUTH'" \
  --limit 100
```

Test Password Hash Locally

```
// test-password.js
const bcrypt = require('bcryptjs');

async function test() {
  const password = 'Admin2025!';
  const hash = '$2a$10$...'; // Get from database

  const result = await bcrypt.compare(password, hash);
  console.log('Password matches:', result);
}

test();
```

Checklist

Use this checklist to systematically resolve the issue:

- [] Verify exact credentials from seed script
- [] Try login with `admin@crtlpyme.com` and `Admin2025!`
- [] If failed, run `fix-admin-password.ts check` to verify user exists
- [] If user doesn't exist, run `create-admin-user.ts`
- [] If user exists but password wrong, run `fix-admin-password.ts reset`
- [] Deploy debug version if still failing
- [] Check Cloud Run logs for detailed error info
- [] Verify database connection works
- [] Check user and tenant are active in database
- [] Test authentication locally if possible
- [] Deploy fix to production

Related Files

- **Authentication Config:** `/lib/auth.ts`
- **Seed Script:** `/prisma/seed-complete.ts`
- **Password Fix Script:** `/scripts/fix-admin-password.ts`

- **User Creation Script:** `/scripts/create-admin-user.ts`
-

If Nothing Works

If all solutions fail:

1. Check Environment Variables:

```
bash
# In Cloud Run, verify NEXTAUTH_SECRET is set
gcloud run services describe ctrlpyme-app --region us-central1 --
format="value(spec.template.spec.containers[0].env)"
```

2. Verify Database Connection:

```
bash
# Test from Cloud Run environment
npx prisma db pull
```

3. Check NextAuth Configuration:

- Verify `NEXTAUTH_URL` matches deployment URL
- Ensure `NEXTAUTH_SECRET` is set and consistent

4. Contact for Support:

- Provide Cloud Run logs
 - Share output from `fix-admin-password.ts check`
 - Include any error messages
-

Additional Resources

- [NextAuth.js Credentials Provider Docs](https://next-auth.js.org/providers/credentials) (<https://next-auth.js.org/providers/credentials>)
 - [bcryptjs Documentation](https://www.npmjs.com/package/bcryptjs) (<https://www.npmjs.com/package/bcryptjs>)
 - [Cloud Run Troubleshooting](https://cloud.google.com/run/docs/troubleshooting) (<https://cloud.google.com/run/docs/troubleshooting>)
-

Last Updated: November 7, 2025

Status:  Solutions Implemented

Branch: `fix/auth-debugging-401`