

1

OverHAuL

2

Harnessing Automation for C Libraries via LLMs

3

Konstantinos Chousos

4

July, 2025

5 Lorem ipsum odor amet, consectetur adipiscing elit. Habitasse congue tempus erat rhoncus
6 sapien interdum dolor nec. Posuere habitant metus tellus erat eu. Risus ultricies eu rhoncus,
7 conubia euismod convallis commodo per. Nam tellus quisque maximus dui eleifend; arcu aptent.
8 Nisi rutrum primis luctus tortor tempor maecenas. Donec curae cras dolor; malesuada ultricies
9 scelerisque. Molestie class tincidunt quis gravida ut proin. Consequat lacinia arcu justo leo maecenas
10 nunc neque ex. Platea eros ullamcorper nullam rutrum facilisis.

Preface

12 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis sagittis posuere ligula sit amet lacinia.
13 Duis dignissim pellentesque magna, rhoncus congue sapien finibus mollis. Ut eu sem laoreet,
14 vehicula ipsum in, convallis erat. Vestibulum magna sem, blandit pulvinar augue sit amet, auctor
15 malesuada sapien. Nullam faucibus leo eget eros hendrerit, non laoreet ipsum lacinia. Curabitur
16 cursus diam elit, non tempus ante volutpat a. Quisque hendrerit blandit purus non fringilla. Integer
17 sit amet elit viverra ante dapibus semper. Vestibulum viverra rutrum enim, at luctus enim posuere
18 eu. Orci varius natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus.

19 Nunc ac dignissim magna. Vestibulum vitae egestas elit. Proin feugiat leo quis ante condimentum,
20 eu ornare mauris feugiat. Pellentesque habitant morbi tristique senectus et netus et malesuada fames
21 ac turpis egestas. Mauris cursus laoreet ex, dignissim bibendum est posuere iaculis. Suspendisse
22 et maximus elit. In fringilla gravida ornare. Aenean id lectus pulvinar, sagittis felis nec, rutrum
23 risus. Nam vel neque eu arcu blandit fringilla et in quam. Aliquam luctus est sit amet vestibulum
24 eleifend. Phasellus elementum sagittis molestie. Proin tempor lorem arcu, at condimentum purus
25 volutpat eu. Fusce et pellentesque ligula. Pellentesque id tellus at erat luctus fringilla. Suspendisse
26 potenti.

27 Etiam maximus accumsan gravida. Maecenas at nunc dignissim, euismod enim ac, bibendum ipsum.
28 Maecenas vehicula velit in nisl aliquet ultricies. Nam eget massa interdum, maximus arcu vel,
29 pretium erat. Maecenas sit amet tempor purus, vitae aliquet nunc. Vivamus cursus urna velit,
30 eleifend dictum magna laoreet ut. Duis eu erat mollis, blandit magna id, tincidunt ipsum. Integer
31 massa nibh, commodo eu ex vel, venenatis efficitur ligula. Integer convallis lacus elit, maximus
32 eleifend lacus ornare ac. Vestibulum scelerisque viverra urna id lacinia. Vestibulum ante ipsum
33 primis in faucibus orci luctus et ultrices posuere cubilia curae; Aenean eget enim at diam bibendum
34 tincidunt eu non purus. Nullam id magna ultrices, sodales metus viverra, tempus turpis.

35 Acknowledgments

36 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis sagittis posuere ligula sit amet lacinia.
37 Duis dignissim pellentesque magna, rhoncus congue sapien finibus mollis. Ut eu sem laoreet,
38 vehicula ipsum in, convallis erat. Vestibulum magna sem, blandit pulvinar augue sit amet, auctor
39 malesuada sapien. Nullam faucibus leo eget eros hendrerit, non laoreet ipsum lacinia. Curabitur
40 cursus diam elit, non tempus ante volutpat a. Quisque hendrerit blandit purus non fringilla. Integer
41 sit amet elit viverra ante dapibus semper. Vestibulum viverra rutrum enim, at luctus enim posuere
42 eu. Orci varius natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus.

Table of contents

44	1	Introduction	1
45	1.1	Motivation	1
46	1.2	Preview of following sections (rename)	2
47	2	Background	3
48	2.1	Fuzzing	3
49	2.1.1	Fuzzing examples	3
50	2.1.2	Fuzzer engines	3
51	2.2	Large Language Models (LLMs)	3
52	2.2.1	Prompting	4
53	2.2.2	LLM Programming Libraries (?)	4
54	2.3	Neurosymbolic AI	4
55	3	Related work	5
56	3.1	Previous projects	5
57	3.1.1	KLEE	5
58	3.1.2	IRIS	5
59	3.1.3	FUDGE	6
60	3.1.4	UTopia	6
61	3.1.5	FuzzGen	6
62	3.1.6	OSS-Fuzz	7
63	3.1.7	OSS-Fuzz-Gen	7
64	3.1.8	AutoGen	8
65	3.2	Differences	8
66	4	Overview	10
67	4.1	Architecture	10
68	5	Evaluation	11
69	5.1	Benchmarks	11
70	5.2	Performance	11
71	5.3	Issues	11
72	5.4	Future work	11
73	5.4.1	Technical future work	11
74	5.4.2	Architectural future work/extensions	11
75	6	Future work	12
76	7	Discussion	13

77	8 Conclusion	14
78	8.1 Acknowledgements	14
79	Bibliography	15

1 Introduction

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis sagittis posuere ligula sit amet lacinia. Duis dignissim pellentesque magna, rhoncus congue sapien finibus mollis. Ut eu sem laoreet, vehicula ipsum in, convallis erat. Vestibulum magna sem, blandit pulvinar augue sit amet, auctor malesuada sapien. Nullam faucibus leo eget eros hendrerit, non laoreet ipsum lacinia. Curabitur cursus diam elit, non tempus ante volutpat a. Quisque hendrerit blandit purus non fringilla. Integer sit amet elit viverra ante dapibus semper. Vestibulum viverra rutrum enim, at luctus enim posuere eu. Orci varius natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus.

Nunc ac dignissim magna. Vestibulum vitae egestas elit. Proin feugiat leo quis ante condimentum, eu ornare mauris feugiat. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris cursus laoreet ex, dignissim bibendum est posuere iaculis. Suspendisse et maximus elit. In fringilla gravida ornare. Aenean id lectus pulvinar, sagittis felis nec, rutrum risus. Nam vel neque eu arcu blandit fringilla et in quam. Aliquam luctus est sit amet vestibulum eleifend. Phasellus elementum sagittis molestie. Proin tempor lorem arcu, at condimentum purus volutpat eu. Fusce et pellentesque ligula. Pellentesque id tellus at erat luctus fringilla. Suspendisse potenti.

1.1 Motivation

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis sagittis posuere ligula sit amet lacinia. Duis dignissim pellentesque magna, rhoncus congue sapien finibus mollis. Ut eu sem laoreet, vehicula ipsum in, convallis erat. Vestibulum magna sem, blandit pulvinar augue sit amet, auctor malesuada sapien. Nullam faucibus leo eget eros hendrerit, non laoreet ipsum lacinia. Curabitur cursus diam elit, non tempus ante volutpat a. Quisque hendrerit blandit purus non fringilla. Integer sit amet elit viverra ante dapibus semper. Vestibulum viverra rutrum enim, at luctus enim posuere eu. Orci varius natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus.

Nunc ac dignissim magna. Vestibulum vitae egestas elit. Proin feugiat leo quis ante condimentum, eu ornare mauris feugiat. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris cursus laoreet ex, dignissim bibendum est posuere iaculis. Suspendisse et maximus elit. In fringilla gravida ornare. Aenean id lectus pulvinar, sagittis felis nec, rutrum risus. Nam vel neque eu arcu blandit fringilla et in quam. Aliquam luctus est sit amet vestibulum eleifend. Phasellus elementum sagittis molestie. Proin tempor lorem arcu, at condimentum purus volutpat eu. Fusce et pellentesque ligula. Pellentesque id tellus at erat luctus fringilla. Suspendisse potenti.

112 1.2 Preview of following sections (rename)

113 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis sagittis posuere ligula sit amet lacinia.
114 Duis dignissim pellentesque magna, rhoncus congue sapien finibus mollis. Ut eu sem laoreet,
115 vehicula ipsum in, convallis erat. Vestibulum magna sem, blandit pulvinar augue sit amet, auctor
116 malesuada sapien. Nullam faucibus leo eget eros hendrerit, non laoreet ipsum lacinia. Curabitur
117 cursus diam elit, non tempus ante volutpat a. Quisque hendrerit blandit purus non fringilla. Integer
118 sit amet elit viverra ante dapibus semper. Vestibulum viverra rutrum enim, at luctus enim posuere
119 eu. Orci varius natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus.

120 2 Background

121 2.1 Fuzzing

122 What is fuzzing [1].

123 terminology: fuzz campaign, harness, driver, target, corpus

124 Why fuzz?

125 2.1.1 Fuzzing examples

126 Heartbleed [2], shellshock [3].

127 2.1.2 Fuzzer engines

128 C/C++: AFL [4] & AFL++ [4, pp. ++]. LibFuzzer [5].

129 Python: Atheris [6].

130 Java, Rust etc...

131 An example of a fuzz target/harness can be seen in Listing 2.1 [5].

132 OSS-Fuzz: 2016, after heartbleed.

133 2.2 Large Language Models (LLMs)

134 Transformers [7], 2017–2025. ChatGPT/OpenAI history & context. Claude, Llama (1–3) etc.

Listing 2.1 A simple function that does something interesting if it receives the input “HI!”.

```
1 cat << EOF > test_fuzzer.cc
2 #include <stdint.h>
3 #include <stddef.h>
4 extern "C" int LLVMFuzzerTestOneInput(const uint8_t *data, size_t size) {
5     if (size > 0 && data[0] == 'H')
6         if (size > 1 && data[1] == 'I')
7             if (size > 2 && data[2] == '!')
8                 __builtin_trap();
9     return 0;
10 }
11 EOF
12 # Build test_fuzzer.cc with asan and link against libFuzzer.
13 clang++ -fsanitize=address,fuzzer test_fuzzer.cc
14 # Run the fuzzer with no corpus.
15 ./a.out
```

135 2.2.1 Prompting

136 Prompting techniques.

- 137 1. Zero-shot.
- 138 2. One-shot.
- 139 3. Chain of Thought [8].
- 140 4. ReACt [9].
- 141 5. Tree of Thoughts [10].

142 Comparison, strengths weaknesses etc. [11].

143 [12]

144 2.2.2 LLM Programming Libraries (?)

145 Langchain & LangGraph, LlamaIndex [13]–[15]. DSPy [16].

146 Comparison, relevance to our usecase.

147 2.3 Neurosymbolic AI

148 **TODO** [17]–[22].

3 Related work

Automated testing, automated fuzzing and automated harness creation have a long research history. Still, a lot of ground remains to be covered until true automation of these tasks is achieved. Until the introduction of transformers [7] and the 2020’s boom of commercial GPTs [23], automation regarding testing and fuzzing was mainly attempted through static and dynamic program analysis methods. These approaches are still utilized, but the fuzzing community has shifted almost entirely to researching the incorporation and employment of LLMs in the last half decade, in the name of automation [24]–[33].

3.1 Previous projects

3.1.1 KLEE

KLEE [34] is a seminal and widely cited symbolic execution engine introduced in 2008 by Cadar et al. It was designed to automatically generate high-coverage test cases for programs written in C, using symbolic execution to systematically explore the control flow of a program. KLEE operates on the LLVM [35] bytecode representation of programs, allowing it to be applied to a wide range of C programs compiled to the LLVM intermediate representation.

Instead of executing a program on concrete inputs, KLEE performs symbolic execution—that is, it runs the program on symbolic inputs, which represent all possible values simultaneously. At each conditional branch, KLEE explores both paths by forking the execution and accumulating path constraints (i.e., logical conditions on input variables) along each path. This enables it to traverse many feasible execution paths in the program, including corner cases that may be difficult to reach through random testing or manual test creation.

When an execution path reaches a terminal state (e.g., a program exit, an assertion failure, or a segmentation fault), KLEE uses a constraint solver to compute concrete input values that satisfy the accumulated constraints for that path. These values form a test case that will deterministically drive the program down that specific path when executed concretely.

3.1.2 IRIS

IRIS [24] is a 2025 open-source neurosymbolic system for static vulnerability analysis. Given a codebase and a list of user-specified Common Weakness Enumerations (CWEs), it analyzes source code to identify paths that may correspond to known vulnerability classes. IRIS combines symbolic analysis—such as control- and data-flow reasoning—with neural models trained to generalize over

code patterns. It outputs candidate vulnerable paths along with explanations and CWE references. The system operates on full repositories and supports extensible CWE definitions.

3.1.3 FUDGE

FUDGE [33] is a closed-source tool, made by Google, for automatic harness generation of C and C++ projects based on existing client code. It was used in conjunction with and in the improvement of Google’s OSS-Fuzz [36]. Being deployed inside Google’s infrastructure, FUDGE continuously examines Google’s internal code repository, searching for code that uses external libraries in a meaningful and “fuzzable” way (i.e. predominantly for parsing). If found, such code is **sliced** [37], per FUDGE, based on its Abstract Syntax Tree (AST) using LLVM’s Clang tool [35]. The above process results in a set of abstracted mostly-self-contained code snippets that make use of a library’s calls and/or API. These snippets are later **synthesized** into the body of a fuzz driver, with variables being replaced and the fuzz input being utilized. Each is then injected in an LLVMFuzzerTestOneInput function and finalized as a fuzzing harness. A building and evaluation phase follows for each harness, where they are executed and examined. Every passing harness along with its evaluation results is stored in FUDGE’s database, reachable to the user through a custom web-based UI.

3.1.4 UTopia

UTopia [29] (stylized UTOPIA) is another open-source automatic harness generation framework. Aside from the library code, It operates solely on user-provided unit tests since, according to Jeong, Jang, Yi, *et al.* [29], they are a resource of complete and correct API usage examples containing working library set-ups and tear-downs. Additionally, each of them are already close to a fuzz target, in the sense that they already examine a single and self-contained API usage pattern. Each generated harness follows the same data flow of the originating unit test. Static analysis is employed to figure out what fuzz input placement would yield the most results. It is also utilized in abstracting the tests away from the syntactical differences between testing frameworks, along with slicing and AST traversing using Clang.

3.1.5 FuzzGen

Another project of Google is FuzzGen [32], this time open-source. Like FUDGE, it leverages existing client code of the target library to create fuzz targets for it. FuzzGen uses whole-system analysis, through which it creates an *Abstract API Dependence Graph* (A^2DG). It uses the latter to automatically generate LibFuzzer-compatible harnesses. For FuzzGen to work, the user needs to provide both client code and/or tests for the API and the API library’s source code as well. FuzzGen uses the client code to infer the *correct usage* of the API and not its general structure, in contrast to FUDGE. FuzzGen’s workflow can be divided into three phases: **1. API usage inference.** By consuming and analyzing client code and tests that concern the library under test, FuzzGen recognizes which functions belong to the library and learns its correct API usage patterns. This process is done with the help of Clang. To test if a function is actually a part of the library, a sample program is created that uses it. If the program compiles successfully, then the function is indeed a valid API call. **2. A^2DG construction mechanism.** For all the existing API calls, FuzzGen

217 builds an A²DG to record the API usages and infers its intended structure. After completion, this
218 directed graph contains all the valid API call sequences found in the client code corpus. It is built
219 in a two-step process: First, many smaller A²DGs are created, one for each root function per client
220 code snippet. Once such graphs have been created for all the available client code instances, they
221 are combined to formulate the master A²DG. This graph can be seen as a template for correct usage
222 of the library. **3. Fuzzer generator.** Through the A²DG, a fuzzing harness is created. Contrary to
223 FUDGE, FuzzGen does not create multiple “simple” harnesses but a single complex one with the
224 goal of covering the whole of the A²DG. In other words, while FUDGE fuzzes a single API call at a
225 time, FuzzGen’s result is a single harness that tries to fuzz the given library all at once through
226 complex API usage.

227 3.1.6 OSS-Fuzz

228 OSS-Fuzz [36], [38] is a continuous, scalable and distributed cloud fuzzing solution for critical
229 and prominent open-source projects. Developers of such software can submit their projects to
230 OSS-Fuzz’s platform, where its harnesses are built and constantly executed. This results in multiple
231 bug findings that are later disclosed to the primary developers and are later patched.

232 OSS-Fuzz started operating in 2016, an initiative in response to the Heartbleed vulnerability [2],
233 [39], [40]. Its hope is that through more extensive fuzzing such errors could be caught and corrected
234 before having the chance to be exploited and thus disrupt the public digital infrastructure. So far,
235 it has helped uncover over 10,000 security vulnerabilities and 36,000 bugs across more than 1,000
236 projects, significantly enhancing the quality and security of major software like Chrome, OpenSSL,
237 and systemd.

238 A project that’s part of OSS-Fuzz must have been configured as a ClusterFuzz [41] project. Cluster-
239 Fuzz is the fuzzing infrastructure that OSS-Fuzz uses under the hood and depends on Google Cloud
240 Platform services, although it can be hosted locally. Such an integration requires setting up a build
241 pipeline, fuzzing jobs and expects a Google Developer account. Results are accessible through a
242 web interface. ClusterFuzz, and by extension OSS-Fuzz, supports fuzzing through LibFuzzer, AFL++,
243 Honggfuzz and FuzzTest—successor to Centipede— with the last two being Google projects [5],
244 [42]–[44]. C, C++, Rust, Go, Python and Java/JVM projects are supported.

245 3.1.7 OSS-Fuzz-Gen

246 OSS-Fuzz-Gen (OFG) [27], [45] is Google’s current State-Of-The-Art (SOTA) project regarding
247 automatic harness generation through LLMs. It’s purpose is to improve the fuzzing infrastructure of
248 open-source projects that are already integrated into OSS-Fuzz. Given such a project, OSS-Fuzz-Gen
249 uses its preexisting fuzzing harnesses and modifies them to produce new ones. Its architecture
250 can be described as follows: 1. With an OSS-Fuzz project’s GitHub repository link, OSS-Fuzz-
251 Gen iterates through a set of predefined build templates and generates potential build scripts
252 for the project’s harnesses. 2. If any of them succeed they are once again compiled, this time
253 through fuzz-introspector [46]. The latter constitutes a static analysis tool, with fuzzer developers
254 specifically in mind. 3. Build results, old harness and fuzz-introspector report are included in a
255 template-generated prompt, through which an LLM is called to generate a new harness. 4. The

newly generated fuzz target is compiled and if it is done so successfully it begins execution inside OSS-Fuzz’s infrastructure.

This method proved meaningful, with code coverage in fuzz campaigns increasing thanks to the new generated fuzz drivers. In the case of [47], line coverage went from 38% to 69% without any manual interventions [45].

In 2024, OSS-Fuzz-Gen introduced an experimental feature for generating harnesses in previously unfuzzed projects [48]. The code for this feature resides in the `experimental/from_scratch` directory of the project’s GitHub repository [27], with the latest known working commit being 171aac2 and the latest overall commit being four months ago.

3.1.8 AutoGen

AutoGen [25] is a closed-source tool that generates new fuzzing harnesses, given only the library code and documentation. It works as following: The user specifies the function for which a harness is to be generated. AutoGen gathers information for this function—such as the function body, used header files, function calling examples—from the source code and documentation. Through specific prompt templates containing the above information, an LLM is tasked with generating a new fuzz driver, while another is tasked with generating a compilation command for said driver. If the compilation fails, both LLMs are called again to fix the problem, whether it was on the driver’s or command’s side. This loop iterates until a predefined maximum value or until a fuzz driver is successfully generated and compiled. If the latter is the case, it is then executed. If execution errors exist, the LLM responsible for the driver generation is used to correct them. If not, the pipeline has terminated and a new fuzz driver has been successfully generated.

3.2 Differences

OverHAuL differs, in some way, with each of the aforementioned works. Firstly, although KLEE and IRIS [24], [34] tackle the problem of automated testing and both IRIS and OverHAuL can be considered neurosymbolic AI tools, the similarities end there. None of them utilize LLMs the same way we do—with KLEE not utilizing them by default, as it precedes them chronologically—and neither are automating any part of the fuzzing process.

When it comes to FUDGE, FuzzGen and UTopia [29], [32], [33], all three depend on and demand existing client code and/or unit tests. On the other hand, OverHAuL requires only the bare minimum: the library code itself. Another point of difference is that in contrast with OverHAuL, these tools operate in a linear fashion. No feedback is produced or used in any step and any point failure results in the termination of the entire run.

OverHAuL challenges a common principle of these tools, stated explicitly in FUDGE’s paper [33]: “Choosing a suitable fuzz target (still) requires a human”. OverHAuL chooses to let the LLM, instead of the user, explore the available functions and choose one to target in its fuzz driver.

OSS-Fuzz-Gen [27] can be considered a close counterpart of OverHAuL, and in some ways it is. A lot of inspiration was gathered from it, like for example the inclusion of static analysis and its

usage in informing the LLM. Yet, OSS-Fuzz-Gen has a number of disadvantages that make it in some cases an inferior option. For one, OFG is tightly coupled with the OSS-Fuzz platform [36], which even on its own creates a plethora of issues for the common developer. To integrate their project into OSS-Fuzz, they would need to: Transform it into a ClusterFuzz project [41] and take time to write harnesses for it. Even if these prerequisites are carried out, it probably would not be enough. Per OSS-Fuzz’s documentation [38]: “To be accepted to OSS-Fuzz, an open-source project must have a significant user base and/or be critical to the global IT infrastructure”. This means that OSS-Fuzz is a viable option only for a small minority of open-source developers and maintainers. One countermeasure of the above shortcoming would be for a developer to run OSS-Fuzz-Gen locally. This unfortunately proves to be an arduous task. As it is not meant to be used standalone, OFG is not packaged in the form of a self-contained application. This makes it hard to setup and difficult to use interactively. Like in the case of FUDGE, OFG’s actions are performed linearly. No feedback is utilized nor is there graceful error handling in the case of a step’s failure. Even in the case of the experimental feature for bootstrapping unfuzzed projects, OFG’s performance varies heavily. During experimentation, a lot of generated harnesses were still wrapped either in Markdown backticks or `tags, or were accompanied with explanations inside the generated .c source file. Even if code was formatted correctly, in many cases it missed necessary headers for compilation or used undeclared functions.`

Lastly, the closest counterpart to OverHAuL is AutoGen [25]. Their similarity stands in the implementation of a feedback loop between LLM and generated harness. However, most other implementation decisions remain distinct. One difference regards the fuzzed function. While AutoGen requires a target function to be specified by the user in which it narrows during its whole run, OverHAuL delegates this to the LLM, letting it explore the codebase and decide by itself the best candidate. Another difference lies in the need—and the lack of—of documentation. While AutoGen requires it to gather information for the given function, OverHAuL leans into the role of a developer by reading the related code and comments and thus avoiding any mismatches between documentation and code. Finally, the LLMs’ input is built based on predefined prompt templates, a technique also present in OSS-Fuzz-Gen. OverHAuL operates one abstraction level higher, leveraging DSPy [16] for programming instead of prompting the LLMs used.

In conclusion, OverHAuL constitutes an *open-source* tool that offers new functionality by offering a straightforward installation process, packaged as a self-contained Python package with minimal external dependencies. It also introduces novel approaches compared to previous work by

1. Implementing a feedback mechanism between harness generation, compilation, and evaluation phases,
2. Using autonomous ReAct agents capable of codebase exploration,
3. Leveraging a vector store for code consumption and retrieval.

329 4 Overview

- 330 1. How is it different?
 - 331 2. What does it offer?
 - 332 3. Example uses
 - 333 4. Scope of Usage
-
- 334 1. In what contexts does it work?
 - 335 2. Prerequisites

336 4.1 Architecture

- 337 • **System diagram**
- 338 • Main Library Architecture/Structure
- 339 • LLM usage
- 340 – Prompting techniques used (callback to Section [2.2.1](#)).
- 341 • Static analysis
- 342 • Code localization(?)
- 343 • Fuzzers
- 344 • GitHub Workflow/Usage

345 5 Evaluation

346 5.1 Benchmarks

347 Results from integration with 10/100 open-source C/C++ projects.

348 5.2 Performance

349 5.3 Issues

350 5.4 Future work

351 5.4.1 Technical future work

352 5.4.2 Architectural future work/extensions

- 353 1. Build system
- 354 2. More (static) analysis tools integrations
- 355 3. General *localization* problem

6 Future work

- More diverse build support
- More language support
- More fuzzers support
 - GraphFuzz [28]
- Experimentation with different LLM providers/models
 - Code-specific LLMs
 - * codex-1, <https://openai.com/index/introducing-codex/>
 - * codegen [49], [50]
- Different chunking techniques
- GitHub Action
- More sophisticated evaluation methods
- Usage of program slicing in static analysis step
- testing in all of clib
- PRs fixing found bugs
- More extensive comparison with OFG
- ablation study Project-by-project manually
- Token/\$ comparison
- leveraging of existing unit tests

375 **7 Discussion**

376 8 Conclusion

377 Recap

378 8.1 Acknowledgements

379 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis sagittis posuere ligula sit amet lacinia.
380 Duis dignissim pellentesque magna, rhoncus congue sapien finibus mollis. Ut eu sem laoreet,
381 vehicula ipsum in, convallis erat. Vestibulum magna sem, blandit pulvinar augue sit amet, auctor
382 malesuada sapien. Nullam faucibus leo eget eros hendrerit, non laoreet ipsum lacinia. Curabitur
383 cursus diam elit, non tempus ante volutpat a. Quisque hendrerit blandit purus non fringilla. Integer
384 sit amet elit viverra ante dapibus semper. Vestibulum viverra rutrum enim, at luctus enim posuere
385 eu. Orci varius natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus.

Bibliography

- [1] V. J. M. Manes, H. Han, C. Han, *et al.* “The Art, Science, and Engineering of Fuzzing: A Survey.” arXiv: [1812.00140 \[cs\]](https://arxiv.org/abs/1812.00140). (Apr. 7, 2019), [Online]. Available: [http://arxiv.org/abs/1812.00140](https://arxiv.org/abs/1812.00140), pre-published.
- [2] “Heartbleed Bug.” (Mar. 7, 2025), [Online]. Available: <https://heartbleed.com/>.
- [3] C. Meyer and J. Schwenk. “Lessons Learned From Previous SSL/TLS Attacks - A Brief Chronology Of Attacks And Weaknesses.” (2013), [Online]. Available: <https://eprint.iacr.org/2013/049>, pre-published.
- [4] “American fuzzy lop.” (), [Online]. Available: <https://lcamtuf.coredump.cx/afl/>.
- [5] “libFuzzer – a library for coverage-guided fuzz testing. — LLVM 21.0.0git documentation.” (2025), [Online]. Available: <https://llvm.org/docs/LibFuzzer.html>.
- [6] *Google/atheris*, Google, Apr. 9, 2025. [Online]. Available: <https://github.com/google/atheris>.
- [7] A. Vaswani, N. Shazeer, N. Parmar, *et al.* “Attention Is All You Need.” arXiv: [1706.03762 \[cs\]](https://arxiv.org/abs/1706.03762). (Aug. 1, 2023), [Online]. Available: [http://arxiv.org/abs/1706.03762](https://arxiv.org/abs/1706.03762), pre-published.
- [8] J. Wei, X. Wang, D. Schuurmans, *et al.* “Chain-of-Thought Prompting Elicits Reasoning in Large Language Models.” arXiv: [2201.11903 \[cs\]](https://arxiv.org/abs/2201.11903). (Jan. 10, 2023), [Online]. Available: [http://arxiv.org/abs/2201.11903](https://arxiv.org/abs/2201.11903), pre-published.
- [9] S. Yao, J. Zhao, D. Yu, *et al.* “ReAct: Synergizing Reasoning and Acting in Language Models.” arXiv: [2210.03629](https://arxiv.org/abs/2210.03629). (Mar. 10, 2023), [Online]. Available: [http://arxiv.org/abs/2210.03629](https://arxiv.org/abs/2210.03629), pre-published.
- [10] S. Yao, D. Yu, J. Zhao, *et al.* “Tree of Thoughts: Deliberate Problem Solving with Large Language Models.” arXiv: [2305.10601 \[cs\]](https://arxiv.org/abs/2305.10601). (Dec. 3, 2023), [Online]. Available: [http://arxiv.org/abs/2305.10601](https://arxiv.org/abs/2305.10601), pre-published.
- [11] P. Laban, H. Hayashi, Y. Zhou, and J. Neville. “LLMs Get Lost In Multi-Turn Conversation.” arXiv: [2505.06120 \[cs\]](https://arxiv.org/abs/2505.06120). (May 9, 2025), [Online]. Available: [http://arxiv.org/abs/2505.06120](https://arxiv.org/abs/2505.06120), pre-published.
- [12] N. Perry, M. Srivastava, D. Kumar, and D. Boneh. “Do Users Write More Insecure Code with AI Assistants?” arXiv: [2211.03622](https://arxiv.org/abs/2211.03622). (Dec. 18, 2023), [Online]. Available: [http://arxiv.org/abs/2211.03622](https://arxiv.org/abs/2211.03622), pre-published.
- [13] H. Chase, *LangChain*, Oct. 2022. [Online]. Available: <https://github.com/langchain-ai/langchain>.
- [14] *Langchain-ai/langgraph*, LangChain, May 21, 2025. [Online]. Available: <https://github.com/langchain-ai/langgraph>.
- [15] J. Liu, *LlamaIndex*, Nov. 2022. DOI: [10.5281/zenodo.1234](https://doi.org/10.5281/zenodo.1234). [Online]. Available: https://github.com/jerryliu/llama_index.

- [16] O. Khattab, A. Singhvi, P. Maheshwari, *et al.* “DSPy: Compiling Declarative Language Model Calls into Self-Improving Pipelines.” arXiv: 2310.03714 [cs]. (Oct. 5, 2023), [Online]. Available: <http://arxiv.org/abs/2310.03714>, pre-published.
- [17] D. Ganguly, S. Iyengar, V. Chaudhary, and S. Kalyanaraman. “Proof of Thought : Neurosymbolic Program Synthesis allows Robust and Interpretable Reasoning.” arXiv: 2409.17270. (Sep. 25, 2024), [Online]. Available: <http://arxiv.org/abs/2409.17270>, pre-published.
- [18] A. d’Avila Garcez and L. C. Lamb. “Neurosymbolic AI: The 3rd Wave.” arXiv: 2012.05876. (Dec. 16, 2020), [Online]. Available: <http://arxiv.org/abs/2012.05876>, pre-published.
- [19] M. Gaur and A. Sheth. “Building Trustworthy NeuroSymbolic AI Systems: Consistency, Reliability, Explainability, and Safety.” arXiv: 2312.06798. (Dec. 5, 2023), [Online]. Available: <http://arxiv.org/abs/2312.06798>, pre-published.
- [20] G. Grov, J. Halvorsen, M. W. Eckhoff, B. J. Hansen, M. Eian, and V. Mavroeidis. “On the use of neurosymbolic AI for defending against cyber attacks.” arXiv: 2408.04996. (Aug. 9, 2024), [Online]. Available: <http://arxiv.org/abs/2408.04996>, pre-published.
- [21] A. Sheth, K. Roy, and M. Gaur. “Neurosymbolic AI – Why, What, and How.” arXiv: 2305.00813 [cs]. (May 1, 2023), [Online]. Available: <http://arxiv.org/abs/2305.00813>, pre-published.
- [22] D. Tilwani, R. Venkataramanan, and A. P. Sheth. “Neurosymbolic AI approach to Attribution in Large Language Models.” arXiv: 2410.03726. (Sep. 30, 2024), [Online]. Available: <http://arxiv.org/abs/2410.03726>, pre-published.
- [23] “ChatGPT.” (2025), [Online]. Available: <https://chatgpt.com>.
- [24] Z. Li, S. Dutta, and M. Naik. “IRIS: LLM-Assisted Static Analysis for Detecting Security Vulnerabilities.” arXiv: 2405.17238 [cs]. (Apr. 6, 2025), [Online]. Available: <http://arxiv.org/abs/2405.17238>, pre-published.
- [25] Y. Sun, “Automated Generation and Compilation of Fuzz Driver Based on Large Language Models,” in *Proceedings of the 2024 9th International Conference on Cyber Security and Information Engineering*, ser. ICCSIE ’24, New York, NY, USA: Association for Computing Machinery, Dec. 3, 2024, pp. 461–468, ISBN: 979-8-4007-1813-7. DOI: 10.1145/3689236.3689272. [Online]. Available: <https://doi.org/10.1145/3689236.3689272>.
- [26] D. Wang, G. Zhou, L. Chen, D. Li, and Y. Miao. “ProphetFuzz: Fully Automated Prediction and Fuzzing of High-Risk Option Combinations with Only Documentation via Large Language Model.” arXiv: 2409.00922 [cs]. (Sep. 1, 2024), [Online]. Available: <http://arxiv.org/abs/2409.00922>, pre-published.
- [27] D. Liu, O. Chang, J. metzman, M. Sablotny, and M. Maruseac, *OSS-fuzz-gen: Automated fuzz target generation*, version <https://github.com/google/oss-fuzz-gen/tree/v1.0>, May 2024. [Online]. Available: <https://github.com/google/oss-fuzz-gen>.
- [28] H. Green and T. Avgerinos, “GraphFuzz: Library API fuzzing with lifetime-aware dataflow graphs,” in *Proceedings of the 44th International Conference on Software Engineering*, Pittsburgh Pennsylvania: ACM, May 21, 2022, pp. 1070–1081. DOI: 10.1145/3510003.3510228. [Online]. Available: <https://dl.acm.org/doi/10.1145/3510003.3510228>.

- [29] B. Jeong, J. Jang, H. Yi, *et al.*, “UTopia: Automatic Generation of Fuzz Driver using Unit Tests,” in *2023 IEEE Symposium on Security and Privacy (SP)*, May 2023, pp. 2676–2692. doi: [10.1109/SP46215.2023.10179394](https://doi.org/10.1109/SP46215.2023.10179394). [Online]. Available: <https://ieeexplore.ieee.org/abstract/document/10179394>.
- [30] Y. Deng, C. S. Xia, C. Yang, S. D. Zhang, S. Yang, and L. Zhang. “Large Language Models are Edge-Case Fuzzers: Testing Deep Learning Libraries via FuzzGPT.” arXiv: [2304.02014](https://arxiv.org/abs/2304.02014) [cs]. (Apr. 4, 2023), [Online]. Available: <http://arxiv.org/abs/2304.02014>, pre-published.
- [31] Y. Deng, C. S. Xia, H. Peng, C. Yang, and L. Zhang, “Large Language Models Are Zero-Shot Fuzzers: Fuzzing Deep-Learning Libraries via Large Language Models,” in *Proceedings of the 32nd ACM SIGSOFT International Symposium on Software Testing and Analysis*, ser. ISSTA 2023, New York, NY, USA: Association for Computing Machinery, Jul. 13, 2023, pp. 423–435, ISBN: 979-8-4007-0221-1. doi: [10.1145/3597926.3598067](https://doi.org/10.1145/3597926.3598067). [Online]. Available: <https://dl.acm.org/doi/10.1145/3597926.3598067>.
- [32] K. Ispoglou, D. Austin, V. Mohan, and M. Payer, “FuzzGen: Automatic fuzzer generation,” in *29th USENIX Security Symposium (USENIX Security 20)*, 2020, pp. 2271–2287. [Online]. Available: <https://www.usenix.org/conference/usenixsecurity20/presentation/ispoglou>.
- [33] D. Babić, S. Bucur, Y. Chen, *et al.*, “FUDGE: Fuzz driver generation at scale,” in *Proceedings of the 2019 27th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, Tallinn Estonia: ACM, Aug. 12, 2019, pp. 975–985, ISBN: 978-1-4503-5572-8. doi: [10.1145/3338906.3340456](https://doi.org/10.1145/3338906.3340456). [Online]. Available: <https://dl.acm.org/doi/10.1145/3338906.3340456>.
- [34] C. Cadar, D. Dunbar, and D. Engler, “KLEE: Unassisted and Automatic Generation of High-Coverage Tests for Complex Systems Programs,” presented at the USENIX Symposium on Operating Systems Design and Implementation, Dec. 8, 2008. [Online]. Available: <https://www.semanticscholar.org/paper/KLEE%3A-Unassisted-and-Automatic-Generation-of-Tests-Cadar-Dunbar/0b93657965e506dfbd56fbc1c1d4b9666b1d01c8>.
- [35] “The LLVM Compiler Infrastructure Project.” (2025), [Online]. Available: <https://llvm.org/>.
- [36] A. Arya, O. Chang, J. Metzman, K. Serebryany, and D. Liu, *OSS-Fuzz*, Apr. 8, 2025. [Online]. Available: <https://github.com/google/oss-fuzz>.
- [37] N. Sasirekha, A. Edwin Robert, and M. Hemalatha, “Program Slicing Techniques and its Applications,” *International Journal of Software Engineering & Applications*, vol. 2, no. 3, pp. 50–64, Jul. 31, 2011, ISSN: 09762221. doi: [10.5121/ijsea.2011.2304](https://doi.org/10.5121/ijsea.2011.2304). [Online]. Available: <http://www.airccse.org/journal/ijsea/papers/0711ijsea04.pdf>.
- [38] “OSS-Fuzz Documentation,” OSS-Fuzz. (2025), [Online]. Available: <https://google.github.io/oss-fuzz/>.
- [39] “CVE - CVE-2014-0160.” (2014), [Online]. Available: <https://cve.mitre.org/cgi-bin/cvename.cgi?name=cve-2014-0160>.
- [40] D. Wheeler. “How to Prevent the next Heartbleed.” (2014), [Online]. Available: <https://dwwheeler.com/essays/heartbleed.html>.
- [41] *Google/clusterfuzz*, Google, Apr. 9, 2025. [Online]. Available: <https://github.com/google/clusterfuzz>.
- [42] *Google/fuzztest*, Google, Jul. 10, 2025. [Online]. Available: <https://github.com/google/fuzztest>.

- 502 [43] *Google/honggfuzz*, Google, Jul. 10, 2025. [Online]. Available: <https://github.com/google/honggfuzz>.
503
- 504 [44] M. Heuse, H. Eißfeldt, A. Fioraldi, and D. Maier, *AFL++*, version 4.00c, Jan. 2022. [Online].
505 Available: <https://github.com/AFLplusplus/AFLplusplus>.
- 506 [45] D. Liu, J. Metzman, O. Chang, and G. O. S. S. Team. “AI-Powered Fuzzing: Breaking the
507 Bug Hunting Barrier,” Google Online Security Blog. (Aug. 16, 2023), [Online]. Available:
508 <https://security.googleblog.com/2023/08/ai-powered-fuzzing-breaking-bug-hunting.html>.
- 509 [46] *OSSF/fuzz-introspector*, Open Source Security Foundation (OpenSSF), Jun. 30, 2025. [Online].
510 Available: <https://github.com/ossf/fuzz-introspector>.
- 511 [47] L. Thomason, *Leethomason/tinysql2*, Jul. 10, 2025. [Online]. Available: <https://github.com/leethomason/tinysql2>.
512
- 513 [48] OSS-Fuzz Maintainers. “Introducing LLM-based harness synthesis for unfuzzed projects,” OSS-
514 Fuzz blog. (May 27, 2024), [Online]. Available: <https://blog.oss-fuzz.com/posts/introducing-llm-based-harness-synthesis-for-unfuzzed-projects/>.
515
- 516 [49] E. Nijkamp, H. Hayashi, C. Xiong, S. Savarese, and Y. Zhou, “CodeGen2: Lessons for training
517 llms on programming and natural languages,” *ICLR*, 2023.
- 518 [50] E. Nijkamp, B. Pang, H. Hayashi, *et al.*, “CodeGen: An open large language model for code
519 with multi-turn program synthesis,” *ICLR*, 2023.