

# Python For Data Science *Cheat Sheet*

## Pandas Basics

### Pandas

The **Pandas** library is built on NumPy and provides easy-to-use **data structures** and **data analysis** tools for the Python programming language.



Use the following import convention:

```
>>> import pandas as pd
```

### Pandas Data Structures

#### Series

A **one-dimensional** labeled array capable of holding any data type

a	3
b	-5
c	7
d	4

Index

```
>>> s = pd.Series([3, -5, 7, 4], index=['a', 'b', 'c', 'd'])
```

#### DataFrame

Columns		Country	Capital	Population
Index	0	Belgium	Brussels	11190846
	1	India	New Delhi	1303171035
	2	Brazil	Brasília	207847528

A **two-dimensional** labeled data structure with columns of potentially different types

```
>>> data = {'Country': ['Belgium', 'India', 'Brazil'],
           'Capital': ['Brussels', 'New Delhi', 'Brasília'],
           'Population': [11190846, 1303171035, 207847528]}
```

```
>>> df = pd.DataFrame(data,
                      columns=['Country', 'Capital', 'Population'])
```

### I/O

#### Read and Write to CSV

```
>>> pd.read_csv('file.csv', header=None, nrows=5)
>>> df.to_csv('myDataFrame.csv')
```

#### Read and Write to Excel

```
>>> pd.read_excel('file.xlsx')
>>> pd.to_excel('dir/myDataFrame.xlsx', sheet_name='Sheet1')

Read multiple sheets from the same file
>>> xlsx = pd.ExcelFile('file.xls')
>>> df = pd.read_excel(xlsx, 'Sheet1')
```

### Asking For Help

```
>>> help(pd.Series.loc)
```

### Selection

Also see NumPy Arrays

#### Getting

```
>>> s['b']
-5

>>> df[1:]
   Country  Capital  Population
1   India  New Delhi  1303171035
2  Brazil  Brasília  207847528
```

Get one element

Get subset of a DataFrame

### Selecting, Boolean Indexing & Setting

#### By Position

```
>>> df.iloc[[0], [0]]
'Belgium'

>>> df.iat([0], [0])
'Belgium'
```

Select single value by row & column

#### By Label

```
>>> df.loc[[0], ['Country']]
'Belgium'

>>> df.at([0], ['Country'])
'Belgium'
```

Select single value by row & column labels

#### By Label/Position

```
>>> df.ix[2]
Country      Brazil
Capital    Brasília
Population  207847528
```

Select single row of subset of rows

```
>>> df.ix[:, 'Capital']
0      Brussels
1    New Delhi
2    Brasilia
```

Select a single column of subset of columns

```
>>> df.ix[1, 'Capital']
'New Delhi'
```

Select rows and columns

#### Boolean Indexing

```
>>> s[~(s > 1)]
>>> s[(s < -1) | (s > 2)]
>>> df[df['Population'] > 1200000000]
```

Series *s* where value is not >1  
*s* where value is <-1 or >2  
Use filter to adjust DataFrame

#### Setting

```
>>> s['a'] = 6
```

Set index *a* of Series *s* to 6

### Dropping

```
>>> s.drop(['a', 'c'])
>>> df.drop('Country', axis=1)
```

Drop values from rows (axis=0)  
Drop values from columns(axis=1)

### Sort & Rank

```
>>> df.sort_index()
>>> df.sort_values(by='Country')
>>> df.rank()
```

Sort by labels along an axis  
Sort by the values along an axis  
Assign ranks to entries

### Retrieving Series/DataFrame Information

#### Basic Information

```
>>> df.shape
>>> df.index
>>> df.columns
>>> df.info()
>>> df.count()
```

(rows,columns)  
Describe index  
Describe DataFrame columns  
Info on DataFrame  
Number of non-NA values

#### Summary

```
>>> df.sum()
>>> df.cumsum()
>>> df.min()/df.max()
>>> df.idxmin()/df.idxmax()
>>> df.describe()
>>> df.mean()
>>> df.median()
```

Sum of values  
Cumulative sum of values  
Minimum/maximum values  
Minimum/Maximum index value  
Summary statistics  
Mean of values  
Median of values

### Applying Functions

```
>>> f = lambda x: x*2
>>> df.apply(f)
>>> df.applymap(f)
```

Apply function  
Apply function element-wise

### Data Alignment

#### Internal Data Alignment

NA values are introduced in the indices that don't overlap:

```
>>> s3 = pd.Series([7, -2, 3], index=['a', 'c', 'd'])
>>> s + s3
a      10.0
b       NaN
c       5.0
d       7.0
```

#### Arithmetic Operations with Fill Methods

You can also do the internal data alignment yourself with the help of the fill methods:

```
>>> s.add(s3, fill_value=0)
a      10.0
b      -5.0
c       5.0
d       7.0

>>> s.sub(s3, fill_value=2)
>>> s.div(s3, fill_value=4)
>>> s.mul(s3, fill_value=3)
```

#### Read and Write to SQL Query or Database Table

```
>>> from sqlalchemy import create_engine
>>> engine = create_engine('sqlite:///memory:')
>>> pd.read_sql("SELECT * FROM my_table;", engine)
>>> pd.read_sql_table('my_table', engine)
>>> pd.read_sql_query("SELECT * FROM my_table;", engine)
```

`read_sql()` is a convenience wrapper around `read_sql_table()` and `read_sql_query()`

```
>>> pd.to_sql('myDf', engine)
```