

# Application of Neural Networks in Medical Image Processing

Zhenghao Shi<sup>1</sup>, and Lifeng He<sup>2</sup>

<sup>1</sup> School of Computer Science and Engineering, Xi'an University of Technology, Xi'an, China  
ylshi@xaut.edu.cn

<sup>2</sup> School of Information Science and Technology, Aichi Prefectural University, Nagoya, Japan  
helifeng@ist.aichi-pu.ac.jp

**Abstract**—This paper reviews the application of artificial neural networks in medical image preprocessing, in medical image object detection and recognition. Main advantages and drawbacks of artificial neural networks were discussed. By this survey, the paper try to answer what the major strengths and weakness of applying neural networks for medical image processing would be.

**Index Terms**—Neural Network; Medical Image preprocessing; Object Detection; Computer Aided Diagnosis

## I. INTRODUCTION

In the past years, artificial neural networks (ANNs) have seen an an increasingly interests in medical image processing[1]-[2]. According to our searching results with Google Scholar, more than 33000 items were found on the topic of medical image processing with ANNs during the past 16 years. The intention of this article is to cover those approaches introduced and to make a map for ANN techniques used for medical image processing. Instead of trying to cover all the issues and research aspects of ANNs in medical image processing, we focus our discussion on three major topics: medical image preprocessing, medical image segmentation, and medical image object detection and recognition. We do not contemplate to go into details of particular algorithms or describe results of comparative experiments, rather we want to summarize main approaches and point out interesting parts of the neural networks for medical image processing, further more by this survey, we try to answer what the major strengths and weaknesses of applying ANNs for medical image processing would be.

## II. APPLICATIONS OF NEURAL NETWORKS IN MEDICAL IMAGE PROCESSING

### A. Preprocessing

Image preprocessing with neural networks generally falls into one of the following two categories: image reconstruction and image restoration. The Hopfield neural network is one of the most used neural works for image reconstruction [3]-[7]. Of our reviewed literatures related to this areas, Hopfield neural network based methods pose 55 percent. The major advantage of using Hopfield neural network for medical image reconstruction is that the problem of medical image reconstruction can be taken as an optimization problem, which is easily solved by

letting the network converge to a stable state while minimizing the energy function.

Reconstruction of images in electrical impedance tomography requires the solution of a nonlinear inverse on noisy data. This problem is typically ill-conditioned and requires either simplifying assumptions or regularization based on a priori knowledge. The feed forward neural network [8]-[9] and the self-organizing Kohonen neural network [10]-[11], which pose 2 of 9 papers among our reviewed literatures, respectively, seem to have more advantage for such medical image reconstruction compared with other techniques, they can calculate a linear approximation of the inverse problem directly from finite element simulations of the forward problem.

The majority of applications of neural networks in medical image preprocessing are found in medical image restoration, 13 of 24 papers among our reviewed literatures focused their interests here [12]-[21]. Among which, one paper for Hopfield neural network, seven papers for the feed forward neural network, and two papers for fuzzy neural network and for cellular neural network, respectively. In the most basic medical image restoration approach, noise is removed from an image by filtering. Suzuki et al. developed neural network based filters (NFs) for this problem [12]-[14]. Suzuki et al. also proposed a new neural edge enhancer (NEE) based on a modified multilayer neural network, for enhancing the desired edges clearly from noisy images [15]. The NEE is a supervised edge enhancer: Through training with a set of input noisy images and teaching edges, the NEE acquires the function of a desired edge enhancer. Compared with conventional edge enhancers, the NEE was robust against noise, was able to enhance continuous edges from noisy images, and was superior to the conventional edge enhancers in similarity to the desired edges.

### B. Image segmentation

The feed forward neural network is the most used neural network for medical image segmentation. Among our reviewed papers, 6 of 17 papers employed the feed forward network for medical image segmentation [22]-[27]. Compared with the traditional Maximum Likelihood Classifier (MLC) based image segmentation method, it has been observed that the feed forward neural networks-based segmented images appear less noisy, and the feed forward neural networks classifier is also less sensitive to

the selection of the training sets than the MLC. However, most feed forward neural network based methods have a very slow convergence rate and require a priori learning parameters. These drawbacks limited the application of feed forward neural networks in medical image segmentation.

Hopfield neural networks were introduced as a tool for finding satisfactory solutions to complex optimization problems. This makes them an interesting alternative to traditional optimization algorithms for medical image reconstruction which can be formulated as optimization problem. Among our reviewed literatures, 4 of 17 paper used Hopfield neural network to segment some organs from a medical image [28]-[31].

### C. Object detection and recognition

For using neural networks for medical image detection and recognition, the back propagation neural network poses most places, 11 of 23 papers among our reviewed literatures employed it [37]-[47]. Compared with conventional image recognition methods, no matter used for the interpretation of mammograms [37], or used for cold lesion detection in SPECT image [38], or used for diagnosing classes of liver diseases based on ultrasonographic [39], or used for separation of melanoma from three benign categories of tumors [41], or distinguish interstitial lung diseases [42], or used for reduction of false positives in computerized detection of lung nodules in LDCT [43]-[46] and chest radiography [47], all these feed forward neural network based methods show their preference in recognition accuracy and computing time compared with conventional methods.

Other neural networks, i.e. Hopfield neural network [48], ART neural network [49], radial basis function neural network [50], Probabilistic Neural Network [51], convolution neural network [53]-[56], and fuzzy neural network [52] [57], have also found their position in medical image detection and recognition, which poses 1 of 23, 1 of 23, 1 of 23, 1 of 23, 2 of 23 and 2 of 23 papers, respectively.

Different from what mentioned above, in [58] and [59], artificial neural network ensembles are employed for cancer detection. The ensemble is built on two-level ensemble architecture. The first-level ensemble is used to judge whether a cell is normal with high confidence where each individual network has only two outputs respectively *normal cell* or *cancer cell*. The predictions of those individual networks are combined by some a method. The second-level ensemble is used to deal with the cells that are judged as cancer cells by the first-level ensemble, where each individual network has several outputs respectively, each of which represents a different type of lung cancer cells. The predictions of those individual networks are combined by a prevailing method, i.e. *plurality voting*. Experiments show that the neural network ensemble can achieve not only a high rate of overall identification but also a low rate of false negative identification, i.e. a low rate of judging cancer cells to be normal ones, which is important in saving lives due to reducing missing diagnoses of cancer patients.

## III. DISCUSSION

From the reviewed literatures, we find that no matter what neural network model employed for medical image processing, compared with conventional image processing methods, the time for applying a trained neural network to solve a medical image processing problem was negligibly small, though the training of a neural network is a time cost work and also medical image processing tasks often require quite complex computation [12]-[15]. We think that this may be the major contribution of using neural network for solving medical image processing tasks.

Despite their success story in medical image processing, artificial neural networks have several major disadvantages compared to other techniques.

The first one is that a neural network is hard to express human expert's knowledge and experience, and the construction of its topological structure lacks of theoretical methods [60]. Moreover the physical meaning of its joint weight is not clear. All these can make the image processing method by neural networks unstable. A solution to these problems may be to combines fuzzy technique with neural networks together by using neural networks to process fuzzy information. It provides neural networks the ability to express qualitative knowledge, and network topological structure and joint weight have clear physical meaning. Also, it can make the initialization of network easier, avoid the local optimization of network training, and ensure the stability of networks [61].

The second problem relates to the amount of input data. For achieving a high and reliable performance for non-training cases, a large number of training cases are commonly required [62] [63]. If an ANN is trained with only a small number of cases, the generalization ability (performance for non-training cases) will be lower (e.g., the ANN may fit only the training cases). Because medical images are progressing rapidly as technology advances, the timely development of CAD schemes is important. However, it is very difficult to collect a large number of abnormal cases for training, particularly for a CAD scheme with a new modality, such as lung cancer screening with multi-detector-row CT. This significantly degraded the results obtained.

## REFERENCES

- [1] Kunio Doi, "Computer-Aided Diagnosis in Medical Imaging: Historical Review, Current Status and Future Potential," *Computerized Medical Imaging and Graphics*. vol.31,no.4-5, pp.198-211, July 2007.
- [2] Miller A.S, Blott B.H, Hames T.K. , "Review of Neural Network Applications in Medical Imaging and Signal Processing," *Medical and Biological Engineering and Computing*. vol.30, no.5,pp.449-464, September 1992.
- [3] A. Cichocki, R. Unbehauen, M. Lendl, K. Weinzierl, "Neural Networks for Linear Inverse Problems with Incomplete Data Especially in Applications to Signal and Image Reconstruction," *Neurocomputing*.vol.8, no.1, pp.7-41, May 1995.
- [4] W. Warsito, L.S. Fan, "Neural Network Based Multi-Criterion Optimization Image Reconstruction Technique

- for Imaging Two and Three Phase Flow Systems Using Electrical Capacitance Tomography," *Chemical Engineering and Processing*. Vol.42, no.8-9, pp.2198-2210, April 2001.
- [5] B. Su, Y. Zhang, L. Peng, D. Yao, B. Zhang, "the Use of Simultaneous iterative reconstruction technique for electrical capacitance tomography," *Chemical Engineering Journal*. Vol.77, no.1-2, pp.37-41, April 2000.
  - [6] Y. Wang, F.M. Wahl, "Vector-Entropy Optimization-Based Neural-Network Approach to Image Reconstruction from Projections," *IEEE Trans. Neural Networks*. Vol.8, no.5, pp.1008-1014, September 1997.
  - [7] Y. Wang, P. Heng, F.M. Wahl, "Image Reconstructions from Two Orthogonal Projections," *International Journal of Imaging Systems and Technology*. vol.13, no.2, pp.141-145, Aug. 2003.
  - [8] F. Ali, Z. Nakao, Y.-W. Chen, K. Matsuo, I. Ohkawa, "An Adaptive Backpropagation Algorithm for Limited-Angle CT Image Reconstruction," *IEICE Trans. Fundamentals*. Vol.E83-A, no.6, pp.1049-1058, 2000.
  - [9] A. Netajatali, I.R. Ciric, "An Iterative Algorithm for Electrical Impedance Imaging Using Neural Networks," *IEEE Trans. Magn.* Vol.34, no.5, pp.2940-2943, September 1998.
  - [10] C. Comtat, C. Morel, "Approximate Reconstruction of PET Data with a Self-Organizing Neural Network," *IEEE Trans. Neural Networks*. Vol.6, no.3, pp.783-789, May 1995.
  - [11] A. Adler, R. Guardo, "A Neural Network Image Reconstruction Technique for Electrical Impedance Tomography," *IEEE Transactions on Medical Imaging*. Vol.13, no.4, pp.594-600, 1994.
  - [12] Kenji Suzuki, Isao Horiba, Noboru Sugie and Michio Nanki, "Neural Filter with Selection of Input Features and Its Application to Image Quality Improvement of Medical Image Sequences," *IEICE Transaction on Information and Systems*. Vol.E85, no.10, pp.1710-1718, 2002.
  - [13] K. Suzuki, I. Horiba, and N. Sugie, "A Simple Neural Network Pruning Algorithm with Application to Filter Synthesis," *Neural Process. Lett.* Vol.11, no.1, pp.45-53, February 2001.
  - [14] K. Suzuki et al., "Efficient Approximation of Neural Filters for Removing Quantum Noise from Images," *IEEE Trans. Signal Process.* vol.50, no.7, pp.1787-1799, July 2002.
  - [15] K. Suzuki et al., "Neural Edge Enhancer for Supervised Edge Enhancement from Noisy Images," *IEEE Trans. Pattern Anal. Mach. Intell.* Vol.25, no.12, pp.1582-1596, December 2003.
  - [16] Chuan Yu Chang, "Contextual-Based Hopfield Neural Network for Medical Image Edge Detection," *Optical Engineering*. Vol.45, pp.37006-37015, March 2006.
  - [17] Clarke, L.P., Wei Qian, "Fuzzy Logic Adaptive Neural Networks for Nuclear Medicine Image Restorations," *Proceedings of the 20th Annual International Conference of the IEEE*. Vol.3, pp.1363-1366, June 1998.
  - [18] Qian W., Li H., Kallergi M., Song D., Clarke L.P., "Adaptive Neural Network for Nuclear Medicine Image Restoration," *The Journal of VLSI Signal Processing*. Vol.18, no.3, pp.297-315, April 1998.
  - [19] N. Aizenberg, I. Aizenberg, T.P. Belikova, "Extraction and Localization of Important Features in Gray-Scale Images: Implementation with CNNs," *Proceedings of the IEEE International Workshop on Cellular Neural Networks and their Applications CNNA, Rome, Italy, IEEECS Press, Silver Springs*, pp.207-212, December 1994.
  - [20] I. Aizenberg, "Processing of Noisy and Small-Detailed Gray-Scale Images Using Cellular Neural Networks," *Journal of Electronic Imaging*. vol.6, no.3, pp.272-285, July 1997.
  - [21] I. Aizenberg, "Multi-Valued Non-linear Filters and Their Implementation on Cellular Neural Networks," *Frontiers in Artificial Intelligence and Applications*. Vol.41, pp.135-140, 1997.
  - [22] Du Yih TSAI, "Automatic Segmentation of Liver Structure in CT Images Using a Neural Network," *IEICE TRANSACTIONS on Fundamentals of Electronics, Communications and Computer Sciences*. Vol. E77-A, no. 11, pp.1892-1895, November 1994.
  - [23] A.Hasegawa, S.C.B. Lo, J.S. Lin, M.T. Freedman and S.K. Mun, "A Shift-Invariant Neural Network for the Lung Field Segmentation in Chest Radiography," *The Journal of VLSI Signal Processing*. Vol. 18, no. 3, pp.241-250, April 1998.
  - [24] Mehmed Ozkan, Benoit M. Dawant and Robert Margolin, "Neural- Network-Based Segmentation of Multi-Modal Medical Images: A Comparative and Prospective Study," *IEEE Transactions on Medical Imaging*. Vol.12, no.3, pp.534-544, September 1993.
  - [25] Yan Li Peng Wen Powers, D. Clark, C.R, "LSB Neural Network Based Segmentation of MR Brain Images," *Systems, Man, and Cybernetics*. Vol.6, pp.822-825, 1999.
  - [26] Ian Middleton and Robert I. Damper, "Segmentation of Magnetic Resonance Images Using a Combination of Neural Networks and Active Contour Models," *Medical Engineering & Physics*. Vol.26, no.1, pp.71-86, January 2004.
  - [27] Chiou GI, Hwang JN, "A Neural Network-Based Stochastic Active Model (NNS-SNAKE) for Contour Finding of Distinct Features," *IEEE Trans Image Process*. Vol.4, no.10, pp.1407-1416, October 1995.
  - [28] John E. Koss, F.D. Newman FD, T.K. Johnson, and D.L. Kirch, "Abdominal Organ Segmentation Using Texture Transforms and a Hopfield Neural Network," *IEEE Transactions on Medical Imaging*. vol.18, no.7, pp.640-648, July 1999.
  - [29] Jzau-Sheng Lin, Kuo-Sheng Cheng, Chi-Wu Mao, "A Fuzzy Hopfield Neural Network for Medical Image Segmentation," *IEEE Transactions on Nuclear Science*. Vol.43, no.4, pp.2389-2398, August 1996.
  - [30] Chwen Liang Chang and Yu Tai Ching, "Fuzzy Hopfield Neural Network with Fixed Weight for Medical Image Segmentation," *Optical Engineering*. Vol.41, no.2, pp.351-358, 2002.
  - [31] K.S. Cheng, J.S. Lin, C.W. Mao, "the Application of Competitive Hopfield neural network to Medical Image Segmentation," *IEEE Transactions on Medical Imaging*. Vol.15, no.4, pp.560-567, August 1996.
  - [32] Wei Sun and Yaonan Wang, "Segmentation Method of MRI Using Fuzzy Gaussian Basis Neural Network," *Neural Information Processing*. Vol.8, no.2, pp.19-24, August 2005.
  - [33] Chien-Cheng Lee, and Pau-Choo Chung, "Recognizing Abdominal Organs in CT Images Using Contextual Neural Networks and Fuzzy Rules," In *Proc. of Int. Conf. of the IEEE Engineering in Medicine and Biology Society*, pp. 1745-1748, Chicago, IL, July 23-28 2000.
  - [34] Y. Wang, T. Adali, S.Y. Kung et al., "Quantification and Segmentation of Brain Tissues from MR Images - a Probabilistic Neural Network Approach," *IEEE Transactions on Image Processing*. Vol.7, no.8, pp.1165-1181, August 1998.
  - [35] W.E. Reddick, J.O. Glass, E.N. Cook et al., "Automated Segmentation and Classification of Multispectral Magnetic Resonance Images of Brain Using Artificial Neural

- Networks," *IEEE Trans. Med. Imaging*. Vol.16, no.6, pp.911-918, December 1997.
- [36] A.Pitiot, A.W.Toga, N.Ayache, P.Thompson,"Texture Based MRI Segmentation with a Two-Stage Hybrid Neural Classifier," *Proceedings of the 2002 International Joint Conference on Neural Networks*.vol.3, pp.2053-2058, 12-17 May 2002.
- [37] Wu Y, Giger ML, Doi K et al,"Artificial Neural Network in Mammography: Application to Decision Making in the Diagnosis of Breast Cancer," *Radiology*. Vol.187, pp.81-87, April 1993.
- [38] Tourassi GD, Floyd CE Jr,"Artificial Neural Networks for Single Photon Emission Computed Tomography," *Invest Radiol*. Vol.28, no.8 , pp.671-677, August 1993.
- [39] Maclin PS, Dempsey J,"Using Artificial Neural Networks to Diagnose Hepatic Masses,"*Journal of Medical Systems*. Vol.16, no.5, pp.215-225, October 1992.
- [40] Wolberg WH, Sreet WN, Mangasarian OL,"Image Analysis and Machine Learning Applied to Breast Cancer Diagnosis and Prognosis," *Anal Quant Cytol Histol*. Vol.17, no.2, pp.77-87, April 1995.
- [41] Fikret Ercal, Anurag Chawla, William V. Stoecker, His-Chieh Lee, and Randy H. Moss,"Neural Network Diagnosis of Malignant Melanoma from Color Images," *IEEE Transactions on biomedical engineering*. Vol.41, no.9 , pp.837-845,September 1994.
- [42] Ashizawa K, Ishida T, MacMahon H, Vyborny CJ, Katsuragawa S, Doi K,"Artificial Neural Networks in Chest Radiography: Application to the Differential Diagnosis of Interstitial Lung Disease," *Academic Radiology*. Vol.6, no.1, pp.2-9, January 1999.
- [43] K. Suzuki, S. G. Armato, F. Li, S. Sone, and K. Doi,"Massive Training Artificial Neural Network (MTANN) for Reduction of False Positives in Computerized Detection of Lung Nodules in Low-Dose CT," *Med. Phys*. Vol.30, no.7, pp.1602-1617, July 2003.
- [44] K. Suzuki, S. G. Armato, F. Li, S. Sone, and K. Doi,"Effect of a Small Number of Training Cases on the Performance of Massive Training Artificial Neural Network (MTANN) for Reduction of False Positives in Computerized Detection of Lung Nodules in Low-Dose CT," In *Proc. SPIE (Medical Imaging)*. Vol.5023, pp.1355-1366, July 2003.
- [45] K. Suzuki and K. Doi,"Characteristics of a Massive Training Artificial Neural Network (MTANN) in the Distinction Between Lung Nodules and Vessels in CT images," in *Computer Assisted Radiology and Surgery (CARS)*, Chicago, IL, pp.923-928, 2004.
- [46] H. Arimura, S. Katsuragawa, K. Suzuki, F. Li, J. Shiraishi, S. Sone, and K. Doi,"Computerized Scheme for Automated Detection of Lung Nodules in Low-Dose CT Images for Lung Cancer Screening," *Acad. Radiol*. Vol.11, no.6, pp.617-629, June 2004.
- [47] K. Suzuki, J. Shiraishi, H. Abe, H. MacMahon, and K. Doi,"False-Positive Reduction in Computer-Aided Diagnostic Scheme for Detecting Nodules in Chest Radiographs by Means of Massive Training Artificial Neural Network," *Acad. Radiol*. Vol.12, no.2 , pp.191-201, February 2005.
- [48] Zhu Y, Yan H,"Computerized Tumor Boundary Detection Using a Hopfield Neural Network," *IEEE Transactions on Medical Imaging*. Vol.16, no.1 , pp.55-67, February 1997.
- [49] Innocent PR, Barnes M, John R,"Application of the Fuzzy ART/MAP and MinMax/MAP Neural Network Models to Radiographic Image Classification," *Artif. Intell. in Med*. Vol.11, no.3, pp.241-263, 1997.
- [50] Yasser M. Kadah, Aly A. Farag, Jacek M. Zaruda, Ahmed M. Badawi, and Abou-Bakr M. Youssef,"Classification Algorithms for Quantitative Tissue Characterization of Diffuse Liver Disease from Ultrasound Images," *IEEE transactions on Medical Imaging*. Vol.15, no.4, pp.466-478, August 1996.
- [51] E-Liang Chen, Pau-CHoo Chung, Ching-Liang Chen, Hong-Ming Tsai and Chein I Chang,"An Automatic Diagnostic system for CT Liver Image Classification," *IEEE Transactions Biomedical Engineering*. Vol.45, no.6, pp.783-794, June 1998.
- [52] Pavlopoulos.S, Kyriacou.E, Koutsouris.D, Blekas.K, Stafylopatis.A, Zoumpoulis.P,"Fuzzy Neural Network-Based Texture Analysis of Ultrasonic Images," *IEEE Engineering in Medicine and Biology*. Vol.19, no.1, pp.39-47, Jan-Feb. 2000.
- [53] H.P. Chan, S.C.B. Lo, B. Sahiner et al,"Computer-Aided Detection of Mammographic Microcalcifications: Pattern Recognition with an Artificial Neural Network," *Medical Physics* vol. 22, no.10, pp.1555-1567, October 1995.
- [54] B. Sahiner, H.P. Chan, N. Petrick et al,"Classification of Mass and Normal Breast Tissue - a Convolution Neural Network Classifier with Spatial Domain and Texture Images," *IEEE Transactions on Medical Imaging*. Vol.15, no.5, pp.598-610, October 1996.
- [55] S.C.B. Lo, H.P. Chan, J.S. Lin et al, "Artificial Convolution Neural Network for Medical Image Pattern Recognition," *Neural Networks*. Vol.8, no.7-8 ,pp.1201-1214, 1995.
- [56] H P Chan *et al*, "Computerized Classification of Malignant and Benign Microcalcifications on Mammograms: Texture Analysis Using an Artificial Neural Network," *Phys. Med. Biol*. Vol.42, no.3 , pp.549-567, March 1997.
- [57] B. Verma, J. Zakos, "A Computer-Aided Diagnosis System for Digital Mammograms Based on Fuzzy-Neural and Feature Extraction Techniques," *IEEE Transactions on Information Technology in Biomedicine*. Vol.5, no.1 , pp.46-54, March 2001.
- [58] Zhi Hua Zhou, Yuan Jiang, Yu Bin Yang, Shi Fu Chen, "Lung Cancer Cell Identification Based on Artificial Neural Network Ensembles," *Artificial Intelligence in Medicine*. Vol.24, no.1, pp.25-36, January 2002.
- [59] K.Tumer, N.Ramanujam, J. Ghosh, and R. Richards-Kortum, "Ensembles of Radial Basis Function Networks for Spectroscopic detection of Cervical Precancer," *IEEE Transactions on Biomedical*. Vol.45, no.8, pp.953-961, August 1998.
- [60] L.Perlovsky,"Conundrum of combinatorial complexity," *IEEE Transactions on Pattern Analysis and Machine Intelligence*. Vol.20, no.6, pp.666-670, June 1998.
- [61] S. Horikawa, T. Furuhashi, and Y. Uchikawa,"On Fuzzy Modeling Using Neural Networks with the Back Propagation Algorithm,"*IEEE Trans. on Neural Networks*. Vol.3, no.5, pp.801-806, September 1992.
- [62] Chan HP, Sahiner B, Wagner RF, et al,"Classifier Design for Computer Aided Diagnosis: Effects of Finite Sample Size on the Mean Performance of Classical and Neural Network Classifiers," *Med Phys*. Vol.26, no.12, pp.2654-2668, 1999.
- [63] Sahiner B, Chan H P, Petrich N, et al," Feature Selection and Classifier Performance in Computer Aided Diagnosis: the Effect of Finite Sample Size," *Med Phys*. Vol.27, no.1, pp.1509-1522, June 2000.