# Class 8

[w200] MIDS Python Bridge Course Spring 2018

#### **Course Content** | moving into **OOP**

- Unit 1 | Introduction, the Command Line, Source Control
- Unit 2 | Starting Out with Python
- Unit 3 | Sequence Types and Dictionaries
- Unit 4 | More About Control and Algorithms
- Unit 5 | Functions
- Unit 6 | Modules and Packages
- Unit 7 | Classes
- Unit 8 | Object-Oriented Programming

### **Agenda**

#### Homework Review

Midterm (10% of final grade)

Inheritance and Polymorphism

Breakout

Midterm Review

Project 1 Discussion

#### **Homework 6 - Scrabble Grading**

- Overall: Really nice (and varied) Scrabble Implementations
- Good Algorithm design:
  - Iterated through scrabble words list only once
  - For wildcards: Did NOT make a list of all possible rack letters
- Compared words to rack while keeping track of wildcards:
  - If word length > rack length immediately discard (& move to next word)
  - If letter not in rack & no wildcards discard
    - i. If wildcards, word could be 'off' by that many letters (1 or 2)
    - ii. If word was off by more than # of wildcards discard
  - If word passes above tests add to valid word list & go to next word

#### **Homework 6 - Top Questions**

- Tabs v Spaces
  - Eternal debate!
  - A reason 4 spaces are better: 4 spaces = 4 spaces wherever you copy and paste the code to; 1 tab isn't necessarily 4 spaces (tab sizes are different, space size is not)
- 79 Character Limit
  - A little arbitrary today (with wide-screen monitors etc)
  - Comes from when UNIX default windows were 80 characters wide
  - Designed to increase readability of code
  - Jupyter nb does not wrap code so code could continue off the screen to the right

#### **Homework 6 - Top Questions**

#### Docstings

Usually done after defining a function to indicate the input arguments and type,
 what the function does and what the function returns; Ex:

#### def function\_with\_docstring(param1, param2):

```
"""This function takes a string, param2, and checks if a number, param1, is in that string.
```

#### Args:

```
param1 (int): The number to check for param2 (str): The string to check
```

#### Returns:

bool: True for success, False otherwise.

#### **Homework 6 - Top Questions**

- Autoformat PEP8?
  - Yes in PyCharm (and maybe others)
  - Might be better in the long run just to start coding that way (in case the tool isn't available)
- Dunder is the \_\_ (like in \_\_init\_\_)
  - Invoked 'behind the scenes' that is, you don't specifically call that method
  - Using \_\_init\_\_ as an example its a method that is automatically called when you first substantiate that object
- Public vs private variables
  - Private Variables are annotated by a dundar \_\_ or one \_ (like \_\_count)
  - Means: that variable is only accessed by that class not from outside that class
  - Python doesn't 'truly' have private variables can still modify these
     (in other languages, private variables cannot be modified outside of the class)

#### **Assignment Review** | Week 7

Due date moved back one week:

- Mon, March 5th for Tuesday classes
- Wed, March 7th for Thursday classes

**Questions & Problem Areas?** 

# **Assignment Review** | Project

Reminder: Your proposal was due, but treat it as your <a href="https://hypothesis">hypothesis</a> as to how you'll solve the problem. You have two weeks to implement, refine, and adjust!

Next week you will have time to discuss your progress and outstanding issues with your breakout group.

#### Reminders |

#### **Course Schedule**

https://docs.google.com/spreadsheets/d/1Skg\_b0rM5jPcVg0ixGrPnK5-QCGrHaF Vr1afqchUN5c

## **Agenda**

Homework Review
Midterm (10% of final grade)
Inheritance and Polymorphism
Breakout
Midterm Review
Project 1 Discussion

### **Agenda**

Homework Review
Midterm (10% of final grade)
Inheritance and Polymorphism
Breakout
Midterm Review

**Project 1 Discussion** 

Disclaimer: This stuff can be hard to wrap your head around!!!

Why Classes?

- 1. Encapsulation
- 2. Modularity
- 3. Inheritance
- 4. Polymorphism

Why did we have you implement a "card" class, even though it didn't need functions?

How can you decide when to use an "object" versus an "attribute" for a given part of your code?

Discuss (Async Notebooks):

• Inheritance (8.4)

Polymorphism (8.7)

Magic Methods (8.9)

Why would we want to use inheritance?

What is "super"?

What is "pass"?

```
class Process:
    """Representation of a Stochastic Process"""
    def __init__(self, start_value = 0):
        self.value = start_value

def time_step(self):
    pass
```

```
class BoundedLinearProcess(Process):
    """A stochastic process that develops linearly, but bounded within 0-1.
    The velocity attribute is the amount the value changes in each time period.
    and it is reset to -velocity whenever the process reaches 0 or 1."""
    def __init__(self, start_value = 0, velocity = 0):
        super(). init (start value)
        self.velocity = velocity
    def time step(self):
        self.value += self.velocity
        if self.value < 0:
            self.value = -self.value
            self.velocity = -self.velocity
        if self.value > 1:
            self.value = 1 - (self.value - 1)
            self.velocity = -self.velocity
       super().time step
```

Why would we want to use inheritance?
A template for other classes

#### What is "super"?

Run the function as defined in the superclass

#### What is "pass"?

Define a function, to be implemented in subclasses

```
class Process:
    """Representation of a Stochastic Process"""
    def __init__(self, start_value = 0):
        self.value = start_value

def time_step(self):
    pass
```

```
class BoundedLinearProcess(Process):
    """A stochastic process that develops linearly, but bounded within 0-1.
    The velocity attribute is the amount the value changes in each time period.
    and it is reset to -velocity whenever the process reaches 0 or 1."""
    def __init__(self, start_value = 0, velocity = 0):
        super(). init (start value)
        self.velocity = velocity
    def time step(self):
        self.value += self.velocity
        if self.value < 0:
            self.value = -self.value
            self.velocity = -self.velocity
       if self.value > 1:
            self.value = 1 - (self.value - 1)
            self.velocity = -self.velocity
        super().time step
```

What is polymorphism?



Check the Wikipedia example: it is very helpful at a high level:







```
class Animal:
   def init (self, name):
                                # Constructor of the class
        self.name = name
                                # Abstract method, defined by convention only
    def talk(self):
        raise NotImplementedError("Subclass must implement abstract method")
class Cat(Animal):
    def talk(self):
        return 'Meow!'
class Dog(Animal):
   def talk(self):
        return 'Woof! Woof!'
animals = [Cat('Missy'),
          Cat('Mr. Mistoffelees'),
          Dog('Lassie')]
for animal in animals:
    print animal.name + ': ' + animal.talk()
# prints the following:
# Missy: Meow!
# Mr. Mistoffelees: Meow!
# Lassie: Woof! Woof!
```

Notice the following: all animals "talk", but they talk differently. The "talk" behaviour is thus polymorphic in the sense that it is realized differently depending on the animal. So, the abstract "animal" concept does not actually "talk", but specific animals (like dogs and cats) have a concrete implementation of the action "talk".

Note: This is Python 2 Code

#### What is polymorphism?

The provision of a single interface to entities of different types.

Discuss: How may this be related to inheritance?



Check the Wikipedia example: it is very helpful at a high level:










Notice the following: all animals "talk", but they talk differently. The "talk" behaviour is thus polymorphic in the sense that it is realized differently depending on the animal. So, the abstract "animal" concept does not actually "talk", but specific animals (like dogs and cats) have a concrete implementation of Note: This is Python 2 Code the action "talk".

What is duck typing?



#### What is duck typing?

Python will not check variable Types before running a function.

"If it looks like a duck and quacks like a duck, it is a duck!"

```
class Duck:
    def quack(self):
        print("Quaaaaaack!")
    def feathers(self):
        print("The duck has white and gray feathers.")
class Person:
    def quack(self):
        print("The person imitates a duck.")
    def feathers(self):
        print("The person takes a feather from the ground and shows it.")
    def name(self):
        print("John Smith")
def in the forest(duck):
    duck.quack()
    duck.feathers()
def game():
    donald = Duck()
    john = Person()
    in the forest(donald)
    in the forest(john)
game()
```

#### **Magic Methods**

What are magic methods?

Can you describe the purpose of the code on this slide?

```
class Card:
   def __init__(self, value, suit):
        self value = value
        self.suit = suit
   def eq (self, other):
        if self.value == other.value:
            return True
       else:
            return False
   def lt__(self, other):
        if self.value < other.value:
            return True
       else:
            return False
   def __gt__(self, other):
        if self.value > other.value:
            return True
       else:
            return False
```

#### **Agenda**

Homework Review
Midterm (10% of final grade)
Inheritance and Polymorphism
Breakout

Midterm Review

Project 1 Discussion

#### **Breakout**

Let's adopt a pet...

### **Gamify** | Breakout - Allow your pets to interact

#### **Agenda**

Homework Review
Midterm (10% of final grade)
Inheritance and Polymorphism
Breakout
Midterm Review

**Project 1 Discussion** 

#### **Midterm Review**

Live Q & A using Poll Features

#### **Agenda**

Homework Review
Midterm (10% of final grade)
Inheritance and Polymorphism
Breakout
Midterm Review
Project 1 Discussion

#### The Project | Your Mission

Create a small, object-oriented program of your choosing:

#### Examples:

- An ATM
- A flower shop
- An adventure game
- Something relating to your everyday work

#### The Project | Code

Python 3 code, 300-500 lines (750 max)

All code should be well commented!

Must use Object Oriented design and classes

Demonstrate various flow controls and data types

Robust to common user errors and exceptions

### The Project | Your Mission

The user will interact with your program via Terminal/Shell

Three documents due before your due date class:

- 1. Proposal (10%)
- 2. Code(s) (80%)
- 3. Reflective Summary (10%)

You will demo your progress in a breakout room one week before the presentation

You may only use Python libraries that come installed with Anaconda

### The Project | Proposal

Describe your project concept

Pseudocode your major classes and functions

- 1. Briefly describe the purpose of each class
- 2. List expected functions belong to each class
- 3. List inputs and outputs for each function

Instructors will "approve" your draft proposal

Coding is iterative. Your final code may not match the proposal exactly

#### The Project | Reflection

Submit a 1-page reflection with your code

Instructors will read your reflection before grading your project

Tell us how to use your project!

Discuss challenges you faced and how you overcame them

# The Project | Demo

As time allows, show 1-2 examples of strong projects from last semester.

# **The Project** | Questions

# Up next | Numpy, strings, Data analysis

Project 1 | build your own object oriented project

- Code at home and collaborate in class

Unit 9 | Working With Text and Binary Data
Unit 10 | NumPy
Unit 11 | Data Analysis With Pandas
Unit 12 | More Analysis With Pandas
Unit 13 | Testing