

# A Brief Introduction to C++



**WATERLOO**  
**ENGINEERING**

**Douglas Wilhelm Harder, M.Math. LEL**  
Department of Electrical and Computer Engineering  
University of Waterloo  
Waterloo, Ontario, Canada

[ece.uwaterloo.ca](http://ece.uwaterloo.ca)  
[dwharder@alumni.uwaterloo.ca](mailto:dwharder@alumni.uwaterloo.ca)

© 2006-2013 by Douglas Wilhelm Harder. Some rights reserved.





# A Brief Introduction to C++

In this topic we will see:

- The similarities between Python and C++
- Some differences, including:
  - Global variables and functions
  - The preprocessor, compilation, namespaces
  - Printing
- Concluding with
  - Classes, templates
  - Pointers
  - Memory allocation and deallocation



# Control Statements

All control statements are similar

```
if ( statement ) {  
    // ...  
} else if ( statement ) {  
    // ...  
} else {  
    // ...  
}  
  
while ( statement ) {  
    // ...  
}  
  
for ( int i = 0; i < N; ++i ) {  
    // ...  
}  
  
do {  
    // ...  
} while ( statement );
```

# Operators

## Operators have similar functionality for built-in datatypes:

- |                 |     |     |     |    |      |   |
|-----------------|-----|-----|-----|----|------|---|
| – Assignment    | =   |     |     |    |      |   |
| – Arithmetic    | +   | -   | *   | /  | %    |   |
|                 | +=  | -=  | *=  | /= | %=   |   |
| – Autoincrement | ++  |     |     |    |      |   |
| – Autodecrement | --  |     |     |    |      |   |
| – Logical       | &&  |     | !   |    |      |   |
| – Relational    | ==  | !=  | <   | <= | >=   | > |
| – Comments      | /*  |     |     |    | */   |   |
|                 | //  | to  | end | of | line |   |
| – Bitwise       | &   |     | ^   | ~  |      |   |
|                 | &=  | =   | ^=  |    |      |   |
| – Bit shifting  | <<  | >>  |     |    |      |   |
|                 | <<= | >>= |     |    |      |   |



# Arrays

Accessing arrays is similar:

```
const int ARRAY_CAPACITY = 10; // prevents reassignment
int array[ARRAY_CAPACITY];
```

```
array[0] = 1;
for ( int i = 1; i < ARRAY_CAPACITY; ++i ) {
    array[i] = 2*array[i - 1] + 1;
}
```

Recall that arrays go from **0** to **ARRAY\_CAPACITY - 1**

Definition:

The *capacity* of an array is the entries it can hold

The *size* of an array is the number of useful entries



# Functions

Function calls are similar, however, they are not required to be part of a class:

```
#include <iostream>
using namespace std;

// A function with a global name
int sqr( int n ) {
    return n*n;
}

int main() {
    cout << "The square of 3 is " << sqr(3) << endl;
    return 0;
}
```



# C++/Python Differences

We will look at categories of differences between C++ and Python:

- Including header files (the preprocessor)
- The file is the base of compilation
- Namespaces
- Printing



# The C++ Preprocessor

C++ is based on C, which was written in the early 1970s

Any command starting with a `#` in the first column is not a C/C++ statement, but rather a preprocessor statement

- The preprocessor performed very basic text-based (or *lexical*) substitutions
- The output is sent to the compiler





# The C++ Preprocessor

The sequence is:

file (filename.cpp) → preprocessor → compiler (g++)

Note, this is done automatically by the compiler: no additional steps are necessary

At the top of any C++ program, you will see one or more directives starting with a #, e.g.,

```
#include <iostream>
```



# The C++ Preprocessor

iostream.h      intro.cpp

```
#include<iostream>
using namespace std;

int sqr( int n ) {
    return n*n;
}

int main() {
    cout << "The square of 3 is " << sqr(3) << endl;
    return 0;
}
```

preprocessor

to the compiler

```
int main() {
    cout << "The square of 3 is " << 9 << endl;
    return 0;
}
```



# Libraries

You will write your code in a file such as `Single_list.h` where you will implement a data structure

This file will be included in our tester file `Single_list_tester.h` with a statement such as:

```
#include "Single_list.h"
```

The file `Single_list_int_driver.cpp` then includes the tester file:

```
#include "Single_list_tester.h"
```



# Libraries

You will note the difference:

```
#include <iostream>  
#include "Single_list.h"
```


The first looks for a file `iostream.h` which is shipped with the compiler (the standard library)

The second looks in the current directory





# The C++ Preprocessor





# The C++ Preprocessor

With all these includes, it is always necessary to avoid the same file being included twice, otherwise you have duplicate definitions

Using a pragma directive

`#pragma once`

```
template <typename Type>
class Single_list {
    ///...
};
```



# The C++ Preprocessor

With all these includes, it is always necessary to avoid the same file being included twice, otherwise you have duplicate definitions

Or (using an old style) with guard statements:

```
#ifndef SINGLE_LIST_H  
#define SINGLE_LIST_H
```

```
template <typename Type>  
class Single_list {  
    ///...  
};
```

```
#endif
```



# The C++ Preprocessor

This class definition contains only the signatures (or *prototypes*) of the operations

the interface, function declaration, class declaration, etc.

The actual member function definitions may be defined elsewhere, either in:

- The same file, or
- Another file which is compiled into an object file

We will use the first method





# The File as the Unit of Compilation

In C/C++, the file is the base unit of compilation:

- Any .cpp file may be compiled into object code
- Only files containing an `int main()` function can be compiled into an executable

The signature of main is:

```
int main (int argc, char* argv[]) {  
    // does some stuff  
    return 0;  
}
```

The operating system is expecting a return value

- Usually 0



# The File as the Unit of Compilation

This file (`example.cpp`) contains two functions

```
#include<iostream>
using namespace std;

int sqr( int n ) {      // Function declaration and definition
    return n*n;
}

int main() {
    cout << "The square of 3 is " << sqr(3) << endl;
    return 0;
}
```



# The File as the Unit of Compilation

To compile this file, we execute on the command line:

```
{ecelinux:1} g++ example.cpp -o example
```

```
{ecelinux:2} ls
```

```
example      example.cpp
```

```
{ecelinux:3} ./example
```

```
The square of 3 is 9
```

```
{ecelinux:4}
```



# The File as the Unit of Compilation

This is an alternate form:

```
#include<iostream>
using namespace std;

int sqr( int );                // Function declaration

int main() {
    cout << "The square of 3 is " << sqr(3) << endl;
    return 0;
}

int sqr( int n ) {            // Function definition
    return n*n;               // The definition can be in another file
}
```





# Namespaces

Variables defined:

- In functions are *local variables*
- In classes are *member variables*
- Elsewhere are *global variables*

Functions defined:

- In classes are *member functions*
- Elsewhere are *global functions*

In all these cases, the keyword **static** can modify the scope



# Namespaces

Global variables/variables cause problems, especially in large projects

- Hundreds of employees
- Dozens of projects
- Everyone wanting a function `init()`

In C++ (and XML), this is solved using namespaces



# Namespaces

A namespace adds an extra disambiguation between similar names

```
namespace ca_uwaterloo_dwharder {  
    int n = 4;  
    double mean = 2.34567;  
  
    void init() {  
        // Does something...  
    }  
}
```

There are two means of accessing these global variables and functions outside of this namespace:

- The namespace as a prefix: `ca_uwaterloo_dwharder::init()`
- The using statement:

```
using namespace ca_uwaterloo_dwharder;
```



# Namespaces

You will only need this for the standard name space

- All variables and functions in the standard library are in the **std** namespace

```
#include <iostream>
std::cout << "Hello world!" << std::endl;
```

```
#include <iostream>
using namespace std;           // never used in production code

cout << "Hello world!" << endl;
```





# Printing

Printing in C++ is done through overloading the << operator:

```
cout << 3;
```

If the left-hand argument of << is an object of type **ostream** (output *stream*) and the right-hand argument is a **double**, **int**, **string**, etc., an appropriate function which prints the object is called



# Printing

The format is suggestive of what is happening:

- The objects are being *sent* to the `cout` (*console output*) object to be printed

```
cout << "The square of 3 is " << sqr(3) << endl;
```

The objects being printed are:

- a `string`
- an `int`
- a platform-independent end-of-line identifier



# Printing

How does

```
std::cout << "The square of 3 is " << sqr(3) << endl;
```

work?

This is equivalent to

```
(std::cout << "The square of 3 is ") << sqr(3) << endl;
```

where `<<` is an operation (like `+`) which prints the object and returns the `cout` object



# Printing

Visually:

```
(cout << "The square of 3 is ") << sqr(3) << endl;
```

print "The square of 3 is " and return cout

```
(cout << sqr(3)) << endl;
```

print the result of `sqr(3)` and return cout

```
cout << endl;
```

print an end-of-line character (and return cout)

```
cout;
```



# Printing

Another way to look at this is that

```
cout << "The square of 3 is " << sqr(3) << endl;
```

is the same as:

```
operator<<( operator<<( operator<<( cout, "The square of 3 is " ), sqr(3) ), endl );
```

This is how C++ treats these anyway...



# Introduction to C++

The next topics in C++ will be:

- Classes
- Pointers
- Memory allocation
- *Templates*





# Classes

To begin, we will create a complex number class

To describe this class, we could use the following words:

- Store the real and imaginary components
- Allow the user to:
  - Create a complex number
  - Retrieve the real and imaginary parts
  - Find the absolute value and the exponential value
  - Normalize a non-zero complex number



# UML Class Diagrams

Instead, another way to summarize the properties of a class is through UML Class Diagrams

UML, the Unified Modeling Language is a collection of *best practices* used in designing/modeling (among other things) software systems



# UML Class Diagrams

The Class Diagram for what we describe may be shown as the following box:

Complex
-re:Real -im:Real
<u>+create( in r:Real = 0, in i:Real = 0 ):Complex</u> +real():Real +imag():Real +abs():Real +exp():Complex +normalize() +destroy()



# UML Class Diagrams

The three components include:

- the name, the attributes, and the operations

Class Name

**Complex**

-re:Real

-im:Real

Attributes (class members)

+create( in r:Real = 0, in i:Real = 0 ):Complex

+real():Real

+imag():Real

+abs():Real

+exp():Complex

+normalize()

+destroy()

Operations


(member functions,  
methods, behaviours)



# UML Class Diagrams

The attributes are described by:

- a visibility modifier, a name, and a type






# UML Class Diagrams

The operations (a.k.a. functions) include:

- a visibility modifier, a name, parameters (possibly with default values) and return values







# Classes

An example of a C++ class declaration is:

```
class Complex {  
    private:  
        double re, im;  
  
    public:  
        Complex( double = 0.0, double = 0.0 );  
  
        double real() const;  
        double imag() const;  
        double abs() const;  
        Complex exp() const;  
  
        void normalize();  
};
```



# Classes

This only declares the class structure

- It does not provide an implementation

We could, like Python, include the implementation in the class declaration, however, this is not, for numerous reasons, standard practice



# The Complex Class

The next slide gives both the declaration of the `Complex` class as well as the associated definitions

- The assumption is that this is within a single file



# The Complex Class

```
#ifndef _COMPLEX_H
#define _COMPLEX_H
#include <cmath>
class Complex {
    private:
        double re, im;

    public:
        Complex( double = 0.0, double = 0.0 );

        // Accessors
        double real() const;
        double imag() const;
        double abs() const;
        Complex exp() const;

        // Mutators
        void normalize();
};
```



# The Complex Class

```
// Constructor
Complex::Complex( double r, double i ):
re( r ),
im( i ) {
    // empty constructor
}
```

Associates functions back to the class

Each member variable should be assigned

The order must be the same as the order in which the member variables are defined in the class

For built-in datatypes, this is a simple assignment.  
For member variables that are objects, this is a call to a constructor.

For built-in datatypes, the above is equivalent to:

```
// Constructor
Complex::Complex( double r, double i ):re( 0 ), im( 0 ) {
    re = r;
    im = i;
}
```



# The Complex Class

```
// return the real component
double Complex::real() const {
    return re;
}

// return the imaginary component
double Complex::imag() const {
    return im;
}

// return the absolute value
double Complex::abs() const {
    return std::sqrt(re*re + im*im);
}
```

Refers to the member variables re and im of this class





# The Complex Class

```
// Return the exponential of the complex value
Complex Complex::exp() const {
    double exp_re = std::exp( re );

    return Complex( exp_re*std::cos(im), exp_re*std::sin(im) );
}
```



# The Complex Class

```
// Normalize the complex number (giving it unit absolute value,  $|z| = 1$ )  
void Complex::normalize() {  
    if ( re == 0 && im == 0 ) {  
        return;  
    }  
  
    double absval = abs();  
    re /= absval;  
    im /= absval;  
}  
  
#endif
```

This calls the member function `double abs() const` from the `Complex` class on the object on which `void normalize()` was called



# Visibility

Visibility in C# and Java is described by placing public/private/protected in front of each class member or member function

In C++, this is described by a block prefixed by one of

`private:`

`protected:`

`public:`



# Visibility

```
class Complex {  
    private:  
        double re, im;  
  
    public:  
        Complex( double, double );  
  
        double real() const;  
        double imag() const;  
        double abs() const;  
        Complex exp() const;  
  
        void normalize();  
};
```



# Visibility

The reason for the change in Java/C# was that the C++ version has been noted to be a source of errors

Code could be cut-and-paste from one location to another, and a poorly placed paste could change the visibility of some code:

`public` → `private` automatically caught

`private` → `public` difficult to catch and dangerous



# Visibility

It is possible for a class to indicate that another class is allowed to access its **private** members

If class `ClassX` declares class `ClassY` to be a friend, then class `ClassY` can access (and modify) the private members of `ClassX`





# Visibility

```
class ClassY;                // declare that ClassY is a class

class ClassX {
    private:
        int privy;           // the variable privy is private

    friend class ClassY;      // ClassY is a "friend" of ClassX
};

class ClassY {
    private:
        ClassX value;        // Y stores one instance of X
    public:
        void set_x() {
            value.privy = 42; // a member function of ClassY can
                               // access and modify the private
                               // member privy of "value"
        }
};
```



# Accessors and Mutators

We can classify member functions into two categories:

- Those leaving the object unchanged
- Those modifying the member variables of the object

Respectively, these are referred to as:

- **Accessors:** we are accessing and using the class members
- **Mutators:** we are changing—mutating—the class members



## Accessors and Mutators

Good programming practice is to enforce that a routine specified to be an accessor cannot be accidentally changed to a mutator

This is done with the `const` keyword after the parameter list

```
double abs() const;
```



## Accessors and Mutators

If a junior programmer were to try change

```
double Complex::abs() const {  
    return std::sqrt( re*re + im*im );  
}
```

to

```
double Complex::abs() const {  
    re = 1.0;                // modifying (mutating) 're'  
    return std::sqrt( re*re + im*im );  
}
```

the compiler would signal an error



# Pointers

One of the simplest ideas in C, but one which most students have a problem with is a pointer

- Every variable (barring optimization) is stored somewhere in memory
- That address is an integer, so why can't we store an address in a variable?



<http://xkcd.com/138/>



# Pointers

We could simply have an 'address' type:

```
address ptr;    // store an address  
                // THIS IS WRONG
```

however, the compiler does not know what it is an address of (is it the address of an int, a double, etc.)

Instead, we have to indicate what it is pointing to:

```
int *ptr;    // a pointer to an integer  
             // the address of the integer variable 'ptr'
```



# Pointers

First we must get the address of a variable

This is done with the & operator

(**a**mpersand/**a**ddress of)

For example,

```
int m = 5;      // m is an int storing 5
int *ptr;       // a pointer to an int
ptr = &m;       // assign to ptr the
                // address of m
```





# Pointers

We can even print the addresses:

```
int m = 5;      // m is an int storing 5
int *ptr;       // a pointer to an int
ptr = &m;       // assign to ptr the
                // address of m
cout << ptr << endl;
```

prints `0xffffd352`, a 32-bit number

- The computer uses 32-bit addresses



# Pointers

We have pointers: we would now like to manipulate what is stored at that address

We can access/modify what is stored at that memory location by using the \* operator (dereference)

```
int m = 5;  
int *ptr;  
ptr = &m;  
cout << *ptr << endl; // prints 5
```




# Pointers

Similarly, we can modify values stored at an address:

```
int m = 5;
int *ptr;
ptr = &m;
```

```
*ptr = 3;    // store 3 at that memory location
cout << m << endl;  // prints 3
```





# Pointers

Pointers to objects must, similarly be dereferenced:

```
Complex z( 3, 4 );  
Complex *pz;  
pz = &z;  
cout << z.abs() << endl;  
cout << (*pz).abs() << endl;
```



# Pointers

One short hand for this is to replace

```
(*pz).abs();
```

with

```
pz->abs();
```



# Memory Allocation

Memory allocation in C++ is done through the **new** operator

This is an explicit request to the operating system for memory

- This is a very expensive operation
- The OS must:
  - Find the appropriate amount of memory,
  - Indicate that it has been allocated, and
  - Return the address of the first memory location



# Memory Allocation

Memory deallocation differs, however:

- C# uses automatic garbage collection
- C++ requires the user to explicitly deallocate memory

Note however, that:

- *managed* C++ has garbage collection
- other tools are also available for C++ to perform automatic garbage collection





# Memory Allocation

Memory for a single instance of a class (one object) is allocated using the new operator, e.g.,

```
int *pq = new int;  
int *pz = new int[10];
```

The new operator returns the address of the first byte of the memory allocated



# Memory Allocation

We can even print the address to the screen

If we were to execute

```
cout << "The address pz is " << pz << endl;
```

we would see output like:

The address pz is 0x00ef3b40



# Memory Allocation

Next, to deallocate the memory (once we're finished with it) we must explicitly tell the operating system using the delete operator:

```
delete pq; // free the allocated memory
```

```
delete [] pz; // freed the block of allocated memory
```



# Templates

Now that we have seen an introduction to classes, the next generalization is templates



# Templates

This mechanism uses a tool called templates

- A function has parameters which are of a specific type
- A template is like a function, however, the parameters themselves are types



# Templates

That mechanism is called a template:

```
template <typename Type>  
Type sqr( Type x ) {  
    return x*x;  
}
```

This creates a function which returns something of the same type as the argument



# Templates

To tell the compiler what that type is, we must suffix the function:

```
int n = sqr<int>( 3 );  
double x = sqr<double>( 3.141592653589793 );
```

Usually, the compiler can determine the appropriate template without it being explicitly stated





# Templates

## Example:

```
#include<iostream>
using namespace std;
```

```
template <typename Type>
Type sqr( Type x ) {
    return x*x;
}
```

```
int main() {
    cout << "3 squared is " << sqr<int>( 3 ) << endl;
    cout << "Pi squared is " << sqr<double>( 3.141592653589793 ) << endl;

    return 0;
}
```

## Output:

3 squared is 9

Pi squared is 9.8696



# Templates

Thus, calling `sqr<int>( 3 )` is equivalent to calling a function defined as:

```
int sqr( int x ) {  
    return x*x;  
}
```

```
template <typename Type>  
Type sqr( Type x ) {  
    return x*x;  
}
```

The compiler replaces the symbol **Type** with **int**



# Templates

Our complex number class uses double-precision floating-point numbers

What if we don't require the precision and want to save memory with floating-point numbers

- Do we write the entire class twice?
- How about templates?



# Templates

```
#ifndef _COMPLEX_H
#define _COMPLEX_H
#include <cmath>
template <typename Type>
class Complex {
    private:
        Type re, im;

    public:
        Complex( Type const & = Type(), Type const & = Type() );

        // Accessors
        Type real() const;
        Type imag() const;
        Type abs() const;
        Complex exp() const;

        // Mutators
        void normalize();
};
```



# Templates

The modifier template `<typename Type>` applies only to the following statement, so each time we define a function, we must restate that **Type** is a templated symbol:

```
// Constructor
template <typename Type>
Complex<Type>::Complex( Type const &r, Type const &i ):re(r), im(i) {
    // empty constructor
}
```



# Templates

```
// return the real component
template <typename Type>
Type Complex<Type>::real() const {
    return re;
}

// return the imaginary component
template <typename Type>
Type Complex<Type>::imag() const {
    return im;
}

// return the absolute value
template <typename Type>
Type Complex<Type>::abs() const {
    return std::sqrt( re*re + im*im );
}
```



# Templates

```
// Return the exponential of the complex value
template <typename Type>
Complex<Type> Complex<Type>::exp() const {
    Type exp_re = std::exp( re );

    return Complex<Type>( exp_re*std::cos(im), exp_re*std::sin(im) );
}

// Normalize the complex number (giving it unit norm, |z| = 1)
template <typename Type>
void Complex<Type>::noramlize() {
    if ( re == 0 && im == 0 ) {
        return;
    }

    Type absval = abs();
    re /= absval;
    im /= absval;
}

#endif
```





# Templates

## Example:

```
#include <iostream>
#include "Complex.h"
using namespace std;

int main() {
    Complex<double> z( 3.7, 4.2 );
    Complex<float> w( 3.7, 4.2 );
    cout.precision( 20 ); // Print up to 20 digits

    cout << "|z| = " << z.abs() << endl;
    cout << "|w| = " << w.abs() << endl;

    z.normalize();
    w.normalize();

    cout << "After normalization, |z| = " << z.abs() << endl;
    cout << "After normalization, |w| = " << w.abs() << endl;

    return 0;
}
```

## Ouput:

```
|z| = 5.5973207876626123181
|w| = 5.597320556640625
After normalization, |z| =
1.0000000412736744781
After normalization, |w| = 1
```



# A Quick Introduction to C++

To summarize:

- we have seen some of the similarities and differences between Python and C++
- these slides touch on all of the topics which you will need to know to implement all of your projects



# Usage Notes

- These slides are made publicly available on the web for anyone to use
- If you choose to use them, or a part thereof, for a course at another institution, I ask only three things:
  - that you inform me that you are using the slides,
  - that you acknowledge my work, and
  - that you alert me of any mistakes which I made or changes which you make, and allow me the option of incorporating such changes (with an acknowledgment) in my set of slides

Sincerely,

Douglas Wilhelm Harder, MMath

`dwharder@alumni.uwaterloo.ca`