customers

PK	customer_id	SERIAL
	first_name	VARCHAR(50)
	last_name	VARCHAR(50)
	email	VARCHAR(100)
	phone_num	VACHAR(10)

from customer to concession it as 0 or many because a customer can make purchase from the concession 0 or many times.

concessions

PK	concessions_id	SERIAL
FK	customer_id	INTEGER
	beverage	VARCHAR(30)
	food	VARCHAR(30)
	candy	VARCHAR(30)

from consession to customers, it as 0 or one time becuase concession can tend to the customer 0 or 1 per visit.

from customer to ticket a customer have to get 1 or many tickets because that's is the only way of entry to see the movie.

from ticket to movie it is 1 or many because ticket purchases can be toward many movies.

from movie to ticket it's one and only one because it one movies per ticket

tickets

PK	ticket_id	SERIAL
FK	customer_id	INTEGER
	type_of_ticket	VARCHAR(10)
FK	movie_id	INTEGER
	price	VARCHAR(10)
	seat_id	VARCHAR(5)
	movie_time	TIMESTAMP

movies

PK	movies_id	SERIAL
	title	VARCHAR(150)
	rating	VARCHAR(10)
	genre	VARCHAR(25)
FK	ticket_id	INTEGER

from ticket to customer it's one and only one ticket per customer.