

~~Server/server_data.py~~

```
# server_data.py
# ! 0t 0 0i .i 0 E. of< 0"00

import os
import json
import sys
sys.path.append(os.path.dirname(os.path.dirname(os.path.abspath(__file__))))
from env_utils import DATA_DIR

class ServerDataManager:
    """! 0t 0 0i .i 0 E. of< i .0 i /"""

    def __init__(self):
        self.users_file = os.path.join(DATA_DIR, "users.json")
        self.folders_file = os.path.join(DATA_DIR, "folders.json")
        self.files_file = os.path.join(DATA_DIR, "files.json")

        # 0 0 i of< i i -
        self.ensure_directories()

        # 0 0i .i 0 0i 0
        self.load_data()

    def ensure_directories(self):
        """! i i 0 0 i of< i i -"""
        os.makedirs(DATA_DIR, exist_ok=True)

    def load_data(self):
        """0 0i .i 0 i i ... 0i 0 """
        # i <i 'i 0 0i .i 0
        if os.path.exists(self.users_file):
            with open(self.users_file, 'r', encoding='utf-8') as f:
                self.users = json.load(f)
        else:
            self.users = {}

        # i .0 0 0i .i 0
        if os.path.exists(self.folders_file):
            with open(self.folders_file, 'r', encoding='utf-8') as f:
                self.folders = json.load(f)
        else:
            self.folders = {}

        # i i ... 0 0i .i 0
        if os.path.exists(self.files_file):
            with open(self.files_file, 'r', encoding='utf-8') as f:
                self.files = json.load(f)
        else:
            self.files = {}

    def save_data(self):
        """0 0i .i 0 i i ... i i ¥"""
        with open(self.users_file, 'w', encoding='utf-8') as f:
```

```
Server/server_data.py
    json.dump(self.users, f, ensure_ascii=False, indent=2)
    with open(self.folders_file, 'w', encoding='utf-8') as f:
        json.dump(self.folders, f, ensure_ascii=False, indent=2)
    with open(self.files_file, 'w', encoding='utf-8') as f:
        json.dump(self.files, f, ensure_ascii=False, indent=2)
```