

```

env_utils.py
# env_utils.py
# í Ę†% 0†ì ì í ,°f<í ° °"¤° (.env í ì ...ì ì ì %Ė,°)

import os

# .env í ì ...ì ì í Ę†% 0†ì °í °
def load_env_file():
    """.env í ì ...ì ì í Ę†% 0†ì °í ° """
    env_path = os.path.join(os.path.dirname(os.path.abspath(__file__)), '.env')
    if os.path.exists(env_path):
        try:
            with open(env_path, 'r', encoding='utf-8') as f:
                for line in f:
                    line = line.strip()
                    # ìĖ...ì ì .° °" ì / °<·ì
                    if not line or line.startswith('#'):
                        continue
                    # KEY=VALUE í ì í ì -
                    if '=' in line:
                        key, value = line.split('=', 1)
                        key = key.strip()
                        value = value.strip().strip('"').strip("'")
                        os.environ[key] = value
        except Exception as e:
            print(f"í Ę†% 0†ì í ì ... °í ° ì /°¥ : {e}")

# .env í ì ... °í °
load_env_file()

# í Ę†% 0†ì ì %Ė,° í ¤ì ° / (.env í ì ...ì ì °$ ì %Ė,°)
def get_default_host():
    value = os.getenv('DEFAULT_HOST')
    if value is None:
        raise ValueError("DEFAULT_HOSTĖ° .env í ì ...ì ì /ì ° ì ·ì ì$ ì ì μ° ° /.")
    return value

def get_default_port():
    value = os.getenv('DEFAULT_PORT')
    if value is None:
        raise ValueError("DEFAULT_PORTĖ° .env í ì ...ì ì /ì ° ì ·ì ì$ ì ì μ° ° /.")
    return int(value)

def get_bufsize():
    value = os.getenv('BUFSIZE')
    if value is None:
        raise ValueError("BUFSIZEĖ° .env í ì ...ì ì /ì ° ì ·ì ì$ ì ì μ° ° /.")
    return int(value)

def get_receive_dir():
    value = os.getenv('RECEIVE_DIR')
    if value is None:
        raise ValueError("RECEIVE_DIRì · .env í ì ...ì ì /ì ° ì ·ì ì$ ì ì μ° ° /.")
    return value

```

```

def get_data_dir():
    value = os.getenv('DATA_DIR')
    if value is None:
        raise ValueError("DATA_DIR is not set in .env file. Please set it in the .env file.")
    return value

def get_supabase_url():
    value = os.getenv('SUPABASE_URL')
    if value is None:
        raise ValueError("SUPABASE_URL is not set in .env file. Please set it in the .env file.")
    return value

def get_supabase_anon_key():
    value = os.getenv('SUPABASE_ANON_KEY')
    if value is None:
        raise ValueError("SUPABASE_ANON_KEY is not set in .env file. Please set it in the .env file.")
    return value

def get_openai_api_key():
    return os.getenv('OPENAI_API_KEY', '') # OpenAI API key

def get_openai_model():
    value = os.getenv('OPENAI_MODEL')
    if value is None:
        raise ValueError("OPENAI_MODEL is not set in .env file. Please set it in the .env file.")
    return value

def get_whisper_model():
    """Whisper model, default is 'whisper-1'"""
    # OpenAI Whisper API model
    return os.getenv('WHISPER_MODEL', 'whisper-1')

def get_whisper_language():
    """Whisper language, default is None"""
    # OpenAI Whisper API language
    return os.getenv('WHISPER_LANGUAGE', None)

# Default host and port (default is localhost)
DEFAULT_HOST = get_default_host()
DEFAULT_PORT = get_default_port()
BUFSIZE = get_bufsize()
RECEIVE_DIR = get_receive_dir()
DATA_DIR = get_data_dir()
SUPABASE_URL = get_supabase_url()
SUPABASE_ANON_KEY = get_supabase_anon_key()
OPENAI_API_KEY = get_openai_api_key()
OPENAI_MODEL = get_openai_model()
WHISPER_MODEL = get_whisper_model()
WHISPER_LANGUAGE = get_whisper_language()

```