

supabase_client.py

```
# supabase_client.py
# Supabase í .° ...î .î ,í , °"¤°
```

```
import os
import sys
sys.path.append(os.path.dirname(os.path.abspath(__file__)))
```

```
try:
```

```
    from supabase import create_client, Client
    SUPABASE_MODULE_AVAILABLE = True
```

```
except ImportError:
```

```
    SUPABASE_MODULE_AVAILABLE = False
```

```
    print("⚠️ : supabase °"¤° ì ì°¼ ì ì ì µ° ° /. pip install supabase ì /í í ì ,ì .
```

```
    Client = None
```

```
# env_utils.pyì ì í ⚠️ °± ì °i °
```

```
from env_utils import SUPABASE_URL, SUPABASE_ANON_KEY
```

```
# Supabase í .° ...î .î ,í , ì· ⚠️,°í
```

```
supabase: Client | None = None
```

```
if SUPABASE_MODULE_AVAILABLE and SUPABASE_URL and SUPABASE_ANON_KEY:
```

```
    try:
```

```
        supabase = create_client(SUPABASE_URL, SUPABASE_ANON_KEY)
```

```
        print("Supabase í .° ...î .î ,í , ì· ⚠️,°í ì °£ ")
```

```
    except Exception as e:
```

```
        print(f"Supabase í .° ...î .î ,í , ì· ⚠️,°í ì /í ¢: {e}")
```

```
        supabase = None
```

```
else:
```

```
    if not SUPABASE_MODULE_AVAILABLE:
```

```
        print("⚠️⚠️ : supabase °"¤° ì . ì /ì„ ° ì$ ì ì ì µ° ° /.")
```

```
    elif not SUPABASE_URL or not SUPABASE_ANON_KEY:
```

```
        print("⚠️⚠️ : Supabase ì /ì ì . .env í ì ... ì ì µ° ° /.")
```

```
        supabase = None
```

```
SUPABASE_AVAILABLE = supabase is not None
```