```
#!/usr/bin/python3
#required libraries
import sys
import ssl
import json
import paho.mqtt.client as mqtt
#called while client tries to establish connection with the server
def on connect(mqttc, obj, flags, rc):
    if rc==0:
       print ("Subscriber Connection status code: "+str(rc)+" | Connection status: successful")
        mqttc.subscribe("$aws/things/pi assn4/shadow/update/accepted", qos=0)
        mqttc.publish("$aws/things/pi assn4/shadow/update",'{"state":{"reported":{"color":"Fu"}}}
        ')
    elif rc==1:
        print ("Subscriber Connection status code: "+str(rc)+" | Connection status: Connection
        refused")
#called when a topic is successfully subscribed to
def on subscribe(mqttc, obj, mid, granted qos):
    print("Subscribed: "+str(mid)+" "+str(granted qos)+"data"+str(obj))
#called when a message is received by a topic
def on message(mqttc, obj, msg):
    print("Received message from topic: "+msg.topic+" | QoS: "+str(msg.qos)+" | Data Received:
    "+str(msg.payload))
#creating a client with client-id=mqtt-test
mgttc = mgtt.Client(client id="cgao")
mgttc.on connect = on connect
mqttc.on subscribe = on subscribe
mqttc.on message = on message
#Configure network encryption and authentication options. Enables SSL/TLS support.
#adding client-side certificates and enabling tlsv1.2 support as required by aws-iot service
mqttc.tls set(ca certs="/home/pi/Desktop/rootCA.pem.crt",
          certfile="/home/pi/Downloads/7409fdbcb2-certificate.pem.crt",
          keyfile="/home/pi/Downloads/7409fdbcb2-private.pem.key",
              tls version=ssl.PROTOCOL TLSv1 2,
              ciphers=None)
#connecting to aws-account-specific-iot-endpoint
mqttc.connect("a1qup6k0p06lhy.iot.us-west-2.amazonaws.com", port=8883) #AWS IoT service
hostname and portno
#automatically handles reconnecting
mqttc.loop forever()
```