

Write a query that uses a subquery to obtain all orders for the customer named Cisneros. Assume you do not know his customer number (cnum).

```
KD4-98876-Anuradha> SELECT *
-> FROM orders
-> WHERE cnum = (
->     SELECT cnum
->     FROM customers
->     WHERE cname = 'Cisneros'
-> );
```

onum	amt	odate	cnum	snum
3001	18.69	1990-10-03	2008	1007
3006	1098.16	1990-10-03	2008	1007

2 rows in set (0.006 sec)

Extract all the orders of Motika.

```
KD4-98876-Anuradha> SELECT * FROM orders
-> WHERE snum=(SELECT snum FROM salespeople WHERE sname ='Motika')
```

onum	amt	odate	cnum	snum
3002	1900.10	1990-10-03	2007	1004

1 row in set (0.072 sec)

Find all the orders of salespeople servicing customers in London.

```
KD4-98876-Anuradha> SELECT * FROM orders
-> WHERE snum IN (SELECT snum FROM customers WHERE city ='London');
```

onum	amt	odate	cnum	snum
3003	767.19	1990-10-03	2001	1001
3008	4723.00	1990-10-04	2006	1001
3011	9891.88	1990-10-04	2006	1001

3 rows in set (0.082 sec)

Write a query that selects all orders for amounts greater than any for the customers in London.

```

KD4-98876-Anuradha> SELECT * FROM orders
  -> WHERE amt > ANY (SELECT amt FROM orders WHERE cnum IN (SE
ERROR 1146 (42S02): Table 'sales_db.customer' doesn't exist
KD4-98876-Anuradha> SELECT *
  -> FROM orders
  -> WHERE amt > ANY
  -> (
  ->     SELECT amt
  ->     FROM orders
  ->     WHERE cnum IN
  ->     (
  ->         SELECT cnum
  ->         FROM customers
  ->         WHERE city = 'London'
  ->     )
  -> );

```

onum	amt	odate	cnum	snum
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3011	9891.88	1990-10-04	2006	1001

6 rows in set (0.083 sec)

Write a query that selects all customers whose ratings are equal to or greater than ANY of Serres'. (Hint: find all customers of serres salesperson).

```

KD4-98876-Anuradha> SELECT * FROM customers
  -> WHERE rating >= ANY (SELECT rating FROM customers WHERE snum IN (SELECT snum FROM salespeople WHERE sname = 'Serres'));

```

cnum	cname	city	rating	snum
2002	Giovanni	Rome	200	1003
2003	Liu	San Jose	200	1002
2004	Grass	Berlin	300	1002
2008	Cisneros	San Jose	300	1007

4 rows in set (0.104 sec)

Select customers who have a greater rating than any other customer in Rome.

```

KD4-98876-Anuradha> SELECT * FROM customers
  -> WHERE rating > ANY(SELECT rating FROM customers WHERE city = 'ROME');

```

cnum	cname	city	rating	snum
2002	Giovanni	Rome	200	1003
2003	Liu	San Jose	200	1002
2004	Grass	Berlin	300	1002
2008	Cisneros	San Jose	300	1007

4 rows in set (0.008 sec)

Select all orders that had amounts that were greater than at least one of the orders from '1990-10-04'.

```
KD4-98876-Anuradha> SELECT * FROM orders
-> WHERE amt > ANY(SELECT amt FROM orders WHERE odate='1990-10-04');
```

onum	amt	odate	cnum	snum
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

```
8 rows in set (0.030 sec)
```

Find all orders with amounts smaller than any amount for a customer in San Jose.

```
KD4-98876-Anuradha> SELECT *
-> FROM orders
-> WHERE amt < ANY (
->     SELECT o.amt
->     FROM orders o
->     JOIN customers c
->     ON o.cnum = c.cnum
->     WHERE c.city = 'San Jose'
-> );
```

onum	amt	odate	cnum	snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002

```
8 rows in set (0.090 sec)
```

Write a query to display the order amount, customer names and ratings of all customers where the amount is greater than the average amount from the orders table.

```

RD4-98876-Anuradha> SELECT o.amt, c.cname, c.rating
-> FROM orders o
-> JOIN customers c
-> ON o.cnum = c.cnum
-> WHERE o.amt > (SELECT AVG(amt) FROM orders);
+-----+-----+-----+
| amt      | cname    | rating |
+-----+-----+-----+
| 5160.45   | Liu      | 200    |
| 9891.88   | Clemens  | 100    |
| 4723.00   | Clemens  | 100    |
+-----+-----+-----+
3 rows in set (0.035 sec)

```

Select those customers whose rating are higher than every customer in London.

```

RD4-98876-Anuradha> SELECT *
-> FROM customers
-> WHERE rating > ALL (
-> SELECT rating
-> FROM customers
-> WHERE city = 'London'
-> );
+-----+-----+-----+-----+-----+
| cnum | cname    | city      | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome      | 200    | 1003 |
| 2003 | Liu      | San Jose  | 200    | 1002 |
| 2004 | Grass    | Berlin    | 300    | 1002 |
| 2008 | Cisneros | San Jose  | 300    | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.122 sec)

```

Write a query that will find all salespeople who have no customers located in their city. (Hint: Choose the correct keyword ANY/ALL).

```

KD4-98876-Anuradha> SELECT *
-> FROM salespeople s
-> WHERE s.city <> ALL (
->     SELECT c.city
->     FROM customers c
-> );
+-----+-----+-----+-----+
| snum | sname  | city      | comm |
+-----+-----+-----+-----+
| 1007 | Rifkin  | Barcelona | 0.15 |
| 1003 | Axelrod | New York  | 0.10 |
+-----+-----+-----+-----+
2 rows in set (0.095 sec)

KD4-98876-Anuradha> SELECT s.snum, s.sname
-> FROM salespeople s

```

Find salespeople number, name and city who have multiple customers. Display the count of customers as well.

```

KD4-98876-Anuradha> SELECT s.snum, s.sname
-> FROM salespeople s
-> JOIN customers c
-> ON s.snum = c.snum
-> GROUP BY s.snum, s.sname
-> HAVING COUNT(c.cnum) > 1;
+-----+-----+
| snum | sname |
+-----+-----+
| 1001 | Peel  |
| 1002 | Serres |
+-----+-----+
2 rows in set (0.082 sec)

```

Write a query that selects the total amount in orders for each salesperson for whom this total is greater than the amount of the largest order in the table.

```
KD4-98876-Anuradha> SELECT snum, SUM(amt) AS total_amount  
-> FROM orders  
-> GROUP BY snum  
-> HAVING SUM(amt) > (SELECT MAX(amt) FROM orders);
```

```
+-----+-----+  
| snum | total_amount |  
+-----+-----+  
| 1001 |      15382.07 |  
+-----+-----+  
1 row in set (0.083 sec)
```