

Write a query that lists each order number followed by the name of the customer who made the order.

```
KD4-98876-Anuradha> SELECT o.onum AS order_number, c.cname AS customer_name
-> FROM orders o
-> JOIN customers c
-> ON o.cnum = c.cnum;
```

order_number	customer_name
3001	Cisneros
3003	Hoffman
3002	Pereira
3005	Liu
3006	Cisneros
3009	Giovanni
3007	Grass
3008	Clemens
3010	Grass
3011	Clemens

10 rows in set (0.103 sec)

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number

```
KD4-98876-Anuradha> SELECT o.onum AS order_number,
-> s.sname AS salesperson_name,
-> c.cname AS customer_name
-> FROM orders o
-> JOIN salespeople s
-> ON o.snum = s.snum
-> JOIN customers c
-> ON o.cnum = c.cnum;
```

order_number	salesperson_name	customer_name
3003	Peel	Hoffman
3009	Axelrod	Giovanni
3005	Serres	Liu
3010	Serres	Grass
3007	Serres	Grass
3011	Peel	Clemens
3008	Peel	Clemens
3006	Rifkin	Cisneros
3001	Rifkin	Cisneros
3002	Motika	Pereira

10 rows in set (0.057 sec)

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```

KD4-98876-Anuradha> SELECT c.cname AS customer_name,
->      s.sname AS salesperson_name,
->      s.comm AS commission
-> FROM customers c
-> JOIN salespeople s
-> ON c.snum = s.snum
-> WHERE s.comm > 0.12;

```

customer_name	salesperson_name	commission
Liu	Serres	0.13
Grass	Serres	0.13
Cisneros	Rifkin	0.15

```

3 rows in set (0.068 sec)

```

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```

KD4-98876-Anuradha> SELECT o.onum, s.comm, s.comm * o.amt
-> FROM orders o
-> JOIN customers c ON o.cnum = c.cnum
-> JOIN salespeople s ON o.snum = s.snum
-> WHERE c.rating > 100;

```

onum	comm	s.comm * o.amt
3010	0.13	40.2935
3007	0.13	9.8475
3005	0.13	670.8585
3006	0.15	164.7240
3001	0.15	2.8035
3009	0.10	171.3230

```

6 rows in set (0.071 sec)

```

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed

KD4-98876-Anuradha>

KD4-98876-Anuradha> SELECT

-> s1.sname AS Salesperson1,

-> s2.sname AS Salesperson2,

-> s1.city

-> FROM salespeople s1

-> JOIN salespeople s2

-> ON s1.city = s2.city

-> AND s1.snum < s2.snum;

Salesperson1	Salesperson2	city
Peel	Motika	London

1 row in set (0.127 sec)