

Assignment-6
Using Special Operators in Conditions.

- 1) Write two different queries that would produce all orders taken on October 3rd or 4th, 1990.
- 2) Write a query that selects all of the customers serviced by Peel or Motika.
(Hint: the snum field relates the two tables to one another).
- 3) Write a query that will produce all the customers whose names begin with a letter from 'A' to 'G'.
- 4) Write a query that selects all customers whose names begin with the letter 'C'.
- 5) Write a query that selects all orders except those with zeroes or NULLs in the amt field.

1)

```
kd4_92410_saishiva>select * from orders where Odate in('1990-10-03','1990-10-04');
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002

```
7 rows in set (0.01 sec)
```

```
kd4_92410_saishiva>select * from orders where Odate='1990-10-03' or odate='1990-10-04'
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002

```
7 rows in set (0.00 sec)
```

2)

```
kd4_92410_saishiva>select Snum Salesperson_No,Cname Customer_Nam
e from customers where Snum =1001 or Snum =1004;
+-----+-----+
| Salesperson_No | Customer_Name |
+-----+-----+
|          1001 | Hoffman       |
|          1001 | Clemens       |
|          1004 | Pereira       |
+-----+-----+
3 rows in set (0.00 sec)
```

3)

```
kd4_92410_saishiva>select * from customers where Cname between 'A' and 'H';
+-----+-----+-----+-----+-----+
| Cnum | Cname   | City   | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome   | 200    | 1003 |
| 2004 | Grass    | Berlin | 300    | 1002 |
| 2006 | Clemens  | London | 100    | 1001 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

4)

```
kd4_92410_saishiva>select * from customers where cname like 'C%'
;
+-----+-----+-----+-----+-----+
| cnum | cname   | city   | rating | snum |
+-----+-----+-----+-----+-----+
| 2006 | Clemens | London | 100    | 1001 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

5)

```
kd4_92410_saishiva>select * from orders where amt !=0 and amt is not null;
```

onum	amt	odate	cnum	snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

```
10 rows in set (0.01 sec)
```