

VS-40 Portable Transmitter

The Visiplex Portable Transmitter is designed to provide portable paging capability in a small package. The VS-40 comes standard with trigger input which can be programmed through an RS232 connection. Transmitter power varies from 10 milliwatts to 5 Watts.

VP-40 Portable Transmitter

- Small & versatile
- Switch / Logic Trigger Input
- RS232 program port
- 10 milliwatts to 5 Watts power
- VHF, UHF & 900MHz
- POCSAG signaling format
- 512/1200 selectable baud rate
- Power On Indicator
- Operates on 3-12 volt DC power
- Optional rechargeable battery operation



Performance / Specifications:

Power output	10 milliwatts to 5 Watts
Modulation	Direct FM
Attack Time	8 M/SEC
Audio Response	Flat (300-3KHz)
Distortion	<5%
Max Mod. input	25mV-2V RMS for 5KHz @ 1KHz, adjustable
Spurious & Harmonic Emissions	<60dB
Audio Distortion	<5%
FCC ID/Part	GOX KS1000/15,22,90
Frequency	150-174MHz, 402-470 MHz & 906-930Mhz
Operating Temp	-30 to +60C
Voltage	3.0-12.0 V DC
Weight	5.0 OZ.

Visiplex Technologies, Inc.

111 Deer Lake Road, Suite 120
Deerfield, IL 60015

Phone: (847) 405-0771 Fax: (847) 405-0776

E-mail: sales@visiplex.com

Web site: www.visiplex.com

