4-Line Alphanumeric Pager







## **VP-4AW Alphanumeric 4-Line Pager**

- 4-line normal display with 88 characters per screen
- 2-line big size alpha display with 32 characters per screen
- Total 25,000 character storage capacity
- Memory retention (memory back-up battery inside)
- Unread message reminder alert every 3 minutes
- Message time stamping
- Date and time display
- Choice to delete individual message or erase all
- Message full indication
- Selectable alert mode: 4 kinds of beep, 10 kinds of melody, vibration & silent
- 3 alarm settings
- Back light control function
- Adjustable LCD contrast
- Low battery indication
- Automatic power on/off
- Out of range indication
- Message lock function
- CE approval



## Performance /Specifications:

Frequency	410-510 MHz,	138-174 MHz,	278-286 MHz,	929-932 MHz
Signal format	POCSAG & FLEX			
Paging sensitivity	7UV/M	7UV/M	7.5UV/M	8UV/M
Channel spacing	25/12.5 KHz	25/12.5 KHz	25/12.5 KHz	25/12.5 KHz
Selectivity	>60db	>60db	>60db	>50db
Spurious rejection	>50db	>50db	>50db	>50db
Image Rejection	>50db	>50db	>50db	>50db
Alarm output	75 DB (MIN)			
Baud Rate	512 BPS / 1200 BPS /2400 BPS			
Frequency stability	<10ppm	<10ppm	<10ppm	<10ppm
Power supply	ONE 1.5 V AAA size alkaline battery			
Average life of battery 500 - 700 hours				
Dimension	L=2.5 " x H=1.75 " x D=.5"			
Weight	1.8 oz (including battery & clip)			



## Visiplex Technologies, Inc.

111 Deer Lake Road, Suite 120 Deerfield, IL 60015 Phone: (847) 405-0771 Fax: (847) 405-0776

E-mail: <a href="mailto:sales@visiplex.com">sales@visiplex.com</a>
Web site: <a href="mailto:www.visiplex.com">www.visiplex.com</a>