

Java Datatypes

Java has 8 primitive data types; *char*, *boolean*, *byte*, *short*, *int*, *long*, *float*, and *double*. For this exercise, we'll work with the primitives used to hold integer values (*byte*, *short*, *int*, and *long*):

- A *byte* is an 8-bit signed integer.
- A *short* is a 16-bit signed integer.
- An *int* is a 32-bit signed integer.
- A *long* is a 64-bit signed integer.

Given an input integer, you must determine which primitive data types are capable of properly storing that input.

To get you started, a portion of the solution is provided for you in the editor.

Reference: <https://docs.oracle.com/javase/tutorial/java/nutsandbolts/datatypes.html>

Input Format

The first line contains an integer, *T*, denoting the number of test cases.

Each test case, *T*, is comprised of a single line with an integer, *n*, which can be arbitrarily large or small.

Output Format

For each input variable *n* and appropriate primitive *dataType*, you must determine if the given primitives are capable of storing it. If yes, then print:

```
n can be fitted in:  
* dataType
```

If there is more than one appropriate data type, print each one on its own line and order them by size (i.e.: *byte* < *short* < *int* < *long*).

If the number cannot be stored in one of the four aforementioned primitives, print the line:

```
n can't be fitted anywhere.
```

Sample Input

```
5  
-150  
150000  
1500000000  
21333333333333333333333333333333  
-1000000000000000
```

Sample Output

```
-150 can be fitted in:  
* short  
* int  
* long  
150000 can be fitted in:  
* int
```

Explanation

21333333333333333333333333333333 is very large and is outside of the allowable range of values for the primitive data types discussed in this problem.