

Caesar Cipher



Julius Caesar protected his confidential information by encrypting it using a cipher. [Caesar's cipher](#) shifts each letter by a number of letters. If the shift takes you past the end of the alphabet, just rotate back to the front of the alphabet. In the case of a rotation by 3, w, x, y and z would map to z, a, b and c.

```
Original alphabet:  abcdefghijklmnopqrstuvwxyz
Alphabet rotated +3: defghijklmnopqrstuvwxyzabc
```

For example, the given cleartext $s = \text{There's-a-starman-waiting-in-the-sky}$ and the alphabet is rotated by $k = 3$. The encrypted string is **Wkhuh'v-d-vwdupdq-zdlwlqj-lq-wkh-vnb**.

Note: The cipher *only* encrypts letters; symbols, such as `'`, remain unencrypted.

Function Description

Complete the `caesarCipher` function in the editor below. It should return the encrypted string.

`caesarCipher` has the following parameter(s):

- s : a string in cleartext
- k : an integer, the alphabet rotation factor

Input Format

The first line contains the integer, n , the length of the unencrypted string.

The second line contains the unencrypted string, s .

The third line contains k , the number of letters to rotate the alphabet by.

Constraints

$$1 \leq n \leq 100$$

$$0 \leq k \leq 100$$

s is a valid ASCII string without any spaces.

Output Format

For each test case, print the encoded string.

Sample Input

```
11
middle-Outz
2
```

Sample Output

```
okffng-Qwvb
```

Explanation

```
Original alphabet:  abcdefghijklmnopqrstuvwxyz
Alphabet rotated +2: cdefghijklmnopqrstuvwxyzab
```

```
m -> o
i -> k
d -> f
d -> f
l -> n
e -> g
```

- -
O -> Q
u -> w
t -> v
z -> b