



Unsupervised Sentiment Analysis with Lexicon Models

We talked about unsupervised learning methods in the past, which refer to specific modeling methods that can be applied directly to data features without the presence of labeled data. One of the major challenges in any organization is getting labeled datasets due the lack of time as well as resources to do this tedious task. Unsupervised methods are very useful in this scenario and we look at some of these methods in this section. Even though we have labeled data, this section should give you a good idea of how lexicon based models work and you can apply them to your own datasets when you do not have labeled data.

Unsupervised sentiment analysis models use well curated knowledgebases, ontologies, lexicons, and databases, which have detailed information pertaining to subjective words, phrases including sentiment, mood, polarity, objectivity, subjectivity, and so on.

A lexicon model typically uses a lexicon, also known as a dictionary or vocabulary of words specifically aligned to sentiment analysis. These lexicons contain a list of words associated with positive and negative sentiment, polarity (magnitude of negative or positive score), parts of speech (POS) tags, subjectivity classifiers (strong, weak, neutral), mood, modality, and so on.

You can use these lexicons and compute the sentiment of a text document by matching the presence of specific words from the lexicon and then looking at other factors like presence of negation parameters, surrounding words, overall context, phrases, and aggregate overall sentiment polarity scores to decide the final sentiment score.

There are several popular lexicon models used for sentiment analysis. Some of them are as follows:

- Bing Liu's lexicon
- MPQA subjectivity lexicon
- Pattern lexicon
- TextBlob lexicon
- AFINN lexicon
- SentiWordNet lexicon
- VADER lexicon

This is not an exhaustive list of lexicon models but these are definitely among the most popular ones available today.

▼ Install Dependencies

```
!pip install textblob
!pip install textsearch
!pip install contractions
```

```
!pip install afinn
import nltk
nltk.download('punkt')
nltk.download('stopwords')
nltk.download('vader_lexicon')
```

```
Requirement already satisfied: textblob in /usr/local/lib/python3.7/dist-packages (0.15.3)
Requirement already satisfied: nltk>=3.1 in /usr/local/lib/python3.7/dist-packages (from textblob) (3.2.5)
Requirement already satisfied: six in /usr/local/lib/python3.7/dist-packages (from nltk>=3.1->textblob) (1.15.0)
Requirement already satisfied: textsearch in /usr/local/lib/python3.7/dist-packages (0.0.21)
Requirement already satisfied: pyahocorasick in /usr/local/lib/python3.7/dist-packages (from textsearch) (1.4.4)
Requirement already satisfied: anyascii in /usr/local/lib/python3.7/dist-packages (from textsearch) (0.3.0)
Requirement already satisfied: contractions in /usr/local/lib/python3.7/dist-packages (0.1.66)
Requirement already satisfied: textsearch>=0.0.21 in /usr/local/lib/python3.7/dist-packages (from contractions) (0.0.21)
Requirement already satisfied: pyahocorasick in /usr/local/lib/python3.7/dist-packages (from textsearch>=0.0.21->contractions) (1.4.4)
Requirement already satisfied: anyascii in /usr/local/lib/python3.7/dist-packages (from textsearch>=0.0.21->contractions) (0.3.0)
Requirement already satisfied: afinn in /usr/local/lib/python3.7/dist-packages (0.1)
[nltk_data] Downloading package punkt to /root/nltk_data...
[nltk_data] Package punkt is already up-to-date!
[nltk_data] Downloading package stopwords to /root/nltk_data...
[nltk_data] Package stopwords is already up-to-date!
[nltk_data] Downloading package vader_lexicon to /root/nltk_data...
[nltk_data] Package vader_lexicon is already up-to-date!
True
```

▼ Load Dependencies

```
import pandas as pd
import numpy as np
import nltk
import textblob
from sklearn.metrics import confusion_matrix, classification_report
np.set_printoptions(precision=2, linewidth=80)
```

▼ Load Dataset

```
# adapted code to download files from storage
from google.colab import files

uploaded = files.upload()
```

Choose Files noneutral_o...pt2021.xlsx

- **noneutral_orange_luna_15sept2021.xlsx**(application/vnd.openxmlformats-officedocument.spreadsheetml.sheet) - 39699 bytes, last modified: 2/18/2022 - 100% done
Saving noneutral_orange_luna_15sept2021.xlsx to noneutral_orange_luna_15sept2021.xlsx

```
# adapted code to read xlsx files
import pandas as pd
import io
dataset = pd.read_excel(io.BytesIO(uploaded['noneutral_orange_luna_15sept2021.xlsx']))

#reviews = np.array(dataset['review'])
reviews = np.array(dataset['text']) # the dataset field is called 'text' on orange xlsx results
sentiments = np.array(dataset['sentiment'])

# extract data for model evaluation
test_reviews = reviews[1:]
test_sentiments = sentiments[1:]
sample_review_ids = [2,5,10,50,100,150]
```

▼ Sentiment Analysis with TextBlob

The lexicon that TextBlob uses is the same one as pattern and is available in their source code on GitHub

(<https://github.com/sloria/TextBlob/blob/dev/textblob/en/en-sentiment.xml>). Some sample examples are shown from the lexicon as follows.

```
<word form="abhorrent" wordnet_id="a-1625063" pos="JJ" sense="offensive
to the mind" polarity="-0.7" subjectivity="0.8" intensity="1.0"
reliability="0.9" />
<word form="able" cornetto_synset_id="n_a-534450" wordnet_id="a-01017439"
pos="JJ" sense="having a strong healthy body" polarity="0.5"
subjectivity="1.0" intensity="1.0" confidence="0.9" />
```

Typically, specific adjectives have a polarity score (negative/positive, -1.0 to +1.0) and a subjectivity score (objective/subjective, +0.0 to +1.0).

The reliability score specifies if an adjective was hand-tagged (1.0) or inferred (0.7). Words are tagged per sense, e.g., ridiculous (pitiful) = negative, ridiculous (humorous) = positive.

The Cornetto id (lexical unit id) and Cornetto synset id refer to the Cornetto lexical database for Dutch. The WordNet id refers to the WordNet3 lexical database for English. The part-of-speech tags (POS) use the Penn Treebank convention. Let's look at how we can use TextBlob for sentiment analysis.

▼ Predict sentiment for sample reviews

```
for review, sentiment in zip(test_reviews[sample_review_ids], test_sentiments[sample_review_ids]):
    print('REVIEW:', review)
    print('Actual Sentiment:', sentiment)
    print('Predicted Sentiment polarity:', textblob.TextBlob(review).sentiment.polarity)
    print('-'*60)

REVIEW: @HighCoinviction @terra_money What happens to wrapped Terra based coins once IBC is in play?
Actual Sentiment: negative
Predicted Sentiment polarity: 0.0
-----
REVIEW: 1/n First came @mirror_protocol , a kick ass innovation that brought minting and trading of synthetics on the @terra_money blockchain 🟡. It
Actual Sentiment: positive
Predicted Sentiment polarity: 0.3166666666666667
-----
REVIEW: @Chadilac0x @terra_money ooooh I'd love this so much.
Actual Sentiment: positive
Predicted Sentiment polarity: 0.35
-----
REVIEW: @Coin98Analytics @avalancheavax @dfinity @NEARProtocol @FantomFDN @ElrondNetwork @Algorand @Polkadot @0xPolygon @terra_money @solana Good Analy
Actual Sentiment: positive
Predicted Sentiment polarity: 0.7
-----
REVIEW: @jonathan6620 @Fetch_ai IBC will get you in contact with @terra_money , whereupon problem solved!
Actual Sentiment: negative
Predicted Sentiment polarity: 0.0
-----
REVIEW: @terranaut3 @spaceloot_nft @terra_money @KubaBe777 @MaciejSobon Loop will be great!
Actual Sentiment: positive
Predicted Sentiment polarity: 1.0
-----
```

▼ Predict sentiment for test dataset

```
sentiment_polarity = [textblob.TextBlob(review).sentiment.polarity for review in test_reviews]

# adapted codo to get positive score above 0, instead of score >= 0.1
predicted_sentiments = ['positive' if score > 0 else 'negative' for score in sentiment_polarity]
```

▼ Evaluate model performance

```
labels = ['negative', 'positive']
print(classification_report(test_sentiments, predicted_sentiments))
pd.DataFrame(confusion_matrix(test_sentiments, predicted_sentiments), index=labels, columns=labels)
```

	precision	recall	f1-score	support
negative	0.51	0.61	0.55	46
positive	0.84	0.77	0.80	119
accuracy			0.73	165
macro avg	0.67	0.69	0.68	165
weighted avg	0.75	0.73	0.73	165

	negative	positive
negative	28	18
positive	27	92

▼ Sentiment Analysis with AFINN

The AFINN lexicon is perhaps one of the simplest and most popular lexicons and can be used extensively for sentiment analysis. Developed and curated by Finn Årup Nielsen, you can find more details on this lexicon in the paper by Finn Årup Nielsen, entitled “A New ANEW: Evaluation of a Word List for Sentiment Analysis in Microblogs,” from the proceedings of the ESWC2011 workshop.

The current version of the lexicon is AFINN-en-165.txt and it contains over 3,300 words with a polarity score associated with each word. You can find this lexicon at the author’s official GitHub repository along with previous versions of this lexicon including AFINN-111 at <https://github.com/fnielsen/afinn/blob/master/afinn/data/>.

The author has also created a nice wrapper library on top of this in Python called `afinn`, which we will be using for our analysis needs

```
from afinn import Afinn

afn = Afinn(emoticons=True)
```

▼ Predict sentiment for sample reviews

```
for review, sentiment in zip(test_reviews[sample_review_ids], test_sentiments[sample_review_ids]):
    print('REVIEW:', review)
    print('Actual Sentiment:', sentiment)
    print('Predicted Sentiment polarity:', afn.score(review))
    print('-'*60)
```

REVIEW: @HighCoinviction @terra_money What happens to wrapped Terra based coins once IBC is in play?

Actual Sentiment: negative

Predicted Sentiment polarity: 0.0

REVIEW: 1/n First came @mirror_protocol , a kick ass innovation that brought minting and trading of synthetics on the @terra_money blockchain 🟡. It

Actual Sentiment: positive

Predicted Sentiment polarity: -1.0

REVIEW: @Chadilac0x @terra_money ooooh I'd love this so much.

Actual Sentiment: positive

Predicted Sentiment polarity: 3.0

REVIEW: @Coin98Analytics @avalancheavax @dfinity @NEARProtocol @FantomFDN @ElrondNetwork @Algorand @Polkadot @0xPolygon @terra_money @solana Good Analy

Actual Sentiment: positive

Predicted Sentiment polarity: 3.0

REVIEW: @jonathan6620 @Fetch_ai IBC will get you in contact with @terra_money , whereupon problem solved!

Actual Sentiment: negative

Predicted Sentiment polarity: -1.0

REVIEW: @terranaut3 @spaceloot_nft @terra_money @KubaBe777 @MaciejSobon Loop will be great!

Actual Sentiment: positive

Predicted Sentiment polarity: 3.0

▼ Predict sentiment for test dataset

```
sentiment_polarity = [afn.score(review) for review in test_reviews]
```

```
# adapted codo to get positive score above 0, instead of score >= 1.0
```

```
predicted_sentiments = ['positive' if score > 0 else 'negative' for score in sentiment_polarity]
```

▼ Evaluate model performance

```
labels = ['negative', 'positive']
```

```
print(classification_report(test_sentiments, predicted_sentiments))
```

```
pd.DataFrame(confusion_matrix(test_sentiments, predicted_sentiments), index=labels, columns=labels)
```

	precision	recall	f1-score	support
negative	0.65	0.67	0.66	46
positive	0.87	0.86	0.86	119
accuracy			0.81	165
macro avg	0.76	0.77	0.76	165
weighted avg	0.81	0.81	0.81	165

```
import nltk
import re
import numpy as np
import contractions

stop_words = nltk.corpus.stopwords.words('english')

def normalize_document(doc):
    # lower case and remove special characters\whitespaces
    doc = re.sub(r'^a-zA-Z0-9\s', '', doc, re.I|re.A)
    doc = doc.strip()
    doc = contractions.fix(doc)
    return doc

normalize_corpus = np.vectorize(normalize_document)

norm_corpus = normalize_corpus(test_reviews)
len(norm_corpus)

165
```

▼ Sentiment Analysis with VADER

The VADER lexicon, developed by C.J. Hutto, is based on a rule-based sentiment analysis framework, specifically tuned to analyze sentiments in social media. VADER stands for Valence Aware Dictionary and sEntiment Reasoner. Details about this framework can be read in the original paper by Hutto, C.J., and Gilbert, E.E. (2014), entitled “VADER: A Parsimonious Rule-based Model for Sentiment Analysis of Social Media Text,” from the proceedings of the Eighth International Conference on Weblogs and Social Media (ICWSM-14). You can use the library based on NLTK’s interface under the `nltk.sentiment.vader` module.

You can also download the actual lexicon or install the framework from <https://github.com/cjhutto/vaderSentiment>, which also contains detailed information about VADER. This lexicon, present in the file titled `vader_lexicon.txt`, contains necessary sentiment scores associated with words, emoticons, and slangs (like wtf, lol, nah, and so on).

There were a total of over 9,000 lexical features from which over 7,500 curated lexical features were finally selected in the lexicon with proper validated valence scores.

Each feature was rated on a scale from "[-4] Extremely Negative" to "[4] Extremely Positive", with allowance for "[0] Neutral (or Neither, N/A)".

The process of selecting lexical features was done by keeping all features that had a non-zero mean rating and whose standard deviation was less than 2.5, which was determined by the aggregate of ten independent raters. We depict a sample from the VADER lexicon as follows:

```
:( -1.9 1.13578 [-2, -3, -2, 0, -1, -1, -2, -3, -1, -4]
:) 2.0 1.18322 [2, 2, 1, 1, 1, 1, 4, 3, 4, 1]
...
terrorizing -3.0 1.0 [-3, -1, -4, -4, -4, -3, -2, -3, -2, -4]
thankful 2.7 0.78102 [4, 2, 2, 3, 2, 4, 3, 3, 2, 2]
```

Each line in the preceding lexicon sample depicts a unique term, which can either be an emoticon or a word. The first token indicates the word/emoticon, the second token indicates the mean sentiment polarity score, the third token indicates the standard deviation, and the final token indicates a list of scores given by 10 independent scorers.

```
from nltk.sentiment.vader import SentimentIntensityAnalyzer

def analyze_sentiment_vader_lexicon(review,
                                     threshold=0.1,
                                     verbose=False):
    # analyze the sentiment for review
    analyzer = SentimentIntensityAnalyzer()
    scores = analyzer.polarity_scores(review)
    # get aggregate scores and final sentiment
    agg_score = scores['compound']
    final_sentiment = 'positive' if agg_score >= threshold\
        else 'negative'

    if verbose:
        # display detailed sentiment statistics
        positive = str(round(scores['pos'], 2)*100)+'%'
        final = round(agg_score, 2)
        negative = str(round(scores['neg'], 2)*100)+'%'
        neutral = str(round(scores['neu'], 2)*100)+'%'
        sentiment_frame = pd.DataFrame([[final_sentiment, final, positive,
                                         negative, neutral]],
                                       columns=pd.MultiIndex(levels=[['SENTIMENT STATS:'],
                                                                       ['Predicted Sentiment', 'Polarity Score',
                                                                       'Positive', 'Negative', 'Neutral']],
                                                             codes=[[0,0,0,0,0],[0,1,2,3,4]]))

        print(sentiment_frame)

    return final_sentiment
```


▼ Predict sentiment for sample reviews

```
for review, sentiment in zip(norm_corpus[sample_review_ids], test_sentiments[sample_review_ids]):
    print('REVIEW:', review)
    print('Actual Sentiment:', sentiment)
    pred = analyze_sentiment_vader_lexicon(review, threshold=0.4, verbose=True)
    print('-'*60)
```

REVIEW: HighCoinviction terramoney What happens to wrapped Terra based coins once IBC is in play
Actual Sentiment: negative

SENTIMENT STATS:

	Predicted Sentiment	Polarity Score	Positive	Negative	Neutral
0	negative	0.34	16.0%	0.0%	84.0%

REVIEW: 1n First came mirrorprotocol a kick ass innovation that brought minting and trading of synthetics on the terramoney blockchain It allowed for
Actual Sentiment: positive

SENTIMENT STATS:

	Predicted Sentiment	Polarity Score	Positive	Negative	Neutral
0	positive	0.61	21.0%	11.0%	67.0%

REVIEW: Chadilac0x terramoney ooooh Id love this so much
Actual Sentiment: positive

SENTIMENT STATS:

	Predicted Sentiment	Polarity Score	Positive	Negative	Neutral
0	positive	0.64	38.0%	0.0%	62.0%

REVIEW: Coin98Analytics avalancheavax dfinity NEARProtocol FantomFDN ElrondNetwork Algorand Polkadot 0xPolygon terramoney solana Good Analytics
Actual Sentiment: positive

SENTIMENT STATS:

	Predicted Sentiment	Polarity Score	Positive	Negative	Neutral
0	positive	0.44	20.0%	0.0%	81.0%

REVIEW: jonathan6620 Fetchai IBC will get you in contact with terramoney whereupon problem solved
Actual Sentiment: negative

SENTIMENT STATS:

	Predicted Sentiment	Polarity Score	Positive	Negative	Neutral
0	negative	-0.15	13.0%	17.0%	70.0%

REVIEW: terranaut3 spacelootnft terramoney KubaBe777 MaciejSobon Loop will be great
Actual Sentiment: positive

SENTIMENT STATS:

	Predicted Sentiment	Polarity Score	Positive	Negative	Neutral
0	positive	0.62	34.0%	0.0%	66.0%

▼ Predict sentiment for test dataset

```
predicted_sentiments = [analyze_sentiment_vader_lexicon(review, threshold=0.4, verbose=False) for review in test_reviews]
```

▼ Evaluate model performance

```
labels = ['negative', 'positive']
print(classification_report(test_sentiments, predicted_sentiments))
pd.DataFrame(confusion_matrix(test_sentiments, predicted_sentiments), index=labels, columns=labels)
```


```

┌─┐
precision    recall  f1-score   support

negative     0.51     0.76     0.61         46
positive     0.89     0.71     0.79        119

accuracy              0.73         165
macro avg     0.70     0.74     0.70         165
weighted avg   0.78     0.73     0.74         165

```

	negative	positive	
negative	35	11	
positive	34	85	

