Digital Signal Processing

Lecture 7 – Autocorrelation

상명대학교 컴퓨터과학과 강상욱 교수



Definition of correlation

- Very useful tool for signal analysis.
 - The analysis of autocorrelation is a mathematical tool for finding repeating patterns, such as the presence of a <u>periodic signal</u> obscured by <u>noise</u>.
 - Identifying the <u>missing fundamental frequency</u> in a signal implied by its <u>harmonic</u> frequencies.
- Correlation between variables
 - If you know the value of one, you have some information about the other.
 - Pearson product-moment correlation coefficient (to quantify the correlation)

$$\rho = \frac{\sum_{i} (x_i - \mu_x)(y_i - \mu_y)}{N\sigma_x \sigma_y}, \quad -1 \le \rho \le 1$$

 μ_x , μ_y : mean of x and y

 σ_x , σ_y : standard deviation of x and y

The meaning of correlation

- If ρ is positive,
 - The correlation is positive
 - When one variable is high, the other tends to be high.
 - And, vice versa.
- $lue{}$ The magnitude of ρ
 - The strength of the correlation.
 - If $\rho = 1$ or -1, the variables are perfectly correlated and if you know one, you can make a perfect prediction about the other.
 - If $\rho \sim 0$, the correlation is probably weak.
 - "probably weak" because it is also possible that there is a nonlinear relationship that is not captured by the coefficient of correlation.
- Correlation in Python


```
>>> from numpy import *
>>> T = array([1.3, 4.5, 2.8, 3.9]) # temperature measurements
>>> P = array([2.7, 8.7, 4.7, 8.2]) # corresponding pressure measurements
>>> print corrcoef([T,P]) # correlation matrix of temperature and pressure
[[ 1. 0.98062258]
  [ 0.98062258 1. ]]
```

Correlation example 1

```
def make_sine(offset):
    signal = thinkdsp.SinSignal(freq=440, offset=offset)
    wave = signal.make_wave(duration=0.5, framerate=10000)
    return wave
```

```
wave1 = make_sine(offset=0)
wave2 = make_sine(offset=1)
```

make_sine(offset) constructs sine waves with different phase offsets



The option ddof=0 indicates that corrcoef should divide by N, as in the equation above, rather than use the default, N-1.

Correlation example 2

As the offset increases, the correlation decreases until the waves are 180 degrees (π) out of phase, which yields correlation - I




Figure 5.2: The correlation of two sine waves as a function of the phase offset between them. The result is a cosine.

thinkdsp provides a simple interface for computing the correlation between waves: >>> wave1.corr(wave2)

0.54

Serial correlation 1

- The correlation between each element and the next (or the previous).
 - To compute it, we can shift a signal and then compute the correlation of the shifted version with the original.

```
def serial_corr(wave, lag=1):
    n = len(wave)
    y1 = wave.ys[lag:]
    y2 = wave.ys[:n-lag]
    corr = np.corrcoef(y1, y2, ddof=0)[0, 1]
    return corr
```

serial_corr takes a Wave object and lag, which is the integer number of places to shift the wave. It computes the correlation of the wave with a shifted version of itself.

Serial correlation 2

```
signal = thinkdsp.UncorrelatedGaussianNoise()
wave = signal.make_wave(duration=0.5, framerate=11025)
serial_corr(wave)
```

The result value will be small or large? -- Yes, comparably small (0.06). Why?

```
signal = thinkdsp.BrownianNoise()
wave = signal.make_wave(duration=0.5, framerate=11025)
serial_corr(wave)
```

How about the Brownian noise? -- Yes, comparably large (0.999). Why?

```
signal = thinkdsp.PinkNoise(beta=1)
wave = signal.make_wave(duration=0.5, framerate=11025)
serial_corr(wave)
```

How about pink noise? -- Yes, inbetween Brownian and UU noise (0.851). Why?




Figure 5.3: Serial correlation for pink noise with a range of parameters.

Autocorrelation 1

Definition

- Serial_corr can be thought as a function that maps from each value of lag to the corresponding correlation.
- We can evaluate that function by looping through values of lag.

```
def autocorr(wave):
    lags = range(len(wave.ys)//2)
    corrs = [serial_corr(wave, lag) for lag in lags]
    return lags, corrs
```

autocorr takes a Wave object and returns the autocorrelation function as a pair of sequences: lags is a sequence of integers from 0 to half the length of the wave; corrs is the sequence of serial correlations for each lag.

Autocorrelation 2

Definition

- Serial_corr can be thought as a function that maps from each value of lag to the corresponding correlation.
- We can evaluate that function by looping through values of lag.

```
def autocorr(wave):
    lags = range(len(wave.ys)//2)
    corrs = [serial_corr(wave, lag) for lag in lags]
    return lags, corrs
```

autocorr takes a Wave object and returns the autocorrelation function as a pair of sequences: lags is a sequence of integers from 0 to half the length of the wave; corrs is the sequence of serial correlations for each lag.

Autocorrelation example

For low values of β , the signal is less correlated.

For high values of β , the serial correlation is stronger and drops off more slowly, which is called "long-range dependence




Figure 5.4: Autocorrelation functions for pink noise with a range of parameters.

Autocorrelation of periodic signals 1

A chirp that starts near 500Hz and drops down to about 300Hz.

28042 bcjordan voicedownbew.wav : listen to this duration = 0.01segment = wave.segment(start=0.2, duration=duration) spectrum = segment.make_spectrum() spectrum.plot(high=1000) 4000 3500 It drops from 500Hz to 3000 The length of the 300Hz. 50 segment is 441 samples 2500 at framerate 4#100Hz 40 1500 1000 10 Time (s) Figure 5.5: Spectrogram of a vocal chirp. Frequency (Hz) A clear peak near 400Hz Figure 5.6: Spectrum of a segment from a vocal chirp.

Autocorrelation of periodic signals 2

- Is the peak 400Hz precisely?
 - The freq. resolution : I00Hz (Why?)
 - The estimated peak might be off by 50Hz.
 - The peak ranges from 350Hz to 450Hz.
 - We could get better freq. resolution by taking a longer segment, but pitch is changing over time.
- We can estimate the pitch more precisely using autocorrelation.
 - If a signal is periodic, the autocorrelation spikes when the lag equals the period.


Finding period using autocorrelation 1

```
def plot_shifted(wave, offset=0.001, start=0.2):
    thinkplot.preplot(2)
     segment1 = wave.segment(start=start, duration=0.01)
     segment1.plot(linewidth=2, alpha=0.8)
     segment2 = wave.segment(start=start-offset, duration=0.01)
     segment2.shift(offset)
     segment2.plot(linewidth=2, alpha=0.4)
     corr = segment1.corr(segment2)
     text = r'$\rho =$ %.2g' % corr
     thinkplot.text(segment1.start+0.0005, -0.8, text)
     thinkplot.config(xlabel='Time (s)')
```

lags, corrs = autocorr(segment)
thinkplot.plot(lags, corrs)

The result is shown in Figure 5.8

Finding period using autocorrelation 2



*What is the freq. of the segment?

*What is the freq. precision?

If lag=100
$$\rightarrow$$
 432 Hz
If lag=102 \rightarrow 441 Hz, so <10 Hz

Figure 5.8: Autocorrelation function for a segment from a chirp.

Increased framerate incurs increased freq. precision, which contradicts Gabor limit.

* Comparison of the freq. precision? 432 – 437 – 441

350 - 400 - 450

Correlation as a dot product

In signal processing, unbiased and normalized signals are often used, where the mean is 0 and the standard deviation is 1.

$$\rho = \frac{\sum_{i}(x_{i} - \mu_{x})(y_{i} - \mu_{y})}{N\sigma_{x}\sigma_{y}} = \frac{\sum_{i}x_{i}y_{i}}{N}, \text{ or }$$

- $r = \sum_{i} x_i y_i$
- If x and y is in the form of vector, r is the dot product.
- $\cos \theta = \frac{x \cdot y}{\|x\| \|y\|}$, where θ is the angle between the vectors. Also see Figure 5.2 which is a cosine wave.

Using Numpy

corrs2 = np.correlate(segment.ys, segment.ys, mode='same')

The option mode tells correlate what range of lag to use. With the value 'same', the range is from -N/2 to N/2, where N is the length of the wave array.




Figure 5.9: Autocorrelation function computed with np.correlate.

Using Numpy

```
corrs2 = np.correlate(segment.ys, segment.ys, mode='same')
```

The option mode tells correlate what range of lag to use. With the value 'same', the range is from -N/2 to N/2, where N is the length of the wave array.

We can correct the decreasing correlation with the following.

Divide the correlation by gradually decreasing numbers

```
lengths = range(N, N//2, -1)
half /= lengths
```

Normalize the result so the correlation with lag=0 is 1.

half /= half[0]