
## Phys 2010 (NSCC), Spring 2007 Problem Set #9


1. A 300-N sign is suspended from a horizontal 4.00-meter long uniform 100-N rod as indicated at the right. The sign is attached to the rod at a point which is 3.0 m from the wall; The left end of the rod is pivoted and the right end is supported by a thin cable making a 30.0° angle with the vertical.

Find the tension T in the cable.



**2.** A uniform rod 1.00 m in length and of weight 180 N is supported by two wires as shown at the right.

What is the tension in each of the cables supporting the rod?




**3.** The rod from Problem 2 is now supported (horizontally) by *three* ropes, as shown to the right.

Find the tensions in all the ropes.



4. A uniform beam of weight 500 N, 6.00 m in length is supported by a cable at the far end as shown at the right. The cable will break if its tension exceeds  $1300~\rm N$ 


A man of weight 700 N goes walking out on the beam. How away from the wall can he get before the cable breaks?



**5.** A uniform solid sphere of mass 4.0 kg, when rotated about its axis of symmetry, has a moment of inertia of  $9.70 \times 10^{-3} \text{ kg} \cdot \text{m}^2$ . What is the radius of the sphere?

**6.** A uniform rod of mass  $1.0~\rm kg$  and length  $0.80~\rm m$  is turned about an axis through one of its ends and perpendicular to the rod. A *small*  $1.5~\rm kg$  is attached to the very end of the rod, as shown.

Find the moment of inertia of this system about the given axis.



7. If the shpere in Problem 5 is set in rotation, find the torque that will produce an angular acceleration of  $3.00 \frac{\text{rad}}{\text{s}^2}$ 

**8.** A 200-kg merry-go-round in the shape of a uniform, solid horizontal disk of radius 1.60 m is set in motion by wrapping a rope about the rim of the disk and pulling on the rope. What constant force must be exerted on the rope to bring the merry-go-round from rest to an angular speed of  $0.600 \, \text{rev/s}$  in  $2.00 \, \text{s}$ ?

