

# How we do GBS...

## And what's next?

Kevin Murray

@kdmurray91

kevin@kdmurray.id.au

Borevitz Lab, ANU

MapNet GBS workshop


23 Oct 2014

- ▶ Bioinformatics R/A
  - ▶ TraitCapture Project Developer
  - ▶ Genomics (Low level sequence analysis)
  - ▶ Phenomics (Image analysis)
  - ▶ Sample tracking, data standards, HPC.
- ▶ Starting PhD in Bioinformatics of Evolutionary Genomics next year
- ▶ *"Data Intensive Biologist"*

- ▶ Bioinformatics R/A
  - ▶ TraitCapture Project Developer
  - ▶ Genomics (Low level sequence analysis)
  - ▶ Phenomics (Image analysis)
  - ▶ Sample tracking, data standards, HPC.
- ▶ Starting PhD in Bioinformatics of Evolutionary Genomics next year
- ▶ *"Data Intensive Biologist"*
- ▶ A **very** lapsed kiwi (from Napier)


# What do we use GBS for?

- ▶ Population and Landscape Genomics
- ▶ Population re-sampling
- ▶ Genotype verification
- ▶ Epigenomics - HpaII/Mspl




# What do we use GBS for?

- ▶ Population and Landscape Genomics
- ▶ Population re-sampling
- ▶ Genotype verification
- ▶ Epigenomics - HpaII/Mspl



# What do we use GBS for?

- ▶ Population and Landscape Genomics
- ▶ Population re-sampling
- ▶ Genotype verification
- ▶ Epigenomics - HpaII/Mspl




# Library preparation

- ▶ We do all our library prep. in house
- ▶ Cost  $\approx$  \$10/sample including extraction
- ▶ Done in lots of 96
- ▶ Semi-automated wet-lab protocol



# Library preparation

- ▶ We do all our library prep. in house
- ▶ Cost  $\approx$  \$10/sample including extraction
- ▶ Done in lots of 96
- ▶ Semi-automated wet-lab protocol






# Library preparation

- ▶ We do all our library prep. in house
- ▶ Cost  $\approx$  \$10/sample including extraction
- ▶ Done in lots of 96
- ▶ Semi-automated wet-lab protocol




# Library preparation protocol

- ▶ Modified protocol from Elshire et al. (2011)
- ▶ PE 101bp HiSeq 2500 reads
- ▶ We use in read barcodes
- ▶ Sequence 576-1152 samples/lane
- ▶ Need “combinatorial” barcoding (next slide)



# Library preparation protocol

- ▶ Modified protocol from Elshire et al. (2011)
- ▶ PE 101bp HiSeq 2500 reads
- ▶ We use in read barcodes
- ▶ Sequence 576-1152 samples/lane
- ▶ Need “combinatorial” barcoding (next slide)



# Combinatorial Barcoding

- ▶ We use dual in read barcodes
- ▶ Independent barcodes for R1 & R2
- ▶ Set of  $96 \times 12 = 1152/\text{lane}$
- ▶ Must be balanced & staggered
- ▶ Hamming distance  $>2$

TGCG  
AGGAT  
TTCAGA  
CGCGGT  
GAATTCA  
CTACGGA  
....  
CCGGATAT  
TTCCTGGA

X

TGCG  
AGGAT  
TTCAGA  
CGCGGT  
GAATTCA  
CTACGGA  
....  
CCGGATAT  
TTCCTGGA

=

CTCG	ATGAAAG	1_A1
TGCA	ATGAAAG	1_A2
ACTA	ATGAAAG	1_A3
AACT	ATGAAAG	1_A5
.....		
GCTGTGGA	CTTGCTT	12_H8
GTGAGGGT	CTTGCTT	12_H10
TATCGGGA	CTTGCTT	12_H11
TTCCTGGA	CTTGCTT	12_H12


96 R1

12 R2

1152 pairs

# De-multiplex with AXE

- ▶ Barcoding scheme requires advanced de-multiplexing
- ▶ Trie-based lookup algorithm
- ▶ Fast (PE lane in 5-10 mins)
- ▶ Highly accurate (99.6%TPR, 100%TNR)
- ▶ Open source at <http://git.io/kIhEZA>
- ▶ IPython notebook “torture-test” at <http://bit.ly/1sXrx4E>




- ▶ Sample-tracking system manages FASTQs after demux:
  - ▶ QC reads (scythe, sickle, seqqs)
  - ▶ After QC, 16-mer globally unique ID re-added to reads
  - ▶ Auto-creates TASSEL KeyFile & working dir for new analysis
  - ▶ Auto-remove 16-mer unique ID from reads if not using TASSEL.

- ▶ Sample-tracking system manages FASTQs after demux:
  - ▶ QC reads (scythe, sickle, seqqs)
  - ▶ After QC, 16-mer globally unique ID re-added to reads
  - ▶ Auto-creates TASSEL KeyFile & working dir for new analysis
  - ▶ Auto-remove 16-mer unique ID from reads if not using TASSEL.
- ▶ DB links FASTQs to real world
  - ▶ Integrate w/ ALA
  - ▶ Provide user-friendly names to downstream analysis


# Downstream Analysis

- ▶ Variant calling:
  - ▶ TASSEL!!
  - ▶ We use UNEAK mostly
  - ▶ Ref-based pipeline w/  
BWA-MEM






- ▶ Variant calling:
  - ▶ TASSEL!!
  - ▶ We use UNEAK mostly
  - ▶ Ref-based pipeline w/  
BWA-MEM
- ▶ Post analysis in R
  - ▶ Custom filtering for  
missing data/paralogy
  - ▶ H-Clust




# Downstream Analysis

- ▶ Variant calling:
  - ▶ TASSEL!!
  - ▶ We use UNEAK mostly
  - ▶ Ref-based pipeline w/  
BWA-MEM
- ▶ Post analysis in R
  - ▶ Custom filtering for  
missing data/paralogy
  - ▶ H-Clust
- ▶ Downstream:
  - ▶ Structure
  - ▶ BayENV
  - ▶ QTLRel




## ► Better adaptors




# The Future!

- ▶ Better adaptors
- ▶ Home-brew NexTera
  - ▶ NextRAD
  - ▶ Low coverage WGS
  - ▶ Long Pseudo-reads




# The Future!

- ▶ Better adaptors
- ▶ Home-brew NexTera
  - ▶ NextRAD
  - ▶ Low coverage WGS
  - ▶ Long Pseudo-reads
- ▶ Informatics:
  - ▶ Imputation?
  - ▶ Paralog/Ploidy detection
  - ▶ Streaming Variant Calling (my PhD)



# Thanks

- ▶ Justin Borevitz
- ▶ Comrades in Informatics
  - ▶ Aaron Chuah
  - ▶ Riyan Chen
  - ▶ Jared Streich
- ▶ Wet-lab Wizardry
  - ▶ Niccy Aitken
  - ▶ Norman Warthmann
- ▶ Rob for the invitation
- ▶ You all for listening!!



`git.io/TYrIFw`