

# kWIP: The k-mer Weighted Inner Product

Estimating genetic similarity of sequencing runs

Kevin Murray

PhD Candidate  
Borevitz Lab, ANU

2016-11-02




# Motivation





# Collection Re-structuring

- ▶ Collect 100s or 1,000s of natural samples
- ▶ “First look” at genetic relatedness
  - ▶ Assert replicates cluster, detect mixups
  - ▶ Carry best samples to detailed analysis




after Brachi *et al.* [1]



# Collection Re-structuring

- ▶ Collect 100s or 1,000s of natural samples
- ▶ “First look” at genetic relatedness
  - ▶ Assert replicates cluster, detect mixups
  - ▶ Carry best samples to detailed analysis




after Brachi *et al.* [1]



# Collection Re-structuring

- ▶ Collect 100s or 1,000s of natural samples
- ▶ “First look” at genetic relatedness
  - ▶ Assert replicates cluster, detect mixups
  - ▶ Carry best samples to detailed analysis




after Brachi *et al.* [1]



# (Initial) Genetic Similarity Estimation

- ▶ Initial genetic analyses inspect
  - ▶ Outgroups (widest relationships)
  - ▶ Replicates
  - ▶ Mix-ups
  - ▶ Broad groupings
- ▶ Current genetic similarity, *not evolutionary history*



after Peterson *et al.* [2]



# Genetic Similarity Estimation – Algorithms

- ▶ Efficient algorithms to analyse large-scale genomic data
  - ▶ Reference & alignment free: *less bias, de novo*
  - ▶ Platform/protocol agnostic: *future proof*
  - ▶ Computationally efficient: *not the bottleneck*



# Alignment-free Sequence Comparison

- ▶ Many existing metrics, and tools
  - ▶ *D2* and related statistics
  - ▶ **spaced** and other spaced-word approaches<sup>3,4</sup>
  - ▶ **Cnidaria** and other Jaccard index approaches<sup>5</sup>
  - ▶ **mash** and other MinHash approaches<sup>6</sup>
- ▶ Most require assembled gene/genome sequence
- ▶ **Most assume evolutionary history between samples**









# Presenting kWIP

- ▶  $k$ -mer based *de novo* genetic similarity estimator
- ▶ Produces a distance matrix from raw NGS reads
- ▶ Uses Weighted Inner Product between  $k$ -mer counts

```
@D954KXP1.261.C3L8WACXX.3:1101:2570:2264 1:N:0:
TGCTGAAGGCAGAAGATGACCAAGCAAGAGCAAGAAATCATGAGCC
+
DADHHBDFIIIIIEHIIIC9CGCCECEGGIIIEIIGIIGGGGG
@D954KXP1.261.C3L8WACXX.3:1101:2570:2264 2:N:0:
TGCAGAAAGTGCAGAAATCAACCGACCCACCAAACTACTAGGTTCAATC
+
FFFDHFFBFA<FHGGIIIGGGHHHHHHHHHHHHHHGGGGHHHGD=FH
@D954KXP1.261.C3L8WACXX.3:1101:3208:2295 1:N:0:
TGCAGGTGAAGGAGAGATCAGACAGTGAATTATAGAACTGCTATGATT
+
FFFHHHFHIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
@D954KXP1.261.C3L8WACXX.3:1101:3208:2295 2:N:0:
TGCAGATTTTATAAACAATTAAGTAATTACGTCCTGCAATGACCACA
+
FFFFHHHHHHIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
@D954KXP1.261.C3L8WACXX.3:1101:3632:2456 1:N:0:
TGCAGCGATTATCACATATTGTTTCAGTGAGTGATTTATTTGTCGATT
+
FFFFHHHHHHIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
@D954KXP1.261.C3L8WACXX.3:1101:3632:2456 2:N:0:
TGCAGTATAAATTCTCTGTTTATACAGACTTTCTAGAAAGAGTAGA
+
FFFFHHHHHHIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
GEGHJDFH
```






# kWIP Algorithm

- ▶ Count each sample's  $k$ -mers probabilistically (**khmer**)
- ▶ Calculate information content of each  $k$ -mer
- ▶ Compute each pairwise distance using weighed inner product (WIP)

Sketch 1	4	1				1	6			1	1
Sketch 2	1					2	3			1	
Sketch 3		2		2		1		1			2
Sketch 4		2	1	7		1					2
Sketch 5	1	4				12	6			9	6
Frequency Sketch	0.6	0.8	0.2	0.4	0	1	0.6	0.2	0	0.6	0.8





# kWIP – Software

- ▶ Uses **khmer** for  $k$ -mer counting
- ▶ Parallelised with OpenMP
- ▶ GNU GPL licensed, C++11 source code on GitHub
- ▶ Precompiled binaries provided
- ▶ Documentation & tutorials online

**kWIP**  
latest

Search docs

kWIP  
Example kWIP Analysis Protocols  
Experiments Around kWIP

Docs » Welcome to kWIP's documentation! [Edit on GitHub](#)

## Welcome to kWIP's documentation!

Contents:

- [kWIP](#)
  - Overview
  - Installation
  - [kWIP](#) CLI Usage
  - The Concepts Behind [kWIP](#)
- Example [kWIP](#) Analysis Protocols
  - *Oryza sativa* grouping
- Experiments Around [kWIP](#)

### Indices and tables

- [Index](#)

[Next](#)

© Copyright 2015, Kevin Murray. Revision 8a8621a4a2573bedcfa7e71d294ab9325c998492.  
Built with [Sphinx](#) using a [theme](#) provided by [Read the Docs](#).

[Read the Docs](#) v:latest



# kWIP Case Studies

- ▶ Rice genomes project<sup>7</sup>
  - ▶ 3000 rice varieties (25k runs)
  - ▶  $\approx$  2-fold sequencing per run
- ▶ Chlamydomonas<sup>8</sup>
  - ▶ High-coverage sequencing of 20 wild & lab strains
- ▶ Rice root-associated microbiome metagenomics
  - ▶ Shotgun sequencing of root-soil interface
- ▶ Simulation
  - ▶ Fake population genome sequencing studies




# Replicate and Subspecies Clustering

- ▶ Set of 96 rice runs from 16 samples, 6 tech reps.
- ▶  $\approx$  3-fold sequencing per run
- ▶ Expectations:
  - ▶ All runs cluster into samples of 6 reps
  - ▶ Big split between 2 major groups (Indica, Japonica)
- ▶ Recover known grouping w/ **kWIP**, not w/ unweighted IP
- ▶ Took 6 hours on 16 CPU, 64GB RAM supercomputer node




# WIP






## IP





# Chlamydomonas

- ▶ Avoid reference bias with “leftover assembly”<sup>8</sup>
  - ▶ Sequence *very* deep (> 200x)
  - ▶ Map to reference
  - ▶ Assemble unmapped reads
  - ▶ Map to reference + leftovers
  - ▶ Call variants
  - ▶ SNPrelate + PCA





“Sample CC-4414 (red) is hidden behind the cluster of laboratory strains (light blue)”







# Chlamydomonas – with kWIP

- ▶ Download SRA files
- ▶ Count  $k$ -mers
- ▶ Run kWIP





# Metagenomes






# Simulation

- ▶ Perform simulated sequencing experiment (50 times):
  - ▶ Simulate natural population structure
  - ▶ Simulate sample genomes
  - ▶ Simulate sequencing runs (with random variation)
  - ▶ Sketch reads, kWIP
  - ▶ Compare kWIP results to known truth
  - ▶ Spearmans Rank Correlation ( $\rho$ ), “Performance”
- ▶ kWIP quantitatively outperforms unweighted equivalent
  - ▶ Performs reasonably at low-moderate coverage
  - ▶ Performance stable across scale of variation




# Performance vs Coverage





# Performance vs Mean pairwise distance ( $\pi$ )






## kWIP Summary

- ▶ kWIP is implemented, no known bugs
- ▶ Publicly available at [github.com/kdmurray91/kwip](https://github.com/kdmurray91/kwip)
- ▶ We show the utility of kWIP
- ▶ Publication in review at PLoS Comp. Biol. ([bit.do/kwip](http://bit.do/kwip))
- ▶ Version 2 on the way
  - ▶ MPI parallel
  - ▶ More metrics
  - ▶ Even faster











# Thanks

- ▶ Norman Warthmann, Justin Borevitz
- ▶ Christfried Webers, Cheng Soon Ong
- ▶ Sylvain Forêt
- ▶  $AB^3ACBS$  Organisers and Yourselfes





-  Brachi, B., Morris, G. P. & Borevitz, J. O. Genome-wide association studies in plants: the missing heritability is in the field. *Genome biology* **12**, 232 (2011).
-  Peterson, B. K. *et al.* Double Digest RADseq: An Inexpensive Method for De Novo SNP Discovery and Genotyping in Model and Non-Model Species. *PLoS ONE* **7**, e37135 (2012).
-  Morgenstern, B. *et al.* Estimating evolutionary distances between genomic sequences from spaced-word matches. *Algorithms for Molecular Biology* **10**, 5 (2015).
-  Leimeister, C.-A. *et al.* Fast alignment-free sequence comparison using spaced-word frequencies. *Bioinformatics*, btu177 (2014).
-  Afitos, S. A. *et al.* Cnidaria: fast, reference-free clustering of raw and assembled genome and transcriptome NGS data. *BMC Bioinformatics* **16**, 352 (2015).
-  Ondov, B. D. *et al.* Fast genome and metagenome distance estimation using MinHash. *bioRxiv*, 029827 (2015).
-  The 3,000 rice genomes project. The 3,000 rice genomes project. *GigaScience* **3**, 7 (2014).
-  Flowers, J. M. *et al.* Whole-Genome Resequencing Reveals Extensive Natural Variation in the Model Green Alga *Chlamydomonas reinhardtii*. *The Plant Cell* **27**, 2353–2369 (2015).