# **Assignment 4: API Spec & Data Model**

https://marblek-project.uc.r.appspot.com/

# **CS 493: Cloud Application Development**

Fall 2020

#### Oregon State University

Last Update: November 30, 2020 11:14 am EST

Change log	1
Data Model	2
Create a User	3
Get all Users	3
Create a Boat	4
Get a Boat	6
List all Boats	8
Delete a Boat	10
Edit a Load (PATCH)	11
Edit a Load (PUT)	13
Create a Load	15
Edit a Load (PATCH)	17
Edit a Load (PUT)	19
Get a Load	21
List all Loads	22
Delete a Load	24
Add Load to Boat	25
Remove Load from Boat	26

#### Change log

Page	Change	Date
	Initial version.	M, Nov 30

# Data Model

# Boat

Property Name	Notes	
id	String. The id of the boat. Datastore automatically generates it.	
name	String. Name of the boat.	
type	String. Type of the boat. E.g., Sailboat, Catamaran, etc.	
length	Integer. The length of the boat in feet	
public	Boolean. Whether or not the boat is viewable from an unprotected endpoint	
owner	String. The uuid of the User that owns this Boat	
loads	Array. List of Load objects currently on Boat (1:M relationship)	

## Load

Property Name	Notes	
id	String. The id of the load. Datastore automatically generates it.	
weight	Integer. The weight of the load	
content	String. The contents of the load	
delivery_date	String. The estimated delivery date of the load	
current_boat	String. The ID of the boat that the load is currently on (1:M relationship)	

### User

Property Name	Notes	
id	String. The Datastore id of the user. Datastore automatically generates it.	
uuid	String. User's unique ID. Equal to the "sub" value of their JWT	

### Create a User

Authorize the Marina to use your Google credentials as a login

Access https://marblek-project.uc.r.appspot.com/ via a browser to authorize access to Google account

### Get all Users

GET /users

Request

**Request Parameters** 

None

**Request Body** 

None

**Request Headers** 

None

Response

Response MIME Types

Application/json

Response Body Format

JSON

#### Response Statuses

Outcome	Status Code	Notes
Success	200 OK	
Failure	400 Bad Request	If the request is missing any of the 3 required attributes, the bound must not be created, and 400 status code must be returned.
Failure	403 Forbidden	The name provided is not unique
Failure	405 Method Not Allowed	Client sent a PUT or DELETE request, which is unsupported for endpoint
Failure	406 Not Acceptable	Client requested a content type not supported

#### **Response Examples**

```
Status: 200 OK

{
    "id": "abc123",
    "uuid": "55af1e37-0734-46d8-b070-a1e42e4fc392",
    "self": "https://<your-app>/boats/abc123"
}
```

#### Create a Boat

Protected Route

Allows you to create a new boat.

POST /boats

Request

**Request Parameters** 

None

Request Body

Required

**Request Body Format** 

**JSON** 

#### **Request JSON Attributes**

Name	Туре	Description	Required?
name	String	The name of the boat.	Yes
type	String	The type of the boat. E.g., Sailboat, Catamaran, etc.	Yes
length	Integer	Length of the boat in feet.	
owner	String	The UUID of the User that owns this Boat Yes	
public	Boolean	Whether or not the boat is viewable from unprotected endpoints  Yes	
loads	Array	A list of Load IDs that are currently on the boat. Will be undefined if No	
		a boat is created with no loads	

### Request Headers

Name	Туре	Description	Required?
Authorization	String	"Bearer <token>". Valid JWT for owner of Boat</token>	Yes

### Request Body Example

```
{
    "name": "Sea Witch",
    "type": "Catamaran",
    "length": 28,
    "public": false,
    "owner": "55af1e37-0734-46d8-b070-a1e42e4fc392"
}
```

Response

Response MIME Types

Application/json

Response Body Format

JSON

#### **Response Statuses**

Outcome	Status Code	Notes

Success	201 Created	
Failure	400 Bad Request	If the request is missing any of the 3 required attributes, the bound must not be created, and 400 status code must be returned.
Failure	403 Forbidden	The name provided is not unique
Failure	405 Method Not Allowed	Client sent a PUT or DELETE request, which is unsupported for endpoint
Failure	406 Not Acceptable	Client requested a content type not supported

#### **Response Examples**

```
Status: 201 Created
  "id": "abc123",
  "name": "Sea Witch",
 "type": "Catamaran",
 "length": 28,
 "public": false,
 "owner": "55af1e37-0734-46d8-b070-a1e42e4fc392"
 "loads":[
 {"id":"123abc",
 "self": "https://<your-app>/loads/123abc"},
 {"id":"456",
 "self":"https://<your-app>/loads/456"}
  "self": "https://<your-app>/boats/abc123"
```

```
Failure
Status: 400 Bad Request
"Error": "The request object is missing at least one of the required attributes, or they are invalid"
Status: 403 Forbidden
"Error": "The supplied name is already in use"
Status: 405 Method Not Allowed
"Error": "Unsupported method called on endpoint"
Status: 406 Not Acceptable
"Error": "Requested a content type that is not supported"
```

#### Get a Boat

**Public Route** 

Allows you to get an existing boat

```
GET /boats/:boat_id
```

Request

**Request Parameters** 

Name	Туре	Description	Required?
boat_id	String	ID of the boat	Yes

**Request Body** 

None

Response

Response MIME Types

Application/json

Response Body Format

JSON

#### **Response Statuses**

Outcome	Status Code	Notes
Success	200 OK	
Failure	404 Not Found	No boat with this boat_id exists
Failure	406 Not Acceptable	Client requested a content type not supported

#### Response Examples

```
Status: 200 OK

{

"id": "abc123",

"name": "Sea Witch",

"type": "Catamaran",

"length": 28,

"public": false,

"owner": "55af1e37-0734-46d8-b070-a1e42e4fc392"

"loads":[

{"id":"123abc",

"self":"https://<your-app>/loads/123abc"},

{"id":"456",

"self":"https://<your-app>/loads/456"}

],

"self": "https://<your-app>/boats/abc123"
}
```

```
Status: 404 Not Found

{
"Error": "No boat with this boat_id exists"
}

Status: 406 Not Acceptable

{
"Error": "Requested a content type that is not supported"
}
```

#### **List all Boats**

#### Public/Protected Route

List all the boats in pages of 5. Uses offset/limit pagination. If Authorization token is provided in request, then only the boats associated with that User will be shown. If no Authorization token is provided, then all public, unowned boats will be returned

#### GET /boats?limit=x&offset=y

#### Request

#### **Request Parameters**

Name	Туре	Description	Required?
Limit	Integer	The maximum number of resources to return per request	Yes
Offset	Integer	The number of results to skip before returning	Yes

#### **Request Headers**

Name	Туре	Description	Required?
Authorization	String	"Bearer <token>". Valid JWT for owner of Boat</token>	No

#### **Request Body**

None

#### Response

Response Body Format

JSON

#### **Response Statuses**

Outcome	Status Code	Notes
Success	200 OK	Returns 5 boats per page, with a link to next page if applicable
Failure	406 Not Acceptable	Client requested a content type not supported

#### **Response Examples**

```
Status: 200 OK

{
    "boats": [
    {
        "id": "abc123",
        "name": "Sea Witch",
        "type": "Catamaran",
        "length": 28,
        "public": false,
        "owner": "55af1e37-0734-46d8-b070-a1e42e4fc392"
        "loads": [
        {"id":"123abc",
        "self":"https://<your-app>/loads/123abc"},
```

```
{"id":"456",
  "self": "https://<your-app>/loads/456"}
   "self": "https://<your-app>/boats/abc123"
 },
 "id": "def456",
 "name": "Adventure",
 "type": "Sailboat",
  "length": 50,
  "public": false,
 "owner": "55af1e37-0734-46d8-b070-a1e42e4fc392"
 "loads":[
  {"id":"123cdf",
  "self": "https://<your-app>/loads/123cdf"},
  {"id":"789",
  "self": "https://<your-app>/loads/789"}
   "self": "https://<your-app>/boats/def456"
 },
  "id": "xyz123",
  "name": "Hocus Pocus",
  "type": "Sailboat",
  "length": 100,
  "public": false,
  "owner": "55af1e37-0734-46d8-b070-a1e42e4fc392"
  "loads":[
  {"id":"123ghi",
  "self": "https://<your-app>/loads/123ghi"},
  {"id":"324",
  "self": "https://<your-app>/loads/324"}
   "self": "https://<your-app>/boats/xyz123"
 },
]
"offset": 3,
"limit": 3,
"count": 3,
"next": "https://<your-app>/boats/?limit=3&offset=6"
}
Failure
```

```
Status: 406 Not Acceptable

{
"Error": "Requested a content type that is not supported"
}
```

#### Delete a Boat

#### **Protected Route**

Allows you to delete a boat. Note that if the boat has any loads, they will be unloaded upon deletion of boat.

### DELETE /boats/:boat\_id

Request

**Request Parameters** 

None

#### **Request Headers**

Name	Туре	Description	Required?
Authorization	String	"Bearer <token>". Valid JWT for owner of Boat</token>	Yes

Request Body

None

Response

No body

Response Body Format Success: No body

Failure: JSON

#### **Response Statuses**

Outcome	Status Code	Notes
Success	204 No Content	
Failure	404 Not Found	No boat with this boat_id exists

#### Response Examples

#### Success

Status: 204 No Content

#### Failure

```
Status: 404 Not Found
```

"Error": "No boat with this boat\_id exists"

}

# Edit a Boat (PATCH)

#### **Protected Route**

PATCH /boats/:boat\_id

Request

Request MIME Types

Application/json

**Request Parameters** 

Name	Туре	Description	Required?
boat_id	String	ID of the boat	Yes

#### **Request Headers**

Name	Туре	Description	Required?
Authorization	String	"Bearer <token>". Valid JWT for owner of Boat</token>	Yes

Request Body

Request JSON Attributes

At least one attribute is required

Name	Туре	Description	Required?
name	String	The name of the boat.	No
type	String	The type of the boat. E.g., Sailboat, Catamaran, etc.	No
length	Integer	Length of the boat in feet.	No
public	Boolean	Whether or not the boat is viewable from unprotected endpoints	No
owner	String	The UUID of the User that owns this Boat	No

### Request Body Example

```
name": "Sea Witch",
"length": 28
```

Response

Response MIME Types

Application/json

Response Body Format

JSON

#### Response Statuses

Outcome	Status Code	Notes		
Success	200 OK	Entity successfully updated		
Failure	400 Bad Request	If the request is missing all attributes or they are invalid		
Failure	403 Forbidden	The name provided is not unique		
Failure	404 Not Found	No boat with this boat_id exists		
Failure	406 Not Acceptable	Client requested a content type not supported		

Failure

415 Unsupported Media Tyr Client sent an unsupported media type

#### **Response Examples**

#### Success

```
Status: 200 OK

{
    "id": "abc123",
    "name": "Sea Witch",
    "type": "Catamaran",
    "length": 28,
    "owner": "55af1e37-0734-46d8-b070-a1e42e4fc392"
    "self": Error! Hyperlink reference not valid.,
    "loads":[
    {"id":"123abc",
        "self":"https://<your-app>/loads/123abc"},
    {"id":"456",
        "self":"https://<your-app>/loads/456"}
],
}
```

```
Status: 400 Bad Request

{
"Error": "The request object is missing at least one of the required attributes, or they are invalid"
}
Status: 403 Forbidden

{
"Error": "The supplied name is already in use"
}
Status: 404 Not Found

{
"Error": "No boat with this boat_id exists"
}
Status: 406 Not Acceptable

{
"Error": "Requested a content type that is not supported"
}
Status: 415

{
"Error": "Request includes an unsupported media type"
}
```

# Edit a Boat (PUT)

#### **Protected Route**

PUT /boats/:boat\_id

Request

Request MIME Types

Application/json

**Request Parameters** 

Name	Туре	Description	Required?
boat_id	String	ID of the boat	Yes

#### **Request Headers**

Name	Туре	Description	Required?
Authorization	String	"Bearer <token>". Valid JWT for owner of Boat</token>	Yes

#### Request Body

### **Request JSON Attributes**

Name	Туре	Description	Required?
name	String	The name of the boat.	Yes
type	String	The type of the boat. E.g., Sailboat, Catamaran, etc.	Yes
length	Integer	Length of the boat in feet.	Yes
public	Boolean	Whether or not the boat is viewable from unprotected endpoints	Yes
owner	String	The UUID of the User that owns this Boat	Yes

### Request Body Example

```
{
    "name": "Sea Witch",
    "type": "Sailboat",
    "length": 28,
    "public": false,
    "owner": "55af1e37-0734-46d8-b070-a1e42e4fc392"
}
```

Response

Response MIME Types

Application/json

Response Body Format

JSON

#### Response Headers

Name	Description
Location	Upon successful edit, this header will contain the location of the new entity. Can use a GET request on
	location to see edited entity

**Response Statuses** 

Outcome	Status Code	Notes
Success	303 See Other	Entity successfully updated
Failure	400 Bad Request	If the request is missing any attribute, or they are invalid
Failure	403 Forbidden	The name provided is not unique
Failure	404 Not Found	No boat with this boat_id exists
Failure	406 Not Acceptable	Client requested a content type not supported
Failure	415 Unsupported Media Type	Client sent an unsupported media type

#### Response Examples

```
Status: 303 See Other
 "self": "https://<your-app>/boats/abc123"
```

```
Failure
Status: 400 Bad Request
"Error": "The request object is missing at least one of the required attributes, or they are invalid"
Status: 403 Forbidden
"Error": "The supplied name is already in use"
Status: 404 Not Found
"Error": "No boat with this boat_id exists"
Status: 406 Not Acceptable
"Error": "Requested a content type that is not supported"
Status: 415
"Error": "Request includes an unsupported media type"
```

#### Create a Load

**Public Route** 

Allows you to create a new load.

POST /loads

Request

**Request Parameters** 

None

**Request Body** 

Required

Request Body Format

**JSON** 

#### Request JSON Attributes

Name	Туре	Description	Required?
weight	Integer	The weight of the load	Yes
content	String	The contents of the load	Yes
delivery_date	String	The estimated delivery date of the load	Yes

```
Request Body Example
```

```
{
 "weight": 5,
 "content": "LEGO Blocks",
 "delivery_date": "10/31/2020"
}
```

Response

Response Body Format

**JSON** 

#### Response Statuses

Outcome	Status Code	Notes
Success	201 Created	
Failure	400 Bad Request	If the request is missing any attribute, the load must not be created, and 400 status code must be returned.

#### **Response Examples**

All newly created loads will begin unassigned to any boat

```
Status: 201 Created

{
    "id": "123abc",
    "weight": 5,
    "content": "LEGO Blocks",
    "delivery_date": "10/31/2020",
```

```
"current_boat": null,
    "self": "https://<your-app>/loads/123abc"
}

Failure

Status: 400 Bad Request

{
    "Error": "The request object is missing at least one of the required attributes"
}
```

# Edit a Load (PATCH)

**Public Route** 

Allows you to edit a load.

# PATCH /loads/:load\_id

Request

**Request Parameters** 

Name	Туре	Description	Required?
load_id	String	ID of the load	Yes

**Request Body** 

Required

Request Body Format

JSON

#### **Request JSON Attributes**

Name	Туре	Description	Required?
weight	Integer	The weight of the load	No
content	String	The contents of the load	No
delivery_date	String	The estimated delivery date of the load	No
current_boat	String	The boat ID that the load is associated with. Will be undefined if load	No
		created without it at first	

### Request Body Example

```
{
"weight": 5,
"content": "LEGO Blocks",
"delivery_date": "10/31/2020"
}
```

Response

Response Body Format

JSON

### **Response Statuses**

Outcome	Status Code	Notes
Success	201 Created	
Failure	400 Bad Request	If the request is missing any attribute, the load must not be created, and 400 status code must be returned.

```
Status: 201 Created

{
    "id": "123abc",
    "weight": 5,
    "content": "LEGO Blocks",
```

```
"delivery_date": "10/31/2020",
"current_boat": "fdc123",
"self": "https://<your-app>/loads/123abc"
}
```

```
Failure
```

```
Status: 400 Bad Request

{
"Error": "The request object is missing at least one of the required attributes"
}
```

# Edit a Load (PUT)

**Public Route** 

Allows you to edit a load.

```
PUT /loads/:load_id
```

Request

**Request Parameters** 

Name	Туре	Description	Required?
load_id	String	ID of the load	Yes

Request Body

Required

Request Body Format

JSON

#### Request JSON Attributes

Name	Туре	Description	Required?
weight	Integer	The weight of the load	Yes
content	String	The contents of the load	Yes
delivery_date	String	The estimated delivery date of the load	Yes
current_boat	String	The boat ID that the load is associated with. Will be undefined if load	Yes
		created without it at first	

### Request Body Example

```
{
"weight": 5,
"content": "LEGO Blocks",
"delivery_date": "10/31/2020",
"current_boat": "fdc123",
}
```

Response

Response MIME Types

Application/json

Response Body Format

JSON

#### Response Headers

Name	Description
Location	Upon successful edit, this header will contain the location of the new entity. Can use a GET request on
	location to see edited entity

#### **Response Statuses**

Outcome	Status Code	Notes
Success	303 See Other	Entity successfully updated
Failure	400 Bad Request	If the request is missing any attribute, or they are invalid

Failure	403 Forbidden	The name provided is not unique
Failure	404 Not Found	No boat with this boat_id exists
Failure	406 Not Acceptable	Client requested a content type not supported
Failure	415 Unsupported Media Type	Client sent an unsupported media type

#### Response Examples

#### Success

```
Status: 303 See Other

{
    "self": "https://<your-app>/boats/abc123"
}
```

```
Status: 400 Bad Request

{
"Error": "The request object is missing at least one of the required attributes, or they are invalid"
}
Status: 403 Forbidden

{
"Error": "The supplied name is already in use"
}
Status: 404 Not Found

{
"Error": "No boat with this boat_id exists"
}
Status: 406 Not Acceptable

{
"Error": "Requested a content type that is not supported"
}
Status: 415

{
"Error": "Request includes an unsupported media type"
}
```

### Get a Load

**Public Route** 

Allows you to get an existing load.

```
GET /loads/:load_id
```

Request

**Request Parameters** 

Name	Туре	Description	Required?
load_id	String	ID of the load	Yes

Request Body

None

Response

Response Body Format

JSON

#### **Response Statuses**

Outcome	Status Code	Notes
Success	200 OK	
Failure	404 Not Found	No load with this load_id exists

Response Examples

Success

```
Status: 200 OK

{
    "id": "123abc",
    "weight": 5,
    "content": "LEGO Blocks",
    "delivery_date": "10/31/2020",
    "current_boat": "fdc123",
    "self": "https://<your-app>/loads/123abc"
}
```

```
Status: 404 Not Found

{
"Error": "No load with this load_id exists"
}
```

#### List all Loads

#### **Public Route**

List all the loads in pages of 5. Uses offset/limit pagination.

### GET /loads?limit=x&offset=y

#### Request

#### **Request Parameters**

Name	Туре	Description	Required?
Limit	Integer	The maximum number of resources to return per request	Yes
Offset	Integer	The number of results to skip before returning	Yes

**Request Body** 

None

Response

Response Body Format

**JSON** 

#### **Response Statuses**

Outcome	Status Code	Notes
Success	200 OK	Returns 5 loads per page, with a link to next page if applicable

#### **Response Examples**

```
Status: 200 OK
 "loads": [
 "id": "123abc",
 "weight": 5,
 "content": "LEGO Blocks",
 "delivery_date": "10/31/2020",
 "current_boat": "fdc123",
  "self": "https://<your-app>/loads/123abc"
 },
  "id": "123cdf",
  "weight": 10,
  "content": "Red Bricks",
  "delivery date": "10/31/2020"
  "current_boat": "fdc456",
  "self": "https://<your-app>/loads/123cdf"
 },
 "id": "123ghi",
  "weight": 2,
```

```
"content": "Socks",

"delivery_date": "10/31/2020"

"current_boat": "fdc789",

"self": "https://<your-app>/loads/123ghi"

},

]

"offset": 3,

"limit": 3,

"count": 3,

"next": "https://<your-app>/boats/?limit=3&offset=6"
}
```

#### Delete a Load

#### **Public Route**

Allows you to delete a load. If the load being deleted is on a boat, the boat carrying it will be updated.

### DELETE /loads/:load\_id

Request

**Request Parameters** 

None

Request Body

None

Response

No body

Response Body Format

Success: No body

Failure: JSON

#### **Response Statuses**

Outcome	Status Code	Notes
Success	204 No Content	
Failure	404 Not Found	No load with this load_id exists

### Response Examples

Success

Status: 204 No Content

```
Status: 404 Not Found

{
"Error": "No load with this load_id exists"
}
```

#### Add a Load to a Boat

#### **Public Route**

PUT/boats/:boat\_id/loads/:load\_id

Request

**Request Parameters** 

None

**Request Body** 

None

Note: Set Content-Length to 0 in your request when calling out to this endpoint.

Response

No body

Response Body Format Success: No body

Failure: JSON

#### **Response Statuses**

Outcome	Status Code	Notes
Success	204 No Content	Succeeds only if a boat exists with this boat_id, a load exists with
		this load_id and the load is empty.
Failure	403 Forbidden	There is already a boat assigned to this load.
Failure	404 Not Found	No boat with this boat_id exists, and/or no load with this load_id
		exits.

#### Response Examples

Success

Status: 204 No Content

Failure

```
Status: 403 Forbidden

{
"Error": "The load is already assigned to another boat_id"
```

```
Status: 404 Not Found
{
"Error": "The specified boat and/or load does not exist"
}
```

#### Comment

A load cannot be assigned to multiple boats.

### Remove Load from Boat

#### **Public Route**

DELETE /boats/:boat\_id/loads/:load\_id

Request

**Request Parameters** 

None

Request Body

None

Response

No body

Response Body Format

Success: No body

Failure: JSON

#### **Response Statuses**

Outcome	Status Code	Notes
Success	204 No Content	Succeeds only if a boat exists with this boat_id, a load exists with
		this load_id and this load is at this boat.
Failure	404 Not Found	No boat with this boat_id is at the load with this load_id.

### Response Examples

Success

Status: 204 No Content

```
Status: 404 Not Found

{
"Error": "No load with this load_id is at the boat with this boat_id"
}
```