
SPRITES ARE CHEAP

*How to write a retro-style game in
JavaScript*

SCHEDULE

1. Introduction - what are sprites & JS
2. PHASER library
3. Phaser setup + sprites creation
4. Live coding
5. Other examples
6. Summary

1.Java Script

- programming language used to create interactive websites
- runs in web browsers to add dynamic content and features
- can also be used for server-side development with tools like Node.js
- created by Brendan Eich in 1995 (as LiveScript) and has become a fundamental technology of the web
- easily available from browser console

2.PHASER

- open-source JavaScript library used to create 2D games for web browsers
- framework for rendering graphics, handling input, and managing game physics
- known for its ease of use, extensive documentation, and active community support.

PHASER SETUP

1. Create an HTML page
2. Include this link to phaser.js in your page
<https://cdn.jsdelivr.net/npm/phaser@3/dist/phaser.js>

```
1 <html>
2 <head>
3   <script src="https://cdn.jsdelivr.net/npm/phaser@3/dist/phaser.js"></script>
4 </head>
5 </html>
```

3. Create an HTML div to display the game

```
5 <body>
6   <div id="game-container"></div>
7 </body>
```

4. Add JS section with phaser parameters

```
8      <script>
9          const config = {
10              type: Phaser.AUTO, // rendering style (WebGL or Canvas)
11              width: 800,
12              height: 600,
13              parent: 'game-container'
14          };
15      </script>
```

5. Create game object

```
16      const game = new Phaser.Game(config);
```

Full code so far:

```
1  <html>
2  <head>
3      <script src="https://cdn.jsdelivr.net/npm/phaser@3/dist/phaser.js"></script>
4  </head>
5  <body>
6      <div id="game-container"></div>
7      <script>
8          const config = {
9              type: Phaser.AUTO, // rendering style (WebGL or Canvas)
10             width: 800,
11             height: 600,
12             parent: 'game-container'
13         };
14
15         const game = new Phaser.Game(config);
16     </script>
17 </body>
18 </html>
```

6. Add default scene and functions preload(), create() and update

```
7 <script>
8   const config = {
9     type: Phaser.AUTO, // rendering style (WebGL or Canvas)
10    width: 800,
11    height: 600,
12    parent: 'game-container',
13    scene: {
14      preload: preload,
15      create: create,
16      update: update
17    }
18  };
19
20  const game = new Phaser.Game(config);
21
22  function preload() {
23  }
24
25  function create() {
26    this.add.text(20, 20, 'Super fajna gra!', { font: '24px Arial', fill: 'ffffff' });
27  }
28
29  function update() {
30  }
31 </script>
```


Super fajna gra!

