

- Diesel-Resistant Elastomeric Polyolefin
- Superior protection from aviation & diesel fuels, hydraulic fluids, greases and lubricants.

Diesel-Resistant Heat Shrink Tubing

Product Number IP56DR

IP56DR is a heat shrinkable, flame retarded, elastomer tubing specially formulated for long term resistance to fluids, heat and mechanical abuse.

Recommended for protecting cables and wire harnesses on military ground vehicles and is used in a variety of applications requiring ruggedness and fluid resistance.

IP56DR remains flexible at low temperatures which makes it ideal for cables and harness applications that operate in severe environmental conditions.



Flexible, abrasion resistant covering for wires

Specifications:

Order Size	Expanded Diameter	Recovered Diameter	Recovered Wall
1/8"	.125	.062	.028
3/16"	.187	.093	.031
1/4"	.250	.125	.035
3/8"	.375	.187	.039
1/2"	.500	.250	.047
3/4"	.750	.375	.059
1"	1.000	.500	.071
1-1/2"	1.500	.750	.094
2"	2.000	1.000	.110

M23053/16

MIL-R-46846 Type 1 Class 1

Temperature Ratings: -75°C to +120°C

Shrink Temperature: 150°C minimum

Standard Color: Black

Markers and Cut Pieces Available

INSULATION PRODUCTS CORPORATION