


- Exceptional Temperature Range
- Flame Retardant
- Flexible

# General Purpose Vinyl Tubing

Product Number IP12GA

IP12GA is a general purpose, extruded PVC tubing with a wide temperature range designed for appliances, electric motors, commercial and military aircraft, general purpose bundling, harnessing, and many other uses that require a low temperature tubing that remains flexible.

IP1274 has a high dielectric strength, excellent flexibility, fungus resistance and is non-corrosive.



*A superior general purpose PVC tubing*

Order Size	Nom. I.D.	Wall
#24	.022	.012
#22	.027	.012
#20	.034	.016
#19	.038	.016
#18	.042	.016
#17	.047	.016
#16	.053	.016
#15	.059	.016
#14	.066	.016
#13	.076	.016
#12	.085	.016
#11	.095	.016
#10	.106	.016
#9	.118	.020
#8	.133	.020
#7	.148	.020
#6	.166	.020
#5 (3/16")	.186	.020
#4	.208	.020
#3	.234	.020
1/4"	.250	.020
#2	.263	.020
#1	.294	.020
#0	.330	.020
5/16"	.313	.025
3/8"	.375	.025
7/16"	.437	.025
1/2"	.500	.025
9/16"	.563	.030
5/8"	.625	.030
3/4"	.750	.035
7/8"	.875	.035
1"	1.000	.035
1-1/8"	1.125	.035
1-1/4"	1.250	.040
1-3/8"	1.375	.045
1-1/2"	1.500	.045
1-3/4"	1.750	.055
2"	2.000	.060

## Specifications:

MIL-I-631 Grade A & B, Form U, Subform Ua, Class 1 and II, Category 1

ASTM D922

Colors: Black, Clear

Continuous operating temperature: -55 to +90°C

Dielectric Strength: 1000 VPM

Tensile Strength: 3000 PSI

**INSULATION PRODUCTS CORPORATION**