

```
File Virtual Machine View Send Key
Activities Terminal Sep 9 13:29 netadmin@netsecsys: -
root@netsecsys:/etc/bind# cat named.conf.options
options {
    directory "/var/cache/bind";

    // If there is a firewall between you and nameservers you want
    // to talk to, you may need to fix the firewall to allow multiple
    // ports to talk. See http://www.kb.cert.org/vuls/id/800113

    // If your ISP provided one or more IP addresses for stable
    // nameservers, you probably want to use them as forwarders.
    // Uncomment the following block, and insert the addresses replacing
    // the all-0's placeholder.

    forwarders {
        192.168.170.35;
        192.168.170.51;
        192.168.170.52;
        192.168.170.20;
        0.0.0.0;
    };

    //=====
    // If BIND logs error messages about the root key being expired,
    // you will need to update your keys. See https://www.isc.org/bind-keys
    //=====
    dnssec-validation auto;

    listen-on-v6 { any; };
};
root@netsecsys:/etc/bind#
```

```
File Virtual Machine View Send Key
Activities Terminal Sep 9 13:29 netadmin@netsecsys: -
root@netsecsys:/etc/bind# cat db.100.168.192
;
; BIND reverse data file for local loopback interface
;
$TTL 604800
@ IN SOA ozy.cns. root.ozy.cns. (
    1 ; Serial
    604800 ; Refresh
    86400 ; Retry
    2419200 ; Expire
    604800 ) ; Negative Cache TTL
;
@ IN NS 192.168.100.136.
136 IN PTR ozy.cns.
root@netsecsys:/etc/bind#
```

```
~ took 1m13s
> : nslookup www.ozy.cns
Server:      192.168.122.84
Address:     192.168.122.84#53

www.ozy.cns canonical name = internetworking.1.srv.ozy.cns.
Name:   internetworking.1.srv.ozy.cns
Address: 192.168.100.133
```

```
~
> : nslookup 192.168.100.136
136.100.168.192.in-addr.arpa name = ozy.cns.
```

```
~
> : █
```