SQL Operatoret

SQL Operatoret

- AND, OR, NOT
- ORDER BY
- NULL Values
- SELECT TOP (LIMIT)
- MIN and MAX
- COUNT(), AVG(), SUM()
- LIKE operator
- IN operator
- BETWEEN operator
- GROUP BY

AND

```
SELECT * FROM student
WHERE emri='Arianit' AND mbiemri='Tershnjaku';

DELETE FROM student
WHERE emri='Arianit' AND mbiemri='Tershnjaku';
```

OR

```
SELECT * FROM student
WHERE emri='arianit' OR mbiemri='tershnjaku';

DELETE FROM student
WHERE emri='Arianit‘ OR mbiemri='Tershnjaku';
```

NOT

```
SELECT * FROM student
WHERE NOT emri='Arianit';

DELETE FROM student
WHERE NOT emri='Arianit';
```

Kombinimi i (AND,OR,NOT)

```
SELECT * FROM student
WHERE emri='niti' AND (mbiemri='tershnjaku'
        OR mosha='25');

SELECT * FROM student
WHERE emri='niti' AND NOT
                mbiemri='tershnjaku';
```

ORDER BY

```
SELECT * FROM student
ORDER BY emri;

SELECT *FROM student
ORDER BY emri DESC;

SELECT *FROM student
ORDER BY emri ASC;
```

NULL Values

```
SELECT * FROM student
WHERE emri IS NULL;

SELECT * FROM student
WHERE emri IS NOT NULL;
```

SELECT TOP (LIMIT)

```
SELECT * FROM student
WHERE emri='Arianit'
LIMIT 3;
```

MIN and MAX

```
SELECT MIN(mosha) AS MoshaUlet
FROM student;
```

```
SELECT MAX(mosha) AS MoshaLart
FROM student;
```

COUNT(), AVG(), SUM()

```
SELECT COUNT(mosha)
FROM student;

SELECT AVG (mosha)
FROM student;

SELECT SUM(mosha)
FROM student;
```

LIKE operator

```
SELECT * FROM student
WHERE emri LIKE 'a%';
```

```
SELECT * FROM student
WHERE emri LIKE '%i';
```

```
SELECT * FROM student
WHERE emri LIKE '%i%';
```

LIKE operator -(vazhdim)

```
SELECT * FROM student
WHERE emri LIKE '_r%';

SELECT * FROM student
WHERE emri LIKE 'a___%';

SELECT * FROM student
WHERE emri LIKE 'a%i';
```

LIKE operator -(vazhdim)

```
SELECT * FROM student
WHERE emri LIKE 'a%i'
AND mbiemri LIKE 't%';

SELECT * FROM student
WHERE emri LIKE 'a%i'
OR mbiemri LIKE 't%';
```

IN operator

```
SELECT * FROM student
WHERE emri IN ('Arianit','niti');

SELECT * FROM student
WHERE emri NOT IN ('Arianit','niti');
```

IN operator –(vazhdim)

```
SELECT * FROM profesori
WHERE emri IN (SELECT emri FROM student);

SELECT * FROM student
WHERE emri
NOT IN (SELECT emri FROM profesori);
```

BETWEEN operator

```
SELECT * FROM student
WHERE Id BETWEEN 1 and 4;

SELECT * FROM student
WHERE Id NOT BETWEEN 1 and 4;

SELECT * FROM student
WHERE emri BETWEEN 'arianit' and 'niti';
```

BETWEEN operator -(vazhdim)

```
SELECT * FROM student
WHERE emri BETWEEN 'arianit' and 'niti'
AND Id IN (1,2,3);

SELECT * FROM student
WHERE emri BETWEEN 'arianit' and 'niti'
AND Id NOT IN (1,2,3);
```

GROUP BY

```
SELECT * FROM student
GROUP BY emri;

SELECT COUNT(id), emri
FROM student
GROUP BY emri;
```