SQL

ALIASES, JOINS

ALIASES

```
SELECT sid AS Id, emri AS Studentat
FROM student;
```

```
SELECT sid AS Id, emri AS "Studentat e shkolles"
FROM student;
```

ALIASES –vazhdim (Concat)

```
SELECT sid, CONCAT (sid,', ',emri,',
        ',mbiemri,',',mosha, ', ',email)
AS "Te dhenat"
FROM student;
```

JOINS

- INNER JOIN
- LEFT OUTER JOIN
- RIGHT OUTER JOIN

INNER JOIN

```
SELECT student.sid, student.emri, kursi.nota
FROM student
INNER JOIN kursi
ON student.sid = kursi.kid;
```

LEFT JOIN

```
SELECT student.sid, student.emri, kursi.nota
FROM student
LEFT JOIN kursi
ON student.sid = kursi.kid;
```

RIGHT JOIN

```
SELECT student.sid, student.emri, kursi.nota
FROM student
RIGHT JOIN kursi
ON student.sid = kursi.kid;
```

UNION

```
SELECT emri FROM student
UNION
SELECT emri FROM kursi;

SELECT emri FROM student
UNION ALL
SELECT emri FROM kursi;
```

HAVING

```
SELECT COUNT(mosha), emri
FROM student
GROUP BY emri
HAVING COUNT(mosha) < 15;
```

INSERT INTO

```
INSERT INTO
student(sid,emri,mbiemri,mosha,email)
SELECT pid, emri, mbiemri, mosha, email
FROM profesori;
```

CASE

```
SELECT sid, mosha,
CASE
        WHEN mosha > 20 THEN 'Mosha me e larte se 20'
        WHEN mosha = 20 THEN 'Mosha e barabart me 20'
        ELSE 'Mosha me e vogel se 20'
END AS Mosha
FROM student;
```