Clients and reservations - ER diagram

Member A: 5 tables; shaded boxes reference another domain



Assumptions and notation

PK = primary key; FK = foreign key; ? = nullable. Unmarked attributes are required.
Endpoint cardinalities: 1 = exactly one; 0..1 = zero or one; 0..* = zero or more.
Each labelled line represents its child foreign key. Reference boxes repeat existing entities.
Uniqueness, time intervals, allocation limits and billing rules: analysis report R1-R9.
A client has at most one parent; client hierarchy cycles are prohibited.
An item selects at most one preferred location level; approved reservations must contain items.

Infrastructure - ER diagram

Member B: 5 tables; shaded boxes reference another domain



Assumptions and notation

PK = primary key; FK = foreign key; ? = nullable. Unmarked attributes are required.
Endpoint cardinalities: 1 = exactly one; 0..1 = zero or one; 0..* = zero or more.
Each labelled line represents its child foreign key. Reference boxes repeat existing entities.
Uniqueness, time intervals, allocation limits and billing rules: analysis report R1-R9.
Each data center belongs to one zone, and each zone belongs to one region.
Resources store capacity; occupancy is derived from allocations, not duplicated as a status.

Deployments and usage - ER diagram

Member C: 5 tables; shaded boxes reference another domain



Assumptions and notation

PK = primary key; FK = foreign key; ? = nullable. Unmarked attributes are required.
Endpoint cardinalities: 1 = exactly one; 0..1 = zero or one; 0..* = zero or more.
Each labelled line represents its child foreign key. Reference boxes repeat existing entities.
Uniqueness, time intervals, allocation limits and billing rules: analysis report R1-R9.
Allocations must match the reservation item and deployment; overlapping fractions total at most one.
Replacement and state intervals retain history; actual usage and estimates are reported separately.

Services and billing - ER diagram

Member D: 5 tables; shaded boxes reference another domain



Assumptions and notation

PK = primary key; FK = foreign key; ? = nullable. Unmarked attributes are required.
Endpoint cardinalities: 1 = exactly one; 0..1 = zero or one; 0..* = zero or more.
Each labelled line represents its child foreign key. Reference boxes repeat existing entities.
Uniqueness, time intervals, allocation limits and billing rules: analysis report R1-R9.
Each charge has exactly one context: usage, direct service, or adjustment of an earlier charge.
Shares belong to draft invoices; the payer is derived from the invoice. Issued invoices are immutable.