CloudNine Systems - connected ERD overview

20 entities | 37 relationships | A: clients | B: infrastructure | C: deployments and usage | D: billing

B / region

PK	regionId	int
	name	text
	regulatoryNote	text

B / availability_zone

PK	zoneId	int
FK	regionId	int
	name	text
	redundancyNote	text
	connectivityNote	text

B / data_center

PK	dataCenterId	int
FK	zoneId	int
	name	text
	location	text

A / reservation_item

PK	reservationItemId	int
FK	reservationId	int
FK	resourceTypeId	int
	quantity	int
	minVcpu	int
	minMemoryGib	decimal
	minStorageGib	decimal
	minNetworkGbps	decimal
FK	preferredRegionId	int ?
FK	preferredZoneId	int ?
FK	preferredDataCenterId	int ?
	locationMode	text

B / resource_type

PK	resourceTypeId	int
	name	text
	intendedWorkload	text

B / resource

PK	resourceId	int
FK	resourceTypeId	int
FK	dataCenterId	int
	localIdentifier	text
	performanceTier	text
	vcpuCount	int
	memoryGib	decimal
	storageGib	decimal
	networkGbps	decimal

C / resource_allocation

PK	allocationId	int
FK	deploymentId	int
FK	reservationItemId	int
FK	resourceId	int
	capacityFraction	decimal
	startsAt	timestamp
	endsAt	timestamp ?
	allocationStatus	text
FK	supersedesAllocationId	int ?
	changeReason	text
FK	assignedByUserId	int ?

A / reservation

PK	reservationId	int
FK	clientId	int
	createdAt	timestamp
	startTime	timestamp
	endTime	timestamp
	status	text
	agreementNote	text ?
FK	approvedByUserId	int ?

C / deployment

PK	deploymentId	int
FK	reservationId	int
	name	text
	workloadNote	text
	startedAt	timestamp ?
	endedAt	timestamp ?
	confidentialityLevel	text
	status	text
	priority	int
	scalingMode	text

C / resource_state

PK	stateId	int
FK	resourceId	int
	status	text
	reason	text
	startsAt	timestamp
	endsAt	timestamp ?
FK	recordedByUserId	int ?

C / usage_record

PK	usageId	int
FK	deploymentServiceId	int
FK	allocationId	int ?
	quantity	decimal
	periodStart	timestamp
	periodEnd	timestamp
	recordType	text
	recordedAt	timestamp
FK	supersedesUsageId	int ?

A / client

PK	clientId	int
FK	parentClientId	int ?
	name	text
	clientType	text
	contactEmail	text
	qualificationNote	text ?

A / user_account

PK	userId	int
FK	clientId	int ?
	name	text
	email	text
	accountKind	text
	staffRole	text ?
	status	text

C / deployment_service

PK	deploymentServiceId	int
FK	deploymentId	int
FK	serviceId	int
	startsAt	timestamp
	endsAt	timestamp ?

D / charge

PK	chargeId	int
FK	usageId	int ?
FK	deploymentServiceId	int ?
FK	serviceRateId	int ?
FK	adjustmentOfChargeId	int ?
FK	authorizedByUserId	int ?
	chargeType	text
	amount	decimal
	status	text
	reason	text
	createdAt	timestamp

D / service

PK	serviceId	int
	name	text
	serviceType	text
	billingUnit	text

D / service_rate

PK	serviceRateId	int
FK	serviceId	int
	validFrom	timestamp
	validTo	timestamp ?
	unitPrice	decimal

A / billing_account

PK	billingAccountId	int
FK	responsibleClientId	int
	name	text
FK	billingContactUserId	int ?

D / invoice

PK	invoiceId	int
FK	billingAccountId	int
	issuedAt	timestamp
	dueAt	timestamp
	status	text

D / charge_share

PK	chargeShareId	int
FK	chargeId	int
FK	invoiceId	int
	allocatedAmount	decimal

is preferred by
contains
hosts
is fulfilled by
classifies
has
is replaced by
supports
is corrected by
has child client
approves reservation
assigns allocation
records resource state
generates
produces
has adjustment
is responsible for
is contact for
authorizes charge
prices
is split into

PK = primary key | FK = foreign key | ? = nullable | 1 = exactly one | 0..1 = optional one | 0..* = zero or more