

**Ansible** is an open-source automation tool used for **IT configuration management, application deployment, orchestration, and infrastructure as code (IaC)**. It simplifies complex tasks by automating repetitive operations, allowing system administrators and developers to manage IT infrastructure efficiently.

## **Core Components:**

### **1. Inventory:**

- A file listing the target systems (hosts) Ansible will manage.
- Can be static (INI/YAML format) or dynamic (integrated with cloud APIs).

### **2. Modules:**

- Predefined functions that perform specific tasks, like managing files, packages, or services.

### **3. Playbooks:**

- YAML files that define a sequence of tasks to execute on target hosts.

### **4. Ad-Hoc Commands:**

- One-off commands executed directly from the command line for quick tasks.

### **5. Roles:**

- A way to organize and reuse playbooks, variables, tasks, and other components for modular automation.

# Launched two instances

EC2

S3

CodeDeploy

CodePipeline

RDS

VPC

IAM

CloudFormation

☰

Dashboard

EC2 Global View

Events

▼ Instances

Instances

Instance Types

Launch Templates

Spot Requests

Savings Plans

Reserved Instances

Dedicated Hosts

Capacity Reservations

▼ Images

AMIs

AMI Catalog

▼ Elastic Block Store

Volumes

Snapshots

Lifecycle Manager

Instances (1/2) Info

Last updated 2 minutes ago

Refresh

Connect

Instance state ▼

Actions ▼

Launch instances ▼

Find Instance by attribute or tag (case-sensitive)

All states ▼

< 1 >

⚙

|                                     | Name    | Instance ID         | Instance state | Instance type | Status check | Alarm status  | Availability Zone | Public IPv4 DI |
|-------------------------------------|---------|---------------------|----------------|---------------|--------------|---------------|-------------------|----------------|
| <input type="checkbox"/>            | Ansible | i-03dd91213a33950bd | Running        | t2.micro      | Initializing | View alarms + | us-east-1a        | ec2-52-23-18:  |
| <input checked="" type="checkbox"/> | Slave   | i-0644e3aade07bc770 | Running        | t2.micro      | Initializing | View alarms + | us-east-1a        | ec2-34-207-2:  |

i-0644e3aade07bc770 (Slave)

⚙

▼

Details

Status and alarms

Monitoring

Security

Networking

Storage

Tags

▼ Instance summary Info

Instance ID

i-0644e3aade07bc770

IPv6 address

-

Hostname type

IP name: ip-172-31-18-151.ec2.internal

Public IPv4 address

34.207.242.22 | open address

Instance state

Running

Private IP DNS name (IPv4 only)

ip-172-31-18-151.ec2.internal

Private IPv4 addresses

172.31.18.151

Public IPv4 DNS

ec2-34-207-242-22.compute-1.amazonaws.com | open address

# Installed ansible in control server

```
ubuntu@ip-172-31-22-185:~$ ansible --version
ansible 2.10.8
  config file = None
  configured module search path = ['/home/ubuntu/.ansible/plugins/modules', '/usr/share/ansible/plugins/modules']
  ansible python module location = /usr/lib/python3/dist-packages/ansible
  executable location = /usr/bin/ansible
  python version = 3.10.12 (main, Sep 11 2024, 15:47:36) [GCC 11.4.0]
ubuntu@ip-172-31-22-185:~$ ssh 172.31.18.151
The authenticity of host '172.31.18.151 (172.31.18.151)' can't be established.
ED25519 key fingerprint is SHA256:DkFEYlNittvAC2iMQ9SPxhK+jorI3FM+mKCQUpKODYM.
This key is not known by any other names
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '172.31.18.151' (ED25519) to the list of known hosts.
ubuntu@172.31.18.151: Permission denied (publickey).
ubuntu@ip-172-31-22-185:~$
```

**i-03dd91213a33950bd (Ansible)**

PublicIPs: 52.23.185.100 PrivateIPs: 172.31.22.185

**Passwordless Authentication** is a method of verifying a user's identity without requiring them to enter a traditional password. Instead, it relies on alternative methods such as biometrics, hardware tokens, magic links, or cryptographic keys to authenticate users securely.

## **Common Methods of Passwordless Authentication:**

1. **Biometrics:**
  - Uses fingerprint scans, facial recognition, or retina scans.
  - Example: Unlocking a phone with Face ID or Touch ID.
2. **Hardware Tokens:**
  - Physical devices like **YubiKeys** or **smart cards** that authenticate users.
3. **Magic Links:**
  - A link sent to the user's email or SMS that, when clicked, logs them in without requiring a password.
4. **One-Time Passwords (OTPs):**
  - Temporary codes sent via SMS, email, or authentication apps (e.g., Google Authenticator).
5. **Public Key Infrastructure (PKI):**
  - Uses cryptographic key pairs (private and public keys).
  - Example: SSH key-based authentication.
6. **Push Notifications:**
  - Sends a prompt to a registered device for approval.

# To logged into slave server from ansible server but permission denied

```
ubuntu@ip-172-31-22-185:~$ ssh 172.31.18.151
ubuntu@172.31.18.151: Permission denied (publickey).
ubuntu@ip-172-31-22-185:~$ ssh-keygen
Generating public/private rsa key pair.
Enter file in which to save the key (/home/ubuntu/.ssh/id_rsa):
/home/ubuntu/.ssh/id_rsa already exists.
Overwrite (y/n)? yes
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in /home/ubuntu/.ssh/id_rsa
Your public key has been saved in /home/ubuntu/.ssh/id_rsa.pub
The key's fingerprint is:
SHA256:OmftNamrsPRyZnTwF+CI7HZyFszhzNXCUX+GFZM20Zk ubuntu@ip-172-31-22-185
The key's randomart image is:
+---[RSA 3072]---+
|      .+.  +O|
|      . = .. Eo|
|    . B = o  + +|
|    o X . .  o |
|    . S+    .  |
|    +.=.o  ..  |
|    .=*o...+   |
|    ..B+. o .  |
|    .=o.+      |
+-----[SHA256]-----+
ubuntu@ip-172-31-22-185:~$
```

**i-03dd91213a33950bd (Ansible)**

PublicIPs: 52.23.185.100 PrivateIPs: 172.31.22.185

# publickey

```
ubuntu@ip-172-31-22-185:~$ cd /home/ubuntu/.ssh
ubuntu@ip-172-31-22-185:~/.ssh$ ls
authorized_keys  id_rsa  id_rsa.pub  known_hosts
ubuntu@ip-172-31-22-185:~/.ssh$ cat id_rsa.pub
ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQgQDW25gNDTVYuBz7hLvbikh030kiig/YkJ8QGhCPWQQ5qR7Ot35Yb6umdz/ks+97H8f2BrqQB+QpBNnt+twSQRkzFRXubCLkZG/GRx+/zSKLpEM3fbgv1FMf0YXD1PpUx75
jOO/7HZ9KgxBGU8943ZoqKGlHqM7kymnVF6sVbrNwai8N9M+8fedbwo86WzU9y5gAsak0+vOUWf66S4ZuHEy+5gG/GzMn3DgWFgcLCqpG2Az86yX3f6+CxAHDRD3v6iXMu9jTbSme24UIPhOeV2c9Q6FnojBbakeVvb4lW
ob6ow1YydatzkJzPV3cyJreUtYlWe+hHRJwj6X7ipO5h43GMrRoQTODquXRlJhx2wCifwdMbmHZCdOwwKB9/itTKMvSaIccWVb1LTUnPnOB156kdwWhBkTmbIR1VETVBKKFGmH/99qirLGZu3g3o4QH/ad2F5yjsUE5vVz/
1HvMS8BF7gaB30Q46TiKax2430x6FByIqPrWfLGHnxBNWwDKV0=
ubuntu@ip-172-31-22-185:~/.ssh$
```



# Logged into slave machine, and creating vi authorized\_keys file and stored public key of ansible server

```
ubuntu@ip-172-31-18-151:~$ ssh-keygen
Generating public/private rsa key pair.
Enter file in which to save the key (/home/ubuntu/.ssh/id_rsa):
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in /home/ubuntu/.ssh/id_rsa
Your public key has been saved in /home/ubuntu/.ssh/id_rsa.pub
The key fingerprint is:
SHA256:HogR3JE35dRRAHL5og80xHpno85IdJDGxrD4WJ89N6k ubuntu@ip-172-31-18-151
The key's randomart image is:
+---[RSA 3072]-----+
|    ...oB.o=+o+.    |
|    .oo.%=. .       |
|    o o* o..        |
|    *.o=o= ..       |
|    o o+S*oo+       |
|    .+.o+ .         |
|    ..*E.           |
|    . +             |
|                   |
+-----[SHA256]-----+
ubuntu@ip-172-31-18-151:~$ cd /home/ubuntu/.ssh
ubuntu@ip-172-31-18-151:~/.ssh$ ls
authorized_keys  id_rsa  id_rsa.pub
ubuntu@ip-172-31-18-151:~/.ssh$ vi authorized_keys
ubuntu@ip-172-31-18-151:~/.ssh$
```

**i-0644e3aade07bc770 (Slave)**

PublicIPs: 34.207.242.22 PrivateIPs: 172.31.18.151



# To log in to a remote machine (slave) using **SSH key-based authentication**

```
* Documentation:  https://help.ubuntu.com
* Management:    https://landscape.canonical.com
* Support:        https://ubuntu.com/pro

System information as of Mon Dec 30 17:04:04 UTC 2024

System load:  0.0                Processes:            103
Usage of /:   24.1% of 7.57GB    Users logged in:     1
Memory usage: 23%                IPv4 address for eth0: 172.31.18.151
Swap usage:   0%
```

Expanded Security Maintenance for Applications is not enabled.

47 updates can be applied immediately.  
36 of these updates are standard security updates.  
To see these additional updates run: `apt list --upgradable`

Enable ESM Apps to receive additional future security updates.  
See <https://ubuntu.com/esm> or run: `sudo pro status`

New release '24.04.1 LTS' available.  
Run 'do-release-upgrade' to upgrade to it.

```
Last login: Mon Dec 30 16:48:34 2024 from 18.206.107.29
ubuntu@ip-172-31-18-151:~$ █
```

**i-03dd91213a33950bd (Ansible)**

PublicIPs: 52.23.185.100 PrivateIPs: 172.31.22.185



An **ad-hoc command** in Ansible is a one-time, quick command used to perform tasks on managed nodes without writing a playbook. These commands are useful for simple tasks like checking system status, restarting services, or running shell commands across multiple hosts.

```
ubuntu@ip-172-31-22-185:~$ ls
ubuntu@ip-172-31-22-185:~$ vi inventory
ubuntu@ip-172-31-22-185:~$ ls
inventory
ubuntu@ip-172-31-22-185:~$ cat inventory
172.31.18.151
ubuntu@ip-172-31-22-185:~$ ansible -i inventory all -m "shell" -a "touch kechiya"
[WARNING]: Consider using the file module with state=touch rather than running 'touch'.
false' to this command task or set 'command_warnings=False' in ansible.cfg to get rid of this message.
172.31.18.151 | CHANGED | rc=0 >>

ubuntu@ip-172-31-22-185:~$ ansible -i inventory all -m "shell" -a "df -h"
172.31.18.151 | CHANGED | rc=0 >>
Filesystem      Size  Used Avail Use% Mounted on
/dev/root        7.6G  1.9G  5.8G  25% /
tmpfs            479M    0  479M   0% /dev/shm
tmpfs            192M  876K  191M   1% /run
tmpfs            5.0M    0   5.0M   0% /run/lock
/dev/xvda15      105M   6.1M   99M   6% /boot/efi
tmpfs            96M   4.0K   96M   1% /run/user/1000
ubuntu@ip-172-31-22-185:~$ ansible -i inventory all -m "shell" -a "nproc"
172.31.18.151 | CHANGED | rc=0 >>
1
ubuntu@ip-172-31-22-185:~$
```

```
ubuntu@ip-172-31-18-151:~$ ls
kechiya
ubuntu@ip-172-31-18-151:~$
```

# Playbook for install and start nginx

```
---
- name: Install and start nginx
  hosts: all
  become: true

  tasks:
    - name: install nginx
      apt:
        name: nginx
        state: present

    - name: start service nginx, if not started
      service:
        name: nginx
        state: started
```

In **Ansible**, a **module** is a reusable, standalone script or tool that performs a specific task on a managed node. Modules are the building blocks of Ansible, enabling users to perform operations like installing packages, managing files, configuring services, and executing commands.

In **Ansible**, a **module** is a reusable, standalone script or tool that performs a specific task on a managed node. Modules are the building blocks of Ansible, enabling users to perform operations like installing packages, managing files, configuring services, and executing commands.

# When i execute the commands in Ansible server

```
ubuntu@ip-172-31-22-185:~$ vi myplaybook.yaml
ubuntu@ip-172-31-22-185:~$ ansible-playbook -i inventory myplaybook.yaml

PLAY [Install and start nginx] *****

TASK [Gathering Facts] *****
ok: [172.31.18.151]

TASK [install nginx] *****
changed: [172.31.18.151]

TASK [start service nginx, if not started] *****
ok: [172.31.18.151]

PLAY RECAP *****
172.31.18.151          : ok=3    changed=1    unreachable=0    failed=0    skipped=0    rescued=0    ignored=0

ubuntu@ip-172-31-22-185:~$
```

**i-03dd91213a33950bd (Ansible)**

PublicIPs: 52.23.185.100 PrivateIPs: 172.31.22.185

## Output in a slave server

[illegible]

**i-0644e3aade07bc770 (Slave)**

PublicIPs: 34.207.242.22 PrivateIPs: 172.31.18.151



In **Ansible, verbosity** refers to the level of detail displayed in the output of commands or playbook executions. By default, Ansible provides standard output, but you can increase verbosity to debug or gain more insights into what Ansible is doing behind the scenes.

```
TASK [install nginx] *****
ok: [172.31.18.151] => {"cache_update_time": 1735577404, "cache_updated": false, "changed": false}

TASK [start service nginx, if not started] *****
ok: [172.31.18.151] => {"changed": false, "name": "nginx", "state": "started", "status": {"ActiveEnterTimestamp": "Mon 2024-12-30 18:05:00 UTC", "ActiveEnterTimestampMonotonic": "7618425563", "ActiveExitTimestamp": "n/a", "ActiveExitTimestampMonotonic": "n/a", "ActiveState": "active", "After": "systemd-journald.socket nss-loopback.target network.target sysinit.target basic.target system.slice", "AllowIsolate": "no", "AssertResult": "yes", "AssertTimestamp": "Mon 2024-12-30 18:05:00 UTC", "AssertTimesampMonotonic": "7618409879", "Before": "multi-user.target shutdown.target", "BlockIOAccounting": "no", "BlockIOWeight": "[not set]", "CPUAccounting": "yes", "CPUAffinityFromNUMA": "no", "CPUQuotaPerSecUsec": "infinity", "CPUQuotaPeriodUsec": "infinity", "CPUSchedulingPolicy": "0", "CPUSchedulingPriority": "0", "CPUSchedulingResetOnFork": "no", "CPUShares": "[not set]", "CPUUsageNsec": "20919000", "CPUWeight": "[not set]", "CacheDirectoryMode": "0755", "CanFreeze": "yes", "CanIsolate": "no", "CanReload": "yes", "CanStart": "yes", "CanStop": "yes", "CapabilityBoundingSet": "cap_chown cap_dac_override cap_dac_read_search cap_fowner cap_fsetid cap_kill cap_setgid cap_setuid cap_setpcap cap_linux_immutable cap_net_bind_service cap_net_broadcast cap_net_admin cap_net_raw cap_ipc_lock cap_ipc_owner cap_sys_module cap_sys_rawio cap_sys_chroot cap_sys_chroot cap_sys_ptrace cap_sys_pacct cap_sys_nice cap_sys_resource cap_sys_time cap_sys_tty_config cap_kmod cap_lease cap_audit write cap_audit_control cap_setfcap cap_mac_override cap_mac_admin cap_syslog cap_wake_alarm cap_block_suspend cap_audit_read cap_perfmon cap_bpf cap_checkpoint_restore", "CleanResult": "success", "CollectMode": "inactive", "ConditionResult": "yes", "ConditionTimestamp": "Mon 2024-12-30 18:05:00 UTC", "ConditionTimestampMonotonic": "7618409877", "ConfigurationDirectoryMode": "0755", "Conflicts": "shutdown.target", "ControlGroup": "/system.slice/nginx.service", "ControlPID": "0", "CoreDumpFilter": "0x33", "DefaultDependencies": "yes", "DefaultMemoryLow": "no", "DefaultMemoryMin": "0", "Delegate": "no", "Description": "A high performance web server and a reverse proxy server", "DevicePolicy": "auto", "Documentation": "\\\n(mann:nginx(8))'", "DynamicUser": "n/a", "EffectiveCPUs": "0", "EffectiveMemoryNodes": "0", "ExecMainCode": "n/a", "ExecMainExitTimestamp": "n/a", "ExecMainExitTimestampMonotonic": "0", "ExecMainPID": "3176", "ExecMainStartTimestamp": "Mon 2024-12-30 18:05:02 UTC", "ExecMainStartTimestampMonotonic": "7620162730", "ExecMainStatus": "0", "ExecReload": "{ path=/usr/sbin/nginx ; argv[1]=/usr/sbin/nginx -g daemon on: master process on: -s reload ; ignore errors=0 ; start time=[n/a] ; stop time=[n/a] ; pid=0 ; code=(null) ; status=0/0 }", "ExecReloadEx": "{ path=/usr/sbin/nginx ; argv[1]=/usr/sbin/nginx -g daemon on: master process on: -s reload ; ignore errors=0 ; start time=[n/a] ; pid=0 ; code=(null) ; status=0/0 }", "ExecStart": "{ path=/usr/sbin/nginx ; argv[1]=/usr/sbin/nginx -g daemon on: master process on: ignore errors=0 ; start time=[Mon 2024-12-30 18:05:00 UTC] ; stop time=[Mon 2024-12-30 18:05:00 UTC] ; pid=3083 ; code=exited ; status=0 }", "ExecStartEx": "{ path=/usr/sbin/nginx ; argv[1]=/usr/sbin/nginx -g daemon on: master process on: ignore errors=0 ; start time=[Mon 2024-12-30 18:05:00 UTC] ; stop time=[Mon 2024-12-30 18:05:00 UTC] ; pid=3083 ; code=exited ; status=0 }", "ExecStartPre": "{ path=/usr/sbin/nginx ; argv[1]=/usr/sbin/nginx -t -q -g daemon on: master process on: flags ; start time=[Mon 2024-12-30 18:05:00 UTC] ; stop time=[Mon 2024-12-30 18:05:00 UTC] ; pid=3082 ; code=exited ; status=0 }", "ExecStartPreEx": "{ path=/usr/sbin/nginx ; argv[1]=/usr/sbin/nginx -t -q -g daemon on: master process on: flags ; start time=[Mon 2024-12-30 18:05:00 UTC] ; stop time=[Mon 2024-12-30 18:05:00 UTC] ; pid=3082 ; code=exited ; status=0 }", "ExecStop": "{ path=/sbin/start-stop-daemon ; argv[1]=/sbin/start-stop-daemon --quiet --stop --retry QUIT/5 --pidfile /run/nginx.pid ; ignore errors=yes ; start time=[n/a] ; stop time=[n/a] ; pid=0 ; code=(null) ; status=0/0 }", "ExecStopEx": "{ path=/sbin/start-stop-daemon ; argv[1]=/sbin/start-stop-daemon --quiet --stop --retry QUIT/5 --pidfile /run/nginx.pid ; flags=ignore-failure ; start time=[n/a] ; stop time=[n/a] ; pid=0 ; code=(null) ; status=0/0 }", "FailureAction": "none", "FileDescriptorStoreMax": "0", "FinalKillSignal": "9", "FragmentPath": "/lib/systemd/system/nginx.service", "FreezerState": "running", "GID": "[not set]", "GuessMainPID": "yes", "IOAccounting": "no", "IOReadBytes": "18464744073709551615", "IOReadOperations": "18464744073709551615", "IOSchedulingClass": "2", "IOSchedulingPriority": "4", "IOWeight": "[not set]", "IOWriteBytes": "18464744073709551615", "IOWriteOperations": "18464744073709551615", "IPAccounting": "no", "IPEgressBytes": "[no data]", "IPEgressPackets": "[no data]", "IPIngressBytes": "[no data]", "IPIngressPackets": "[no data]", "Id": "nginx.service", "IgnoreOnIsolate": "no", "IgnoreSIGPIPE": "yes", "InactiveEnterTimestamp": "n/a", "InactiveEnterTimestampMonotonic": "0", "InactiveExitTimestamp": "Mon 2024-12-30 18:05:00 UTC", "InactiveExitTimestampMonotonic": "7618414160", "InvocationID": "4d28b6b8af4147bce81d244095cb4", "JobRunningTimeoutUsec": "infinity", "JobTimeoutAction": "none", "JobTimeoutUsec": "infinity", "KeyringMode": "private", "KillMode": "mixed", "KillSignal": "15", "LimitAS": "infinity", "LimitASSoft": "infinity", "LimitCORE": "infinity", "LimitCORESoft": "0", "LimitCPU": "infinity", "LimitCPUSoft": "infinity", "LimitDATA": "infinity", "LimitDATASoft": "infinity", "LimitFSIZE": "infinity", "LimitFSIZESoft": "infinity", "LimitLOCKS": "infinity", "LimitLOCKSSoft": "infinity", "LimitMEMLOCK": "8388608", "LimitMEMLOCKSoft": "8388608", "LimitMSGQUEUE": "819200", "LimitMSGQUEUESoft": "819200", "LimitNICE": "0", "LimitNICESoft": "0", "LimitNOFILE": "524288", "LimitNOFILESoft": "1024", "LimitNPROC": "3769", "LimitNPROCSOft": "3769", "LimitRSS": "infinity", "LimitRSSSoft": "infinity", "LimitRTTIME": "0", "LimitRTTIMESoft": "infinity", "LimitSIGPENDING": "3769", "LimitSIGPENDINGSoft": "3769", "LimitSTACK": "infinity", "LimitSTACKSoft": "8388608", "LoadState": "loaded", "LockPersonality": "no", "LogLevelMax": "-1", "LogRateLimitBurst": "0", "LogRateLimitIntervalUsec": "0", "LogsDirectoryMode": "0755", "MainPID": "3176", "ManagedOOMMemoryPressure": "auto", "ManagedOOMMemoryPressureLimit": "0", "ManagedOOMPreference": "none", "ManagedOOMSwap": "auto", "MemoryAccounting": "yes", "MemoryAvailable": "infinity", "MemoryCurrent": "4911104", "MemoryDenyWriteExecute": "no", "MemoryHigh": "infinity", "MemoryLimit": "infinity", "MemoryLow": "0", "MemoryMax": "infinity", "MemoryMin": "0", "MemorySwapMax": "infinity", "MountAPIVFS": "no", "NFFileDescriptorStore": "0", "NREstart": "0", "NUMAPolicy": "n/a", "Names": "nginx.service", "NeedDaemonReload": "no", "Nice": "0", "NoNewPrivileges": "no", "NonBlocking": "no", "NotifyAccess": "none", "OOMPolicy": "stop", "OOMScoreAdjust": "0", "OnFailureJobMode": "replace", "OnSuccessJobMode": "fail", "PIDFile": "/run/nginx.pid", "Perpetual": "no", "PrivateDevices": "no", "PrivateIPC": "no", "PrivateMounts": "no", "PrivateNetwork": "no", "PrivateTmp": "no", "PrivateUsers": "no", "ProcSubset": "all", "ProtectClock": "no", "ProtectControlGroups": "no", "ProtectHome": "no", "ProtectHostname": "no", "ProtectKernelLogs": "no", "ProtectKernelTunables": "no", "ProtectKernelTunables": "no", "ProtectProc": "default", "ProtectSystem": "no", "RefuseManualStart": "no", "RefuseManualStop": "no", "ReloadResult": "success", "RemainAfterExit": "no", "RemoveIPC": "no", "Requires": "system.slice systemd-journald.service", "Restart": "no", "RestartKillSignal": "15", "RestartUsec": "100ms", "RestrictNamespaces": "no", "RestrictRealtime": "no", "RestrictSUIDSGID": "no", "Result": "success", "RootDirectoryStartOnly": "no", "RuntimeDirectoryMode": "0755", "RuntimeDirectoryPreserve": "no", "RuntimeMaxUsec": "infinity", "SameProcessGroup": "no", "SecureBits": "0", "SendSIGHUP": "no", "SendSIGKILL": "yes", "Slice": "system.slice", "StandardError": "inherited", "StandardOutput": "journal", "StartLimitAction": "none", "StartLimitBurst": "5", "StartLimitIntervalUsec": "10s", "StartupCPUShares": "[not set]", "StartupCPUWeight": "[not set]", "StartupIOWeight": "[not set]", "StateChangeTimestamp": "Mon 2024-12-30 18:05:00 UTC", "StateChangeTimestampMonotonic": "7618425563", "StateDirectoryMode": "0755", "StatusError": "no", "SubState": "running", "SuccessAction": "none", "SyslogFacility": "3", "SyslogLevel": "6", "SyslogCleanLease": "yes", "SyslogPriority": "30", "SystemCallErrorNumber": "2147483646", "TTYReset": "no", "TTYVhangup": "no", "TTYVDisallocate": "no", "TasksAccounting": "yes", "TasksCurrent": "23", "TasksMax": "1130", "TimeoutAbortUsec": "5s", "TimeoutCleanUsec": "infinity", "TimeoutStartFailureMode": "terminate", "TimeoutStartUsec": "1min 30s", "TimeoutStopFailureMode": "terminate", "TimeoutStopUsec": "5s", "TimesSlackNsec": "50000", "Transient": "no", "Type": "forking", "UID": "[not set]", "UMask": "002", "UnitFilePreset": "enabled", "UnitFileState": "enabled", "UtmpMode": "init", "WantedBy": "multi-user.target", "WatchdogSignal": "6", "WatchdogTimestamp": "n/a", "WatchdogTimestampMonotonic": "0", "WatchdogUsec": "0"}
```

```
PLAY RECAP *****
172.31.18.151 : ok=3 changed=0 unreachable=0 failed=0 skipped=0 rescued=0 ignored=0
```

```
ubuntu@ip-172-31-22-185-4:~$
```