



Default of Credit Card Clients

BAN 620 – Data Mining Group Project

Project By:

Rutweek Sawant

Siddharth Naik

Kedar Patil

Ankur Bhagwat

Sagar Pawar

Table of Contents

Report Section:	Page Number:
Abstract	3
Goal	3
Data Set Summary	3
Process Design	4
Exploratory Data Analysis	5
Main Chapter:	7
Model 1: Decision Tree	7
Model 2: Boosted Tree	10
Model 3: K-Nearest Neighbor	10
Model 4: Fit Nominal Logistics	12
Model 5 Neural Networks	13
Model 6: Bootstrap Forrest	15
Model Comparison	17
Tuning	18
Conclusion	19
Bibliography	19
Appendix	20

Abstract


Credit Risk Assessment has become pivotal among financial institutions to avoid financial risk and reduce the count of defaulters globally. A credit risk is the risk of default on a credit card payment that may arise from a borrower/credit card user failing to make required payments. In this process the credit history of the customer undergoes a rigorous check to ensure that whether they are capable enough to pay off the credit amount. The objective is to make a prediction whether the customer will pay his debt timely or not and then decide on a cut-off criterion.

Goal

- Predict the Credit Card Payment Defaulters and Non-Defaulters for the next month.
- Aim is to find/build a Data Mining model that will help us determine defaulters with high accuracy.
- Find potential customers for the institute/banks who can make the credit card payments on time.
- Classify potential customers who will default according to Profiling and Propensity.

Data Set Summary

The data set is of a Taiwanese Financial firm dated from April 2005 to September 2005, including 30000 unique customers (rows). It has 25 variables including the dependent variable default.payment.next.month (June 2005). The data set can be portrayed as combination of 5 parts .




Variable	Description	Variable Segment
ID	ID of each client	Client Description Variables
LIMIT_BAL	Amount of given credit in NT dollars (includes individual and family/supplementary credit)	
SEX	Gender (1=male, 2=female)	
EDUCATION	(1=graduate school, 2=university, 3=high school, 4=others)	
MARRIAGE	Marital status (1=married, 2=single, 3=others)	
AGE	Age in years	Repayment status variables
PAY_0	Repayment status in September, 2005 (-1=pay duly, 1=payment delay for one month 2=for 2 months, ...)	
PAY_2	Repayment status in August, 2005 (scale same as above)	
PAY_3	Repayment status in July, 2005 (scale same as above)	
PAY_4	Repayment status in June, 2005 (scale same as above)	
PAY_5	Repayment status in May, 2005 (scale same as above)	
PAY_6	Repayment status in April, 2005 (scale same as above)	
BILL_AMT1	Amount of bill statement in September, 2005 (NT dollar)	Amount of bill statement Variables
BILL_AMT2	Amount of bill statement in August, 2005 (NT dollar)	
BILL_AMT3	Amount of bill statement in July, 2005 (NT dollar)	
BILL_AMT4	Amount of bill statement in June, 2005 (NT dollar)	
BILL_AMT5	Amount of bill statement in May, 2005 (NT dollar)	
BILL_AMT6	Amount of bill statement in April, 2005 (NT dollar)	
PAY_AMT1	Amount of previous payment in September, 2005 (NT dollar)	Amount of previous payment variables
PAY_AMT2	Amount of previous payment in August, 2005 (NT dollar)	
PAY_AMT3	Amount of previous payment in July, 2005 (NT dollar)	
PAY_AMT4	Amount of previous payment in June, 2005 (NT dollar)	
PAY_AMT5	Amount of previous payment in May, 2005 (NT dollar)	
PAY_AMT6	Amount of previous payment in April, 2005 (NT dollar)	
default.payment.next.month	Default payment in June, 2005 (1=yes, 0=no)	Dependent Variable

Process Design

- The process is done by Supervised learning Algorithm
- The idea behind using this is we have a prior knowledge on our output values
- It acts as a guide to teach the algorithms what conclusion it should come up with
- Proposed algorithms are Decision Tree, Logistic Regression, Boosted Tree, Bootstrap Forest, Neural Network, K-NN.




Process Approach




Exploratory Data Analysis:

Defaulters vs Non-Defaulters



(a)

Defaulters on the basis of sex




(b)

Report a -> Out of 30000 unique customers 6636 are defaulters while 23364 are non-defaulters which gives a percentile ratio of 22% defaulters: 88% non-defaulters hence we can say that that data is not biased to one category.


Report b->It gives the overview about the split on male and female. As we can see there are 60% of the data consist of women while 56% of defaulters are women.

Level of education vs Balance Limit



(c)

Age vs Balance Limit



(d)

Report c -> We can see our dataset follows global data trends I.e. higher the level of education higher is the balance limit.


Report d -> we can see the graph is of a form of bell curve, as the age increases it is natural the debt repayment capability of an individual increases as his salary/designation increases. As the individual nears his retirement gradually his debt repayment will decrease because of the time factor.

Main Chapter


Model 1: Decision Tree:

We created a Decision Tree model, we took default payment (Yes = 1, No = 0), as the response variable. We obtained the following results using the Fit Details, Leaf Report, Column Contribution, ROC curve, Lift curve and Profiler.

- This is the small tree view which show all the splits of the Model.



Split History



Validation Data in Red


Fit Details

Measure	Training	Validation	Definition
Entropy RSquare	0.1759	0.1794	$1 - \text{Loglike}(\text{model}) / \text{Loglike}(0)$
Generalized RSquare	0.2603	0.2643	$(1 - (L(0)/L(\text{model}))^{2/n}) / (1 - L(0)^{2/n})$
Mean -Log p	0.4367	0.4318	$\sum -\text{Log}(p[j]) / n$
RMSE	0.3696	0.3670	$\sqrt{\sum (y[j] - p[j])^2 / n}$
Mean Abs Dev	0.2732	0.2708	$\sum y[j] - p[j] / n$
Misclassification Rate	0.1799	0.1774	$\sum (p[j] \neq p_{\text{Max}}) / n$
N	17875	12125	n

Confusion Matrix

Training			Validation		
Actual Y	Predicted Count		Actual Y	Predicted Count	
	no	yes		no	yes
no	13191	709	no	8995	469
yes	2507	1468	yes	1682	979

- The Fit details of the Decision tree model are seen above. As seen in the results, we observe a RSquare value for training and validation data at 0.2603 and 0.2643 respectively, which tell us that this model does not suffer from overfitting. Moreover, we see that there were a total 15 splits used for the final Decision tree. Moreover, we observe that Training and Validation data RMSE values are at 0.3696 & 0.3670; which will be used for model performance comparisons. Misclassification rate is 17.74% which is less.
- From the split history, we can see that the validation data (red line) is split with $n = 15$ as this represents the most optimal split value which was chosen due to its highest R^2 value. It is seen that although the number of splits remains same for the training data.
- Confusion Matrix of Validation states
 - 8995 entries are predicated non defaulters which are actually non defaulter
 - 1682 entries are predicted non defaulters which are actually defaulters
 - 469 entries are predicted defaulters which are actually non defaulters
 - 979 entries are predicted defaulter which are actually defaulters
 - $[(8995+978) / 8995+978+469+1682] = 82.26\%$ entries are predicted correctly




ROC curve:

- ROC curve tells us whether model is statistically significant or vice versa.
- As we can see from the Curve below, Curve is above diagonal.
- We can say that model is accurate and statistically significant

Lift curve

- From the lift curve we can say that our model predicts the defaulters 3 times better than base line or output which we get after running the random sample data.



- The Prediction Profiler tells us the relationship of input variables with response variable.
- Eg- SEX_N, EDUCATION_N, AGE_N has linear relationship with response variable Y.
- PAY0_N has no relationship with response variable Y

Model 2: Boosted Tree:

Boosted tree is improved model of Regression Tree. Like a bootstrap forest, a boosted tree is a small tree that is repeatedly fit to the data using a random sample of predictors. The difference is that boosted trees make use of residuals based on misclassifications or errors which are reduced until an optimal tree is generated. From the snippet below we can see that a small tree was used with 3 splits and 50 layers were used for the model.

Overall Statistics

Measure	Training	Validation	Definition
Entropy RSquare	0.1919	0.1835	1-Loglike(model)/Loglike(0)
Generalized RSquare	0.2816	0.2698	(1-(L(0)/L(model))^(2/n))/(1-L(0)^(2/n))
Mean -Log p	0.4282	0.4297	$\sum -\text{Log}(\rho[j])/n$
RMSE	0.3655	0.3659	$\sqrt{\sum (y[j]-\rho[j])^2/n}$
Mean Abs Dev	0.2724	0.2723	$\sum y[j]-\rho[j] /n$
Misclassification Rate	0.1761	0.1758	$\sum (\rho[j]\neq\rho_{\text{Max}})/n$
N	17875	12125	n

Confusion Matrix

Training

Actual Y	Predicted Count	
	no	yes
no	13272	628
yes	2519	1456

Validation

Actual Y	Predicted Count	
	no	yes
no	9041	423
yes	1708	953

- The R square of Boosted tree is 26.98% which is slightly better than Decision tree.
- RMSE is 0.3659 which is less than Decision tree as well.
- Misclassification tree is 17.58% which is also less than Decision tree


Model 3: K – Nearest Neighbor

k-Nearest Neighbors method (k-NN) can be used for Classification of a categorical outcome or Prediction of a numerical outcome. To classify or predict a new record, this method relies on finding “similar” records in the training data. k-NN is a nonparametric method. Does not make assumptions about the form of the relationship between the class membership (Y) and the predictors X1, X2, ... Xp. Does not involve estimation of parameters in an assumed function form (e.g., linear relationship in regression) Characteristics are:

- Data driven, not model driven (like multiple regression)
- No assumptions about the data relationship
- Conceptually simple/straightforward
- Highly automated

Model Selection

- Output below is of model selection.
- Model selection gives us the least classification rate with selection of optimal k
- Here Red line represents the Validation where 19 is the optimal k with least classification rate



- The misclassification rate is 18.54% at optimal k = 19.
- The misclassification rate is little more compared to decision tree and boosted tree

Model 4: Fit Nominal Logistic:

We created a Fit nominal Logistic model, we took default payment (Yes = 1, No = 0), as the response variable. We obtained the following results using the Fit Details, Effect Summary table, Parameter Estimate, Confusion Matrix

- Effect Summary Table shows us the parameter Contribution to the model
- As we can see PAY0_N has contributed the most in the prediction model
- The parameters who contributed are Pay_amt1_n, bill_amt1_1
- Bill_amt6, Bill_amt5, py6_n has least contribution to the model.

Fit Details			
Measure	Training	Validation	Definition
Entropy RSquare	0.1201	0.1197	$1 - \text{Loglike}(\text{model}) / \text{Loglike}(0)$
Generalized RSquare	0.1829	0.1818	$(1 - (L(0)/L(\text{model}))^{2/n}) / (1 - L(0)^{2/n})$
Mean -Log p	0.4663	0.4633	$\sum -\text{Log}(p[j])/n$
RMSE	0.3814	0.3794	$\sqrt{\sum (y[j] - p[j])^2 / n}$
Mean Abs Dev	0.2954	0.2938	$\sum y[j] - p[j] / n$
Misclassification Rate	0.1905	0.1877	$\sum (p[j] \neq p_{\text{Max}}) / n$
N	17875	12125	n

Confusion Matrix

Training

Actual	Predicted Count	
	no	yes
Y		
no	13537	363
yes	3043	932

Validation

Actual	Predicted Count	
	no	yes
Y		
no	9213	251
yes	2025	636

- The Rquare of this model is 18.18% which is less compared to other models
- RMSE is 0.3794 which is more compared to other models
- The misclassification rate is 18.77% which is more compared to other models

Model 6: Bootstrap Forest

The Bootstrap Forest platform fits an ensemble model by averaging many decision trees each of which is fit to a bootstrap sample of the validation data. Each split in each tree considers a random subset of the predictors.

The specifications of bootstrap forest is mentioned below

We selected no. of trees in forest = 300, no. of terms samples per split = 5 and sample rate = 1

Bootstrap Forest Specification

Number of Rows: 30000
Number of Terms: 23

Forest

Number of Trees in the Forest: 300
Number of Terms Sampled per Split: 5
Bootstrap Sample Rate: 1
Minimum Splits per Tree: 10
Maximum Splits per Tree: 2000
Minimum Size Split: 30
☒ Early Stopping

Multiple Fits

☐ Multiple Fits over Number of Terms
Max Number of Terms: 11
☐ Use Tuning Design Table

Reproducibility

☐ Suppress Multithreading
Random Seed: 0

OK Cancel


Overall Statistics

Measure	Training	Validation	Definition
Entropy RSquare	0.3329	0.1971	$1 - \text{Loglike}(\text{model}) / \text{Loglike}(0)$
Generalized RSquare	0.4550	0.2878	$(1 - (L(0)/L(\text{model}))^{2/n}) / (1 - L(0)^{2/n})$
Mean -Log p	0.3535	0.4225	$\sum -\text{Log}(p[j]) / n$
RMSE	0.3329	0.3635	$\sqrt{\sum (y[j] - p[j])^2 / n}$
Mean Abs Dev	0.2446	0.2661	$\sum y[j] - p[j] / n$
Misclassification Rate	0.1695	0.1757	$\sum (p[j] \neq p_{\text{Max}}) / n$
N	17875	12125	n


Confusion Matrix

Training			Validation		
Actual	Predicted Count		Actual	Predicted Count	
Y	no	yes	Y	no	yes
no	13344	556	no	9052	412
yes	2474	1501	yes	1718	943

- The R square of Bootstrap forest model is 28.78% which is better than all the models mentioned above.
- RMSE is 0.3635 which is least compared to other models.
- Misclassification tree is 17.57% which is also least compared to other models.



From the lift curve we can say that our model predicts the defaulters 3.5 times better than base line or output which we get after running the random sample data.



- ROC curve tells us whether model is statistically significant or vice versa.
- As we can see from the Curve below, Curve is above diagonal.
- We can say that model is accurate and statistically significant

Model Comparison

Measures of Fit for Y											
Creator	.2	.4	.6	.8	Entropy RSquare	Generalized RSquare	Mean -Log p	RMSE	Mean Abs Dev	Misclassification Rate	N
Partition					0.1794	0.2643	0.4318	0.3670	0.2708	0.1774	12125
Boosted Tree					0.1835	0.2698	0.4297	0.3659	0.2723	0.1758	12125
Bootstrap Forest					0.1965	0.2870	0.4228	0.3636	0.2663	0.1757	12125
K Nearest Neighbors										0.1855	12125
Fit Nominal Logistic					0.1197	0.1818	0.4633	0.3794	0.2938	0.1877	12125
Neural					0.1840	0.2704	0.4294	0.3663	0.2691	0.1772	12125
Neural					0.1842	0.2707	0.4293	0.3662	0.2670	0.1770	12125
Neural					0.1884	0.2764	0.4271	0.3654	0.2682	0.1767	12125
Neural					0.1853	0.2722	0.4287	0.3660	0.2663	0.1767	12125

Since the required prediction is a classification problem the three main criteria for model selection are

- Low Misclassification Rate
- Low RMSE
- High Rsquare
- No overfitting

Bootstrap forest follows all the four criteria's and hence it is the best model.

Tuning the Model

- Type 2 (Applicant will not pay the loan) Accuracy Rate for Bootstrap forest = 35%
- As You can see the overall misclassification rate is 93% but the downside is type 2 accuracy is also low
- Hence to improve it we have tuned the model based on p value in python using spyder, following results were obtained


```
from sklearn.metrics import confusion_matrix, accuracy_score
cfm=confusion_matrix(Y_test.tolist(),y_pred_class)#we are tycasting to list
print(cfm)
accuracy_score=accuracy_score(Y_test.tolist(),y_pred_class)
print("Accuracy of the model:",accuracy_score)

#####
for a in np.arange(0,1,0.05):
    predict_mine = np.where(y_pred_prob[:,0]<a,1,0)
    cfm=confusion_matrix(Y_test.tolist(),predict_mine)
    total_err=cfm[0,1]+cfm[1,0]
    print("Errors at treshhold",a,":",total_err,"type 2 error :",cfm[1,0])

##### auc
from sklearn import metrics
fpr, tpr, threshold = metrics.roc_curve(Y_test, Y_pred)
auc = metrics.auc(fpr,tpr)
print(auc)

##### roc
import matplotlib.pyplot as plt
plt.title('Receiver Operating Characteristic')
plt.plot(fpr, tpr, 'b', label = auc)
plt.legend(loc = 'lower right')
plt.plot([0, 1], [0, 1], 'r--')
plt.xlim([0, 1])
plt.ylim([0, 1])
plt.ylabel('True Positive Rate')
plt.xlabel('False Positive Rate')
plt.show()
```

```
Errors at treshhold 0.0 : 2018 type 2 error : 2018
Errors at treshhold 0.05 : 2014 type 2 error : 2011
Errors at treshhold 0.1 : 2011 type 2 error : 2005
Errors at treshhold 0.15000000000000002 : 2006 type 2 error : 1997
Errors at treshhold 0.2 : 1986 type 2 error : 1973
Errors at treshhold 0.25 : 1965 type 2 error : 1949
Errors at treshhold 0.30000000000000004 : 1944 type 2 error : 1921
Errors at treshhold 0.35000000000000003 : 1918 type 2 error : 1884
Errors at treshhold 0.4 : 1866 type 2 error : 1804
Errors at treshhold 0.45 : 1790 type 2 error : 1685
Errors at treshhold 0.5 : 1724 type 2 error : 1560
Errors at treshhold 0.55 : 1646 type 2 error : 1388
Errors at treshhold 0.60000000000000001 : 1661 type 2 error : 1267
Errors at treshhold 0.65 : 1701 type 2 error : 1171
Errors at treshhold 0.70000000000000001 : 1786 type 2 error : 1086
Errors at treshhold 0.75 : 2209 type 2 error : 883
Errors at treshhold 0.8 : 3453 type 2 error : 600
Errors at treshhold 0.85000000000000001 : 4706 type 2 error : 397
Errors at treshhold 0.9 : 5748 type 2 error : 171
Errors at treshhold 0.95000000000000001 : 6598 type 2 error : 31
```



```
[[5138 1844]
 [ 779 1239]]
Accuracy of the model: 0.7085555555555556
```

Results: Though the accuracy was reduced to 71%, the model got trained well on type 2 errors improving the type 2 accuracy rate to 61% and reducing the type 1 accuracy to smaller extent of 74%.

Conclusion

To summarize we can conclude that bootstrap forest marginally outperformed other models in terms of misclassification rate, RMSE, R square and overfitting criterion. Also, the model was tuned so that it can classify type 2 errors more efficiently with an overall accuracy of 71%.

We can conclude that thus Taiwanese financial institutions can use the Bootstrap forest model to reduce credit risk in there by safeguarding their organizations from potential risks.

Bibliography

- <https://archive.ics.uci.edu/ml/datasets/default+of+credit+card+clients#>
- Data Mining for Business Analytics – Concepts, Techniques, and Applications with JMP PRO, by Galit Shmueli, Peter C. Bruce, Mia L. Stephens, Nitin R. Patel

Appendix

Variable Name	Description
Activation function	Abstraction representing the rate of action potential firing in the cell
Biased	Belonging to particular type(defaulter/non-defaulter)
Confusion Matrix	Matrix that helps to find accuracy
Credit Risk	Chance of Default
Categorical	Data can be measured (usually 0,1,2,3.... or Yes/No)
Classification	Classify into classes
Cut-off	Criteria to give the individual card credit or not
Data driven	Determined by or dependent on the collection or analysis of data.
Defaulter	The individual to fails to repay his credit card bill
ensemble	Group of items viewed as a whole rather than individually.
Exploratory	Mining Data trends
Financial Risk	Potential Risk due to defaulter
Global data trends	Data trends that are accepted globally
Model	Prediction Model
Neural	Relating to a nerve or the nervous system.
Predictors	Independent variables
Profiling	The recording and analysis of a person's psychological and behavioral characteristics
Propensity	An inclination or natural tendency to behave in a particular way.
ROC	Receiver Operating Characteristics
Regression	A measure of the relation between the mean value of one variable and corresponding values of other variables
Supervised	We know the output criteria (Yes/No)
Statistically significant	Supports our cause
Snippet	Screenshot
Tuning	Improve the accuracy
Training	Data that our model trains on
Validation	Data on which our model checks its accuracy