

SYNTHETIC ENVIRONMENTAL OPERATING PERMIT

FOR SOFTWARE TESTING ONLY - NOT A REAL PERMIT

This synthetic operating permit (Permit No. PTP-2026-0001) is issued to Crystal Valley Manufacturing, LLC, located at 1200 Industrial Parkway, for the sole purpose of testing the Permit-to-Proof software. All facilities, limits, and citations below are fictional. The permit combines Title V air emission conditions and NPDES water discharge conditions in the regular numbered style used by real permits.

SECTION 3 - AIR EMISSION LIMITS (TITLE V)

Condition 3.1. Nitrogen oxides (NO_x) emissions from Boiler Unit B-1 shall not exceed 30 ppm, corrected to 15 percent oxygen, on a 30-day rolling average. NO_x shall be monitored continuously by a certified CEMS. (40 CFR 60.44c)

Condition 3.2. Sulfur dioxide (SO₂) emissions from Boiler Unit B-1 shall not exceed 0.30 lb/MMBtu on a 30-day rolling average, monitored continuously. (40 CFR 60.43c)

Condition 3.3. Carbon monoxide (CO) emissions shall not exceed 100 ppm at the stack outlet, monitored continuously by CEMS. (Condition 3.3)

Condition 3.4. Particulate matter (PM₁₀) emissions shall not exceed 0.030 gr/dscf, demonstrated by an annual stack test conducted in accordance with Method 5. (40 CFR 60.42c)

Condition 3.5. Volatile organic compounds (VOC) emissions from the coating line shall not exceed 25 tons/yr on a 12-month rolling total, with records updated monthly. (Condition 3.5)

Condition 3.6. Visible emissions from any stack shall not exceed 20 % opacity, monitored continuously, except for one six-minute period per hour of up to 27 percent opacity. (40 CFR 60.42)

SECTION 4 - WATER DISCHARGE LIMITS (NPDES)

Condition 4.1. The pH of the discharge from Outfall 001 shall be maintained between 6.0 and 9.0 standard units at all times, monitored daily by grab sample. (Condition 4.1)

Condition 4.2. Five-day biochemical oxygen demand (BOD5) shall not exceed 30 mg/L as a monthly average, monitored weekly. (40 CFR 133.102)

Condition 4.3. Total suspended solids (TSS) shall not exceed 30 mg/L as a monthly average, monitored weekly by composite sample. (40 CFR 133.102)

Condition 4.4. The temperature of the discharge shall not exceed 32 deg C, monitored daily. (Condition 4.4)

Condition 4.5. Fecal coliform bacteria shall not exceed 200 cfu/100 mL as a monthly geometric mean, monitored monthly. (Condition 4.5)

Condition 4.6. The discharge flow from Outfall 001 shall not exceed 5.0 MGD, monitored continuously by a calibrated flow meter. (Condition 4.6)

SECTION 5 - MONITORING, REPORTING, AND RECORDKEEPING

Condition 5.1. The permittee shall submit Discharge Monitoring Reports (DMRs) within 28 days after the end of each monitoring period. (40 CFR 122.41)

Condition 5.2. The permittee shall maintain all monitoring records, including calibration and maintenance logs, for a period of five years and make them available to the Administrator upon request. (40 CFR 122.41)

Condition 5.3. The permittee shall report any exceedance of an emission or effluent limit by telephone within 24 hours and in writing within 5 days of becoming aware of the exceedance. (Condition 5.3)