

PRE-DISPATCH INSPECTION REPORT (PDIR)

CUSTOMER NAME : KOEL

SUPPLIER NAME : Shriram Foundry Pvt.Ltd

PART NO : 4H.001.02.7.03

DATE : 26/5/2026

PART NAME : BEARING CAP G.E. (SemiFinish)

QTY : 100

REV. LEVEL : 03

CH.NO

SR NO	Product Specification	Specification	Measurement Techniques	Supplier Observations					Remark
				1754	1891	17.2	1616	1792	
1	Flatness	0.04	Filler Gauge	ok	ok	ok	ok	ok	ok
2	Counter Bore	Dia 16.99 +0.038	Air Pluge Gauge	ok	ok	ok	ok	ok	ok
3	Distance for Dia 16.99	102.0 ± 0.03	CMM/Receiving Gauge	ok	ok	ok	ok	ok	ok
4	Notch Cutter Diameter	63.0-2.0	SPI. Type Gauge	ok	ok	ok	ok	ok	ok
5	Distance	10.4-0.6/+1.0	Hight Gauge/ spi Type Gauge	10.5	10.5	10.6	10.5	10.6	ok
6	Notch Depth	17.85-3.5	Hight Gauge	16.4	16.5	16.7	16.4	16.7	ok
7	Notch Width	6.00 ± 0.1	Width Gauge	ok	ok	ok	ok	ok	ok
8	Notch Distance	11.4 ± 0.1	Height Gauge/ spi Type Gauge	11.45	11.45	11.46	11.45	11.46	ok
9	Milling Distance	16.2 ± 0.2	Height Gauge	16.24	16.25	16.24	16.24	16.26	ok
10	Total Hight	81.0 ± 0.2	Hight Gauge	80.91	80.91	80.91	80.91	80.91	ok
11	Parallelism	0.1 w.r.t. A	Comparator Stand	ok	ok	ok	ok	ok	ok
12	Distance for Dia 15	102.0 ± 0.2	Receiving Gauge	ok	ok	ok	ok	ok	ok
13	Cast Ref.	86.0 ± 0.5	Hight Gauge	86.14	86.14	86.14	86.15	86.14	ok
14	Diameter	70.0 ± 0.5	Vernier Caliper	70.1	70.11	70.11	70.12	70.11	ok
15	Angle	10°	Receiving Gauge	ok	ok	ok	ok	ok	ok
16	Depth	9.0 ± 1.0	Vernier Caliper	9.24	9.26	9.25	9.24	9.26	ok
17	Hole I.D.	15.0 ± 0.3	Pluge Gauge	ok	ok	ok	ok	ok	ok
18	Chamfar	0.5 ± 2°45'	Vernier Caliper	ok	ok	ok	ok	ok	ok
19	Hole Dia	dia 3.0	Pluge Gauge	ok	ok	ok	ok	ok	ok
20	Hole Depth	70.8 ± 0.3	Vernier Caliper	70.96	70.98	70.95	70.96	70.96	ok
21	Distance	CL OF 16.99	Receiving Gauge	ok	ok	ok	ok	ok	ok
22	RZ	25.00	Surface Tester	16.14	16.72	16.71	16.14	16.91	ok
23	Distance	74 ± 0.3	Vernier Caliper	74.11	74.12	74.11	74.11	74.13	ok
24	Perpendicularity	0.20	CMM/Receiving Gauge	ok	ok	ok	ok	ok	ok
25	visual	free from dent, burr, rust, sharp edges	visual	ok	ok	ok	ok	ok	ok

Checked By Name & Sign :

Checked By Name & Sign

Approved By Name & Sign :

Approved By Name & Sign