


Predispatch Inspection Report

Supplier : Shriram Foundry Pvt. Ltd.
Component Name : Crank Pulley
Drawing No. : 04.195.05
Drawing Alt No. : Rev.no-10

D.C NO. :

Doc. No. : PES/QA/F/03
Issue No./ Date :
Rev No./ Date : 02/ 12-1-21
Date / Qty: 26/5/2026/30/005

Sr. No.	Parameters	Specification	Tolerance	Parameter Class	Measuring Equipment	1	2	3	4	5	Remarks
1	O.D	Dia. 95.00	-0.120 / -0.207		Snap Gauge	ok	ok	ok	ok	ok	
2	O.D	Dia. 65.00	+0.0/-0.190		Snap Gauge	ok	ok	ok	ok	ok	
3	I.D	Dia. 36	+0.039/+0.00		Plug Gauge	ok	ok	ok	ok	ok	
4	I.D	Dia. 24.5	+0.5		Plug Gauge	ok	ok	ok	ok	ok	
5	I.D	Dia. 45	+0.5		Plug Gauge	ok	ok	ok	ok	ok	
6	O.D	Dia. 95.00	-0.120 / -0.207		Snap Gauge	ok	ok	ok	ok	ok	
7	O.D	Dia. 224.62	-0.0/-0.5		POD Gauge	ok	ok	ok	ok	ok	
8	O.D	Dia. 219.6	-0.00 / -0.29		Vernier Caliper	219.41	214.41	219.41	219.41	219.41	
9	I.D	8.2	+0.1		Plug Gauge	ok	ok	ok	ok	ok	
10	Distance	72.5	+0.2		Ht.Gauge	72.61	72.62	72.81	72.82	72.82	
11	Distance	96	+/- 0.1		Ht.Gauge	96.04	96.54	96.08	96.54	92.85	
12	Distance	18	+/- 0.2		Ht.Gauge	18.11	18.11	18.11	18.11	18.12	
13	Distance	122	+0.2		Ht.Gauge	112.11	112.11	112.12	112.12	112.13	
14	V.Gr.Distance	<0.2			Run Out Fixture	0.04	0.05	0.04	0.05	0.04	
15	Surface Finish	Rz 1 to 4			Roughness Taster	2.434	2.161	7.114	2.992	2.161	
16	C.D	25.00	+/- 0.05		C.M.M/Receiving gauge	ok	ok	ok	ok	ok	
17	Tapping	M8X1.25			Thread Plug Gauge	ok	ok	ok	ok	ok	
18	P.C.D	116			C.M.M/Receiving gauge	ok	ok	ok	ok	ok	
19	Position	<0.25			C.M.M/Receiving gauge	ok	ok	ok	ok	ok	
20	Balancing	<25gm			Balancing Machine	5	12	16	14	17	
21	Position	<0.60			C.M.M/Receiving gauge	ok	ok	ok	ok	ok	
22	Visual Deffect	No Dent,Damage,Blow Holes			Visual	OK	OK	OK	OK	OK	
23	Runout	0.05			Run Out Fixture	0.02	0.02	0.02	0.02	0.02	
24	flatness	0.03			Feeler gauge	OK	OK	OK	OK	OK	
25	V Groove depth	12.5 ±0.2			Vernier Caliper	12.56	12.85	12.85	12.86	12.88	
26	Runout	0.25			Run Out Fixture	0.04	0.05	0.04	0.04	0.05	
27	Case depth	2.0 MIN			MTC			ok			
28	Case hardness	35 to 50 HRC			MTC			ok			

Prepared By : 
Sign :

Approved By : 
Sign :