

PRE-DISPATCH INSPECTION REPORT (PDIR)

CUSTOMER NAM : KOEL				SUPPLIER NAME : Shriram Fopundry Pvt.Ltd					
PART NO : 03.001.23.9.04				DATE		28/5/2026			
PART NAME : MAIN BEARING CAP (FEW) (SEMI FINISH)				QTY		200			
REV. LEVEL : 04				CH.NO					
SR NO	Product Specification	Specification	Measurement Techniques	Supplier Observations					Remark
				31/2	30/2	392	396	31/4	
1	Flatness	0.04	Filler Gauge	ok	ok	ok	ok	ok	ok
2	Counter Bore	Dia 16.99 +0.038	Air Pluge Gauge	ok	ok	ok	ok	ok	ok
3	Distance for Dia 16.99	102.0 ± 0.03	CMM/Receiving Gauge	ok	ok	ok	ok	ok	ok
4	Notch Cutter Diameter	63.0-2.0	SPI. Type Gauge	ok	ok	ok	ok	ok	ok
5	Notch Distance	11.4 ± 0.1	Height Gauge/ spl Type Gauge	11.45	11.45	11.44	11.46	11.45	ok
6	Notch Width	6.00 ± 0.1	Width Gauge	ok	ok	ok	ok	ok	ok
7	Notch Depth	17.85-3.5	Hight Gauge	16.9	16.9	16.8	16.9	16.6	ok
8	Distance	10.4-0.6/+1.0	Hight Gauge/ spl Type Gauge	10.6	10.5	10.6	10.5	10.6	ok
9	Total Hight	81.0 ± 0.2	Hight Gauge	81.11	81.11	81.12	81.12	81.12	ok
10	Parallelism	0.1 w.r.t. A	Comparator Stand	ok	ok	ok	ok	ok	ok
11	Distance for Dia 15	102.0 ± 0.2	CMM/Receiving Gauge	ok	ok	ok	ok	ok	ok
12	Hole I.D.	15.0+0.3	Pluge Gauge	ok	ok	ok	ok	ok	ok
13	Chamfar	0.5 ± 2°45'	Vernier Caliper	ok	ok	ok	ok	ok	ok
14	Depth	9.0+1.0	Vernier Caliper	9.24	9.24	9.26	9.24	9.26	ok
15	Thred Depth	11.5+2.5	TPG+Vernier Caliper	12.6	12.5	12.5	12.5	12.6	ok
16	Drill Depth	19.0+2	Vernier Caliper	19.4	19.4	19.5	19.4	19.5	ok
17	Distance	50.0 ± 0.5	CMM/Receiving Gauge	ok	ok	ok	ok	ok	ok
18	Tapping	M8	TPG	ok	ok	ok	ok	ok	ok
19	RZ	25.00		17.14	16.14	16.91	16.14	18.12	ok
20	Diameter	70.0 ± 0.5	Vernier Caliper	70.1	70.11	70.11	70.12	70.11	ok
21	WIDTH	35-0.3	Width Gauge	ok	ok	ok	ok	ok	ok
22	Perpendicularity	0.20	CMM/Receiving Gauge	ok	ok	ok	ok	ok	ok
23	visual	free from dent, burr, rust, sharp edge	visual	ok	ok	ok	ok	ok	ok
Supplier Checked By Name & Sign : <i>[Signature]</i>				Checked By Name & Sign					
Supplier Approved By Name & Sign : <i>[Signature]</i>				Approved By Name & Sign					

