

PRE-DISPATCH INSPECTION REPORT (PDIR)

CUSTOMER NAME : KOEL

SUPPLIER NAME : Shriram Foundry Pvt.Ltd

PART NO : 4H.001.02.7.03

DATE : 9/5/2026

PART NAME : BEARING CAP G.E. (SemiFinish)

QTY : 100

REV. LEVEL : 03

CH.NO

SR NO	Product Specification	Specification	Measurement Techniques	Supplier Observations					
				701	712	766	716	819	
1	Flatness	0.04	Filler Gauge	ok	ok	ok	ok	ok	OK
2	Counter Bore	Dia 16.99 +0.038	Air Plug Gauge	ok	ok	ok	ok	ok	
3	Distance for Dia 16.99	102.0 ± 0.03	CMM/Receiving Gauge	ok	ok	ok	ok	ok	
4	Notch Cutter Diameter	63.0-2.0	SPI. Type Gauge	ok	ok	ok	ok	ok	
5	Distance	10.4-0.6/+1.0	Hight Gauge/ spi Type Gauge	10.6	10.6	10.5	10.6	10.5	OK
6	Notch Depth	17 85-3.5	Hight Gauge	16.9	16.8	16.4	16.9	16.8	OK
7	Notch Width	6.00 ± 0.1	Width Gauge	ok	ok	ok	ok	ok	
8	Notch Distance	11.4 ± 0.1	Height Gauge/ spi Type Gauge	11.45	11.44	11.45	11.45	11.45	OK
9	Milling Distance	16.2 +0.2	Height Gauge	16.24	16.25	16.24	16.24	16.25	OK
10	Total Hight	81.0± 0.2	Hight Gauge	80.91	80.91	80.91	80.91	80.92	OK
11	Parallelism	0.1 w.r.t. A	Comparator Stand	ok	ok	ok	ok	ok	
12	Distance for Dia 15	102.0 ± 0.2	Receiving Gauge	ok	ok	ok	ok	ok	
13	Cast Ref.	86.0 ± 0.5	Hight Gauge	86.14	86.14	86.14	86.13	86.14	OK
14	Diameter	70.0 ± 0.5	Vernier Caliper	70.1	70.11	70.12	70.11	70.12	OK
15	Angle	10°	Receiving Gauge	ok	ok	ok	ok	ok	
16	Depth	9.0+1.0	Vernier Caliper	9.24	9.26	9.24	9.24	9.26	OK
17	Hole I.D.	15.0+0.3	Plug Gauge	ok	ok	ok	ok	ok	
18	Chamfer	0.5± 2*45°	Vernier Caliper	ok	ok	ok	ok	ok	OK
19	Hole Dia	dia3.0	Plug Gauge	ok	ok	ok	ok	ok	
20	Hole Depth	70.8 ± 0.3	Vernier Caliper	70.96	70.96	70.96	70.95	70.96	OK
21	Distance	CL OF *16.99	Receiving Gauge	ok	ok	ok	ok	ok	
22	RZ	25.00	Surface Tester	17.14	16.78	16.14	19.61	16.14	OK
23	Distance	74 ± 0.3	Vernier Caliper	74.11	74.11	74.11	74.12	74.12	OK
24	Perpendicularity	0.20	CMM/Receiving Gauge	ok	ok	ok	ok	ok	
25	visual	free from dent, burr, rust, sharp edges	visual	ok	ok	ok	ok	ok	

Checked By Name & Sign : *[Signature]*

Checked By Name & Sign

Approved By Name & Sign : *[Signature]*

Approved By Name & Sign