

Predespach Inspection Report

Supplier :

Shriram Foundry pvt.Ltd

Doc. No. :

Component Name :

crank pully (s p z single Groove)

Issue No./ Date :

Drawing No. :

02.1047.01.0.002

D.C NO. :

Rev No./ Date : 01/ 19-9-21

Drawing Alt No. :

Rev-03

Date / Qty: 9/57 2026/10/05

Sr. No.	Parameters	Specification	Tolerance	Parameter Class	Measuring Equipment	1	2	3	4	5	Remarks
1	O.D.	65.0	+0.00 / -0.19	M	MICROMETER/S.G.	OK	OK	OK	OK	OK	
2	I.D.	36.0	+0.039	M	PLUG GAUGE	OK	OK	OK	OK	OK	
3	I.D.	8.2	+/- 0.1		PLUG GAUGE	OK	OK	OK	OK	OK	
4	DEPTH	18.0			VERNIER CALIPER	18.11	18.11	18.12	18.12	18.11	
5	SURFACE FINISH	RZ 1 TO 4			ROUGHNESS TESTER	2.412	1.462	2.162	2.188	2.164	
6	DISTANCE	92.0			HT. GAUGE	92.41	92.41	92.41	92.45	92.45	
7	GROOVE C.D.	102.0	+/- 0.15	M	HT. GAUGE	102.06	102.06	102.06	102.06	102.07	
8	DISTANCE	112.00			HT. GAUGE	112.11	112.11	112.12	112.12	112.12	
9	O.D.	177.5	+0.5		VERNIER CALIPER	177.67	177.66	177.66	177.67	177.66	
10	ROLLER DIA.	186.2	-0.5		9 MM PIN & VERNIER	OK	OK	OK	OK	OK	
11	VISUAL DEFECT	NO DENT DAMAGE BLOW HOLES			VISUAL	OK	OK	OK	OK	OK	
12	C.D.	25	+/- 0.050		CMM/C.D GAUGE	OK	OK	OK	OK	OK	
13	BALANCING	< 40GM			BALANCING M/C	8	16	14	15	19	
14	V.GROOVE RUN OUT	< 0.2			R/O MANDRILL	0.04	0.03	0.04	0.05	0.04	
15	RUNOUT	0.05			R/O MANDRILL	0.02	0.02	0.03	0.02	0.03	
16	Angle	35° 10'			CMM/C.D GAUGE	OK	OK	OK	OK	OK	
17	Angle	36° ± 30'			CMM/Contracer	OK	OK	OK	OK	OK	
18	DIAMETER	45			PLUG GAUGE	OK	OK	OK	OK	OK	
19	DEPTH	14			VERNIER CALIPER	14.11	14.12	14.12	14.13	14.12	
20	OD	64-0.5			VERNIER CALIPER	63.91	63.92	63.91	63.92	63.91	
21	OD Length	28-0.2			HT. GAUGE	28.11	28.11	28.11	28.12	28.12	

Prepared By: *11/11/16*

Reviewed By: *11/11/16*

Approved By: *11/11/16*

Signature

Signature

Signature