

Notes on
Recursive Introduction to the Theory of Computation
by Carl Smith [**carl-smith-1994**]

Kedar Mhaswade

30 June 2026

These notes are dedicated to the memory of Carl Smith (1950-2004).

Reflection 1 (Introduction). These are the author’s highly personal notes based on this book [carl-smith-1994]. They may occasionally sound like author’s conversation with the reader (or even himself). Even if they are personal and appear in the public domain, they may help the reader, although the author isn’t exactly sure how. He wrote them for 0) the love of mathematics and writing 1) $\text{\LaTeX}$ practice (of writing hopefully readable mathematics, albeit longer than appearing in standard texts), and 2) reliable archival (paper, on which most work is created, tends to get lost) that incurs minimal overhead.

These notes are interspersed with “reflection boxes” like this one. They are meant to express author’s ‘rough’ thinking process (mental catharsis of sorts), of which frustration is often an inseparable part. The author writes mostly in first person for an authentic conversational tone.

0.1 Preface

Audience, level, and treatment—a description of such matters is what prefaces are supposed to be about.

— Paul Halmos

I WANT TO BE A MATHEMATICIAN [halmos-iwtbam]

This is a graduate-level textbook that can be covered in one semester. It defines ‘computation’ succinctly:

*Computation is the **movement and transformation of ‘data’ through ‘processors’**, which are understood as expressly designed systems made of well-defined components.*

— Carl Smith

The book describes three “models of computation”, each offering a different perspective. It also describes which functions are *computable* (emphasis mine):

*Given the **firm knowledge of what is and what is not computable**, we move on to consider the complexity of computing the things that are computable.*

— Carl Smith

About ‘recursion’ in the title of the book:

*The title of this book contains the word ‘recursion,’ which has several meanings, many of which are appropriate. The original meaning of the word **recurse** was “a looking back.” Indeed, in this book we look back at the fundamental results that shaped the theory of computation as it is today. The object of study for most of the book is the **partial recursive functions**, functions that derive their name from the way they are defined, using an operator that ‘looks back’ to prior function values. There is also a **recursion theorem**, which enables us to construct programs that can look back on their own code. In this treatment, recursion theorems are introduced relatively early and used often.*

— Carl Smith

Reflection 2. For a while now, I wanted to understand the basic theory of computation better. In particular, I wanted to understand the equivalence between Turing machines and recursive functions as “models of computation.” A cursory glance at the book finally made me commit to doing it along with other things I have committed to.

The textbook is about a fundamental computation itself. It may not be relevant in the age of faulty A.I., but I don’t care. This was overlooked during my previous graduate days, and I wanted to try and fill that gap. There are several excellent books on this topic, but I will take a look at them later. For now, I have this book.

I may not be able to finish it in time, but try I shall.

Chapter 1

Models of Computation

*The first artifact of computation that we will dismiss is the notion that arguments may be of different types. All our inputs, outputs, temporary variables, etc., will be natural numbers (members of $\mathbb{N}$). We will argue informally that **all the other commonly used argument types are included solely for convenience of programming and are not essential to computation.***

— Carl Smith

1.1 Random Access Machines

1.2 Partial Recursive Functions

Base Functions

Not all of these need be ‘functions’, but are defined as such to keep the notation consistent.

$$\begin{array}{ll} \text{(Zero)} & Z(x) = 0 \quad \forall x \\ \text{(Successor)} & S(x) = x + 1 \quad \forall x \\ \text{(Projection or Selection)} & U_j^n(x_1, x_2, \dots, x_j, \dots, x_n) = x_j \end{array} \quad (1.1)$$

Reflection 3 (No Identity Function!). Interestingly, he doesn’t define the identity function, $I(x) = x$, as a base function. However, $I = U_1^1$. His thrust may be on defining more generic (and hence more powerful) functions.

Definition 1 (Functions defined by ‘primitive’ recursion). A function f of $n + 1$ arguments is defined by *primitive recursion* from 1) g , a function of n arguments, and 2) h , a function of $n + 2$ arguments, if and only if for each¹ $x_1, x_2, \dots, x_n$:

$$\begin{aligned} f(x_1, x_2, \dots, x_n, 0) &= g(x_1, x_2, \dots, x_n) \\ f(x_1, x_2, \dots, x_n, y + 1) &= h(x_1, x_2, \dots, x_n, y, f(x_1, x_2, \dots, x_n, y)) \end{aligned} \quad (1.2)$$

For the $n = 0$ case (i.e., functions applied to zero arguments²), we adopt the convention that a function of 0 arguments is a *constant*.

¹I think he means for every sequence of n arguments, $x_1, x_2, \dots, x_n$, not for each argument like x_1 .

²Many programming languages call such functions void.

Box 1.2.1: What is Primitive Recursion?

The recursion of the above definition is ‘primitive’ because the value $f(x_1, x_2, \dots, x_n, y)$ can be determined from the value of $f(x_1, x_2, \dots, x_n, z)$ for some $z < y$ (“looking back”). **Forms of recursion that are not primitive will be discussed extensively later in the book^a.**

^aNon-primitive’ recursive functions? I am curious!

— Carl Smith

Reflection 4 (General vs. Concrete). This definition [1.2] appears too complicated at first. A typical definition of a recursive function usually refers to the hackneyed ‘factorial’ ($\text{factorial} : \mathbb{N} \rightarrow \mathbb{N}$) that is applied to a nonnegative integer:

$$\text{factorial}(x) = \begin{cases} 1, & \text{if } x = 0 \\ x \times \text{factorial}(x - 1), & \text{otherwise} \end{cases}$$

This is typical in formal sciences, especially math and computer science. We tend to *generalize* operations. In time, we become better at finding a *level of generality* that balances flexibility with complexity. In this case, to define f in terms of itself, we also define g and h . To keep them generic, we consider functions with several arguments.

How does one *conceive* a definition such as [1]? I believe they start with some definition and refine it to a sufficient level of generality. Experience may be their guide to judge that level. With functions, their *arguments* and *return values* are all we have. Using that effectively may have also helped such a conception. $f : \mathbb{N}^{n+1} \rightarrow \mathbb{N}$ is defined by cases:

1. If the last argument is 0, f returns what $g : \mathbb{N}^n \rightarrow \mathbb{N}$, applied to the remaining (n) arguments, returns.
2. Otherwise, f returns what $h : \mathbb{N}^{n+2} \rightarrow \mathbb{N}$, applied to the remaining ones (n) and two carefully chosen arguments (that is, a total of $n + 2$ arguments), returns. In this case, the calculation of the last argument to h requires a recursive application of f .

Nonetheless, it feels mysterious at first.

Definition 2 (Functions defined by ‘composition’). A function f of n arguments is defined by *composition* from 1) g , a function of m arguments, and 2) functions $h_1, h_2, \dots, h_m$, each of n arguments, if and only if, for each $x_1, x_2, \dots, x_n$:

$$f(x_1, x_2, \dots, x_n) = g(h_1(x_1, x_2, \dots, x_n), h_2(x_1, x_2, \dots, x_n), \dots, h_m(x_1, x_2, \dots, x_n)) \quad (1.3)$$

The $m = 1$ case yields the traditional composition scheme, e.g., $f(x) = g(h(x))$.

Definition 3 (Class of primitive recursive functions). The class of primitive recursive functions is the smallest class of functions containing all the base functions that is closed under the operations of primitive recursion and composition.

Examples

Reflection 5 (Creating functions from the ‘base functions’). The book provides a definition of a function that adds its two arguments. Starting from the definition [1] and base functions [1.1], I will try to *derive* it here. Let’s denote the function as A which returns an integer when applied to two integer arguments,

x, y .

From equation [1.2], it follows that

$$\begin{aligned} A(x, 0) &= g(x) \\ A(x, y + 1) &= h(x, y, A(x, y)) \end{aligned} \tag{1.4}$$

Since our function A applies to two arguments, **our job is to find definitions of g (applies to one argument) and h (applies to three arguments) so that A returns the sum of its arguments.**

From the first of these equations, it is sufficiently clear that g is the identity function, $g = U_1^1$, which returns its argument when applied to any argument: $g(x) = x$.

If $y \neq 0$, applying A results in at least one more application of A . This process continues until y becomes zero, when applying A results in applying g , which returns the first argument (x). We say that, at that point, the (primitive) recursion ‘bottoms out.’ We can visualize applications of h thus:

$$\begin{array}{c} {}_1 A(x, y) = h(x, y - 1, A(x, y - 1)) \\ \quad | \\ {}_2 h(x, y - 2, A(x, y - 2)) \\ \quad | \\ {}_3 h(x, y - 3, A(x, y - 3)) \\ \quad | \\ \quad \vdots \\ \quad | \\ {}_y h(x, 0, A(x, 0)) = h(x, 0, x) \end{array}$$

Therefore, one application of A to two arguments, x, y , results in y applications of h ; in each application of h , the last argument is decremented. What should h return in general then?

If h returned the successor of its last argument, every application of h simply counts up from x , y times! Therefore, h is just the successor of its last argument: $h(x, y, z) = S(z)$. In general, using our base functions:

$$\begin{aligned} g(x) &= x \\ h(x_1, x_2, x_3) &= S(x_3) \\ A \text{ is now defined by primitive recursion:} \\ A(x_1, 0) &= g(x_1) \\ A(x_1, x_2 + 1) &= h(x_1, x_2, A(x_1, x_2)) \end{aligned} \tag{1.5}$$

Reflection 6 (Defining multiplication, M , by primitive recursion and composition).

$$\begin{aligned} M(x_1, 0) &= g(x_1) \\ M(x_1, x_2 + 1) &= h(x_1, x_2, M(x_1, x_2)) \end{aligned} \tag{1.6}$$

Define g, h .

Since the product of anything and 0 is 0, g is the zero function, which we simply write as 0.

It is similar to addition, but I needed some experimentation. When the recursion bottoms out, M returns what g returns (i.e., 0). If h returns the sum of its first and last arguments, things work out nicely.

Consider $M(2, 3)$:

$$\begin{aligned}
 M(2, 3) &= h(2, 2, M(2, 2)) \\
 &= h(2, 2, h(2, 1, M(2, 1))) \\
 &= h(2, 2, h(2, 1, h(2, 0, M(2, 0)))) \\
 &= h(2, 2, h(2, 1, h(2, 0, 0))) \\
 &= h(2, 2, h(2, 1, 2)) \\
 &= h(2, 2, h(2, 1, 2)) \\
 &= h(2, 2, 4) \\
 &= 6
 \end{aligned} \tag{1.7}$$

Therefore,

$$\begin{aligned}
 g(x) &= 0 \\
 h(x_1, x_2, x_3) &= A(x_1, x_3) \quad \text{See equation [1.5]} \\
 M \text{ is now defined by primitive recursion:} & \tag{1.8} \\
 M(x_1, 0) &= 0 \\
 M(x_1, x_2 + 1) &= h(x_1, x_2, M(x_1, x_2))
 \end{aligned}$$

Indeed, one can start mechanically^a to define new functions from simple, yet general (and hence powerful) base functions (See equation [1.1]), primitive recursion (See definition [1]), and composition (See definition [2])!

^aSome creativity is also needed.

We can now define a very large class of functions. This class is large enough to include all the functions that we can actually compute today. In fact, all the functions we are likely to ever be able to compute are included in the class of primitive recursive functions (which is closed under primitive recursion and composition).

— Carl Smith

Reflection 7 (The predecessor function). We already have a successor function, S (See equation [1.1]). Let's define a predecessor function, PR . The only peculiarity is that the predecessor of any number less than or equal to 0 is 0. Such subtraction where a negative number is *never* produced is called “proper subtraction”.

We start with primitive recursion: PR is applied to one argument, therefore, $n = 0$, i.e., g is a ‘constant’ (applies to 0 arguments) and h applies to 2 arguments:

$$\begin{aligned}
 PR(0) &= 0 \\
 PR(x + 1) &= h(x, PR(x))
 \end{aligned} \tag{1.9}$$

Our task is the same: Define h .

Applying P to a familiar number like 2, we get:

$$PR(2) = h(1, PR(1)) = h(1, h(0, PR(0))) = h(1, h(0, 0))$$

This should return 1. That means, h should just return the first argument. It just works!

$$PR(2) = h(1, PR(1)) = h(1, h(0, PR(0))) = h(1, h(0, 0)) = h(1, 0) = 1$$

Here is how we define the predecessor function by primitive recursion:

$$\begin{aligned} h(x_1, x_2) &= x_1 \\ PR(0) &= 0 \\ PR(x+1) &= h(x, PR(x)) \end{aligned} \tag{1.10}$$

Functions are great. Their syntax can result in complicated expressions, however. Therefore, the book adopts a more familiar or succinct notation for the remainder of our discussion:

- Since the projection function *selects and returns the j^{th} argument*, we simply make it return x_j , instead of $U_j^n(x_1, x_2, \dots, x_n)$.
- $x + y$ is preferred to $A(x, y)$.
- $x \times y$ is preferred to $M(x, y)$.
- Proper subtraction (the one that never produces a negative number) is shown by the $\dot{-}$ symbol³: $x \dot{-} y$.

A few functions useful for testing conditions are defined next. However, the author does not provide English names for them⁴. I'll reuse his notation for these functions and provide the informal and formal definitions (using primitive recursion) for them.

The logical true function, sg

This function can be used to turn any function into a function with range $\{0, 1\}$. Informally:

$$sg(x) = \begin{cases} 0, & \text{if } x = 0 \\ 1, & \text{otherwise} \end{cases}$$

Formally:

$$\begin{aligned} h_2(x, y) &= S(Z(x)) \\ sg(0) &= 0 \\ sg(x+1) &= h_2(x+1, x+1) \end{aligned} \tag{1.11}$$

Reflection 8. Such formalism is perhaps necessary as a practice. For defining functions by primitive recursion, we define h in terms of *known functions* (which themselves may be defined by base functions, primitive recursion, and composition). We don't use 1 as it is not a previously defined function, but we could easily have done that: $f(x) = S(Z(x))$. In mathematics, we solve new problems by referring to already solved problems.

The logical false function, $\overline{sg}$

This function can also be used to turn any function into a function with range $\{0, 1\}$. Informally:

$$\overline{sg}(x) = \begin{cases} 1, & \text{if } x = 0 \\ 0, & \text{otherwise} \end{cases}$$

Formally:

$$\begin{aligned} h_2(x, y) &= Z(x) \\ \overline{sg}(0) &= S(Z(x)) \\ \overline{sg}(x+1) &= h_2(x+1, x+1) \end{aligned} \tag{1.12}$$

³Macro '\dotdiv' from the mathabx package.

⁴I'll try to name them, hopefully succinctly.

By interpreting 0 as ‘false’ and 1 as ‘true’ a 0, 1-valued function represents a predicate. Logical predicates that can be represented by 0, 1-valued primitive recursive functions are called primitive recursive predicates.

— Carl Smith

Reflection 9 (Other logical operations as primitive recursive functions). I thought of defining other basic logical operations primitive-recursively. We can of course exploit logical formulas and tautologies.

1. logical not. We can either compose it from the logical true and logical false functions above (See equations [1.11], [1.12]), or we can define it from scratch by primitive recursion.

$$\begin{aligned} \text{not}(x) &= sg(\overline{sg}(x)) \\ \text{Or,} \\ \text{not}(x) &= \overline{sg}(sg(x)) \end{aligned} \tag{1.13}$$

Or,

$$\begin{aligned} h_2(x_1, x_2) &= Z(x_1) \\ \text{And,} \\ \text{not}(0) &= S(Z(x)) \\ \text{not}(x + 1) &= h_2(x, \text{not}(x)) \end{aligned} \tag{1.14}$$

2. logical (inclusive) or. Some experimentation helps us arrive at:

$$\begin{aligned} g(x) &= sg(x) \\ h_3(x_1, x_2, x_3) &= S(Z(x_1)) \quad (\text{Basically 1}) \\ \text{And,} \\ \text{or}(x_1, 0) &= g(x_1) \\ \text{or}(x_1, x_2 + 1) &= h_3(x_1, x_2, \text{or}(x_1, x_2)) \end{aligned} \tag{1.15}$$

3. logical and.

$$\begin{aligned} g(x) &= Z(x) \\ h_3(x_1, x_2, x_3) &= sg(x_1) \\ \text{And,} \\ \text{and}(x_1, 0) &= g(x_1) \\ \text{and}(x_1, x_2 + 1) &= h_3(x_1, x_2, \text{and}(x_1, x_2)) \end{aligned} \tag{1.16}$$

4. logical xor.

5. logical (material) implication.

The proper subtraction function, $\dot{-}$

We denote this⁵ by $\text{PSUB}(x_1, x_2)$, but adopt the more symbolic $x_1 \dot{-} x_2$, just like we adopt $x_1 + x_2$ instead of $A(x_1, x_2)$ for the sum function.

Informally,

$$x_1 \dot{-} x_2 = \begin{cases} x_1 - x_2, & \text{if } x_1 \geq x_2 \\ 0, & \text{otherwise} \end{cases}$$

Some experimentation shows that once the third argument of the h_3 function becomes zero (through recursion), it should stay 0. This suggests:

⁵Read ‘ x_1 dot-minus x_2 ’.

$$\begin{aligned}
g(x) &= x \\
h_3(x_1, x_2, x_3) &= PR(x_3) \quad (\text{See reflection[7]}) \\
\text{And,} \\
x_1 \dot{-} 0 &= g(x_1) \\
x_1 \dot{-} (x_2 + 1) &= h_3(x_1, x_2, (x_1 \dot{-} x_2))
\end{aligned} \tag{1.17}$$

The difference function, $|x_1 - x_2|$

We denote it by $\text{DIFF}(x_1, x_2)$, but adopt the symbolic notation, $|x_1 - x_2|$.

Informally,

$$|x_1 - x_2| = \begin{cases} x_1 - x_2, & \text{if } x_1 \geq x_2 \\ x_2 - x_1, & \text{otherwise} \end{cases}$$

There are similarities between DIFF and PSUB (See [1.2]). This yields another informal definition of DIFF :

$$|x_1 - x_2| = (x_1 \dot{-} x_2) + (x_2 \dot{-} x_1)$$

Therefore, we can define DIFF by composition:

$$\text{DIFF}(x_1, x_2) = A(\text{PSUB}(x_1, x_2), \text{PSUB}(x_2, x_1))$$

How can we define it by primitive recursion (See definition [1])?

TBD

The logical equality function, ϵ

Informally,

$$\epsilon(x_1, x_2) = \begin{cases} 1, & \text{if } |x_1 - x_2| = 0 \\ 0, & \text{otherwise} \end{cases}$$

By composition, $\epsilon(x_1, x_2) = \overline{sg}(|x_1 - x_2|)$.

By primitive recursion (some experimentation helps; h_3 should return 1, when $x_1 - x_2 = 1$ and 0 otherwise),

$$\begin{aligned}
g(x) &= \text{not}(x) \quad \text{See equation [1.14]} \\
h_3(x_1, x_2, x_3) &= \overline{sg}(x_1 - x_2 - 1) \\
\text{And,} \\
\epsilon(x_1, 0) &= g(x_1) \\
\epsilon(x_1, x_2 + 1) &= h_3(x_1, x_2, \epsilon(x_1, x_2))
\end{aligned} \tag{1.18}$$

The logical inequality function, $\bar{\epsilon}$

Informally, $\bar{\epsilon}(x_1, x_2) = \text{not}(\epsilon(x_1, x_2))$.

Exercise 1.1 (The ‘rm’ function is primitive recursive). Show that $rm(x, y) =$ ‘The remainder left after dividing x by y ’ is primitive recursive.

Solution. The division algorithm states that for any two integers (for now, we consider nonnegative integers), $x, y (y \neq 0)$, there exist two integers, q, r , such that $x = by + r \mid 0 \leq r < y$.

We need to define a function $rm(x, y)$ by primitive recursion. It’s a partial function. It is not defined for $y = 0$.

$$\begin{aligned}
rm(0, y) &= 0 \\
rm(x + 1, y) &= h(x, y, rm(x, y))
\end{aligned} \tag{1.19}$$

In this case, we don't need g , or, if we need it, then it is the zero function, Z (See equation [1.1]): rm returns 0 when x is 0. We adopt the simpler syntax.

Small examples help. When the first argument of rm is nonzero, rm will be called recursively, every time with predecessor of the first argument; recursion eventually bottoms out when it becomes zero:

$$rm(3, 2) = h(2, 2, rm(2, 2)) = h(2, 2, h(1, 2, rm(1, 2))) = h(2, 2, h(1, 2, h(0, 2, rm(0, 2)))) = h(2, 2, h(1, 2, h(0, 2, 0)))$$

It becomes clear that $h(x, y, z)$ returns what $rm(z + 1, y)$ returns.

This gives the recursive definition as:

$$\begin{aligned} rm(0, y) &= 0 \\ rm(x + 1, y) &= rm(rm(x, y) + 1, y) \end{aligned} \tag{1.20}$$

The textbook answer (which uses S for the successor function and M for the multiplication function) has a different answer. I will explore more:

$$\begin{aligned} rm(0, y) &= 0 \\ rm(x + 1, y) &= h(x, y, rm(x, y)) \\ &= M(S(rm(x, y)), \bar{e}(S(rm(x, y)), y)) \end{aligned} \tag{1.21}$$

Is my answer (equation [1.20]) wrong? I hope not, although it does not follow *the form* of the primitive recursive functions (See definition [1]), but neither does the textbook answer (See equation [1.21]). My definition does make rm primitive recursive because the function is defined in terms of itself, allowing recursion.

Exercise 1.2 (The ‘integer division’ is primitive recursive). *Show that integer division is primitive recursive. Make and state a convention about division by 0.*

Solution.

Let's denote it by: /

Reflection 10. I took inspiration from JavaScript, which defines anything divided by 0 to be a special literal, NaN, which is not a real number.

$$\begin{aligned} g(x) &= \text{NaN} \\ h_3(x_1, x_2, x_3) &= ?? \\ \text{And,} \\ x_1 / 0 &= g(x_1) \\ x_1 / (x_2 + 1) &= h_3(x_1, x_2, x_1 / x_2) \end{aligned} \tag{1.22}$$

Reflection 11. This is tricky! I feel stuck. $h_3(x_1, x_2, x_3) = 0$ if $x_1 \leq x_2$, but otherwise I am not sure yet.

After a while, I reminded myself of the grade-school maxim, “Division is repeated subtraction.” Then there was a ray of hope, although it renders a recursive definition for h_3 . Is that okay?

$$h_3(x_1, x_2, x_3) = \begin{cases} 1 + h_3(x_1 - x_2, x_2, x_3), & \text{if } x_1 \geq x_2 \\ 0, & \text{otherwise} \end{cases}$$

That feels convoluted. The function we seek is defined by cases thus:

$$x_1 / x_2 = \begin{cases} \text{NaN}, & \text{if } x_2 = 0, \\ 0, & \text{else if } x_1 < x_2, \\ 1 + (x_1 - x_2) / x_2 & \text{otherwise} \end{cases} \tag{1.23}$$

Reflection 12. According to the definition [1], equation [1.23] may not be primitive recursive, but according to the box [1.2] (and like the factorial function (See reflection [4])), it is.

The book does not provide a solution to this problem; I'll need to ask someone to check.

That raises another question: Are functions, like equation [1.23], that clearly set up recurrence, *not* defined by primitive recursion?

TBD

Exercise 1.3 ($\lfloor \sqrt{x} \rfloor$). Show that $f(x) = \text{'The largest integer less than or equal to } \sqrt{x} \text{'}$ is primitive recursive.

Proof. Let me first write down the *skeleton*. We don't need g because $f(0)$ is just 0. We may also do $g(x) = Z(x) = 0$:

$$h_2(x_1, x_2) = ??$$

And,

$$f(0) = Z(x) \tag{1.24}$$

$$f(x_1 + 1) = h_2(x_1, f(x_1))$$

We need to define h_2 .

Reflection 13. Hmm. Tricky again! The floor function is introduced because $\sqrt{x}$ may not be integral or rational; flooring converts the argument into an integer. But the h_2 function seems elusive.

Reflection 14 (Patience is key, but ...). The definition of h_2 is still elusive...

I made a table of applications of h_2 to small arguments. That helps!

Table 1.1: Applications of f, h_2 to a Few Small Arguments. What is h_2 ?

f	h_2	h_2 Simplified	h_2 Return
$f(9)$	$h_2(\sqrt{9}, \lfloor \sqrt{9} \rfloor)$	$h_2(3, 3)$	3
$f(8)$	$h_2(\sqrt{8}, \lfloor \sqrt{8} \rfloor)$	$h_2(2.82, 2)$	2
$f(7)$	$h_2(\sqrt{7}, \lfloor \sqrt{7} \rfloor)$	$h_2(2.64, 2)$	2
$f(6)$	$h_2(\sqrt{6}, \lfloor \sqrt{6} \rfloor)$	$h_2(2.44, 2)$	2
$f(5)$	$h_2(\sqrt{5}, \lfloor \sqrt{5} \rfloor)$	$h_2(2.23, 2)$	2
$f(4)$	$h_2(\sqrt{4}, \lfloor \sqrt{4} \rfloor)$	$h_2(2, 2)$	2
$f(3)$	$h_2(\sqrt{3}, \lfloor \sqrt{3} \rfloor)$	$h_2(1.73, 1)$	2
$f(2)$	$h_2(\sqrt{2}, \lfloor \sqrt{2} \rfloor)$	$h_2(1.41, 1)$	1
$f(1)$	$h_2(\sqrt{1}, \lfloor \sqrt{1} \rfloor)$	$h_2(1, 1)$	1
$f(0)$	$h_2(\sqrt{0}, \lfloor \sqrt{0} \rfloor)$	$h_2(1, 0)$	1
$f(0)$	NA	NA	NA, f returns 0

Initially, I guessed it incorrectly. But then, something struck me. I observed that $h_2(x_1, x_2)$ is a step function returning x_2 , stepping up to $x_2 + 1$ only when its first argument is the square root of a number one less than a perfect square (e.g., $\sqrt{8}, \sqrt{3}$), and its second argument is always an integer. Here is an attempt to define it:

$$h_2(x_1, x_2) = \begin{cases} x_2, & \text{if } (x_2 + 1)^2 - (x_1)^2 > 1 \\ x_2 + 1, & \text{otherwise} \end{cases} \tag{1.25}$$

This appears to work. And we know how to convert such functions into boolean functions (using $sg, \overline{sg}$).

We assume a function, sq , which squares its argument: $sq(x) = x \times x$. Since multiplication is primitive recursive, sq is so too.

$$\begin{aligned} h_2(x_1, x_2) &= x_2 + \overline{sg}(sq(x_2) - sq(x_1) - 1) \\ \text{And,} \\ f(0) &= Z(x) \\ f(x_1 + 1) &= h_2(x_1, f(x_1)) \end{aligned} \tag{1.26}$$

Therefore, $f(x)$ = ‘The largest integer less than or equal to $\sqrt{x}$ ’ is primitive recursive. ■

Exercise 1.4. Suppose that f is primitive recursive.

Show that

$$\sum_{y \leq z} f(x_1, x_2, \dots, y) = f(x_1, x_2, \dots, 0) + \dots + f(x_1, x_2, \dots, z) \tag{1.27}$$

is primitive recursive.

Reflection 15 (Notational Fastidiousness ...). Equation [1.27] is fine, but I will employ a more standard notation:

$$\sum_{y=0}^z f(x_1, x_2, \dots, y) = f(x_1, x_2, \dots, 0) + \dots + f(x_1, x_2, \dots, z) \tag{1.28}$$

We are asked to prove that a function that returns a finite sum of applying a primitive recursive function to various arguments is also primitive recursive.

Informally, since $f, +$ are primitive recursive, by definition, $f_2(x_1) = f(x_1, 0) + f(x_1, 1)$ is primitive recursive, but we have to prove it rigorously.

Proof. ■