NEEDLE: A Live Benchmark of Web Search APIs for AI Agents

Ilya Gusev **Matthias Petri** **Andrey Styskin**
Keenable
{ilya.gusev,matthias,andrey}@keenable.ai

Abstract

AI agents rely on web search APIs, yet no public benchmark tracks how well these APIs retrieve, and a fixed query set goes stale or gets tuned against. We present NEEDLE, an open-source benchmark that builds fresh queries and gold from public sources on every run (one fixed stream excepted), and a measurement study of the 26 search API configurations it has run. Queries come hourly from news feeds and daily from seven public registries and archives. Deterministic matchers or an LLM judge score each result without annotators, and an engine's score is its share of a ceiling pooled from all configurations. On the 13 days when all 21 non-variant engines ran (13.1k query-runs), shares span 14–73% and paired tests separate 183 of 210 engine pairs after Bonferroni adjustment. Over 30 days of scholar runs, 22 of 26 configurations find a paper from its title (recall@10 .71–.98) but spread from .08 to .72 when the query names a detail from its body. Keenable, the authors' engine, led all eight weeks, yet on the one day of runs after we froze the rules, Perplexity edged past it. Blinded LLM raters from three vendors agree with one another at κ .90–.94 and with the judge at .77–.79; no human audited the scorers. The evidence supports choosing a search API by bench and by pairwise tests, not by rank. Code, data and dashboard: https://keenableai.github.io/needle.

1 Introduction

An agent that searches for a detail from the body of a recent paper, such as the phrase "gap rent regularity", can read the paper only if its search API returns it. From 29 September to 28 October 2026, our engine, Keenable, put the paper in its top ten for 72% of such body-keyword queries and ChatGPT search for 8%. Yet both found papers from their titles more than 80% of the time (Figure 1a). Public evidence for choosing between such APIs is thin. IR test collections target document rankers over fixed corpora, and their labels age ("Fed rate decision" changes every six weeks). Agent benchmarks such as BrowseComp score the whole agent, so a weak retriever hides behind a strong model.

NEEDLE measures the search API alone, on five benches (Figure 2). Its unit of evaluation is one search request (retried on errors): a query in, up to k results out, scored on the title, URL and snippet the agent would see. Every run generates fresh queries and gold from public sources, so no fixed test set accumulates (the rare bench and registry facts excepted; Limitations). Where the gold has a canonical identity, such as an arXiv id, a reporter citation or a 10-Q figure, a deterministic matcher checks the results. Where relevance is graded, as for news, an LLM judge rates each result. Each engine's score is a share of a ceiling pooled from all configurations. Scores rest on snippets and, for two benches, on one judge; we audit both with LLMs, not humans (Limitations). We contribute:

- A benchmark that regenerates queries and gold on every run and scores them without annotators. On its two judged benches, blinded LLM raters from three vendors agree with the judge at κ .77–.79 on 1,200 results (§3, Appendix G).
- A normalization by a pooled ceiling that no single engine drives: scoring each engine against a ceiling pooled without it moves its overall share by at most 0.7 points (§3).
- Public results for 26 configurations: over 13 days, overall shares span 14–73% (Table 1), and body-keyword queries separate engines that title queries do not (Figure 1).

The combination is new; each scoring ingredient follows prior work (§4).

2 The Benchmark

Figure 2 shows the five benches. A *configuration* is one search API at one setting: we test 26, from 20 vendors, five of them variants such as a vendor's




Figure 1: Most engines find a paper from its title but spread apart when the query names a detail from its body (a), and Keenable leads every week while the ranks below it shift (b). (a) Scholar recall@10 per query bucket, 31 runs from 29 September to 28 October 2026, 2,600–3,005 query-runs per line and bucket; lines: the seven engines of (b); grey dots: the other 19 configurations; dashed: the pooled ceiling. (b) Overall share per ISO week, 31 August to 25 October 2026; ChatGPT and Claude search start on 14 September; the pool grew from 18 to 25 configurations. Points: query-weighted means; vertical lines: 95% run-level bootstrap intervals. Failures count as in Table 1, except in runs before 17 October whose per-query records we did not fetch (Appendix A).

fast or realtime mode. We call a configuration under evaluation an *engine*. A query issued in one run is a *query-run*.

2.1 Query generation

News. Each hour an LLM writes a terse query on the specific event of the newest item from each of 124 feeds and of the Google Trends RSS for 52 US geographies, and refuses evergreen items. Each run samples 20 queries round-robin over topics. **Finance.** Queries ask for registry facts such as a CEO or a ticker (Wikidata, GLEIF), quarterly 10-Q line items (SEC XBRL) or a filing by description. **Scholar.** Each paper yields a *title* query with case and punctuation stripped; a *body keyword* query on a detail absent from title and abstract; a *body question* that asks for the same fact in prose; and a *tip-of-tongue* description with every name and exact value banned. A paper enters only if all four queries pass, so the buckets are paired. **Legal.** Recent opinions from 14 federal courts yield one caption-style query each; the gold is the citation, docket number and CourtListener id. Sections of the Code of Federal Regulations (CFR) yield an LLM query built on one verbatim span of two to eight words, quoted in one variant in four; a query that leaks the citation is rejected (Appendix D). **Rare.** English agent queries from a public stream that contain a word WordPiece splits into five or more pieces. **Operators.** Agent queries often carry operators (Meng et al., 2026; Pezzuti et al., 2026), so at least half of the legal queries and of the finance money and filing queries carry a quoted phrase, `site:`, `after:` or `before:`. The search layer maps each operator to the engine's native filter where one exists (Appendix C).

2.2 Scoring

Graded relevance with a pooled ceiling. For news and rare queries an LLM judge (GPT-6 at temperature 0) sees today's date, the query, a precomputed per-query profile (Appendix B) and one result (title, URL, date, snippet). The judge outputs a 0–4 rating adapted from the Needs Met scale of Google's rater guidelines (Google, 2025), with gates for entity, coverage, freshness and literal operator compliance. Gains are $\{4:1, 3:0.667, 2:0.117, 1:0, 0:0\}$, top-heavy after ERR (Chapelle et al., 2009), and a repeated URL scores zero (Clarke et al., 2008) except on `site:` queries. The judge rates each distinct result once, and every snippet is capped at 2,000 characters. The *ceiling* of a query keeps the best rating per deduplicated URL over every configuration that ran, variants included, sorted by rating; an engine's nDCG@5 takes the ceiling's list as the ideal. A judged query on which no configuration reaches a rating of 2 is dropped; finance, scholar and legal keep every query (Appendices E and G).

Identifier and answer matching. Scholar and legal scan result URLs and snippets for arXiv ids, DOIs, PMIDs, reporter citations, docket numbers and CFR citations. Recall@k is the fraction of queries whose top-k results carry the gold identity. For caselaw the identity is the case (opinion, docket page or a citing page), so the metric is case-identity




Figure 2: Every run draws its queries, and any gold, from public sources. One search layer sends each query, without its gold, to every configuration; the scorer checks the returned title, URL and snippet against the gold, or the judge rates them.

recall (Appendix G). Finance asks whether the top-k snippets *contain the answer*, within 0.1% for money (table figures and parenthesized losses included) and 15% for headcounts (Appendix F). An LLM backstop may upgrade a rejected non-money result, never revoke a hit. Here the ceiling is a hit by any configuration.

2.3 Aggregation

An engine's *overall share* $S(e)$ is the mean, over the five benches b, of its *bench share* $M_b(e)/M_b(\text{ceiling})$, where M_b is the bench metric. $S(e)$ is a share of the best any configuration found, not of the web. Table 1 uses the 305 runs in which all 21 listed engines took part (one per vendor, two for Brave). All scores use *the paper's scoring rules* (scorer version `paper-2026-10-31`, Appendix A), which we froze at 01:13 UTC on 30 October 2026 and revised in three rules on 31 October. We classify each failure by its error record: a service-side one (rate limit, server error, timeout) scores zero, as it does for an agent, and an account-side one (our own quota, authentication or credit) is excluded; the exclusion removes 35% of Claude search's query-runs (Appendix G). Intervals are 95% bootstraps over runs.

3 Results

The judge agrees with LLM raters, and the ceiling is stable. Blinded LLM raters from three vendors (two Claude Opus 5.5 sessions, Gemini 4, Grok 4.7) graded 1,200 judged results from the snippet and the first 3,000 characters of the page. They agree with one another at quadratic-weighted κ .90–.94 and with the judge at .77–.79 (Appendix G). On every result of 100 queries, graded from snippets only, Gemini and Grok rank the 21 engines at Spearman .94 with the judge (95% intervals .89–.97 and .87–.96). These checks show agreement between models, not correctness. Scoring each engine against a ceiling pooled without it moves its overall share by at most 0.7 points.

Shares span 14–73%, and most engine pairs differ. Ceramic is lowest and Keenable highest (Table 1). A run-resampled paired test separates 194 of the 210 engine pairs at 95% and 183 after a Bonferroni adjustment; 177 stay separated under day-level resampling and matched support (Appendix G). After adjustment only Keenable and Ceramic are separated from every other engine; the unseparated pairs form chains of neighbors, such as Exa to Brave (LLM ctx). The lead depends on how the benches are weighted: scholar carries 3.7 of Keenable's 4.6-point lead over Exa, and without scholar the lead is 1.1 points (Appendix G).

Body-keyword queries separate engines that title queries do not. From 29 September to 28 October, 22 of the 26 configurations find a paper from its title (recall@10 .71–.98; Figure 1a, Table 12). On body-keyword queries the same 22 spread from .08 (ChatGPT search) to .72 (Keenable), followed by Keenable's realtime variant (.71) and Kagi (.67).

The leader holds week to week; the ranks below it shift. Over eight weeks, adjacent weekly rankings agree at Kendall's τ_b .81–.92 (1 means the same order), and Keenable leads every week (Figure 1b). Below it, Perplexity passes Parallel from 28 September and Claude search falls by about 10 points; neither the growing pool nor Claude search's credit lapse drives these moves (Appendix G). On the one day of runs dispatched after the freeze, Perplexity leads Keenable 72.4 to 71.3 through one scholar and one legal run, each within its bench's run-to-run spread (Appendix G).

A `site:` restriction lowers caselaw recall. In one paired run on 30 October, outside Table 1, adding `site:courtlistener.com` to the same 80 caselaw captions lowers mean recall@5 by .36, from .85. Fourteen of 18 engines lose beyond their 95% intervals (Appendix H). Re-

Engine	Overall share, %		Scholar	News	Finance	Rare	Legal	Failed requests, %		Latency
	mean	95% CI	R@10	nDCG@5	R@5	nDCG@5	R@5	service	account	p_{50}, ms
ceiling (pooled)	*100*		*.901*	*1*	*.993*	*1*	*.974*			
Keenable†	73.0	72.1–73.7	**.731**	.612	.898	**.504**	**.796**	0.0	–	135
Exa	68.4	67.3–69.4	.563	.609	**.915**	.472	.771	0.0	1.9	2,098
Perplexity	66.6	65.1–68.1	.578	**.643**	.886	.463	.673	0.0	–	517
Parallel	65.1	64.0–66.2	.587	.553	.901	.386	.739	0.0	0.8	2,588
Brave (LLM ctx)	64.2	63.2–65.1	.533	.640	.847	.449	.658	0.0	–	1,114
Linkup	57.1	55.8–58.4	.470	.566	.789	.397	.563	0.0	–	1,216
Context	57.0	55.4–58.5	.598	.476	.778	.336	.577	0.0	–	891
Brave	57.0	56.0–58.0	.488	.557	.761	.351	.620	0.0	–	488
DeepSeek	56.5	55.4–57.5	.271	.632	.804	.383	.680	0.0	–	553
You.com	55.5	54.5–56.5	.471	.551	.740	.341	.599	0.0	–	486
ChatGPT search‡§	52.1	50.9–53.4	.300	.357	.794	.396	.702	0.1	10.3	43,909
Kagi§	51.9	50.9–52.8	.560	.318	.718	.299	.617	0.0	11.9	1,275
Claude search‡§	50.8	49.3–52.2	.498	.463	.664	.318	.525	0.1	35.0	34,323
Firecrawl	50.4	49.0–51.6	.488	.285	.813	.262	.595	0.0	–	701
Octen	49.9	48.7–51.1	.307	.513	.715	.319	.588	0.0	–	197
Google (Serper)	47.5	46.6–48.4	.475	.261	.735	.252	.577	0.0	–	1,739
Jina	43.6	42.3–44.7	.492	.210	.719	.160	.525	2.5	2.3	17,263
Tavily	42.3	41.3–43.3	.303	.303	.821	.279	.359	0.1	–	1,953
Bing (SearchAPI)	42.1	38.3–45.6	.416	.292	.630	.171	.533	0.3	–	2,008
TinyFish	37.6	36.4–38.7	.122	.255	.728	.219	.523	27.2	–	1,899
Ceramic	14.4	13.7–15.1	.001	.040	.427	.111	.132	0.1	–	98

Table 1: Overall shares of the ceiling span 14–73%; paired tests separate 194 of the 210 engine pairs, 183 after a Bonferroni adjustment and 177 under two further checks (§3). Data: 305 runs, 17–29 October 2026, in which all 21 listed engines ran (13.1k query-runs; Table 4); the ceiling also pools the variants that ran beside them. †The authors' engine. ‡A model's server-side search tool; latency includes answer generation. §Rank depends on excluded account-side failures: scoring them zero or at the ceiling puts Claude search at 33.5–67.8, Kagi at 46.8–57.7 and ChatGPT search at 48.5–56.5 (Appendix G). Bench cells: absolute metric, best in bold; italic: the ceiling. Intervals: 95% run-level bootstraps (sampling uncertainty, not scorer error). Latency: per-run median on news.

stricting to the source host raises recall on SEC filings by .35 and on CFR sections by .25.

These results support choosing a search API by bench and by pairwise tests, not by rank.

4 Related Work

Static test sets leak; live benchmarks regenerate. Static benchmarks leak into training data and get tuned against (Sainz et al., 2023; Balloccu et al., 2024). LiveBench, LiveCodeBench, RealTime QA, FreshQA and LiveSearchBench draw new items from dated sources or Wikidata deltas (White et al., 2025; Jain et al., 2025; Kasai et al., 2023; Vu et al., 2024; Zhou et al., 2025); they score an answering model, and FreshStack scores retrievers over a fixed corpus (Thakur et al., 2025). NEEDLE borrows the idea of fresh items but evaluates live search APIs.

Agents need the retriever measured alone. BrowseComp, GAIA and AssistantBench measure an agent end to end (Wei et al., 2025; Mialon et al., 2024; Yoran et al., 2024). BrowseComp-Plus freezes a corpus to separate retriever from agent (Chen et al., 2026). The closest API study swaps three providers under one agent on a static set (Selvam and Ghosh, 2026), and web search audits and overlap studies compare engines at a few points in time on fixed queries (Lewandowski, 2015; Bevendorff et al., 2024; Kirsten et al., 2026; Yagci et al., 2022). NEEDLE instead scores 26 configurations alone, on queries regenerated every run.

LLM judges work at the system level, with known failure modes. LLM assessors reproduce system rankings at TREC scale (Thomas et al., 2024; Upadhyay et al., 2024b,a; Arabzadeh and Clarke, 2025), so NEEDLE reports engine-level means only; the Limitations discuss the known risks (Clarke and Dietz, 2024; Balog et al., 2025; Alaofi et al., 2024; Soboroff, 2025; Faggioli et al., 2023).

Known-item gold is free, and synthetic queries can rank systems. Simulated known-item queries date to Azzopardi et al. (2007), and LLM-elicited tip-of-tongue queries (Arguello et al., 2021) rank systems like real ones (He et al., 2025). NEEDLE generates queries from documents, as Doc2query, InPars and Promptagator do (Nogueira et al., 2019; Bonifacio et al., 2022; Dai et al., 2023), but adds leak filters. Citation graphs give annotation-free gold for caselaw (Hou et al., 2025), and full text beats abstracts for retrieval (Lin, 2009); the scholar buckets measure that gap live.

Limitations

Conflict of interest. The authors build Keenable, which leads Table 1 but not the one day of runs after the freeze (§3). Everything that produces the numbers is public: the generator code, the judge prompts, the engine clients, every per-query result with the judge's reasoning, and the workflow that runs the benches. Keenable receives the same snippet cap, the same request pacing and the same judge as every other engine. No engine-specific client changed during the Table 1 window (17–29 October); Appendix A lists the shared code changes inside it. We froze the paper's scoring rules after the finance audits that informed the matcher and before the finance validation samples and the blinded raters, and on 31 October, after the post-freeze day, changed three of them to match production (Appendix A). A repository pull request (PR #82) moves production to the paper's scoring rules; dashboard runs scored before that change keep the earlier rules of Table 3, so their numbers and the paper's are not directly comparable. The benchmark cannot tell whether any vendor, Keenable included, changed its index for the benchmark or as ordinary development. Readers should treat the ranking as a claim to audit; the artifacts exist so that they can.

Snippet-only evidence. The judge and the matchers see what the API returned, not the page. That view is what an agent sees before it fetches, and it keeps engines comparable, but it can understate engines whose snippets are terse, and known-item recall misses a target whose URL and snippet lack the gold. Snippet labels can diverge from full-text labels (Kazai et al., 2022), though judging what the reader sees has its own case (Turpin et al., 2009), and LLM judgments from short text track full-text judgments well (Mohtadi et al., 2026). The ceiling inherits the same limit. Engines return snippets of their own length up to the cap, and we treat that length as part of what the news bench measures, since an agent reads the snippet it receives. Appendix G reports the order under an equal snippet budget and checks that known-item hits are the target page.

The LLM judge. News and rare scores depend on one judge model and one prompt. The checks of §3 use LLM raters, not humans. The raters who saw page text read only its first 3,000 characters, with the snippet in the same prompt, and every rater shares the literal-quote rule with the judge, so the checks bound judge noise but cannot rule out blind spots the models share. Query terms in a snippet can fool LLM judges (Alaofi et al., 2024). LLM judges also favor engines built on a similar LLM (Clarke and Dietz, 2024; Balog et al., 2025; Panickssery et al., 2024) and cap measured quality at their own competence (Soboroff, 2025). The judge shares a vendor with ChatGPT search, and the second judge of Appendix G shares one with Claude search. Scholar and legal scores use no LLM, and finance uses one only as a backstop on non-money fields (§2.2), so a judge error reaches the overall share mainly through news and rare.

Finance matcher. Finance recall depends on how the matcher reads money values. Table 1 uses the tighter matcher of §2.2, not the 2% band and money backstop of earlier dashboard runs (Table 3); Appendix F gives the audits behind the change. The tighter matcher's reading of unit-less table figures cannot tell which period an unlabeled column belongs to, so it can credit a figure for the wrong quarter. Except for the fresh-window audit of that reading, the audits pool engines and so cannot show whether error rates differ by engine. False hits and missed answers need not cancel; Appendix F audits each rule and bounds the effect on every engine.

Coverage and weighting. Queries are English and US-centric (US geographies for trends, US courts and regulations, SEC filers); other languages are unmeasured. The equal weight of the five benches in the overall share is a convention, not an estimate of agent traffic, and Keenable's lead depends on that weighting (§3). Table 1 gives the bench columns for any other weighting, and Table 11 collects the main alternative views of the order. The news bench samples 20 queries per hour, so single runs are noisy; read them through windowed means. Engines run with default settings and a paid key, one configuration per vendor (two for Brave) in Table 1; a vendor's best tier may differ. ChatGPT and Claude search are server-side search tools that retrieve and then generate; we score the sources they return, so they are comparable on quality but not on latency or cost.

Reproducibility. We archive every query, gold value, result and judgment with the judge model and engine list of its run, so anyone can recompute every table from the stored ratings. We did not archive the published dates the APIs returned or stamp runs with their code revision, so a rerun of

the judge only approximates the original judgments (Appendix G). The next release will stamp each run with its commit.

Gaming and repetition. Query texts can recur across runs on any bench: registry facts by design, and rare queries because we sample them from a fixed artifact. These repeats are learnable in principle; Appendix G counts them per bench. The news feeds are public, so a vendor could crawl them ahead of the hourly run. A vendor that indexes the sources faster is simply fresher, which is what the news bench measures. The benchmark would not catch a vendor that detected benchmark traffic and answered it differently, and snippets stuffed with query terms would raise judged scores (Alaofi et al., 2024). The per-query artifacts let readers check for either.

Dispatch, vendor changes and failures. The comparison is live but not synchronized: each engine works through the query list in turn, so slow engines see the web later than fast ones. Appendix A measures the lag and its effect; a synchronized dispatcher is future work. Vendor response formats change without notice. After the window, Google (through Serper) and Jina began to return redirect links instead of result URLs. The URL-based matchers score these links as misses, so both engines score lower in later runs until the clients resolve the redirects (Appendix A). Excluding account-side failures assumes that an engine would have scored on the failed requests as on the rest; without that assumption the ranks of ChatGPT search, Claude search and Kagi are not determined, and Appendix G reports their bounds and the order under matched support. A reader of the dashboard sees ranks first; the dashboard will carry these notes beside them.

Ceiling as normalizer. The ceiling is the best any evaluated configuration found, not the best that exists. Adding a strong engine raises the ceiling and lowers every share, so shares are best compared within one window. Unlike a TREC pool, every returned result is judged, so no engine loses credit for unjudged documents (Buckley et al., 2007); the pool only sets the normalizer, and §3 bounds how far an engine's own results raise the ceiling it is scored against (Webber and Park, 2009).

References

Marwah Alaofi, Paul Thomas, Falk Scholer, and Mark Sanderson. 2024. LLMs can be fooled into labelling a document as relevant. In *Proceedings of the 2024 Annual International ACM SIGIR Conference on Research and Development in Information Retrieval in the Asia Pacific Region (SIGIR-AP)*.

Negar Arabzadeh and Charles L. A. Clarke. 2025. Benchmarking LLM-based relevance judgment methods. In *Proceedings of the 48th International ACM SIGIR Conference on Research and Development in Information Retrieval*.

Jaime Arguello, Adam Ferguson, Emery Fine, Bhaskar Mitra, Hamed Zamani, and Fernando Diaz. 2021. Tip of the tongue known-item retrieval: A case study in movie identification. In *Proceedings of the 2021 ACM SIGIR Conference on Human Information Interaction and Retrieval (CHIIR)*.

Leif Azzopardi, Maarten de Rijke, and Krisztian Balog. 2007. Building simulated queries for known-item topics: An analysis using six European languages. In *Proceedings of the 30th Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 455–462.

Simone Balloccu, Patrícia Schmidtová, Mateusz Lango, and Ondřej Dušek. 2024. Leak, cheat, repeat: Data contamination and evaluation malpractices in closed-source LLMs. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*.

Krisztian Balog, Donald Metzler, and Zhen Qin. 2025. Rankers, judges, and assistants: Towards understanding the interplay of LLMs in information retrieval evaluation. In *Proceedings of the 48th International ACM SIGIR Conference on Research and Development in Information Retrieval*.

Janek Bevendorff, Matti Wiegmann, Martin Potthast, and Benno Stein. 2024. Is Google getting worse? A longitudinal investigation of SEO spam in search engines. In *Advances in Information Retrieval (ECIR 2024)*. Springer.

Luiz Bonifacio, Hugo Abonizio, Marzieh Fadaee, and Rodrigo Nogueira. 2022. InPars: Unsupervised dataset generation for information retrieval. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 2387–2392.

Chris Buckley, Darrin Dimmick, Ian Soboroff, and Ellen M. Voorhees. 2007. Bias and the limits of pooling for large collections. *Information Retrieval*, 10(6):491–508.

Olivier Chapelle, Donald Metzler, Ya Zhang, and Pierre Grinspan. 2009. Expected reciprocal rank for graded relevance. In *Proceedings of the 18th ACM Conference on Information and Knowledge Management (CIKM)*, pages 621–630.

Zijian Chen, Xueguang Ma, Shengyao Zhuang, Ping Nie, Kai Zou, Sahel Sharifymoghaddam, et al. 2026. BrowseComp-Plus: A fair and disentangled evaluation benchmark for deep search agents. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 22349–22370.

Charles L. A. Clarke and Laura Dietz. 2024. LLM-based relevance assessment still can't replace human relevance assessment. *Preprint*, arXiv:2412.17156.

Charles L. A. Clarke, Maheedhar Kolla, Gordon V. Cormack, Olga Vechtomova, Azin Ashkan, Stefan Büttcher, et al. 2008. Novelty and diversity in information retrieval evaluation. In *Proceedings of the 31st Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 659–666.

Zhuyun Dai, Vincent Y. Zhao, Ji Ma, Yi Luan, Jianmo Ni, Jing Lu, et al. 2023. Promptagator: Few-shot dense retrieval from 8 examples. In *International Conference on Learning Representations (ICLR)*.

Guglielmo Faggioli, Laura Dietz, Charles L. A. Clarke, Gianluca Demartini, Matthias Hagen, Claudia Hauff, et al. 2023. Perspectives on large language models for relevance judgment. In *Proceedings of the 2023 ACM SIGIR International Conference on the Theory of Information Retrieval (ICTIR)*.

Google. 2025. *Search Quality Rater Guidelines: General Guidelines*. Version of September 11, 2025.

Yifan He, To Eun Kim, Fernando Diaz, Jaime Arguello, and Bhaskar Mitra. 2025. Tip of the tongue query elicitation for simulated evaluation. In *Proceedings of the 48th International ACM SIGIR Conference on Research and Development in Information Retrieval*.

Abe Bohan Hou, Orion Weller, Guanghui Qin, Eugene Yang, Dawn Lawrie, Nils Holzenberger, et al. 2025. CLERC: A dataset for U.S. legal case retrieval and retrieval-augmented analysis generation. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 7913–7928.

Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, et al. 2025. LiveCodeBench: Holistic and contamination free evaluation of large language models for code. In *International Conference on Learning Representations (ICLR)*.

Jungo Kasai, Keisuke Sakaguchi, Yoichi Takahashi, Ronan Le Bras, Akari Asai, Xinyan Yu, et al. 2023. RealTime QA: What's the answer right now? In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*.

Gabriella Kazai, Bhaskar Mitra, Anlei Dong, Nick Craswell, and Linjun Yang. 2022. Less is less: When are snippets insufficient for human vs machine relevance estimation? In *Advances in Information Retrieval: 44th European Conference on IR Research (ECIR 2022), Part II*, pages 153–162.

Elisabeth Kirsten, Jost Grosse Perdekamp, Qinyuan Wu, Mihir Upadhyay, Krishna P. Gummadi, and Muhammad Bilal Zafar. 2026. Characterizing web search in the age of generative AI. In *Findings of the Association for Computational Linguistics: ACL 2026*, pages 10827–10848.

Dirk Lewandowski. 2015. Evaluating the retrieval effectiveness of web search engines using a representative query sample. *Journal of the Association for Information Science and Technology*.

Zhuofeng Li, Dongfu Jiang, Xueguang Ma, Haoxiang Zhang, Ping Nie, Yuyu Zhang, Kai Zou, Jianwen Xie, Yu Zhang, and Wenhu Chen. 2026. OpenResearcher: A fully open pipeline for long-horizon deep research trajectory synthesis. *Preprint*, arXiv:2603.20278.

Jimmy Lin. 2009. Is searching full text more effective than searching abstracts? *BMC Bioinformatics*, 10:46.

Chuan Meng, Litu Ou, Sean MacAvaney, and Jeff Dalton. 2026. Revisiting text ranking in deep research. In *Proceedings of the 49th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 3006–3016.

Grégoire Mialon, Clémentine Fourrier, Craig Swift, Thomas Wolf, Yann LeCun, and Thomas Scialom. 2024. GAIA: a benchmark for general AI assistants. In *International Conference on Learning Representations (ICLR)*.

Samaneh Mohtadi, Kevin Roitero, Stefano Mizzaro, and Gianluca Demartini. 2026. The effect of document summarization on LLM-based relevance judgments. In *Advances in Information Retrieval: 48th European Conference on IR Research (ECIR 2026)*, pages 70–87.

Jingjie Ning, João Coelho, Yibo Kong, Yunfan Long, Bruno Martins, João Magalhães, Jamie Callan, and Chenyan Xiong. 2026. Agentic search in the wild: Intents and trajectory dynamics from 14m+ real search requests. In *Proceedings of the 49th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 1404–1415.

Rodrigo Nogueira, Wei Yang, Jimmy Lin, and Kyunghyun Cho. 2019. Document expansion by query prediction. *Preprint*, arXiv:1904.08375.

Arjun Panickssery, Samuel R. Bowman, and Shi Feng. 2024. LLM evaluators recognize and favor their own generations. In *Advances in Neural Information Processing Systems 37 (NeurIPS 2024)*.

Francesca Pezzuti, Ophir Frieder, Fabrizio Silvestri, Sean MacAvaney, and Nicola Tonellotto. 2026. How AI agents search. *PLOS ONE*, 21(10):e0360157.

Oscar Sainz, Jon Ander Campos, Iker García-Ferrero, Julen Etxaniz, Oier Lopez de Lacalle, and Eneko Agirre. 2023. NLP evaluation in trouble: On the need to measure LLM data contamination for each benchmark. In *Findings of the Association for Computational Linguistics: EMNLP 2023*.

Sriram Selvam and Anneswa Ghosh. 2026. Similar accuracy, unequal evidence: Search APIs as decision surfaces for tool-using agents. *Preprint*, arXiv:2607.10198.

Ian Soboroff. 2025. Don't use LLMs to make relevance judgments. *Information Retrieval Research*, 1(1):29–46.

Nandan Thakur, Jimmy Lin, Sam Havens, Michael Carbin, Omar Khattab, and Andrew Drozdov. 2025. FreshStack: Building realistic benchmarks for evaluating retrieval on technical documents. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*.

Paul Thomas, Seth Spielman, Nick Craswell, and Bhaskar Mitra. 2024. Large language models can accurately predict searcher preferences. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*.

Andrew Turpin, Falk Scholer, Kalervo Järvelin, Mingfang Wu, and J. Shane Culpepper. 2009. Including summaries in system evaluation. In *Proceedings of the 32nd Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 508–515.

Shivani Upadhyay, Ronak Pradeep, Nandan Thakur, Daniel Campos, Nick Craswell, Ian Soboroff, et al. 2024a. A large-scale study of relevance assessments with large language models: An initial look. *Preprint*, arXiv:2411.08275.

Shivani Upadhyay, Ronak Pradeep, Nandan Thakur, Nick Craswell, and Jimmy Lin. 2024b. UMBRELA: UMbrela is the (open-source reproduction of the) Bing RELevance assessor. *Preprint*, arXiv:2406.06519.

Ellen M. Voorhees. 2000. Variations in relevance judgments and the measurement of retrieval effectiveness. *Information Processing & Management*, 36(5):697–716.

Tu Vu, Mohit Iyyer, Xuezhi Wang, Noah Constant, Jerry Wei, Jason Wei, et al. 2024. FreshLLMs: Refreshing large language models with search engine augmentation. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 13697–13720.

William Webber and Laurence A. F. Park. 2009. Score adjustment for correction of pooling bias. In *Proceedings of the 32nd Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 444–451.

Jason Wei, Zhiqing Sun, Spencer Papay, Scott McKinney, Jeffrey Han, Isa Fulford, et al. 2025. BrowseComp: A simple yet challenging benchmark for browsing agents. *Preprint*, arXiv:2504.12516.

Colin White, Samuel Dooley, Manley Roberts, Arka Pal, Benjamin Feuer, Siddhartha Jain, et al. 2025. LiveBench: A challenging, contamination-limited LLM benchmark. In *International Conference on Learning Representations (ICLR)*.

Nurce Yagci, Sebastian Sünkler, Helena Häußler, and Dirk Lewandowski. 2022. A comparison of source distribution and result overlap in web search engines. *Proceedings of the Association for Information Science and Technology*, 59(1):346–357.

Ori Yoran, Samuel Joseph Amouyal, Chaitanya Malaviya, Ben Bogin, Ofir Press, and Jonathan Berant. 2024. AssistantBench: Can web agents solve realistic and time-consuming tasks? In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Heng Zhou, Ao Yu, Yuchen Fan, Jianing Shi, Li Kang, Hejia Geng, et al. 2025. LiveSearchBench: An automatically constructed benchmark for retrieval and reasoning over dynamic knowledge. *Preprint*, arXiv:2511.01409.

Yuqi Zhou, Sunhao Dai, Changle Qu, Liang Pang, Jun Xu, and Ji-Rong Wen. 2026. Learning to retrieve from agent trajectories. In *Proceedings of the 49th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 2544–2555.

A Protocol and release

Frozen protocol and scoring rules (scorer version `paper-2026-10-31`). This paragraph is the authoritative specification of the paper's scorer. Table 3 lists the earlier production rules that this scorer replaces; PR #82 moves production to this scorer, and dashboard runs scored before that change keep the earlier rules. Every table in the paper uses this version unless its caption says otherwise. We computed the numbers from the archived per-query artifacts with the scripts in `paper/analysis/`, against the benchmark code at repository commit `c84faee3` and the failure classifier of PR #82 (commit `35ee1696`), under the rules stated here. Each failed request is classified from its own error record, as production's `account_side()` does: an HTTP 401–403, 432 or 433 response, or an HTTP 400 or 429 response or API error whose message names a credit balance, too few credits, a usage limit, a quota, billing or an API key, is account-side and excluded; every other failure (such as rate

limits, timeouts and server errors) is service-side and scores zero. A result that carries the gold identity is a hit on any host, `site:` queries included. The finance matcher uses a 0.1% money band with the *table reading* (a bare table figure in thousands or millions or a parenthesized loss, read as a money value unless the number is a year or a percentage) and without a money backstop; diluted EPS, the only field with cue words, matches only in a result that carries one of them (*EPS*, *per share*, *earnings per*). A repeated URL scores zero except on `site:` queries. The rules live in `paper/analysis/common.py`. The judge and the query generators are GPT-6 Luna (`openai/gpt-6-luna`) through OpenRouter at temperature 0 with reasoning effort *high*; the second judge is Claude Opus 5.5. Snippets are capped at 2,000 characters before judging and matching. Scholar papers are balanced over five domains (computer, physical, life, social and health sciences) and three ages (7 days, 30 days, 1 year). Table 2 gives each bench's cadence, query count, k and metric. We froze this version at 01:13 UTC on 30 October 2026. On 31 October, after the post-freeze day had run, we changed three of its rules to match production: a `site:` hit had counted only on the requested host, the duplicate penalty had applied to every query, and failures had been classified by engine rather than per error record. No other rule changed. The development samples that informed the finance rules (the first 80 banded money hits, the 50 money backstop upgrades, the 100 money misses and the 80 table-reading hits), the second judge, the 200-character snippet test, the profile audit and the scholar-miss audit came before the freeze. The finance validation samples (100 exact-band and 59 other-field hits), the fresh finance run, the raters, the paired operator run, the instrumented scholar run and the post-freeze day came after it. No engine-specific client changed inside the 17–29 October window. Shared code changed on 18 October (rare runs query the engines concurrently, each engine still one request at a time; news and rare judge calls run 16 at a time; each request is timestamped; PRs #65–#67; requests, prompts and model unchanged) and on 28 October (Exa Lite joins, PR #69; a revised scholar DOI matcher, used by the last of the 12 scholar runs, PR #70; from 11:05 production excludes every failed request, PR #73).

Bench	Cadence	Queries/run	k	Metric
news	hourly	20	5	nDCG@5 vs. ceiling
finance	daily	120	5	recall@5
scholar	daily	420	10	recall@10
legal	daily	40 + 0–20	5	recall@5
rare	daily	100	5	nDCG@5 vs. ceiling

Table 2: Every engine receives the same k it is scored on. Per-bench protocol. Snippets are capped at 2,000 characters; scholar draws 7 papers per domain and age cell, 4 queries each; legal adds one caption query per opinion the 14 courts published that day.

Rebuilding the tables. Table 4 and `paper/analysis/manifest.json` list, for every headline result, its data, runs, engine set and scoring rules. From the dataset revision named in the manifest (`6a5be09d`), two commands rebuild Table 1 with its intervals and the paired-comparison counts of §3:

```
python analysis/table_rows.py \
    history_v5.jsonl \
    table_results.tex
python analysis/adjacent_pairs.py \
    history_v5.jsonl \
    audit/adjacent_pairs.json
```

Table 1, Table 10 and Figure 1b come from `history_v5.jsonl` (the summary history rescored under these rules). Every run of Table 1 and of the post-freeze day has its failures split from the per-query records. For 665 summary rows from 31 August to 16 October (18,539 failed requests, in weeks 36–42 of Figure 1b and 18 of the 31 scholar runs of Figure 1a) we have not fetched those records, so these rows keep the earlier rule: every failure of Perplexity, Exa, Kagi, Parallel, Claude search and their variants is excluded, the other engines' failures score zero, and scholar bucket recall counts every failure as a miss. They include 1,158 failures of ChatGPT search, some of which may be quota errors. Figure 1a comes from the 31 scholar runs of 29 September to 28 October 2026. Every audit in Appendices F and G names its runs and ships its sample and labels under `paper/analysis/audit/`.

API calls. We call each engine through its client in Table 5 at its default tier, one request at a time, with a 30-second timeout and up to three attempts with exponential back-off (1 to 30 seconds) on 429, 5xx and timeouts. We record each request that still fails, with its error type and message. One day of the benchmark issues about 30,700 search requests over the 26 configurations and up to about 75,000

Rule	Dashboard before PR #82	This paper	Why the paper changes it
Money band	2%	0.1%	Within 2%, neighbouring quarters and related line items matched; .71 of 80 audited banded hits were right.
Table reading	off	on	Reads a bare table figure in thousands or millions ("801" for $801M) and a parenthesized loss ("(458)") as money values; diluted EPS, the only field with cue words, still needs one of them; 19 of 29 audited misses that held the answer were such figures.
Money backstop	on	off	LLM upgrades of money misses were right in .36 of 50 audited.
Account-side failure	scored zero until 28 Oct, 11:05, then excluded	excluded, classified per error record	Our own quota, login, billing or credit failed, not the engine.
Service-side failure	scored zero until 28 Oct, 11:05, then excluded	scored zero	An agent gets no result either.

Table 3: A repository pull request (PR #82) moves production to these rules; dashboard runs scored before that change keep the earlier rules. The last column gives the reason for each change; the finance audits are in Appendix F.

result judgments; a rerun needs the public code, one API key per engine and an OpenRouter key for the judge.

Dispatch order. Within a run the engines are queried concurrently, and each engine works through the query list one request at a time. Across 37 of the news and rare runs in the Table 1 window, the first and the last engine to receive the same query are a median of 16 minutes apart (90th percentile 54 minutes); the two slowest engines create this spread. Mean lag is under 30 seconds for 18 engines, 2.3 minutes for Jina, 4.8 for Claude search and 6.6 for ChatGPT search, so on hourly news the slowest engines see the web later than the fastest. We rescored the 249 news runs of the window that record dispatch times (4,959 query-runs, 100,801 engine–query pairs; `lag_subset.py`), keeping only the pairs dispatched within 5 minutes of the first engine. The filter keeps 96% of pairs. The order of the 21 engines is unchanged (Kendall's τ_b 1.0, where 1 means the same order), and no mean nDCG moves by more than .009 (Claude search $-.009$, query-resampled 95% interval $-.023$ to $+.003$).

Vendor format change. From the hourly news run of 02:56 UTC on 30 October 2026, Google results fetched through Serper, and Jina results, which draw on Google, carry `https://www.google.com/goto?url=...` redirect links in place of the result URL, on 36 to 41 of every 100 news results in each later run that day (`goto_onset.py`). The title and snippet stay intact, so the news judge is unaffected, but the URL-based scholar, legal and filing matchers score such results as misses. The window of Table 1 ends on 29 October and contains no such URL.

Licenses and release. The rare stream is the `agentic/queries.parquet` artifact of the results dataset, sampled from three published agent-trajectory datasets: the DeepResearchGym search logs of Ning et al. (2026) (`cx-cmu/deepresearchgym-agentic-search-logs`, CC BY 4.0; 60% of sampled queries), the OpenResearcher trajectories of Li et al. (2026) (`OpenResearcher/OpenResearcher-Dataset`, MIT; 39%) and the LRAT-Train pairs of Zhou et al. (2026) (`Yuqi-Zhou/LRAT-Train`, no license stated on its card as of 30 October 2026; 1%). The repository describes the stream's filter (English-only language identification, rare-word test, URL and identifier removal, near-duplicate cap). The sources' terms govern the query texts; our code is MIT, and our CC BY 4.0 covers only our results, judgments and metadata. The next artifact revision drops the LRAT-derived queries unless their authors grant a license. These queries are 113 of the 6,901 filtered queries and 19 of the 1,300 rare query-runs of Table 1, and dropping them changes no engine's mean rare nDCG by more than .009 (`rare_drop_lrat.py`). A regular-expression scan of the 1,988 rare queries released with the window's runs found no e-mail address, URL or key-like string; queries do name people, as the public source documents do, so a human reads the queries of each new artifact revision before release. Removal requests go to the repository issue tracker. The per-query artifacts also redistribute the titles,

Result	Runs	Scored units	Engines
Table 1, Table 10	305 (12 scholar, 258 news, 11 finance, 13 rare, 11 legal), 17–29 Oct	13.1k query-runs	21
Figure 1b	every run in ISO weeks 36–43 (pool grows from 18 to 25 configurations)	weekly query-weighted means	7 shown
Figure 1a	31 scholar, 29 Sep–28 Oct	332–420 queries per run	7 lines, 19 dots and the ceiling
Paired differences (§3)	Table 1 runs; 2,000 run- or day-level resamples	13.1k query-runs	21
Matched support	Table 1 runs (256 of 258 news)	5,368 of these runs' 13,109 query-runs	21
Dispatch lag	249 news runs with timestamps	4,959 query-runs, 100,801 pairs	21
Blinded raters*	17–29 Oct runs with $\geq$19 engines	1,200 results, 200 queries	21, hidden
Second judge*	8 news and 8 rare runs	803 and 566 results	23
List-level raters*	100 complete pools (50 news, 50 rare) from Table 1 runs	5,698 results	21, hidden
Rare quoted vs. unquoted; bench weights; scholar strata	Table 1 runs	1,300 rare query-runs; 5 benches; 4,820 scholar query-runs	21
Caselaw identity*	10 legal runs, 18–28 Oct	100 hits	25
Finance audits*	24 finance runs, 29 Sep–28 Oct	399 results (140 of them exact-band hits), 100 misses	21

Table 4: The data behind each result: the runs it uses, what it counts, and which engines it covers. Every result is scored with the paper's scoring rules (scorer version `paper-2026-10-31`, the first paragraph of this appendix), except the checks marked *: the raters follow a written guideline (the list-level raters see snippets only), the second judge reuses the production prompt, and the caselaw and finance audits use an LLM annotator. The machine-readable version is `paper/analysis/manifest.json`.

URLs and snippets the APIs returned; we publish them as evaluation records under the vendors' terms as we read them and withdraw an engine's archived outputs on its request.

B Judge profile and gates

The news and rare judge runs in two steps, both with the same model. A *profile* call sees the query and today's date and returns: query type (*broad*, *specific*, *list*); domain (health, legal, financial, academic, tech, news, commerce, jobs, other); whether the query carries operators; one to three MAIN aspects, phrased as what a document must contain and never as the answer; auxiliary aspects; and a content archetype (*ephemeral*, *persistent*, *evergreen*) that sets the staleness rule. The profile is stored with the query and pasted verbatim into every per-result call, so the judge grades all engines against one interpretation of the query.

The *judgment* call sees the profile, today's date and one result (title, URL, published date if the API returned one, snippet capped at 2,000 characters) and emits a YAML block with eight gates and a rating. Gates: integrity (pass, limit, fail), relevance (entity, jurisdiction, topic), coverage of the MAIN aspects, completeness (list queries only), current-event freshness (dated events only), staleness by archetype, a domain cap (health, legal, financial, commerce and others carry hard caps), and operator compliance (quoted spans must appear verbatim in the snippet or title; `site:` must match the URL host). A failed relevance or operator gate forces 0; a failed coverage or completeness gate caps the rating at 2; staleness lowers the rating by one or two levels, or to 0 for a wrong year or entity status; a dated-event query whose result covers the entity but not the event is capped at 1. The rating maps to the Needs Met labels as 0 and 1 Fails to Meet (FailsM), 2 Slightly Meets (SM), 3 Highly Meets (HM) and 4 Fully Meets (FullyM). The judge is told to score facts against the page's own text and authority, never against its own knowledge of the answer. The prompts are in the repository under `src/needle/shared/prompts`.

C Operator mapping and frozen configuration

Table 5 fixes the configuration behind every engine in Table 1: the endpoint, the variant or model where the vendor exposes one, and the request parameters that differ from the vendor default. We ask every engine for k results ($k = 10$ on scholar, 5 elsewhere) at its default tier and score a shorter list as returned.

Engine	Endpoint	Variant or non-default parameters
Keenable	api.keenable.ai	default; `keenable-realtime` is the realtime variant
Exa	api.exa.ai	`type=auto`; `exa-instant` and `exa-lite` are the instant and lite types
Google	google.serper.dev (Serper)	default
Bing	searchapi.io (SearchAPI)	engine `bing`
Brave	api.search.brave.com	web search; `brave-llmcontext` is the LLM-context endpoint
Parallel	api.parallel.ai	default processor; `parallel-turbo` is the turbo processor
Perplexity	api.perplexity.ai	search API; `perplexity-fast` is the fast mode
Tavily	api.tavily.com	default
Linkup	api.linkup.so	default
TinyFish	api.search.tinyfish.ai	default
Octen	api.octen.ai	default
Ceramic	api.ceramic.ai	default
You.com	ydc-index.io	default
Firecrawl	api.firecrawl.dev	search endpoint, default
Kagi	kagi.com/api/v1	default
Jina	s.jina.ai	default
Context	api.context.dev/v1	default
DeepSeek	api.deepseek.com	search tool endpoint (`/v1/tools/search`), default
Claude search	api.anthropic.com	`claude-sonnet-5` with the `web_search` tool
ChatGPT search	api.openai.com	`gpt-5.5` with `web_search`, `search_context_size=low`

Table 5: Frozen configuration of the Table 1 engines. Operator handling per engine is in Table 6; the clients are in `src/needle/shared/search/`.

Every query is parsed for the operators `site:`, `after:` and `before:` (ISO dates). Table 6 shows what each engine receives. Google (Serper), Bing (SearchAPI) and Jina get the raw string because the underlying engines parse these operators themselves. Quoted phrases are always passed through in the query text. In the 24 finance runs of Appendix F and the 10 legal runs of 18–28 October 2026, an operator or quoted phrase appears in 335 of 667 money, 333 of 445 filing, 64 of 128 caselaw and 200 of 400 CFR query-runs; 100 of the CFR query-runs quote the span.

D Leak and quality filters

Scholar. A title query needs at least four words and a specific title (a digit, acronym, hyphenated term or five content tokens). A body keyword query needs at least three words and at least two content tokens absent from the title and abstract; a body question needs eight words and the same novelty test. A tip-of-tongue query needs twelve words, no quotes, no decimal or five-digit number, at most two content tokens shared with the title, and no coined term (acronym, camel case, digit-bearing word) that appears in the title or abstract. A paper enters only if all four queries pass. An instrumented run of the generator on 30 October 2026 passed 323 of 572 candidate papers (56%), from .41 in life sciences to .73 in health sciences (`scholar_rejects.py`). Each domain-by-age cell takes its first seven accepted papers, and nearly every cell of the 12 scholar runs of Table 1 holds 6 to 8, so the filter changes which papers a cell holds, not how many; whether the rejected papers would rank engines differently is untested.
Legal. A CFR query needs three words, no citation form (*CFR*, *U.S.C.*, §, "section n", "title n"), no part or section number of the gold section, and exactly one span of two to eight words that occurs verbatim in the section text; the quoted variant keeps the span in quotes, the others strip them.
News. The prompt that turns a news item into a query refuses evergreen items and returns a 2–6 word query on the specific event; query ids hash the text and the hour. Table 7 gives one generated query per bench and bucket.

E Worked example of the ceiling

The gains are a design choice, top-heavy so that one FullyM result outweighs one HM result by half and an SM result by a factor of about 8.5; Appendix G shows the engine order under linear and binary alternatives. For engine e and query q with ratings $r_1, \ldots, r_5$,

$$\mathrm{DCG}_e(q) = \sum_{i \le 5} \frac{g(r_i)}{\log_2(i+1)},$$

$$\mathrm{nDCG}_e(q) = \frac{\mathrm{DCG}_e(q)}{\mathrm{IDCG}(q)},$$

with gains $g(4) = 1$, $g(3) = 0.667$, $g(2) = 0.117$, $g(1) = g(0) = 0$, and $\mathrm{IDCG}(q)$ the DCG of the

Engine	`site:`	`after:`/`before:`
Brave, Brave (LLM ctx)	in query text	freshness range
Keenable	in query text	published-date tokens
Exa	includeDomains	start/endPublishedDate
Tavily, Octen, TinyFish	include_domains	start/end dates
Linkup	includeDomains	from/toDate
Context	includeDomains	freshness (after only)
Perplexity	domain filter	date filters
Parallel	include_domains	after_date only
Kagi	lens sites	after/before filters
You.com	include_domains	freshness range
Firecrawl	in query text	cd_min/cd_max
DeepSeek	site: OR site:	appended to text
ChatGPT, Claude	allowed_domains	in prompt text
Ceramic	dropped	dropped
Google, Bing, Jina	raw string	raw string

Table 6: Ceramic drops the `site:`, `after:` and `before:` operators; Google, Bing and Jina get the raw string; the other engines get filter parameters or query text.

Bench	Query	Gold or profile
news	Paramount Warner Bros takeover closes 2026	MAIN: the expected or actual closing date of Paramount's takeover of Warner Bros. in 2026; archetype *ephemeral*
finance, registry	nvidia number of employees	42,000, $\pm$15%
finance, 10-Q	"servicenow" q3 fiscal 2024 operating income	\$418M, $\pm$0.1%
finance, filing	Huntington Bancshares Ann B. Crane director vote 2026 after:2026-03-10 before:2026-06-08	accession 0000049196-26-000038
scholar, title	optimally selling heterogeneous objects by quantity	arXiv 2610.36244
scholar, body keyword	gap rent regularity	same paper
scholar, body question	Which Go City pass for New York does the paper cite as a quantity-menu example, and what restriction applies to each selected attraction?	same paper
scholar, tip-of-tongue	Wasn't there a paper about a seller offering different goods at prices based on how many a buyer takes, letting them choose which ones, and showing this can bring the most revenue under certain value patterns?	same paper
legal, CFR	"modify or waive any" county committees authority	7 CFR 1417.2
legal, caselaw	citation insurance v broan-nutone first circuit after:2026-07-14 before:2026-10-12	docket 25-1426 next to a party token; CourtListener id 10961606
rare	"Krasnogvardeysky District" Russia	judged; rare word splits into 7 pieces

Table 7: News and rare queries carry no gold: the judge profile fixes what a result must contain. One generated query per bench and bucket, with the gold or judge profile it is scored against.

ceiling's list. A bench score $M_b(e)$ is the mean over scored query-runs in the window (a service-side failure scores 0; an account-side failure is left out). The ceiling's score $M_b(\text{ceiling})$ is the same mean over the ceiling's lists (1 for news and rare), and the overall share is

$$S(e) = \frac{1}{|B|} \sum_{b \in B} \frac{M_b(e)}{M_b(\text{ceiling})}$$

over the benches B the engine ran. For example, two engines answer one query. Engine A returns u_1 (rated 4), u_2 (2) and u_1 again under a tracking parameter (rated 3, but URL normalization strips the parameter, so the repeat scores 0). Engine B returns u_3 (3), u_1 (4) and u_4 (1). The *ceiling* keeps the best rating per normalized URL, $\{u_1 : 4, u_3 : 3, u_2 : 2, u_4 : 1\}$, in rating order, so $\text{IDCG} = 1 + 0.667/1.585 + 0.117/2 = 1.479$. Engine A scores $(1 + 0.117/1.585)/1.479 = 0.73$ and Engine B $(0.667 + 1/1.585)/1.479 = 0.88$. We score an engine that returns fewer than k results on the list it returned, against the ceiling's list, which still takes up to k results from the pool. Had no engine returned a result rated 2 or higher, IDCG would be 0 and the query would be dropped from every engine's mean. Ties in the pool do not matter,

because only ratings enter IDCG. As in production, the duplicate penalty does not apply to a query that carries `site:`; no news query in the window carried `site:`, and on the rare bench the exception changes 3 of 1,748 `site:` engine–query pairs. Because the ceiling keeps each URL once, such a repeat can lift an engine's nDCG@5 above 1: Tavily's list for one rare query on 1 October, outside the Table 1 window, scores 1.34.

F Finance matcher check

The finance matcher originally accepted a money figure within 2% of gold, a headcount within 15%, and an LLM backstop upgrade on any field. We checked both bands on the 24 daily finance runs from 29 September to 28 October 2026, a longer span than the 11 runs of Table 1. These runs cover 21 engines and 56,678 scored engine–query pairs, of which 13,140 ask for a quarterly money figure and 4,393 for a headcount.

Tolerance sweep. Table 8 rescores the stored results with other bands. The 2% money band buys 9 recall points over a 0.1% band, and the 15% headcount band buys 10 points over 1%. Counting individual matched results, 21.7% of money matches and 35.6% of headcount matches under the production bands fail at 0.1% and 1%.

Money band	0	.1%	.5%	1%	**2%**	5%	10%
recall@5	.363	.447	.498	.518	**.541**	.583	.629
τ_b vs. 2%	.96	.98	.95	.94	1	.91	.89
Headcount band	0	1%	5%	**15%**	25%	50%	
recall@5	.794	.811	.863	**.915**	.919	.935	
τ_b vs. 15%	.73	.77	.81	1	.93	.79	

Table 8: Wider bands raise recall at every step. The engine order barely moves across money bands of 0.1–1% ($\tau_b \geq .94$) and moves more across headcount bands. Deterministic recall@5 of the production matcher (no backstop, no table reading) over all engine–query pairs of the 24 audit runs, and Kendall's τ_b of the 21 engines' order against the production band (bold; 1 means the same order), by tolerance.

Precision audit. The LLM backstop judged 12,919 engine–query pairs the matcher had missed and upgraded 3,187 (24.7%); 2,621 of the upgrades are money queries (49% of money misses), against 1.8% of identifier misses. We sampled 399 results: 80 money hits that depend on the band (0.1–2%), 140 money hits within 0.1% (the *exact-band* stratum: 40 in a first sample and 100 more drawn from the Table 1 window), 40 headcount hits that depend on the band (1–15%) and 10 within 1%, 59 hits on the other field types in proportion to their frequency, and 70 backstop upgrades (50 money, 20 other). One LLM annotator per item (Claude Opus 5.5, in sessions of 50 to 100 items, without the matcher's verdict or the engine's name) judged whether the result states the gold value on the full 2,000-character text the matcher reads, with reporting rounding allowed and a value for a different period or line item counted as wrong; 21 of the 58 hits rejected in a first pass on 700 characters reversed on the full text. Table 9 summarizes the labels. Two strata are weak: banded money hits of the deterministic matcher (.71) and money upgrades of the backstop, which is lenient on money (.36) and sound elsewhere (.95 on 20); all 10 headcount hits within 1% hold. Weighted by hit frequency, precision of the deterministic matcher is .97 overall, .97 on headcounts, .98 on the other fields and .88 on money (95% Wilson intervals: money within 0.1% .87–.96, banded .61–.80, headcount banded .80–.97, other fields .91–1.00). Almost every remaining false positive is a neighboring quarter or a related line item (basic or adjusted instead of diluted EPS, adjusted net income) that falls within 2%, or a table whose column headers the snippet omits.

Consequence. The audits led to the matcher of Table 1 (Appendix A), rescored from the archived results; Table 9 gives each revision's audit and its effect on the tables. The table reading came after the false-negative audit below. Of its 80 sampled hits, 73 are confirmed (.91, Wilson .83–.96, a development-sample figure); four of the seven failures are tables that stop before the queried row, two a different period. The non-money backstop now supplies under 2% of finance hits. A figure within 0.1% can still be a neighboring quarter's identical value, so money is the matcher's weak spot.

False negatives. We also sampled 100 money query-runs the strict matcher scored as misses, across engines and runs, and asked an LLM annotator (Claude Opus 5.5) whether any of the five results states the gold value for the right company, period and metric. The annotator found the value in 29 (95% interval .21–.39) and a near miss (a different period or line item) in 2 more; 20 of the 29 were at rank 1 or 2. Nearly all of the 29 use formats the matcher does not read: bare table figures in millions or thousands without a

Revision	Rule	Audited precision (sample)	Effect
Production (dashboard)	2% money band; 15% headcount band; LLM backstop on every field	money banded hits .71, money backstop upgrades .36 (80 and 50 items; development sample)	the rules Table 1 replaces
Strict	0.1% money band; no money backstop; non-money backstop kept	exact-band money hits .93 (140; 100 drawn after the rule was frozen), headcount .93 (40), other fields .98 (59); fresh window of 31 October: exact-band .93 (100)	finance recall -2 to -11 points per engine; finance order τ_b .83 vs production; overall shares move ≤ 1.9 points and no overall rank changes
Strict + table reading (paper)	+ unit-less table figures and parenthesized losses	.91 (73 of 80; development sample); fresh window of 31 October: .70 with an unlabeled period counted wrong, .98 counting only contradictions (238 yes, 95 unclear, 6 no of 339)	finance recall $+0$ to $+7$ points; finance order τ_b .86 vs strict; overall shares move ≤ 1.4 points

Table 9: Each finance matcher revision moves overall shares by at most 1.9 points. Revisions, their audit status and their effect on the tables; only the production rules ran live, and the paper rescores the archived results under the last row.

unit word ("801" for $801M), losses in parentheses ("(458)") and prose rounding beyond 0.1% ("$30 million" for $29.5M). The table reading recovers 19 of these 29 and matches 1 of the 71 others. About a tenth of the remaining misses still hold the answer, mostly as prose rounded beyond 0.1%; against this, .07 of exact-band hits and .09 of table-reading hits are false positives. We apply these rates by stratum (`finance_bias_table1.py`, on the 11 finance runs and 21 engines of Table 1, with account-side failures excluded; money queries are 23% of the window's finance queries, headcount 8% and the other fields 69%). For an engine with field shares p_m, p_h, p_o, per-field recall r_m, r_h, r_o, table-reading share x_m of its money queries and share a_m of its money queries with at least one result, expected false positives are $p_m[.07(r_m - x_m) + .09x_m] + .07\,p_h r_h + .02\,p_o r_o$ and expected false negatives $.10\,p_m(a_m - r_m)$. The net correction runs from $-.031$ for Keenable and $-.030$ for Parallel and Exa through $-.013$ for Brave and Context to $-.003$ for Claude search, $-.001$ for Bing and $+.005$ for Ceramic. False hits and missed answers therefore do not cancel: reported finance recall runs .02 to .03 high for the engines above .80, about .01 high in the middle and .005 low for Ceramic. Correcting every engine compresses the finance spread from .488 to .453 and swaps Jina and Kagi, whose reported recall is .719 and .718. The per-engine miss samples (0 to 3 recovered misses each) cannot show whether the error rates differ by engine.

Fresh window under the frozen rules. To validate the frozen matcher on unseen data, we generated finance queries with the production generator on 30 October 2026, kept all 146 money queries (net income, operating income, diluted EPS) and a stratified 161 of the other fields, and ran the 307 queries through 17 configurations between 00:47 and 01:44 UTC on 31 October (`fresh_finance.py`, `audit/fresh/`). Claude search was left out because the account's credit had run out. Google and Jina carried the redirect URLs of Appendix A, which hide the host but not the text the money and name matchers read. Two Claude Opus 5.5 annotators read the matcher's full 2,000-character text and graded every table-reading hit (339), 100 exact-band money hits and 50 other-field hits. Each graded item is the first matching result in a query's top five, so the precision below is that of query-level recall@5 decisions. Exact-band precision is .93 (93 yes, 6 unclear, 1 no), as in the earlier validation. The table reading is weaker and engine-specific. Of its 339 hits, 238 state the gold figure for the right period (.70, Wilson .65–.75), 95 show the figure in a table whose period columns the snippet does not label, and 6 contradict it. We treat the 95 as unresolved: precision is .70 if an unresolved hit counts as wrong and .98 if only contradictions do. The unlabeled hits concentrate where snippets are table dumps: Firecrawl 13 of 43 confirmed, Tavily 12 of 24, Parallel 36 of 48, Brave (LLM ctx) 29 of 39, against Exa 43 of 45 and Perplexity 28 of 32. Of the 50 other-field hits, 39 are confirmed; of the other 11, 4 are `website` hits matched on

the URL host, which the annotators did not see, and 2 are headcounts inside the 15% band, so the rule-consistent figure is .90. To bound the effect on Table 1, we multiply each engine's table-reading hits in the window by its fresh unconfirmed share (its own where 20 or more hits were audited, .30 otherwise) and subtract the result from finance recall (`reading_correction.py`). Firecrawl loses 5.6 points, Tavily 2.7, DeepSeek 2.3, Parallel 2.1 and Brave (LLM ctx) 1.8 and ChatGPT search 1.5; every other engine loses under 1. The finance order keeps τ_b .91 and the overall order .96: ranks 1 to 6 do not move, and Context–Brave, ChatGPT search–Kagi, Firecrawl–Octen and Tavily–Bing swap. The paper's scoring rules keep the table reading; a period-aware version is future work. A strict score that drops the table reading (`strict_vs_readings.py`) lowers finance recall by 0.1 to 7.1 points (Firecrawl 7.1, Parallel 6.7, Exa and Tavily 5.7, Brave (LLM ctx) and ChatGPT search 5.2, DeepSeek and Perplexity 4.6, the rest under 2) and the finance ceiling from .993 to .989; the finance order keeps τ_b .86 and the overall order .96, ranks 1 to 6 are unchanged, and the same four pairs swap. As a check of the finance column, the fresh run's engine shares agree with the Table 1 finance shares at τ_b .79 with a mean absolute difference of .05 (`audit/fresh/summary.json`), and the same five engines lead (Exa .96, Keenable .95, Parallel .95, Brave (LLM ctx) .94, Perplexity .94, against .85–.92 in the table). Half its queries are money queries, against 23% in production; it covers one day, has no LLM backstop for the non-money fields and ran 17 of the 21 configurations, so it checks the direction of the finance column, not its values.

G Robustness checks

The appendices use every active configuration, so names absent from Table 1, such as Parallel Turbo or Exa Instant, appear here. Table 11 collects the alternative views of the engine order from this appendix and Appendix F.

Leave-one-engine-out ceiling. On every sixth hourly news run from 29 September to 29 October 2026 (111 runs, 1,909 query-runs with a non-empty ceiling) we recomputed each engine's nDCG@5 against a ceiling pooled from the other engines only. Because every returned result is judged, the ceiling can only fall when an engine leaves the pool, so the left-out engine's share can only rise. The largest change is +.013 (DeepSeek, which joined on 17 October and so has 578 query-runs). Every other engine moves by .004 or less, and the engine order is identical (Kendall $\tau_b = 1$, where 1 means the same order). An engine beats its leave-one-out ceiling on at most 1% of queries. On the Table 1 window the same check for every bench (`loo_all.py`) moves no scholar, finance or legal share by more than .007, no news share by more than .012 and no rare share by more than .037 (ChatGPT search). The overall share moves by at most 0.7 points, and the overall order stays unchanged. A judged query whose pool the removal empties is dropped for that engine (13 of 5,083 news and 25 of 1,133 rare engine–query cases).

Empty ceilings. A judged query that no engine answers with a rating of 2 or more has an empty ceiling and is dropped: 69 of the 5,101 news query-runs in 256 of the window's 258 news runs (1.4%) and 176 of the 1,300 rare query-runs (13.5%; 149 of the 551 quoted and 27 of the 749 unquoted). Scoring them as zero for every engine and for the ceiling instead lowers every absolute mean nDCG in proportion but changes no bench share by more than .003 and no order (`ceiling_drop.py`), because the zeros enter the engine mean and the ceiling mean alike. The absolute nDCG columns of Table 1 are therefore conditional means.

Sensitivity to scoring choices. On the 111 news runs of the leave-one-out check we recomputed news shares under other gain mappings and compared engine orders with the default by Kendall τ_b: linear gains $\{1, .75, .5, .25, 0\}$ give .95 (one engine moves four places), the exponential mapping $(2^r - 1)/15$ gives .97, binary relevance at rating ≥ 3 gives .93, at $= 4$ .87, and at ≥ 2 .81. Ranking Table 1 by the mean of the five absolute metrics instead of share of ceiling gives $\tau_b = .98$; Context falls from 7th to 9th, and Brave and DeepSeek each rise one place.

Paired differences. In Table 1, 14 of the 20 adjacent pairs have overlapping marginal intervals. Overlap of two marginal intervals is neither a test of equivalence nor transitive, so we also ran a paired test: in each run resample we recomputed every engine's share and took the difference of each pair (`adjacent_pairs.py`, 2,000 resamples, Table 1 runs). The paired 95% interval of the difference excludes zero for 10 of the 20 ad-

jacent pairs and for 194 of the 210 pairs overall. With a Bonferroni adjustment for 210 comparisons (normal approximation on the bootstrap standard deviation, $z = 3.68$) 183 pairs stay separated. The 27 adjusted-unresolved pairs form four groups: Exa to Brave (LLM ctx) (Exa–Perplexity $+1.8$, Perplexity–Parallel $+1.5$, Perplexity–Brave (LLM ctx) $+2.4$, Parallel–Brave (LLM ctx) $+0.9$), Linkup to You.com (Linkup, Context, Brave, DeepSeek, You.com), ChatGPT search to Octen (ChatGPT search, Kagi, Claude search, Firecrawl, Octen; ChatGPT search–Octen $+2.2$ and Kagi–Octen $+2.0$ are its widest links), and Google, Jina, Tavily and TinyFish around Bing (Google–Bing $+5.3$, Bing–TinyFish $+4.5$, Jina–Bing $+1.4$, Jina–Tavily $+1.3$, Tavily–Bing $+0.2$); only Keenable and Ceramic are separated from every other engine (`audit/adjacent_pairs.json` lists every pair). Resampling days instead of runs, so that the hourly news runs of one day move together, separates 9 of the 20 adjacent pairs, 192 of 210 pointwise and 181 adjusted (`audit/adjacent_pairs_day.json`).

Repeated queries and cluster resampling. Runs are not fully independent units. Counting every query-run whose exact text appears in another run of the window (first occurrences included), 35% of finance query-runs recur (registry facts), 18% of rare, 11% of news (mostly within one day), 5% of scholar and 3% of legal; counting only occurrences after the first, the shares are 22%, 9%, 6%, 3% and 2% (`repeat_queries.py`). Day-level resampling leaves unmodeled the cross-day repetition of 35% of finance, 17% of rare and 4% of news query-runs. Resampling clusters of identical query text instead of runs (for scholar, the paper behind the four queries; `cluster_pairs.py`) separates 195 of the 210 pairs pointwise and 186 after the Bonferroni adjustment, with Keenable–Exa at $+4.5$ ($+3.5$ to $+5.5$). The paper reports the run-level counts.

Failures. We classify each failed request from its own error record with production's rule (Appendix A). A failure is account-side when it comes from our own account: an HTTP 401–403, 432 or 433 response, or an HTTP 400 or 429 response or API error whose message names a credit balance, too few credits, a usage limit, a quota, billing or an API key. Table 1 excludes account-side failures and scores every other failure, the service-side ones (such as rate limits, timeouts, server errors and invalid requests), as zero, which is what an agent experiences. In the Table 1 runs the account-side failures are ChatGPT search's 1,351 HTTP 429 responses saying that our credits had run out (10.3% of its query-runs), Claude search's 4,599 refusals because our credit balance ran out (35.0%), Kagi's 1,560 HTTP 401 responses (11.9%) and Jina's 304, Exa's 256 and Parallel's 100 HTTP 402 payment errors (2.3%, 1.9% and 0.8%). Service-side failures are 27.2% of TinyFish's query-runs (HTTP 429 rate limits), 2.5% of Jina's (HTTP 422 errors), 0.3% of Bing's and at most 0.1% of every other engine's. Each request is sent at most three times before a failure is recorded (Appendix A). The account-side failures cluster by date: ChatGPT search's fall on 17, 18, 22 and 27 October, Jina's on 20 October, Claude search's on 22–26 October, peaking on 23–25 October, Parallel's on 22 October, Kagi's on 27–29 October and Exa's on four days. Claude search's, Kagi's, Exa's and Parallel's split evenly between the first and second half of the query list; ChatGPT search's (431 and 920) and Jina's (96 and 208) fall more in the second half (`failure_profile.py`, `audit/failure_profile.json`). Scoring only answered requests for every engine instead moves the engines with service-side failures: TinyFish (27% failed) from 37.6 to 44.9, rank 20 to 17, and Jina from 43.6 to 44.6. Every other engine moves by at most 0.5 points, and the answered-only order agrees with Table 1 at Kendall $\tau_b = .96$.

Matched support. Because the exclusions leave ChatGPT search, Claude search and Kagi scored on fewer query-runs than the other engines, we also apply a matched-support rule: a query-run is dropped for every engine when an account-side failure occurred on it, and service-side failures stay zeros. We applied the rule to the whole Table 1 window (256 of its 258 news runs and every other run; `matched_pairs_paper.py`), scoring each query-run under the paper's scoring rules, so the per-query base reproduces the Table 1 overall shares within 0.02 points. The rule retains 5,368 of the 13,109 query-runs in these runs (the full window has 13,149) and agrees with the order of Table 1 at $\tau_b = .93$. Three differences have run-resampled 95% intervals that exclude zero: Bing $+5.6$ ($+2.2$ to $+9.8$, rank 19 to 16), Parallel -1.9 (-3.1 to -0.8, 4 to 5) and Brave (LLM ctx) $+1.2$ ($+0.3$ to $+2.4$, 5 to 4). Every other engine moves by at most 1.0 points with

Engine	Share	95% CI	Δ matched	95% CI	Sch.	News	Fin.	Rare	Legal
Keenable	73.0	72.1–73.7	+0.8	−0.1, +2.0	.811	.612	.904	.504	.817
Exa	68.4	67.3–69.4	−0.5	−1.6, +0.4	.625	.609	.921	.472	.792
Perplexity	66.6	65.1–68.1	−0.4	−2.0, +1.0	.641	.643	.892	.463	.691
Parallel	65.1	64.0–66.2	−1.9	−3.1, −0.8	.651	.553	.907	.386	.759
Brave (LLM ctx)	64.2	63.2–65.1	+1.2	+0.3, +2.4	.591	.640	.853	.449	.676
Linkup	57.1	55.8–58.4	+1.0	−0.2, +2.4	.521	.566	.794	.397	.579
Context	57.0	55.4–58.5	−0.9	−2.7, +0.8	.664	.476	.783	.336	.593
Brave	57.0	56.0–58.0	+0.7	−0.4, +1.9	.541	.557	.766	.351	.637
DeepSeek	56.5	55.4–57.5	+0.2	−1.0, +1.5	.301	.632	.809	.383	.698
You.com	55.5	54.5–56.5	+0.5	−0.5, +1.5	.523	.551	.745	.341	.615
ChatGPT search	52.1	50.9–53.4	−0.7	−2.3, +0.3	.333	.357	.800	.396	.722
Kagi	51.9	50.9–52.8	−0.2	−1.1, +0.7	.621	.318	.722	.299	.634
Claude search	50.8	49.3–52.2	+0.3	−0.7, +1.6	.553	.463	.669	.318	.539
Firecrawl	50.4	49.0–51.6	−0.01	−1.2, +1.2	.541	.285	.818	.262	.611
Octen	49.9	48.7–51.1	−0.5	−1.8, +0.7	.340	.513	.720	.319	.604
Google (Serper)	47.5	46.6–48.4	−0.1	−0.9, +0.8	.527	.261	.740	.252	.593
Jina	43.6	42.3–44.7	−0.3	−1.5, +0.8	.545	.210	.724	.160	.539
Tavily	42.3	41.3–43.3	+0.2	−0.8, +1.2	.336	.303	.827	.279	.369
Bing (SearchAPI)	42.1	38.3–45.6	+5.6	+2.2, +9.8	.461	.292	.635	.171	.548
TinyFish	37.6	36.4–38.7	−0.6	−1.9, +0.6	.136	.255	.733	.219	.537
Ceramic	14.4	13.7–15.1	−0.4	−1.2, +0.3	.002	.040	.430	.111	.136

Table 10: Under matched query support only Bing (+5.6), Parallel (−1.9) and Brave (LLM ctx) (+1.2) move with intervals that exclude zero. Columns give Table 1 in numbers: overall share (%) with its run-level bootstrap interval; the change in overall share under matched query support over the whole window (every engine rescored on the 5,368 query-runs no engine lost to an account-side failure; Appendix G) with its run-resampled interval; and the bench shares. Both shares in the Δ matched column use the paper's scoring rules (`matched_pairs_paper.py`).

an interval that covers zero, and the top three and bottom two are unchanged. On matched support the paired test of *Paired differences* above separates 7 of 20 adjacent pairs, 188 of 210 pairs pointwise and 181 with the Bonferroni adjustment, with only Keenable, TinyFish and Ceramic separated from every other engine. Across the three estimates (run-level, day-level and matched support; `pairs_survive_paper.py`) 177 of the 210 pairs stay separated under the adjustment in all of them; these counts move by about one pair with the bootstrap seed. Six adjusted primary separations fail at least one check: Linkup–You.com fails day-level resampling, Octen–Bing fails both, and Context–ChatGPT search, Context–Kagi, Firecrawl–Bing and Octen–Google fail matched support (`audit/pairs_survive_paper.json`).
We keep the unequal-support estimate as the primary one because it uses all 13,149 query-runs rather than 5,368, and print the matched-support change beside it in Table 10.

Exclusion bounds. Account-side failures are excluded from the scores of ChatGPT search, Claude search, Kagi, Jina, Exa and Parallel, while the account column of Table 1 still reports them. Exclusion assumes the engine would have scored on the failed requests as it did on the rest; two imputations bound the alternative (`exclusion_bounds.py`): scoring every excluded request zero or scoring it at the ceiling puts Claude search's overall share between 33.5 and 67.8 around the reported 50.8 (29–36% of its requests excluded per bench), Kagi between 46.8 and 57.7 (51.9), ChatGPT search between 48.5 and 56.5 (52.1), Jina between 42.9 and 44.1 (43.6), Exa between 65.0 and 69.1 (68.4) and Parallel between 64.9 and 65.3 (65.1); Perplexity has no account-side failures in the Table 1 runs and so no range. The excluded fraction counts only account-side failures, not the empty-ceiling queries that every engine drops. Without the assumption Claude search's rank is undetermined (ranks 3 to 20), Kagi's range spans ranks 6 to 16 and ChatGPT search's 9 to 15, Jina stays 17th, and Exa, Parallel and Perplexity stay in the top five under either extreme, though Exa's upper bound narrows the Keenable–Exa margin from 4.6 to 3.9 points.

Common support and uncertainty. Engines joined the benchmark at different dates, so Table 1 restricts every bench to the runs since 17 October, when the last engine joined, in which all 21 config-

urations ran. The only gaps are the query-runs lost to account-side failures: 0.8% for Parallel, 1.9% for Exa, 2.3% for Jina, 10.3% for ChatGPT search, 11.9% for Kagi and 35.0% for Claude search. In Kagi's news and rare runs of 27–28 October the production scorer had counted a whole-run account-side failure as zero; rescoring those rows from their per-query records excludes that failure. Over the eight weeks of Figure 1b, adjacent weekly orders of the listed engines agree at τ_b .81–.92 (mean .87), and the 15 configurations present in every week give .81–.96 (mean .91; `weekly_tau.py`, `audit/weekly_tau.json`); Keenable leads every week. Pooling the news ceiling over those 15 engines only, on the sampled runs of weeks 40–43, raises their weekly news shares by .003 to .010 on average and changes no weekly order ($\tau_b = 1$; `fixed_pool_weekly.py`), so the growing pool does not drive the trends in Figure 1b. The drop of Claude search on the dashboard in the week of 19 October came from our credit lapse, not from a change in the service. Figure 1b excludes the lapse: the scoring drops those runs, so Claude search's week-43 share (51.2) rests on runs from 19 October up to the lapse onset at 08:15 UTC on 22 October, plus one partial rare run. If each week keeps only the runs in which Claude search lost at most 10% of its requests, its share still falls from 61.0 in week 39 to 51.3 in week 43, mostly by week 41, when its failures were below 8%. Scoring failures as zero, as the dashboard did until 28 October, gives 56.4 in week 39 and 24.4 in week 43; that larger drop is the lapse (`claude_weekly.py`, `audit/claude_weekly.json`).

Where the scholar lead comes from. Of Keenable's 4.6-point lead over Exa in overall share, scholar contributes 3.7 points, rare 0.6, legal 0.5, news 0.0 and finance -0.3 (`bench_weights.py`). Dropping any one bench keeps Keenable first (τ_b .84–.92 against Table 1) but shrinks the lead to 1.1 points without scholar. Split by stratum over the 12 Table 1 scholar runs (4,820 query-runs; `scholar_strata.py`), Keenable's recall@10 exceeds Exa's by $+.38$ on papers 7 days old (.79 against .41), $+.10$ at 30 days and $+.03$ at one year; by $+.20$ to $+.30$ in computer, life, physical and social sciences but by $-.10$ in health sciences; and by $+.01$ on title queries, $+.17$ on body keywords and tip-of-tongue descriptions and $+.33$ on body questions. The lead is therefore a freshness and full-text lead on recent non-medical papers, not a uniform one.

Known-item hits are the target page. A matcher hit shows that a returned result carries the gold identifier, not that it is the target document. On the three scholar runs of 25–28 October (13,311 hits) the identifier appears in the hit's own URL for 95.1% of hits, and 84% of hits are an arXiv page. On the ten downloaded legal runs, the section number appears in the URL of 94.0% of CFR hits and 95.4% sit on a primary legal host (eCFR, LII, GovInfo). For caselaw, 62.2% of hits carry the docket, cluster id or citation in the URL and 86.8% sit on a primary host (CourtListener, Justia, supremecourt.gov, uscourts.gov). An LLM annotator (Claude Opus 5.5, engine names hidden) classified 100 caselaw hits drawn four per configuration from the ten runs: 80 are the opinion or a court docket page of the gold case, 14 are pages about the same case (Wikipedia, news summaries, SCOTUSblog, a motion in the same docket), 5 are unclear and 1 is a page about another case. Caselaw recall thus credits a page about the right case rather than the target in 14 to 19 of 100 hits. Scaling every engine's caselaw hits by the pooled target fraction .80 (Wilson .71–.87) lowers legal recall by .01 to .05 and keeps the legal order at τ_b .94 (`legal_target_only.py`); applying each configuration's own sampled fraction, which four hits bound only to within .25, gives τ_b .76, so the audit rules out a large pooled effect but not engine-specific ones. In the other direction, the annotator checked 100 scholar body-query runs that the matcher scored as misses: the target paper appears among the ten results, under a URL or snippet that carries no identifier, in 11 (95% interval .06–.19; project pages, aggregators, a podcast page, a news summary), never as a citation inside another document. Scholar recall is thus a lower bound.

Post-freeze day, all benches. The production benches kept running after the freeze, and their archived runs give a one-day prospective window: from the first run after the freeze, the 01:17 UTC news run of 30 October, to the finance run of 03:08 UTC on 31 October, 28 news runs and one scholar, rare, legal and finance run each (1,224 query-runs per engine), rescored under the paper's scoring rules (`prospective_window.py`, `audit/prospective_window.json`). Nineteen configurations have all five benches: Claude search has no finance run because the account's credit had lapsed, and every Kagi request

Alternative view	What moves	Order vs. Table 1	Leader and lead over Exa
Matched query support (5,368 query-runs)	Bing $+5.6$, Parallel -1.9, Brave (LLM ctx) $+1.2$; others within ± 1.0	τ_b .93; 181 of 210 pairs separated (adjusted)	Keenable, $+5.8$
Day-level resampling	intervals widen	181 of 210 pairs separated (adjusted)	Keenable, $+4.6$
Query-cluster resampling (identical text; scholar: paper)	intervals narrow	186 of 210 pairs separated (adjusted)	Keenable, $+4.5$
Excluded requests scored zero or at the ceiling	Claude search 33.5–67.8, Kagi 46.8–57.7, ChatGPT search 48.5–56.5, Exa 65.0–69.1	Claude search undetermined, Kagi ranks 6–16, ChatGPT search 9–15; Exa, Parallel, Perplexity stay in the top five	Keenable, $+3.9$ to $+8.0$
Ceiling pooled without the scored engine	overall share ≤ 0.7 points; rare share $\leq .037$	overall order unchanged	Keenable, $+4.6$
One bench dropped (each of five)	lead from $+1.1$ (no scholar) to $+6.1$ (no finance)	τ_b .84–.92	Keenable in all five
Rare column from unquoted queries only	rare: Exa, Perplexity, Brave (LLM ctx) lead; Keenable fourth	overall τ_b .97	Keenable, $+3.2$
Snippets cut to 200 characters (8 news queries)	news shares move .084 on average	news τ_b .73	leader and bottom three unchanged
Finance error corrected by stratum	finance spread .49 to .45	Jina and Kagi swap on finance	Keenable
Finance without table readings (strict matcher; Appendix F)	finance recall -0.1 to -7.1 (Firecrawl, Parallel, Exa, Tavily most)	finance τ_b .86; overall τ_b .96; ranks 1–6 unchanged, four adjacent swaps	Keenable, $+5.4$
Fresh finance run, 31 Oct 2026 (307 queries, 17 engines; finance column only; Appendix F)	finance shares move .05 on average	finance τ_b .79; same five engines lead	Exa .96, Keenable .95 on finance
Post-freeze day, all benches (30 Oct 2026; 19 engines)	one scholar and one legal run move the leaders	overall τ_b .84; same five lead, Ceramic last	Perplexity 72.4, Keenable 71.3
Rater grades instead of the judge (100 complete pools, Gemini 4 and Grok 4.7; not a full overall score)	engine nDCG shares move .06–.07 on average	Spearman .94 (τ_b .83–.85)	same five engines lead and same three trail; Keenable–Exa unresolved under the judge and both raters
Empty-ceiling queries scored zero	absolute news and rare means fall 1.4% and 13.5%	shares move $\leq .003$; order unchanged	Keenable, $+4.6$

Table 11: Every retrospective view that recomputes the full overall score keeps Keenable first and Ceramic last, while the post-freeze day puts Perplexity first by 1.1 points. The two sampled checks (200-character snippets, rater grades) preserve the top group and the bottom three but not the order within the top group. Rows give the alternative views analyzed in this paper; columns give what each view moves, its order against Table 1, and the leader with its lead over Exa.

failed. The overall order agrees with Table 1 at τ_b .84 (per bench .73 to .86): the same five engines lead and Ceramic is last. The leader changes: Perplexity 72.4 and Keenable 71.3, then Parallel 65.8, Exa 63.7 and Brave (LLM ctx) 61.7. The change comes from the single scholar run (Perplexity's bench share .64 to .77, Keenable's .81 to .77) and the single legal run of 40 queries (Keenable .82 to .73, Perplexity .69 to .78); both moves lie within the run-to-run spread of those benches (per-run bench shares in the runs of Table 1: scholar, Keenable .74–.90 and Perplexity .56–.78; legal, Keenable .71–.89 and Perplexity .47–.85). Finance rises for every leader (.89 to .96), and news holds. Google and Jina returned redirect URLs for 51% and 50% of their results that day and fall 4.5 and 6.6 points. One day is a direction check, not a new leaderboard.

Blinded raters with page text. To test the judge against an independent reading, we sampled 100 news and 100 rare queries from the 17–29 October runs with at least 19 engines and drew six distinct top-5 URLs per query (1,200 results, judge ratings 0:441, 1:120, 2:263, 3:226, 4:150). We fetched each page (1,130 fetched; the rest are login walls, blocked hosts or dead pages) and gave two Claude Opus 5.5 raters (A and B) a written guideline (0–4

Engine	title	body keyword	body question	tip of tongue	query-runs
ceiling (pooled)	*1*	*.888*	*.938*	*.767*	*12,020*
Parallel	**.981**	.453	.642	.278	12,020
Kagi	.962	.674	.640	.091	11,600
Bing (SearchAPI)	.903	.402	.411	.060	12,020
Parallel Turbo	.894	.208	.294	.110	12,020
Brave (LLM ctx)	.893	.440	.620	.194	12,020
You.com	.883	.370	.593	.129	12,020
ChatGPT search	.881	.082	.191	.117	11,069
Brave	.881	.383	.613	.167	12,020
Keenable	.879	**.721**	**.800**	**.510**	12,020
Keenable realtime	.877	.709	.796	.509	12,020
Jina	.862	.629	.470	.030	11,716
Claude search	.860	.427	.620	.182	10,400
Context	.856	.628	.516	.111	12,020
Exa Lite	.848	.371	.305	.219	420
Linkup	.846	.344	.553	.125	8,204
Perplexity	.837	.567	.647	.299	12,020
Firecrawl	.836	.636	.472	.028	12,020
Google (Serper)	.834	.601	.457	.030	12,020
Perplexity Fast	.833	.555	.644	.295	12,020
Exa	.805	.531	.462	.345	12,020
Tavily	.795	.279	.144	.033	12,020
Exa Instant	.713	.409	.374	.273	12,020
Octen	.660	.063	.147	.157	12,020
DeepSeek	.608	.183	.184	.109	4,820
TinyFish	.224	.161	.126	.005	12,020
Ceramic	.011	.000	.000	.000	12,020

Table 12: Most configurations find a paper from its title (22 of 26 at .71–.98), but body-keyword recall runs from .00 to .72. Scholar recall@10 per query bucket over the 31 runs of Figure 1a (29 September to 28 October 2026; 3,005 query-runs per bucket for the ceiling), query-weighted; failures count as in Table 1, except in the 18 runs before 17 October whose per-query records we have not fetched, where every failed request counts as a miss. Query-runs sum the four buckets and are fewer where a configuration missed runs or lost queries. Bold: best configuration per bucket (`bucket_table.py`).

Needs Met scale with the same operator rules, in `analysis/audit/raters/`) and, per item, the date of the run, the query, the URL, the title, the snippet and the first 3,000 characters of the page, with the engine hidden. Each rater saw the 1,200 items in its own random order in 24 sessions of 50 and recorded a snippet grade and a page grade per item. The 128 items with a missing page are the 70 pages no fetch returned plus 58 fetched pages whose text a rater marked as broken. Gemini 4 Argon and Grok 4.7 graded the same items under the same guideline, one item per call at temperature 0, through OpenRouter (`third_rater.py`, `third_rater_analysis.py`). Table 13 gives the agreement. The two Claude raters agree at quadratic κ .94 (query-resampled 95% CI .93–.95), Gemini and Grok agree with each other at .92, and they agree with the judge at .78 and .79 (.75–.82). Raters from three vendors therefore agree with one another more than any agrees with the GPT-6 judge, and all three rate higher than the judge (mean rating 1.88 for Gemini and for Grok, 1.97 for the Claude consensus, 1.60 for the judge). Because the Claude raters saw the page while writing the snippet grade, a staged check (`staged_page.py`, `audit/raters/staged/`) re-graded 400 items with a fetched, unbroken page (200 news, 200 rare) in fresh Opus sessions that saw only the date, query, URL, title and snippet. That snippet-only grade differs from rater A's page grade on 25% of items (21–29%), but page grade minus snippet-only grade is only $+.05$ ($-.01$ to $+.11$), so the page adds noise to a quarter of grades but no systematic shift at this sample size. The snippet-only grade agrees with the judge, which also sees only snippets, at κ .82 (.77–.85). At the engine level the judge and the Claude consensus rank the 21 engines at Spearman .89 on news (.74–.94) and .71 on rare (.50–.94), with 37 to 61 items per engine, so the rare figure is coarse (`rater_engine_ci.py`). The absence of a net page effect is pooled over engines; the sample does not test engine-specific page bias.

List-level checks. Because six results per query cannot give a list metric, Gemini 4 Argon and Grok 4.7 graded 100 complete pools (50 news and 50 rare queries from the Table 1 runs, every top-5 list of all 21 engines, 5,698 unique results, snippet only), one item per call under the written guideline with its page rules removed (`list_sample_big.py`, `api_grader.py`, `audit/lists100/`). Recomputing every engine's pooled nDCG@5 from each rater's grades ranks the 21 engines against the judge at Spearman .94 (query-resampled 95% interval .89–.97; τ_b .85) for Gemini and .94 (.87–.96; τ_b .83) for Grok, with mean absolute share differences of .07 and .06. The same five engines lead under the judge and both raters (Keenable, Exa, Perplexity, DeepSeek, Brave (LLM ctx), in varying order) and the same three trail (TinyFish, Tavily or Kagi, Ceramic). The leading paired differences keep their sign under the judge, Gemini and Grok (Keenable–Parallel $+.204$, $+.168$ and $+.137$; Keenable–Ceramic $+.53$, $+.60$ and $+.56$), but Keenable–Exa is $+.035$ ($-.024$ to $+.090$) by the judge, $+.037$ ($-.016$ to $+.089$) by Gemini and

	News	Rare	All
results	600	600	1,200
page missing for a rater	43	85	128
κ, rater A vs. B (page)	.94	.94	.94
κ, judge vs. consensus (page)	.73	.80	.77
95% CI	.67–.77	.75–.84	.74–.81
within one level, judge vs. consensus	.86	.91	.88
mean rating, judge / consensus	1.83 / 2.32	1.38 / 1.61	1.60 / 1.97
grade revised in-prompt after the page, A / B	.10 / .09	.05 / .05	.08 / .07
staged snippet-only grade $\neq$ page grade (A), 400 items	.28	.22	.25
κ, judge vs. staged snippet-only	.78	.85	.82
Spearman ρ on 21 engine means	.89	.71	.84
κ, Gemini 4 vs. consensus / judge	.91 / .75	.92 / .80	.92 / .78
κ, Grok 4.7 vs. consensus / judge	.90 / .75	.88 / .81	.90 / .79
Spearman ρ on 21 engines, Gemini / Grok vs. judge	.85 / .82	.73 / .72	.84 / .85

Table 13: Blinded raters from three vendors (two Claude Opus 5.5 sessions, Gemini 4, Grok 4.7) agree with each other more than any agrees with the production judge. A staged snippet-only pass shows that the page changes a quarter of grades with no net shift; in-prompt revisions understate that change. Quadratic-weighted κ; intervals from 1,000 query-level bootstrap resamples; consensus is the rounded mean of the two page grades.

.000 ($-.053$ to $+.053$) by Grok, so 100 pools do not separate the top two under the judge or either rater.

Quoted rare queries. Over the Table 1 window (`rare_quoted.py`) 551 of the 1,300 rare query-runs carry a double-quoted span, and 32 are wrapped as `query: "..."` by the source agent, so they are scored on a phrase no page contains. The generator strips the wrapper from the first rare artifact released after 30 October 2026, and dropping the wrapped queries changes no rare share by more than .002. The quoted and unquoted query-runs rank engines differently. On the 722 scored unquoted query-runs (749 issued, 27 dropped for an empty ceiling), Exa, Perplexity and Brave (LLM ctx) lead and Keenable is fourth (τ_b .90 against the full rare order). On the quoted query-runs, Keenable, ChatGPT search and Exa lead, and Parallel, Perplexity, Exa and Linkup lose .14 to .18 of their rare bench share (τ_b .62). The rare column thus rewards literal compliance with quoted phrases as much as retrieval. The literal gate seldom punishes a page that does contain the phrase: of the 212 quoted-span results in the rater sample with page text, 74 show the span in the title or snippet and only 8 more show it on the page alone (`quoted_on_page.py`).

Second judge. We rendered the production prompts for every unique result of eight news queries, one from each of eight runs between 30 September and 24 October 2026 (803 results; 23 of the 25 configurations active then had complete lists for at least six queries), and of eight rare queries from the eight daily runs of 22–29 October (566 unique results, 23 engines with complete lists for at least four queries). The second judge, Claude Opus 5.5, rated them under the same instructions in six independent sessions, without access to the production ratings. The artifacts do not store the published date the API returned, so the second judge saw title, URL and snippet only. To separate that input difference from the model difference we re-ran the production judge (same model, prompt and temperature) on the same rendered prompts without dates. On news the dateless rerun agrees with its own dated ratings exactly on 61% of results and within one level on 91% (quadratic κ .80, query-resampled 95% interval .67–.88), and its mean rating falls from 2.43 to 2.19: the published date is a large input for news. Without dates the rerun agrees with the second judge at κ .76 (.68–.82), against .79 with dates, so the model difference is about as large as the date effect. On rare, where dates seldom matter, the rerun matches the dated ratings at κ .97 and the second judge at .91 (.81–.95). Table 14 gives the agreement of the second judge with the production judge (GPT-6), with engine shares recomputed for each judge against a ceiling pooled from that judge's ratings (Spearman intervals .76–.97 on news and .40–.95 on rare). The second judge is stricter: its mean news rating is 2.22 against 2.43, and 68% of disagreements go that way. Its two largest news drops are Parallel Turbo and Claude search ($-.20$ each), engines whose snippets often paraphrase the event without stating it. Claude

	News	Rare
results	803	566
exact	.554	.730
within one level	.918	.995
κ, quadratic weights	.790	.898
κ, unweighted	.440	.584
Spearman ρ on ratings	.806	.930
κ, binary at ≥ 2 / ≥ 3	.64 / .70	.69 / .83
engines	23	23
Spearman ρ on shares	.903	.874
Kendall τ_b on shares	.746	.728
mean $\lvert\Delta$ share$\rvert$	.064	.061

Table 14: The second judge (Claude Opus 5.5) agrees with the production judge (GPT-6) within one level on 92% of news and 99.5% of rare results and ranks engines at Spearman .90 on news and .87 on rare. Both judges rate the same results under the same prompts, eight queries per bench.

search shares a vendor with the second judge, and ChatGPT search with the judge; in the Table 1 news column, which the judge scores, the two engines rank 12th and 13th of 21. Eight queries per bench are few, so these engine-level figures bound judge disagreement rather than estimate it precisely; as with human assessors (Voorhees, 2000), disagreement on items leaves the engine ranking largely intact. Both judges read the same precomputed query profile, so a profile that misreads a query would not show up as disagreement. An annotator (Claude Opus 5.5) therefore wrote its own profile for the 16 sampled queries before seeing the production ones: 13 production profiles match in intent, two are narrower and one is broader, and none misreads the query or states the answer.

Equal snippet budget. On the 257 Table 1 news runs with per-query artifacts, the per-engine median snippet length ranges from 117 characters (Bing) to the 2,000-character cap (Jina), and its rank correlation with news share is .35 (`snippet_length.py`, `audit/snippet_length.json`). The six engines with medians below 200 characters rank 11th to 19th of 21 on news; of the three longest, Jina and Ceramic rank 20th and 21st but DeepSeek ranks third. To bound the effect of snippet length, the second judge rated the same 803 results again with every snippet cut to 200 characters. Against its own full-snippet ratings, exact agreement is .60, agreement within one level .94 and the quadratic κ .80. Kendall τ_b between the two engine orders is .73 (query-resampled interval .34–.83; `trunc_ci.py`) and Spearman ρ .88, with a mean absolute share difference of .084 (.06–.13). The cap compresses the field: the losses of Exa ($-.22$, interval $-.41$ to $-.08$), Keenable ($-.14$, $-.23$ to $-.05$) and Brave (LLM ctx) ($-.12$, $-.22$ to $-.04$) and the gains of Bing ($+.14$, $+.10$ to $+.19$) and Google ($+.09$, $+.04$ to $+.15$) exclude zero. The interval of the leader's margin over the second engine includes zero both with full snippets and at 200 characters, and the leader and the bottom three do not change. Eight queries thus establish the direction of the length effect but not its size per engine.

H Recall by query operator

The finance and legal generators assign operator syntax by cycling through a fixed list, so in production the variants of one bucket are not paired on the same item. To test operator effects we ran a paired set on 30 October 2026. As in the finance and legal columns of every table, a `site:` hit counts on any host, so a loss measures lost recall, not disobedience.

Paired variants (30 October 2026). To pair the variants on the same item we took 80 filing-document, 80 caselaw and 80 CFR targets from the window's finance and legal query sets, stripped every operator and quotation mark to make a plain query, and wrote the quoted, `site:` and date variants of each (`paired_build.py`; the date variant brackets the filing or decision date by 45 days). We ran the variants of each target adjacently through 18 configurations in one run per bench on 30 October 2026 (`paired_analysis.py`, `audit/paired/`; no Kagi, You.com or DeepSeek). Google and Jina returned redirect URLs (Appendix A) on 43% and 36% of their results, so their rows in Table 15 measure that change too. Keenable ran without an API

	SEC filings (80 targets)				Caselaw captions (80 targets)				CFR sections (80 targets)		
Engine	plain	quoted	site:	dates	plain	quoted	site:	dates	plain	quoted	site:
Perplexity	.66	+.06†	+.07†	+.03†	.97	−.03†	−.07	0†	.64	+.14	+.11†
Claude search	.54	+.01†	+.20	+.09†	.97	−.10†	−.30	0†	–	–	–
Parallel	.53	+.01†	+.29	+.06†	.96	0†	−.14	+.01†	.70	+.09	−.01†
Keenable	.52	+.12	+.28	−.15†	.99	−.09	−.03†	−.03†	.64	+.09	+.25
Exa	.51	+.16	+.28	+.14	.96	−.03†	−.55	0†	.60	+.14	+.21
ChatGPT search	.45	+.05†	+.25	+.05†	.95	−.24	−.88	0†	.56	+.15	+.16
Brave (LLM ctx)	.29	+.11	+.38	−.15	.96	0†	−.03†	−.23	.53	+.05	+.09†
Bing (SearchAPI)	.29	+.01†	+.41	+.01†	.91	−.06†	−.62	−.06†	.51	+.11	+.16
Linkup	.26	−.01†	+.54	−.16	.93	−.01†	−.25	−.33	.45	0†	+.14
Brave	.23	+.10	+.42	−.06†	.97	−.16	−.06	−.33	.55	0†	+.06†
Firecrawl	.15	+.30	+.62	+.04†	.89	−.03†	−.65	−.01†	.31	+.39	+.56
Jina	.15	+.20	+.49	−.06†	.61	+.10†	−.17†	−.15	.25	+.44	+.61
TinyFish	.13	+.19	+.48	−.04†	.88	−.14†	−.68	−.18†	.21	+.47	+.61
Tavily	.12	+.04†	+.39	−.07†	.84	+.04†	−.35	−.25	.55	0†	+.07†
Context	.11	+.23	+.44	+.03†	.82	+.04†	−.61	−.03†	.30	+.38	+.55
Google (Serper)	.07	+.24	+.56	−.03†	.86	−.10†	−.64	−.35	.26	+.47	+.56
Octen	.07	0†	+.24	0†	.69	+.04†	−.41	−.06†	.56	+.07†	+.09†
Ceramic	.00	0†	0†	0†	.19	−.01†	0†	0†	.14	0†	0†

Table 15: A `site:` restriction helps on filings and CFR sections and hurts on caselaw captions; the quoted span helps on filings and CFR and costs a little on captions. This run cannot tell whether the caselaw loss comes from index coverage, ranking or the operator's implementation. Plain recall@5 and the paired change under each variant on the same targets, one run per bench on 30 October 2026; a change printed in dark grey and marked † has a target-resampled 95% interval that includes zero, the others exclude it. Google and Jina returned redirect URLs on 43% and 36% of their results in this run (Appendix A); Keenable's finance cells rest on 229 of 320 requests.

key, so the public rate limit refused 91 of its 320 finance requests (229 answered). On the 80 filing targets the quoted span raises recall@5 by .10 on average (target-resampled 95% intervals exclude zero for 9 of 18 engines; none loses), `site:sec.gov` by .35 (16 of 18 gain), and the 90-day date window changes it by −.02. On the 80 caselaw captions, `site:courtlistener.com` lowers recall@5 by .36 on average and for 14 of 18 engines beyond their intervals, from ChatGPT search (−.88) and TinyFish (−.68) to Keenable and Brave (LLM ctx) (−.03 each) and Ceramic (0); the quoted caption changes recall by −.04 and the date window by −.11. On the 80 CFR sections the quoted span adds .18 (12 of 17 engines) and `site:ecfr.gov` adds .25 (10 of 17). This run does not separate coverage, ranking and operator implementation. In the legal run Claude search has no CFR cell and its caselaw cells rest on 30 targets (credit lapse), Tavily's CFR cells rest on 29 targets and TinyFish's caselaw cells on 34 to 42 (rate limits), and Jina returned no results for 29 captions. Failures fall on whole targets, so each engine's difference uses the targets it answered; if those targets differ in operator effect from the rest, the estimate is biased in a way the interval does not show. Excluding Google and Jina leaves the caselaw `site:` loss at −.36 (14 of 16 engines beyond their intervals), and restricting to the 14 engines with all 80 captions answered gives −.35. Without Google and Jina, the filing `site:` gain is +.33 and the CFR gains are +.14 (quoted) and +.20 (`site:`).

Operator compliance. For every `site:` query of the 24 finance runs of Appendix F and the 10 legal runs of 18–28 October 2026 we measured the share of returned URLs whose host is the requested one. It is 1.00 on both benches for 16 of the 21 engines. Claude search and Google keep 1.00 on finance and .98 and .99 on legal; Bing keeps .95 and .86, Kagi .19 and .09, and Ceramic .06 and .03. The Kagi and Ceramic figures are limits of the vendor interface, not of the clients: Kagi's lens parameter (`sites_included`), its only host filter, does not restrict results, and Ceramic's API takes a bare query string, so the client strips the operators; passing them as raw text returns no results on all 20 test queries (`ceramic_rawops.py`). The stored results carry no published date, so we cannot audit date-operator compliance. Counting only `site:` hits on the requested host, as Table 1 does, lowers recall on `site:` queries, pooled over every configuration's answered requests (`compliant_hits.py`), from .578 to

.527 on captions, .660 to .642 on CFR and .654 to .652 on filings; only Kagi (.91 to .00 on captions) and Ceramic change, and every other engine moves by under .01.