


matt wallpaint application notes



Lullaby Paints
MATT

Description

- Lullaby Paints Matt gives a pleasant flat finish

Storage

- Protect from frost/freezing

Where to Use

- Interior walls and ceilings
- NOTE: For areas of very high humidity, e.g. bathrooms - Eggshell is recommended

Preparation

- Surfaces should be clean, dry, sound and free from grease. If unsure, first clean with sugar soap and rinse well
- On bare plaster/plasterboard, prime with ECOS Plaster Sealer*
- Fillers - seal with ECOS Filler Sealer*

Application


- DO NOT THIN
- Stir gently and thoroughly before use
- Applying two coats by medium pile roller is generally best, but the product can also be sprayed (airless spray only)
- Allow six hours between coats.
- Avoid applying below 41°F (5°C) and above 68°F (20°C)
- DRYING: With good ventilation - is touch dry within one hour
- Clean equipment with water, as soon as you have finished painting

Coverage

- Varies with wall porosity, but on hard non-porous surfaces estimate:
140 sq. ft. per quart (single coat)
560 sq. ft. per gallon (single coat)

Health and Safety

- Avoid contact with skin and eyes. Wash off splashes with water. Do not ingest
- WARNING: Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm



More Tips:

Getting the Most Out of Your Pouch

Twist and squeeze pouch for full use. In addition, the pouch can be cut open using scissors. Squeeze out air before resealing

Discarding Paint Pouches

Let dry in an air cooled place and discard in accordance with local ordinance

Help us to provide a healthy, safe environment for moms and babies

* Where to Find ECOS Paints <http://www.ecospaints.net>

lullaby
PAINTS

www.lullabypaints.com
tel 864.595.3840
fax 864.595.3841
info@lullabypaints.com