

Exercise 1: Logging Error Messages and Warning Levels using SLF4J

Aim:

To demonstrate logging **Error** and **Warning** messages using SLF4J with **Logback**.

Step 1: Add Dependencies (pom.xml)

```
<dependencies>

    <dependency>

        <groupId>org.slf4j</groupId>

        <artifactId>slf4j-api</artifactId>

        <version>1.7.30</version>

    </dependency>

    <dependency>

        <groupId>ch.qos.logback</groupId>

        <artifactId>logback-classic</artifactId>

        <version>1.2.3</version>

    </dependency>

</dependencies>
```

Step 2: LoggingExample.java

```
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;

public class LoggingExample{

    private static final Logger logger=LoggerFactory.getLogger(LoggingExample.class);

    public static void main(String[] args){

        logger.error("This is an error message");

        logger.warn("This is a warning message");

    }

}
```

```
}  
}
```

Explanation

- `LoggerFactory.getLogger()` creates a logger object.
- `logger.error()` logs an **Error** message.
- `logger.warn()` logs a **Warning** message.
- Logback displays the log messages on the console.

Output

ERROR LoggingExample - This is an error message

WARN LoggingExample - This is a warning message

Result: The application successfully logs **Error** and **Warning** messages using the SLF4J logging framework with Logback.