

1: Create a Spring Web Project using Maven

Steps

1. Go to <https://start.spring.io>
2. Group: **com.cognizant**
3. Artifact: **spring-learn**
4. Add Dependencies:
 - Spring Boot DevTools
 - Spring Web
5. Generate and download the project.
6. Extract and import into Eclipse.
7. Run:

mvn clean package

8. Run SpringLearnApplication.java.

application.properties

logging.level.org.springframework=info

logging.level.com.cognizant.springlearn=debug

logging.pattern.console=%d{yyMMdd} | %d{HH:mm:ss.SSS} | %-20.20thread | %5p | %-25.25logger{25} | %25M | %m%n

server.port=8080

SpringLearnApplication.java

```
package com.cognizant.springlearn;
```

```
import org.slf4j.Logger;
```

```
import org.slf4j.LoggerFactory;
```

```
import org.springframework.boot.SpringApplication;
```

```
import org.springframework.boot.autoconfigure.SpringBootApplication;
```

```
@SpringBootApplication
```

```
public class SpringLearnApplication{  
    private static final Logger  
    LOGGER=LoggerFactory.getLogger(SpringLearnApplication.class);  
  
    public static void main(String[] args){  
        SpringApplication.run(SpringLearnApplication.class,args);  
        LOGGER.info("Inside main");  
    }  
}
```

Output

INFO Inside main

Started SpringLearnApplication

Result: Spring Boot Web project is created successfully using Maven and executed successfully.

2: Spring Core – Load Country from Spring Configuration XML country.xml

```
<?xml version="1.0" encoding="UTF-8"?>  
  
<beans xmlns="http://www.springframework.org/schema/beans"  
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"  
xsi:schemaLocation="http://www.springframework.org/schema/beans  
http://www.springframework.org/schema/beans/spring-beans.xsd">  
  
    <bean id="country" class="com.cognizant.springlearn.Country">  
        <property name="code" value="IN"/>  
        <property name="name" value="India"/>  
    </bean>
```

</beans>

Country.java

```
package com.cognizant.springlearn;
```

```
import org.slf4j.Logger;
```

```
import org.slf4j.LoggerFactory;
```

```
public class Country{
```

```
    private static final Logger LOGGER=LoggerFactory.getLogger(Country.class);
```

```
    private String code;
```

```
    private String name;
```

```
    public Country(){
```

```
        LOGGER.debug("Inside Country Constructor.");
```

```
    }
```

```
    public String getCode(){
```

```
        LOGGER.debug("Inside getCode");
```

```
        return code;
```

```
    }
```

```
    public void setCode(String code){
```

```
        LOGGER.debug("Inside setCode");
```

```
        this.code=code;
```

```
    }
```

```
    public String getName(){
```

```

        LOGGER.debug("Inside getName");
        return name;
    }

    public void setName(String name){
        LOGGER.debug("Inside setName");
        this.name=name;
    }

    @Override
    public String toString(){
        return "Country [code="+code+", name="+name+"]";
    }
}

```

SpringLearnApplication.java

```

package com.cognizant.springlearn;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

@SpringBootApplication
public class SpringLearnApplication{

    private static final Logger
    LOGGER=LoggerFactory.getLogger(SpringLearnApplication.class);

    public static void main(String[] args){

```

```
        SpringApplication.run(SpringLearnApplication.class,args);
        displayCountry();
    }

    public static void displayCountry(){
        LOGGER.info("START");
        ApplicationContext context=new ClassPathXmlApplicationContext("country.xml");
        Country country=context.getBean("country",Country.class);
        LOGGER.debug("Country : {}",country);
        LOGGER.info("END");
    }
}
```

Output

INFO START

DEBUG Inside Country Constructor.

DEBUG Inside setCode

DEBUG Inside setName

DEBUG Country : Country [code=IN, name=India]

INFO END

Result

The Country bean is successfully loaded from the Spring XML configuration using ClassPathXmlApplicationContext, and its details are displayed through logging.