keerthanakuppan15-jpg / QRdecomposition

Code | Pull requests | Actions | Projects | Wiki | Security | Insights | Settings

Watch 0

QR Decomposition

BSD-3-Clause license

0 stars | 2.1k forks | 0 watching | Branches | Activity | Tags

Public repository · Forked from etjabajasphin/QRdecomposition

1 Branch | 0 Tags | Go to file t | Go to file | Add file | Code

This branch is 1 commit ahead of `etjabajasphin/QRdecomposition:main` . | Contribute | Sync fork

keerthanakuppan15-jpg Update README.md 9ed8c76 · now

LICENSE	Initial commit	5 years ago
README.md	Update README.md	now
eq1.jpg	added experiment	5 years ago
eq2.jpg	added experiment	5 years ago
eq3.jpg	added experiment	5 years ago
ex1.jpg	updated	5 years ago
ex2.jpg	updated	5 years ago
ex3.jpg	updated	5 years ago
ex4.jpg	updated	5 years ago
ex6.jpg	updated	5 years ago
input.jpg	added experiment	5 years ago

README | License

Algorithm for QR Decomposition

Aim:

To implement QR decomposition algorithm using the Gram-Schmidt method.

Equipment's required:

1. Hardware – PCs
2. Anaconda – Python 3.7 Installation / Moodle-Code Runner

Algorithm:

1. Intialize the matrix Q and u
2. The vector u and e is given by

$$u_1 = a_1$$

$$u_2 = a_2 - (a_2.e_1)e_1$$

$$u_3 = a_3 - (a_3.e_1)e_1 - (a_3.e_2)e_2$$

$$e_1 = \frac{u_1}{\|u_1\|}$$

$$e_2 = \frac{u_2}{\|u_2\|}$$

3. Obtain the Q matrix

$$Q = (e_1|e_2| \dots \dots \dots e_n)$$

4. Construct the upper triangular matrix R

$$R = \begin{bmatrix} a_1.e_1 & a_2.e_1 & a_3.e_1 \\ 0 & a_2.e_2 & a_3.e_2 \\ 0 & 0 & a_3.e_3 \end{bmatrix}$$

Program:

Gram-Schmidt Method

```
Program to QR decomposition using the Gram-Schmidt method
Developed by: KEERTHANA K
RegisterNumber: 212225230137
import os
os.environ["OPENBLAS_NUM_THREADS"]="1"
import numpy as np

def QR_Decomposition(A):
```

```
    n, m = A.shape

    Q = np.zeros((n, m))
    R = np.zeros((m, m))

    for i in range(m):
        u = A[:, i]

        for j in range(i):
            R[j, i] = np.dot(Q[:, j], A[:, i])
            u = u - R[j, i] * Q[:, j]

        R[i, i] = np.linalg.norm(u)
        Q[:, i] = u / R[i, i]

    print("The Q Matrix is\n", Q)
    print("The R Matrix is\n", R)


a = np.array(eval(input()))
QR_Decomposition(a)
```

Output

Write the algorithm for QR decomposition using the Gram-Schmidt method.

For example:

Input	Result
([[1, 1, 0], [1,0,1], [0, 1, 1]])	The Q Matrix is [[0.70710678 0.40824829 -0.57735027] [0.70710678 -0.40824829 0.57735027] [0. 0.81649658 0.57735027]] The R Matrix is [[1.41421356 0.70710678 0.70710678] [0. 1.22474487 0.40824829] [0. 0. 1.15470054]]

Answer: (penalty regime: 0. %)

Reset answer

```python
'''
Program to QR decomposition using the Gram-Schmidt method
Developed by: KEERTHANA K
RegisterNumber: 212225230137
'''
import os
os.environ["OPENBLAS_NUM_THREADS"]="1"
import numpy as np

def QR_Decomposition(A):
    n, m = A.shape

    Q = np.zeros((n, m))
    R = np.zeros((m, m))

    for i in range(m):
        u = A[:, i]

        for j in range(i):
            R[j, i] = np.dot(Q[:, j], A[:, i])
```

Releases

No releases published

Create a new release

Packages

No packages published

Publish your first package

Contributors

No contributors