

# Rajalakshmi Engineering College

Name: keerthana v  
Email: 241501082@rajalakshmi.edu.in  
Roll no: 241501082  
Phone: 7358113357  
Branch: REC  
Department: I AI & ML FA  
Batch: 2028  
Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 7\_COD\_Question 3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

##### *Input Format*

The first line consists of an integer  $n$ , representing the number of contact pairs to be inserted.

Each of the next  $n$  lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string *k*, representing the contact to be checked or removed.

### ***Output Format***

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next *n* - 1 lines print the updated contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!"
2. The next *n* lines print the original contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

Refer to the sample outputs for the formatting specifications.

### ***Sample Test Case***

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

### ***Answer***

```
#include <stdio.h>
```

```
#include <string.h>
```

```
#define MAX 50
```

```
#define MAX_LEN 15
```

```

int main() {
    int n;
    char names[MAX][MAX_LEN], phones[MAX][MAX_LEN], key[MAX_LEN];
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%s %s", names[i], phones[i]);
    }

    scanf("%s", key);

    int found = -1;
    for (int i = 0; i < n; i++) {
        if (strcmp(names[i], key) == 0) {
            found = i;
            break;
        }
    }

    if (found != -1) {
        printf("The given key is removed!\n");
        for (int i = 0; i < n; i++) {
            if (i != found) {
                printf("Key: %s; Value: %s\n", names[i], phones[i]);
            }
        }
    } else {
        printf("The given key is not found!\n");
        for (int i = 0; i < n; i++) {
            printf("Key: %s; Value: %s\n", names[i], phones[i]);
        }
    }

    return 0;
}

```

**Status :** Correct

**Marks :** 10/10