

# Rajalakshmi Engineering College

Name: KEERTHI PRIYA T  
Email: 240701258@rajalakshmi.edu.in  
Roll no: 2116240701258  
Phone: 7397397221  
Branch: REC  
Department: I CSE FC  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_week 1\_CY

Attempt : 1  
Total Mark : 30  
Marks Obtained : 30

### Section 1 : Coding

#### 1. Problem Statement

Akila is a tech enthusiast and wants to write a program to add two polynomials. Each polynomial is represented as a linked list, where each node in the list represents a term in the polynomial.

A term in the polynomial is represented in the format  $ax^b$ , where  $a$  is the coefficient and  $b$  is the exponent.

Akila needs your help to implement a program that takes two polynomials as input, adds them, and stores the result in ascending order in a new polynomial-linked list. Write a program to help her.

#### ***Input Format***

The input consists of lines containing pairs of integers representing the

coefficients and exponents of polynomial terms.

Each line represents a single term, with the coefficient and exponent separated by a space.

The input for each polynomial ends with a line containing "0 0".

### ***Output Format***

The output consists of three lines representing the first, second, and resulting polynomial after the addition operation, with terms sorted in ascending order of exponents.

Each line contains terms of the polynomial in the format "coefficientx^exponent", separated by " + ".

If the resulting polynomial is zero, the output is "0".

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 3 4

2 3

1 2

0 0

1 2

2 3

3 4

0 0

Output:  $1x^2 + 2x^3 + 3x^4$

$1x^2 + 2x^3 + 3x^4$

$2x^2 + 4x^3 + 6x^4$

### ***Answer***

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
typedef struct Node {
```

```
    int coeff;
```

```
    int exp;
```

```
    struct Node* next;  
} Node;
```

```
Node* createNode(int coeff, int exp) {  
    Node* newNode = (Node*)malloc(sizeof(Node));  
    newNode->coeff = coeff;  
    newNode->exp = exp;  
    newNode->next = NULL;  
    return newNode;  
}
```

```
Node* insertNode(Node* head, int coeff, int exp) {  
    if (coeff == 0) return head; // Ignore zero coefficient
```

```
    Node* newNode = createNode(coeff, exp);
```

```
    if (!head || head->exp > exp) {  
        newNode->next = head;  
        return newNode;  
    }
```

```
    Node* current = head;  
    Node* prev = NULL;
```

```
    while (current && current->exp < exp) {  
        prev = current;  
        current = current->next;  
    }
```

```
    if (current && current->exp == exp) {  
        current->coeff += coeff;  
        if (current->coeff == 0) { // Remove zero terms  
            if (prev) prev->next = current->next;  
            else head = current->next;  
            free(current);  
        }  
    }
```

```
    } else {  
        newNode->next = current;  
        if (prev) prev->next = newNode;  
        else head = newNode;  
    }
```

```

    return head;
}

Node* addPolynomials(Node* poly1, Node* poly2) {
    Node* result = NULL;

    while (poly1 || poly2) {
        if (poly1 && (!poly2 || poly1->exp < poly2->exp)) {
            result = insertNode(result, poly1->coeff, poly1->exp);
            poly1 = poly1->next;
        } else if (poly2 && (!poly1 || poly2->exp < poly1->exp)) {
            result = insertNode(result, poly2->coeff, poly2->exp);
            poly2 = poly2->next;
        } else {
            result = insertNode(result, poly1->coeff + poly2->coeff, poly1->exp);
            poly1 = poly1->next;
            poly2 = poly2->next;
        }
    }

    return result;
}

```

```

void printPolynomial(Node* poly) {
    if (!poly) {
        printf("0\n");
        return;
    }
    int f=1;
    while (poly) {
        if(!f){
            printf("+");
        }
        printf("%dx^%d",poly->coeff,poly->exp);
        f=0;
        poly = poly->next;
    }
    printf("\n");
}

```

```

void freePolynomial(Node* poly) {
    while (poly) {
        Node* temp = poly;
        poly = poly->next;
        free(temp);
    }
}

int main() {
    Node *poly1 = NULL, *poly2 = NULL;
    int coeff, exp;

    while (scanf("%d %d", &coeff, &exp) == 2 && !(coeff == 0 && exp == 0)) {
        poly1 = insertNode(poly1, coeff, exp);
    }

    while (scanf("%d %d", &coeff, &exp) == 2 && !(coeff == 0 && exp == 0)) {
        poly2 = insertNode(poly2, coeff, exp);
    }

    printPolynomial(poly1);
    printPolynomial(poly2);

    Node* result = addPolynomials(poly1, poly2);
    printPolynomial(result);

    freePolynomial(poly1);
    freePolynomial(poly2);
    freePolynomial(result);

    return 0;
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Hayley loves studying polynomials, and she wants to write a program to compare two polynomials represented as linked lists and display whether they are equal or not.

The polynomials are expressed as a series of terms, where each term consists of a coefficient and an exponent. The program should read the polynomials from the user, compare them, and then display whether they are equal or not.

### ***Input Format***

The first line of input consists of an integer  $n$ , representing the number of terms in the first polynomial.

The following  $n$  lines of input consist of two integers, each representing the coefficient and the exponent of the term in the first polynomial.

The next line of input consists of an integer  $m$ , representing the number of terms in the second polynomial.

The following  $m$  lines of input consist of two integers, each representing the coefficient and the exponent of the term in the second polynomial.

### ***Output Format***

The first line of output prints "Polynomial 1: " followed by the first polynomial.

The second line prints "Polynomial 2: " followed by the second polynomial.

The polynomials should be displayed in the format  $ax^b$ , where  $a$  is the coefficient and  $b$  is the exponent.

If the two polynomials are equal, the third line prints "Polynomials are Equal."

If the two polynomials are not equal, the third line prints "Polynomials are Not Equal."

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 2

1 2

2 1

2  
1 2  
2 1

Output: Polynomial 1:  $(1x^2) + (2x^1)$

Polynomial 2:  $(1x^2) + (2x^1)$

Polynomials are Equal.

### Answer

// You are using GCC

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```
typedef struct node{
```

```
    int coeff, exp;
```

```
    struct node *next;
```

```
}node;
```

```
node *create(int coeff,int exp){
```

```
    node *newnode=(node*)malloc(sizeof(node));
```

```
    newnode->coeff=coeff;
```

```
    newnode->exp=exp;
```

```
    newnode->next=0;
```

```
    return newnode;
```

```
}
```

```
void insert(node **head,int coeff,int exp){
```

```
    node *newnode=create(coeff,exp);
```

```
    if(*head==0)
```

```
    {
```

```
        *head=newnode;
```

```
    }
```

```
    else{
```

```
        node *temp=*head;
```

```
        while(temp->next!=0){
```

```
            temp=temp->next;
```

```
        }
```

```
        temp->next=newnode;
```

```
    }
```

```
}
```

```
int areequal(node *head1,node *head2){
```

```
    while(head1&&head2){
```

```
        if(head1->coeff!=head2->coeff || head1->exp!=head2->exp)
```

```
            return 0;
```

```
        head1=head1->next;
```

```
        head2=head2->next;
```

```

    }
    return(head1==0 && head2==0);
}
void printList(node *head){
    node *temp=head;
    while(temp!=0){
        printf("(%dx^%d)",temp->coeff,temp->exp);
        if(temp->next)
            printf(" + ");
        temp=temp->next;
    }
    printf("\n");
}
int main()
{
    node *head1=0,*head2=0;
    int n,m,coeff,exp;
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        scanf("%d %d",&coeff,&exp);
        insert(&head1,coeff,exp);
    }
    scanf("%d",&m);
    for(int i=0;i<m;i++){
        scanf("%d %d",&coeff,&exp);
        insert(&head2,coeff,exp);
    }
    printf("Polynomial 1: ");
    printList(head1);
    printf("Polynomial 2: ");
    printList(head2);
    if(aarequal(head1,head2))
        printf("Polynomials are Equal.");
    else
        printf("Polynomials are Not Equal.");
}

```

**Status :** Correct

**Marks :** 10/10



### 3. Problem Statement

John is working on a math processing application, and his task is to simplify polynomials entered by users. The polynomial is represented as a linked list, where each node contains two properties:

Coefficient of the term.

Exponent of the term.

John's goal is to combine all the terms that have the same exponent, effectively simplifying the polynomial.

#### ***Input Format***

The first line of input consists of an integer representing the number of terms in the polynomial.

The next  $n$  lines of input consist of two integers, representing the coefficient and exponent of the polynomial in each line separated by space.

#### ***Output Format***

The first line of output prints the original polynomial in the format ' $cx^e + cx^e + \dots$ ' (where  $c$  is the coefficient and  $e$  is the exponent of each term).

The second line of output displays the simplified polynomial in the same format as the original polynomial.

If the polynomial is 0, then only '0' will be printed.

Refer to the sample output for formatting specifications.

#### ***Sample Test Case***

Input: 3

5 2

3 1

6 2

Output: Original polynomial:  $5x^2 + 3x^1 + 6x^2$

Simplified polynomial:  $11x^2 + 3x^1$

### Answer

```
#include <stdio.h>
#include <stdlib.h>

typedef struct node {
    int coeff;
    int exp;
    struct node* next;
} node;

void insert(node** head, int coeff, int exp) {
    node* newNode = (node*)malloc(sizeof(node));
    newNode->coeff = coeff;
    newNode->exp = exp;
    newNode->next = NULL;

    if (*head == NULL) {
        *head = newNode;
        return;
    }

    node* temp = *head;
    while (temp->next != NULL)
        temp = temp->next;
    temp->next = newNode;
}

void printPolynomial(node* head) {
    if (!head) {
        printf("0x^0\n");
        return;
    }

    node* temp = head;
    while (temp) {
        printf("%dx^%d", temp->coeff, temp->exp);
        if (temp->next)
            printf(" + ");
        temp = temp->next;
    }
    printf("\n");
}
```

```

node* simplifyPolynomial(node* head) {
    if (!head)
        return NULL;

    node* result = NULL;
    node* temp = head;

    while (temp) {
        node* search = result;
        int found = 0;

        while (search) {
            if (search->exp == temp->exp) {
                search->coeff += temp->coeff;
                found = 1;
                break;
            }
            search = search->next;
        }

        if (!found)
            insert(&result, temp->coeff, temp->exp);

        temp = temp->next;
    }

    node* prev = NULL, *curr = result;
    while (curr) {
        if (curr->coeff == 0) {
            if (prev)
                prev->next = curr->next;
            else
                result = curr->next;

            node* toDelete = curr;
            curr = curr->next;
            free(toDelete);
        } else {
            prev = curr;
            curr = curr->next;
        }
    }
}

```

```

    }
    return result;
}

void freeList(node* head) {
    node* temp;
    while (head) {
        temp = head;
        head = head->next;
        free(temp);
    }
}

int main() {
    int n, coeff, exp;
    node* polynomial = NULL;
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d %d", &coeff, &exp);
        insert(&polynomial, coeff, exp);
    }

    printf("Original polynomial: ");
    printPolynomial(polynomial);

    node* simplified = simplifyPolynomial(polynomial);
    printf("Simplified polynomial: ");
    printPolynomial(simplified);

    freeList(polynomial);
    freeList(simplified);

    return 0;
}

```

**Status :** Correct

**Marks : 10/10**